

LibTmsApi

1.2.3

Generated by Doxygen 1.5.6

Thu Dec 18 13:21:07 2008

Contents

1	Main Page	1
1.1	Introduction	1
1.2	Overview	1
1.3	BEAM class library	2
1.4	Examples	3
2	Directory Hierarchy	7
2.1	Directories	7
3	Namespace Index	9
3.1	Namespace List	9
4	Class Index	11
4.1	Class Hierarchy	11
5	Class Index	15
5.1	Class List	15
6	File Index	19
6.1	File List	19
7	Directory Documentation	21
7.1	/src/cern/tms/beam/ Directory Reference	21
7.2	/src/cern/tms/beam/libBeam/ Directory Reference	22
8	Namespace Documentation	25
8.1	Boapns Namespace Reference	25
8.1.1	Function Documentation	26
8.1.1.1	addEntry	26
8.1.1.2	Boapns	26
8.1.1.3	delEntry	26

8.1.1.4	getEntry	26
8.1.1.5	getEntryList	26
8.1.1.6	getNewName	26
8.1.1.7	getVersion	26
8.1.2	Variable Documentation	26
8.1.2.1	apiVersion	26
8.2	Tms Namespace Reference	27
8.2.1	Enumeration Type Documentation	29
8.2.1.1	CaptureClock	29
8.2.1.2	CyclePeriod	30
8.2.1.3	DataFunction	30
8.2.1.4	DataType	30
8.2.1.5	Errors	30
8.2.1.6	Priority	31
8.2.1.7	TestOutput	31
8.2.1.8	TimingSig	31
8.2.2	Variable Documentation	32
8.2.2.1	apiVersion	32
8.2.2.2	tmsNumPickups	32
8.2.2.3	tmsPhaseTableSize	32
9	Class Documentation	33
9.1	BArray< T > Class Template Reference	33
9.1.1	Detailed Description	33
9.1.2	Constructor & Destructor Documentation	33
9.1.2.1	BArray	33
9.1.2.2	BArray	33
9.1.2.3	BArray	33
9.2	BBuffer Class Reference	34
9.2.1	Constructor & Destructor Documentation	34
9.2.1.1	BBuffer	34
9.2.1.2	~BBuffer	34
9.2.2	Member Function Documentation	34
9.2.2.1	setSize	34
9.2.2.2	setData	34
9.2.2.3	writeData	35
9.2.2.4	data	35

9.2.2.5	size	35
9.2.3	Member Data Documentation	35
9.2.3.1	osize	35
9.2.3.2	odatasize	35
9.2.3.3	odata	35
9.3	BCond Class Reference	36
9.3.1	Constructor & Destructor Documentation	36
9.3.1.1	BCond	36
9.3.1.2	~BCond	36
9.3.2	Member Function Documentation	36
9.3.2.1	signal	36
9.3.2.2	wait	36
9.3.2.3	timedWait	36
9.3.3	Member Data Documentation	36
9.3.3.1	omutex	36
9.3.3.2	ocond	36
9.4	BCondBool Class Reference	37
9.4.1	Detailed Description	37
9.4.2	Constructor & Destructor Documentation	37
9.4.2.1	BCondBool	37
9.4.2.2	~BCondBool	37
9.4.3	Member Function Documentation	37
9.4.3.1	set	37
9.4.3.2	clear	38
9.4.3.3	value	38
9.4.3.4	wait	38
9.4.3.5	timedWait	38
9.4.4	Member Data Documentation	38
9.4.4.1	omutex	38
9.4.4.2	ocond	38
9.4.4.3	ovalue	38
9.5	BCondInt Class Reference	39
9.5.1	Detailed Description	40
9.5.2	Constructor & Destructor Documentation	40
9.5.2.1	BCondInt	40
9.5.2.2	~BCondInt	40

9.5.3	Member Function Documentation	40
9.5.3.1	setValue	40
9.5.3.2	increment	40
9.5.3.3	decrement	40
9.5.3.4	value	40
9.5.3.5	wait	40
9.5.3.6	waitIncrement	40
9.5.3.7	waitNotZero	40
9.5.3.8	waitNotZeroDecrement	40
9.5.3.9	tryNotZeroDecrement	40
9.5.3.10	timedWait	41
9.5.3.11	operator++	41
9.5.3.12	operator--	41
9.5.4	Member Data Documentation	41
9.5.4.1	omutex	41
9.5.4.2	ocond	41
9.5.4.3	ovalue	41
9.6	BCondValue Class Reference	42
9.6.1	Detailed Description	43
9.6.2	Constructor & Destructor Documentation	43
9.6.2.1	BCondValue	43
9.6.2.2	~BCondValue	43
9.6.3	Member Function Documentation	43
9.6.3.1	setValue	43
9.6.3.2	value	43
9.6.3.3	increment	43
9.6.3.4	decrement	43
9.6.3.5	waitMoreThanOrEqual	43
9.6.3.6	waitLessThanOrEqual	43
9.6.3.7	waitLessThan	43
9.6.3.8	operator+=	43
9.6.3.9	operator-=	43
9.6.3.10	operator++	44
9.6.3.11	operator--	44
9.6.4	Member Data Documentation	44
9.6.4.1	omutex	44

9.6.4.2	ocond	44
9.6.4.3	ovalue	44
9.7	BCondWrap Class Reference	45
9.7.1	Constructor & Destructor Documentation	46
9.7.1.1	BCondWrap	46
9.7.1.2	~BCondWrap	46
9.7.2	Member Function Documentation	46
9.7.2.1	setValue	46
9.7.2.2	value	46
9.7.2.3	increment	46
9.7.2.4	decrement	46
9.7.2.5	waitMoreThanOrEqual	46
9.7.2.6	waitLessThanOrEqual	46
9.7.2.7	waitLessThan	46
9.7.2.8	operator+=	46
9.7.2.9	operator-=	47
9.7.2.10	operator++	47
9.7.2.11	operator--	47
9.7.2.12	diff	47
9.7.3	Member Data Documentation	47
9.7.3.1	omutex	47
9.7.3.2	ocond	47
9.7.3.3	ovalue	47
9.8	BDir Class Reference	48
9.8.1	Detailed Description	49
9.8.2	Constructor & Destructor Documentation	49
9.8.2.1	BDir	49
9.8.2.2	BDir	49
9.8.2.3	~BDir	49
9.8.3	Member Function Documentation	49
9.8.3.1	open	49
9.8.3.2	error	49
9.8.3.3	read	49
9.8.3.4	clear	49
9.8.3.5	setWild	49
9.8.3.6	setSort	49

9.8.3.7	entryName	50
9.8.3.8	entryStat	50
9.8.3.9	entryStat64	50
9.8.4	Member Data Documentation	50
9.8.4.1	oerror	50
9.8.4.2	odirname	50
9.8.4.3	owild	50
9.8.4.4	osort	50
9.9	BEntry Class Reference	51
9.9.1	Detailed Description	51
9.9.2	Constructor & Destructor Documentation	52
9.9.2.1	BEntry	52
9.9.2.2	BEntry	52
9.9.2.3	BEntry	52
9.9.3	Member Function Documentation	52
9.9.3.1	getName	52
9.9.3.2	getValue	52
9.9.3.3	setLine	52
9.9.3.4	setName	52
9.9.3.5	setValue	52
9.9.3.6	line	52
9.9.3.7	print	52
9.9.4	Member Data Documentation	53
9.9.4.1	oname	53
9.9.4.2	ovalue	53
9.10	BEntryFile Class Reference	54
9.10.1	Detailed Description	54
9.10.2	Constructor & Destructor Documentation	55
9.10.2.1	BEntryFile	55
9.10.2.2	BEntryFile	55
9.10.2.3	~BEntryFile	55
9.10.3	Member Function Documentation	55
9.10.3.1	open	55
9.10.3.2	read	55
9.10.3.3	write	55
9.10.3.4	writeList	55

9.10.3.5	clear	55
9.10.4	Member Data Documentation	55
9.10.4.1	ofilename	55
9.10.4.2	ocomments	55
9.11	BEntryList Class Reference	56
9.11.1	Detailed Description	57
9.11.2	Constructor & Destructor Documentation	57
9.11.2.1	BEntryList	57
9.11.3	Member Function Documentation	57
9.11.3.1	isSet	57
9.11.3.2	find	57
9.11.3.3	findValue	57
9.11.3.4	setValue	57
9.11.3.5	setValueRaw	57
9.11.3.6	deleteEntry	57
9.11.3.7	print	57
9.11.3.8	getString	57
9.11.3.9	insert	58
9.11.3.10	del	58
9.11.3.11	clear	58
9.11.4	Member Data Documentation	58
9.11.4.1	olastPos	58
9.12	BError Class Reference	59
9.12.1	Detailed Description	60
9.12.2	Member Enumeration Documentation	60
9.12.2.1	Type	60
9.12.3	Constructor & Destructor Documentation	60
9.12.3.1	BError	60
9.12.3.2	BError	60
9.12.4	Member Function Documentation	60
9.12.4.1	copy	60
9.12.4.2	set	60
9.12.4.3	setError	60
9.12.4.4	getString	60
9.12.4.5	getErrorNo	60
9.12.4.6	operator int	61

9.12.5	Member Data Documentation	61
9.12.5.1	oerrNo	61
9.12.5.2	oerrStr	61
9.13	BEvent Class Reference	62
9.13.1	Detailed Description	62
9.13.2	Constructor & Destructor Documentation	62
9.13.2.1	BEvent	62
9.13.2.2	~BEvent	62
9.13.3	Member Function Documentation	62
9.13.3.1	getType	62
9.13.3.2	getBinary	62
9.13.3.3	setBinary	62
9.13.4	Member Data Documentation	63
9.13.4.1	otype	63
9.14	BEventError Class Reference	64
9.14.1	Constructor & Destructor Documentation	64
9.14.1.1	BEventError	64
9.14.2	Member Function Documentation	64
9.14.2.1	getBinary	64
9.14.2.2	setBinary	64
9.15	BEventInt Class Reference	65
9.15.1	Detailed Description	65
9.15.2	Constructor & Destructor Documentation	65
9.15.2.1	BEventInt	65
9.15.2.2	~BEventInt	65
9.15.3	Member Function Documentation	65
9.15.3.1	sendEvent	65
9.15.3.2	getEvent	65
9.15.3.3	getFd	66
9.15.4	Member Data Documentation	66
9.15.4.1	ofds	66
9.16	BEventPipe Class Reference	67
9.16.1	Detailed Description	67
9.16.2	Constructor & Destructor Documentation	67
9.16.2.1	BEventPipe	67
9.16.2.2	~BEventPipe	67

9.16.3	Member Function Documentation	67
9.16.3.1	sendEvent	67
9.16.3.2	getEvent	67
9.16.3.3	getReceiveFd	68
9.16.4	Member Data Documentation	68
9.16.4.1	ofds	68
9.17	BFile Class Reference	69
9.17.1	Detailed Description	70
9.17.2	Constructor & Destructor Documentation	70
9.17.2.1	BFile	70
9.17.2.2	BFile	70
9.17.2.3	BFile	70
9.17.2.4	~BFile	70
9.17.3	Member Function Documentation	70
9.17.3.1	open	70
9.17.3.2	open	70
9.17.3.3	close	70
9.17.3.4	error	71
9.17.3.5	getFd	71
9.17.3.6	length	71
9.17.3.7	setVBuf	71
9.17.3.8	read	71
9.17.3.9	readString	71
9.17.3.10	write	71
9.17.3.11	writeString	71
9.17.3.12	seek	71
9.17.3.13	printf	71
9.17.3.14	operator=	72
9.17.4	Member Data Documentation	72
9.17.4.1	ofile	72
9.17.4.2	ofileName	72
9.17.4.3	omode	72
9.17.4.4	oerror	72
9.18	BIter Class Reference	73
9.18.1	Detailed Description	73
9.18.2	Constructor & Destructor Documentation	73

9.18.2.1	BIter	73
9.18.3	Member Function Documentation	73
9.18.3.1	operator void *	73
9.18.3.2	operator==	73
9.18.4	Member Data Documentation	73
9.18.4.1	oi	73
9.19	BList< T > Class Template Reference	74
9.19.1	Detailed Description	76
9.19.2	Member Typedef Documentation	76
9.19.2.1	SortFunc	76
9.19.3	Constructor & Destructor Documentation	77
9.19.3.1	BList	77
9.19.3.2	BList	77
9.19.3.3	~BList	77
9.19.4	Member Function Documentation	77
9.19.4.1	start	77
9.19.4.2	begin	77
9.19.4.3	end	77
9.19.4.4	end	77
9.19.4.5	next	77
9.19.4.6	prev	77
9.19.4.7	goTo	77
9.19.4.8	position	77
9.19.4.9	number	77
9.19.4.10	isEnd	78
9.19.4.11	front	78
9.19.4.12	rear	78
9.19.4.13	get	78
9.19.4.14	get	78
9.19.4.15	append	78
9.19.4.16	insert	78
9.19.4.17	insertAfter	78
9.19.4.18	clear	78
9.19.4.19	del	78
9.19.4.20	deleteLast	79
9.19.4.21	deleteFirst	79

9.19.4.22	push	79
9.19.4.23	pop	79
9.19.4.24	queueAdd	79
9.19.4.25	queueGet	79
9.19.4.26	append	79
9.19.4.27	swap	79
9.19.4.28	sort	79
9.19.4.29	sort	79
9.19.4.30	operator=	79
9.19.4.31	operator[79
9.19.4.32	operator[80
9.19.4.33	operator[80
9.19.4.34	operator[80
9.19.4.35	operator+	80
9.19.4.36	nodeGet	80
9.19.4.37	nodeGet	80
9.19.4.38	nodeCreate	80
9.19.4.39	nodeCreate	80
9.19.5	Member Data Documentation	80
9.19.5.1	onodes	80
9.19.5.2	olength	80
9.20	BList< T >::Node Class Reference	81
9.20.1	Constructor & Destructor Documentation	81
9.20.1.1	Node	81
9.20.2	Member Data Documentation	81
9.20.2.1	next	81
9.20.2.2	prev	81
9.20.2.3	item	81
9.21	BMutex Class Reference	82
9.21.1	Detailed Description	82
9.21.2	Constructor & Destructor Documentation	82
9.21.2.1	BMutex	82
9.21.2.2	BMutex	82
9.21.2.3	~BMutex	82
9.21.3	Member Function Documentation	82
9.21.3.1	lock	82

9.21.3.2	unlock	82
9.21.3.3	tryLock	83
9.21.3.4	operator=	83
9.21.4	Member Data Documentation	83
9.21.4.1	omutex	83
9.22	BNameValue< T > Class Template Reference	84
9.22.1	Constructor & Destructor Documentation	84
9.22.1.1	BNameValue	84
9.22.1.2	BNameValue	84
9.22.2	Member Function Documentation	84
9.22.2.1	getName	84
9.22.2.2	getValue	84
9.22.3	Member Data Documentation	84
9.22.3.1	oname	84
9.22.3.2	ovalue	84
9.23	BNameValueList< T > Class Template Reference	85
9.23.1	Member Function Documentation	85
9.23.1.1	find	85
9.24	BoapClientObject Class Reference	86
9.24.1	Constructor & Destructor Documentation	87
9.24.1.1	BoapClientObject	87
9.24.1.2	BoapClientObject	87
9.24.2	Member Function Documentation	87
9.24.2.1	connectService	87
9.24.2.2	disconnectService	87
9.24.2.3	getServiceName	87
9.24.2.4	ping	87
9.24.2.5	setConnectionPriority	88
9.24.2.6	setMaxLength	88
9.24.2.7	setTimeout	88
9.24.2.8	pingLocked	88
9.24.2.9	checkApiVersion	88
9.24.2.10	performCall	88
9.24.2.11	performSend	88
9.24.2.12	performRecv	88
9.24.2.13	connectService	89

9.24.2.14	performSend	89
9.24.2.15	performRecv	89
9.24.2.16	performCall	89
9.24.3	Member Data Documentation	89
9.24.3.1	oname	89
9.24.3.2	oapiVersion	89
9.24.3.3	opriority	89
9.24.3.4	oservice	89
9.24.3.5	oconnected	89
9.24.3.6	omaxLength	89
9.24.3.7	otx	89
9.24.3.8	orx	89
9.24.3.9	olock	89
9.24.3.10	otimeout	89
9.24.3.11	oreconnect	89
9.25	Boapns::BoapEntry Class Reference	90
9.25.1	Constructor & Destructor Documentation	90
9.25.1.1	BoapEntry	90
9.25.1.2	BoapEntry	90
9.25.2	Member Data Documentation	90
9.25.2.1	name	90
9.25.2.2	hostName	90
9.25.2.3	addressList	90
9.25.2.4	port	90
9.25.2.5	service	90
9.26	BoapFuncEntry Class Reference	91
9.26.1	Constructor & Destructor Documentation	91
9.26.1.1	BoapFuncEntry	91
9.26.1.2	BoapFuncEntry	91
9.26.2	Member Data Documentation	91
9.26.2.1	ocmd	91
9.26.2.2	ofunc	91
9.27	Boapns::Boapns Class Reference	92
9.27.1	Constructor & Destructor Documentation	92
9.27.1.1	Boapns	92
9.27.2	Member Function Documentation	92

9.27.2.1	getVersion	92
9.27.2.2	getEntryList	92
9.27.2.3	getEntry	92
9.27.2.4	addEntry	92
9.27.2.5	delEntry	92
9.27.2.6	getNewName	92
9.28	BoapPacket Class Reference	93
9.28.1	Constructor & Destructor Documentation	96
9.28.1.1	BoapPacket	96
9.28.1.2	~BoapPacket	96
9.28.1.3	BoapPacket	96
9.28.1.4	~BoapPacket	96
9.28.2	Member Function Documentation	96
9.28.2.1	resize	96
9.28.2.2	setData	96
9.28.2.3	nbytes	96
9.28.2.4	data	96
9.28.2.5	peekHead	96
9.28.2.6	getCmd	96
9.28.2.7	pushHead	96
9.28.2.8	push	96
9.28.2.9	push	96
9.28.2.10	push	96
9.28.2.11	push	96
9.28.2.12	push	96
9.28.2.13	push	96
9.28.2.14	push	96
9.28.2.15	push	96
9.28.2.16	push	96
9.28.2.17	push	96
9.28.2.18	push	96
9.28.2.19	push	96
9.28.2.20	popHead	96
9.28.2.21	pop	96
9.28.2.22	pop	96
9.28.2.23	pop	96

9.28.2.24 pop	96
9.28.2.25 pop	96
9.28.2.26 pop	96
9.28.2.27 pop	96
9.28.2.28 pop	96
9.28.2.29 pop	96
9.28.2.30 pop	96
9.28.2.31 pop	96
9.28.2.32 pop	96
9.28.2.33 copyWithSwap	96
9.28.2.34 updateLen	96
9.28.2.35 resize	96
9.28.2.36 setData	96
9.28.2.37 nbytes	96
9.28.2.38 data	96
9.28.2.39 pushHead	96
9.28.2.40 push	96
9.28.2.41 push	96
9.28.2.42 push	96
9.28.2.43 push	96
9.28.2.44 push	96
9.28.2.45 push	96
9.28.2.46 push	96
9.28.2.47 push	96
9.28.2.48 push	96
9.28.2.49 push	96
9.28.2.50 popHead	96
9.28.2.51 pop	96
9.28.2.52 pop	96
9.28.2.53 pop	96
9.28.2.54 pop	96
9.28.2.55 pop	96
9.28.2.56 pop	96
9.28.2.57 pop	96
9.28.2.58 pop	96
9.28.2.59 pop	96

9.28.2.60	pop	96
9.28.2.61	updateLen	96
9.28.3	Member Data Documentation	96
9.28.3.1	osize	96
9.28.3.2	onbytes	96
9.28.3.3	odata	96
9.28.3.4	opos	96
9.29	BoapPacketHead Struct Reference	98
9.29.1	Member Data Documentation	98
9.29.1.1	type	98
9.29.1.2	length	98
9.29.1.3	service	98
9.29.1.4	cmd	98
9.29.1.5	type	98
9.29.1.6	service	98
9.29.1.7	reserved	98
9.30	BoapServer Class Reference	99
9.30.1	Member Enumeration Documentation	100
9.30.1.1	"@5	100
9.30.2	Constructor & Destructor Documentation	101
9.30.2.1	BoapServer	101
9.30.2.2	~BoapServer	101
9.30.2.3	BoapServer	101
9.30.3	Member Function Documentation	101
9.30.3.1	init	101
9.30.3.2	run	101
9.30.3.3	processEvent	101
9.30.3.4	addObject	101
9.30.3.5	process	101
9.30.3.6	sendEvent	101
9.30.3.7	getSocket	101
9.30.3.8	getEventSocket	101
9.30.3.9	processEvent	101
9.30.3.10	getHostName	101
9.30.3.11	clientGone	101
9.30.3.12	getConnectionsNumber	101

9.30.3.13	function	101
9.30.3.14	init	102
9.30.3.15	run	102
9.30.3.16	processEvent	102
9.30.3.17	addObject	102
9.30.3.18	process	102
9.30.3.19	sendEvent	102
9.30.3.20	getSocket	102
9.30.3.21	getEventSocket	102
9.30.3.22	processEvent	102
9.30.3.23	getHostName	102
9.30.4	Member Data Documentation	102
9.30.4.1	othreaded	102
9.30.4.2	oisBoapns	102
9.30.4.3	oboapns	102
9.30.4.4	oclients	102
9.30.4.5	oclientGoneEvent	102
9.30.4.6	oservices	102
9.30.4.7	opoll	102
9.30.4.8	onet	102
9.30.4.9	onetEvent	102
9.30.4.10	onetEventAddress	102
9.30.4.11	ohostName	102
9.30.4.12	oboapNs	102
9.30.4.13	orx	102
9.30.4.14	otx	102
9.31	BoapServerConnection Class Reference	104
9.31.1	Constructor & Destructor Documentation	104
9.31.1.1	BoapServerConnection	104
9.31.2	Member Function Documentation	104
9.31.2.1	process	104
9.31.2.2	getSocket	104
9.31.2.3	setMaxLength	104
9.31.2.4	function	104
9.31.3	Member Data Documentation	105
9.31.3.1	oboapServer	105

9.31.3.2	osocket	105
9.31.3.3	orx	105
9.31.3.4	otx	105
9.31.3.5	omaxLength	105
9.32	BoapServiceEntry Class Reference	106
9.32.1	Constructor & Destructor Documentation	106
9.32.1.1	BoapServiceEntry	106
9.32.1.2	BoapServiceEntry	106
9.32.2	Member Data Documentation	106
9.32.2.1	oservice	106
9.32.2.2	oobject	106
9.33	BoapServiceObject Class Reference	107
9.33.1	Constructor & Destructor Documentation	109
9.33.1.1	BoapServiceObject	109
9.33.1.2	~BoapServiceObject	109
9.33.1.3	BoapServiceObject	109
9.33.1.4	~BoapServiceObject	109
9.33.2	Member Function Documentation	109
9.33.2.1	setName	109
9.33.2.2	sendEvent	109
9.33.2.3	processEvent	109
9.33.2.4	name	109
9.33.2.5	doPing	109
9.33.2.6	doConnectionPriority	109
9.33.2.7	process	109
9.33.2.8	processEvent	109
9.33.2.9	sendEvent	109
9.33.2.10	sendEvent	109
9.33.2.11	processEvent	109
9.33.2.12	name	109
9.33.2.13	process	109
9.33.2.14	processEvent	109
9.33.2.15	sendEvent	109
9.33.3	Member Data Documentation	109
9.33.3.1	oserver	109
9.33.3.2	oname	109

9.33.3.3	oapiVersion	109
9.33.3.4	ofuncList	109
9.34	BoapSignalObject Class Reference	111
9.34.1	Constructor & Destructor Documentation	111
9.34.1.1	BoapSignalObject	111
9.34.1.2	BoapSignalObject	111
9.34.2	Member Function Documentation	111
9.34.2.1	performSend	111
9.34.2.2	performSend	111
9.34.3	Member Data Documentation	111
9.34.3.1	otx	111
9.34.3.2	orx	111
9.35	BObject Class Reference	113
9.35.1	Constructor & Destructor Documentation	114
9.35.1.1	BObject	114
9.35.1.2	~BObject	114
9.35.2	Member Function Documentation	114
9.35.2.1	getBinary	114
9.35.2.2	setBinary	114
9.35.2.3	getString	114
9.35.2.4	setString	114
9.35.2.5	getMemberList	114
9.35.2.6	addMember	114
9.35.2.7	printIt	114
9.35.2.8	getType	114
9.35.2.9	createObj	114
9.35.3	Member Data Documentation	114
9.35.3.1	otype	114
9.36	BPoll Class Reference	115
9.36.1	Detailed Description	115
9.36.2	Member Typedef Documentation	116
9.36.2.1	PollFd	116
9.36.3	Constructor & Destructor Documentation	116
9.36.3.1	BPoll	116
9.36.3.2	~BPoll	116
9.36.4	Member Function Documentation	116

9.36.4.1	append	116
9.36.4.2	delFd	116
9.36.4.3	doPoll	116
9.36.4.4	getPollFdsNum	116
9.36.4.5	getPollFds	116
9.36.4.6	clear	116
9.36.4.7	nextFd	116
9.36.5	Member Data Documentation	116
9.36.5.1	ofdsNum	116
9.36.5.2	ofds	116
9.36.5.3	ofdsNext	116
9.37	BRefData Class Reference	118
9.37.1	Detailed Description	118
9.37.2	Constructor & Destructor Documentation	119
9.37.2.1	BRefData	119
9.37.2.2	BRefData	119
9.37.2.3	BRefData	119
9.37.2.4	~BRefData	119
9.37.3	Member Function Documentation	119
9.37.3.1	copy	119
9.37.3.2	addRef	119
9.37.3.3	deleteRef	119
9.37.3.4	refCount	119
9.37.3.5	data	119
9.37.3.6	len	119
9.37.3.7	setLen	119
9.37.3.8	operator=	119
9.37.4	Member Data Documentation	119
9.37.4.1	oData	119
9.37.4.2	oLen	119
9.37.4.3	oSize	119
9.37.4.4	oRefCount	119
9.38	BRtc Class Reference	120
9.38.1	Detailed Description	120
9.38.2	Constructor & Destructor Documentation	120
9.38.2.1	BRtc	120

9.38.2.2	~BRtc	120
9.38.3	Member Function Documentation	120
9.38.3.1	init	120
9.38.3.2	wait	120
9.38.4	Member Data Documentation	120
9.38.4.1	ofd	120
9.38.4.2	orate	120
9.39	BRtcThreaded Class Reference	122
9.39.1	Detailed Description	122
9.39.2	Constructor & Destructor Documentation	122
9.39.2.1	BRtcThreaded	122
9.39.2.2	~BRtcThreaded	122
9.39.3	Member Function Documentation	122
9.39.3.1	init	122
9.39.3.2	wait	123
9.39.3.3	function	123
9.39.4	Member Data Documentation	123
9.39.4.1	ortc	123
9.39.4.2	orate	123
9.39.4.3	ocond	123
9.40	BRWLock Class Reference	124
9.40.1	Detailed Description	124
9.40.2	Constructor & Destructor Documentation	124
9.40.2.1	BRWLock	124
9.40.2.2	BRWLock	124
9.40.2.3	~BRWLock	124
9.40.3	Member Function Documentation	124
9.40.3.1	rdLock	124
9.40.3.2	tryRdLock	125
9.40.3.3	wrLock	125
9.40.3.4	tryWrLock	125
9.40.3.5	unlock	125
9.40.3.6	operator=	125
9.40.4	Member Data Documentation	125
9.40.4.1	olock	125
9.41	BSema Class Reference	126

9.41.1	Detailed Description	126
9.41.2	Constructor & Destructor Documentation	126
9.41.2.1	BSema	126
9.41.2.2	BSema	126
9.41.2.3	~BSema	126
9.41.3	Member Function Documentation	126
9.41.3.1	post	126
9.41.3.2	wait	127
9.41.3.3	timedWait	127
9.41.3.4	tryWait	127
9.41.3.5	getValue	127
9.41.3.6	operator=	127
9.41.4	Member Data Documentation	127
9.41.4.1	osema	127
9.42	BSignal Class Reference	128
9.42.1	Member Enumeration Documentation	128
9.42.1.1	"@0	128
9.42.2	Constructor & Destructor Documentation	129
9.42.2.1	BSignal	129
9.42.2.2	BSignal	129
9.42.2.3	~BSignal	129
9.42.3	Member Function Documentation	129
9.42.3.1	operator=	129
9.42.4	Member Data Documentation	129
9.42.4.1	id	129
9.42.4.2	numSamples	129
9.42.4.3	numRepeat	129
9.42.4.4	nextId	129
9.42.4.5	data	129
9.43	BSocket Class Reference	130
9.43.1	Member Enumeration Documentation	131
9.43.1.1	NType	131
9.43.1.2	Priority	131
9.43.2	Constructor & Destructor Documentation	133
9.43.2.1	BSocket	133
9.43.2.2	BSocket	133

9.43.2.3	BSocket	133
9.43.2.4	~BSocket	133
9.43.3	Member Function Documentation	133
9.43.3.1	init	133
9.43.3.2	getFd	133
9.43.3.3	bind	133
9.43.3.4	connect	133
9.43.3.5	shutdown	133
9.43.3.6	close	133
9.43.3.7	listen	133
9.43.3.8	accept	133
9.43.3.9	accept	133
9.43.3.10	send	133
9.43.3.11	sendTo	133
9.43.3.12	recv	133
9.43.3.13	recvFrom	133
9.43.3.14	recvWithTimeout	133
9.43.3.15	recvFromWithTimeout	133
9.43.3.16	setSockOpt	133
9.43.3.17	getSockOpt	133
9.43.3.18	setReuseAddress	133
9.43.3.19	setBroadCast	133
9.43.3.20	setPriority	133
9.43.3.21	getMTU	133
9.43.3.22	getAddress	133
9.43.4	Member Data Documentation	133
9.43.4.1	osocket	133
9.44	BSocketAddress Class Reference	135
9.44.1	Detailed Description	135
9.44.2	Member Typedef Documentation	136
9.44.2.1	SockAddr	136
9.44.3	Constructor & Destructor Documentation	136
9.44.3.1	BSocketAddress	136
9.44.3.2	BSocketAddress	136
9.44.3.3	BSocketAddress	136
9.44.3.4	~BSocketAddress	136

9.44.4	Member Function Documentation	136
9.44.4.1	set	136
9.44.4.2	raw	136
9.44.4.3	len	136
9.44.4.4	operator=	136
9.44.4.5	operator const SockAddr *	136
9.44.4.6	operator==	136
9.44.4.7	operator"!="	136
9.44.5	Member Data Documentation	136
9.44.5.1	olen	136
9.44.5.2	oaddress	136
9.45	BSocketAddressINET Class Reference	137
9.45.1	Detailed Description	138
9.45.2	Member Typedef Documentation	138
9.45.2.1	SockAddrIP	138
9.45.3	Member Function Documentation	138
9.45.3.1	set	138
9.45.3.2	set	138
9.45.3.3	set	138
9.45.3.4	setPort	138
9.45.3.5	address	138
9.45.3.6	port	138
9.45.3.7	getString	138
9.45.3.8	getHostName	138
9.45.3.9	getIpAddresses	138
9.45.3.10	getIpAddressList	138
9.45.3.11	getIpAddressListAll	138
9.46	BString Class Reference	140
9.46.1	Constructor & Destructor Documentation	143
9.46.1.1	BString	143
9.46.1.2	BString	143
9.46.1.3	BString	143
9.46.1.4	BString	143
9.46.1.5	BString	143
9.46.1.6	BString	143
9.46.1.7	BString	143

9.46.1.8	BString	143
9.46.1.9	BString	143
9.46.1.10	~BString	143
9.46.2	Member Function Documentation	143
9.46.2.1	convert	143
9.46.2.2	convert	143
9.46.2.3	convert	143
9.46.2.4	convert	143
9.46.2.5	convert	144
9.46.2.6	convert	144
9.46.2.7	convertHex	144
9.46.2.8	convertHex	144
9.46.2.9	copy	144
9.46.2.10	strChanged	144
9.46.2.11	len	144
9.46.2.12	retStr	144
9.46.2.13	retStrDup	144
9.46.2.14	retInt	144
9.46.2.15	retDouble	144
9.46.2.16	compare	144
9.46.2.17	compareWild	145
9.46.2.18	compareWildExpression	145
9.46.2.19	add	145
9.46.2.20	truncate	145
9.46.2.21	pad	145
9.46.2.22	toUpper	145
9.46.2.23	toLower	145
9.46.2.24	removeNL	145
9.46.2.25	subString	145
9.46.2.26	del	145
9.46.2.27	insert	145
9.46.2.28	printf	146
9.46.2.29	find	146
9.46.2.30	findReverse	146
9.46.2.31	getTokenList	146
9.46.2.32	removeSeparators	146

9.46.2.33	pullToken	146
9.46.2.34	pullSeparators	146
9.46.2.35	pullWord	146
9.46.2.36	pullLine	146
9.46.2.37	field	146
9.46.2.38	fields	146
9.46.2.39	operator=	146
9.46.2.40	operator[146
9.46.2.41	operator==	147
9.46.2.42	operator==	147
9.46.2.43	operator>	147
9.46.2.44	operator>	147
9.46.2.45	operator<	147
9.46.2.46	operator<	147
9.46.2.47	operator>=	147
9.46.2.48	operator<=	147
9.46.2.49	operator"!=	147
9.46.2.50	operator"!=	147
9.46.2.51	operator+	147
9.46.2.52	operator+	147
9.46.2.53	operator+=	147
9.46.2.54	operator+=	147
9.46.2.55	operator+	147
9.46.2.56	operator+	147
9.46.2.57	operator+	147
9.46.2.58	operator+	147
9.46.2.59	operator const char *	147
9.46.2.60	Init	147
9.46.2.61	inString	147
9.46.2.62	isSpace	147
9.46.3	Member Data Documentation	147
9.46.3.1	ostr	147
9.47	BThread Class Reference	148
9.47.1	Constructor & Destructor Documentation	149
9.47.1.1	BThread	149
9.47.1.2	~BThread	149

9.47.2	Member Function Documentation	149
9.47.2.1	setInitPriority	149
9.47.2.2	setInitStackSize	149
9.47.2.3	start	149
9.47.2.4	result	149
9.47.2.5	running	149
9.47.2.6	setPriority	149
9.47.2.7	cancel	149
9.47.2.8	waitForCompletion	149
9.47.2.9	getThread	149
9.47.2.10	function	149
9.47.2.11	startFunc	149
9.47.3	Member Data Documentation	149
9.47.3.1	othread	149
9.47.3.2	ostackSize	149
9.47.3.3	opolicy	149
9.47.3.4	opriority	149
9.47.3.5	orunning	149
9.47.3.6	oresult	149
9.48	BTimer Class Reference	150
9.48.1	Detailed Description	150
9.48.2	Constructor & Destructor Documentation	151
9.48.2.1	BTimer	151
9.48.2.2	~BTimer	151
9.48.3	Member Function Documentation	151
9.48.3.1	start	151
9.48.3.2	stop	151
9.48.3.3	clear	151
9.48.3.4	getElapsedTime	151
9.48.3.5	add	151
9.48.3.6	average	151
9.48.3.7	peak	151
9.48.3.8	getTime	152
9.48.4	Member Data Documentation	152
9.48.4.1	oclock	152
9.48.4.2	onum	152

9.48.4.3	ostartTime	152
9.48.4.4	oendTime	152
9.48.4.5	oaverage	152
9.48.4.6	opeak	152
9.49	BUrl Class Reference	153
9.49.1	Detailed Description	153
9.49.2	Constructor & Destructor Documentation	153
9.49.2.1	BUrl	153
9.49.2.2	~BUrl	153
9.49.3	Member Function Documentation	153
9.49.3.1	readString	153
9.49.3.2	writeData	154
9.49.4	Member Data Documentation	154
9.49.4.1	oinit	154
9.49.4.2	ores	154
9.50	Tms::ConfigInfo Class Reference	155
9.50.1	Detailed Description	155
9.50.2	Constructor & Destructor Documentation	155
9.50.2.1	ConfigInfo	155
9.50.2.2	ConfigInfo	155
9.50.3	Member Data Documentation	155
9.50.3.1	puReferences	155
9.51	Tms::CycleInformation Class Reference	156
9.51.1	Constructor & Destructor Documentation	156
9.51.1.1	CycleInformation	156
9.51.1.2	CycleInformation	156
9.51.2	Member Data Documentation	156
9.51.2.1	cycleNumber	156
9.51.2.2	cycleType	156
9.51.2.3	periods	156
9.52	Tms::CycleInformationPeriod Class Reference	157
9.52.1	Detailed Description	157
9.52.2	Constructor & Destructor Documentation	158
9.52.2.1	CycleInformationPeriod	158
9.52.2.2	CycleInformationPeriod	158
9.52.3	Member Data Documentation	158

9.52.3.1	cyclePeriod	158
9.52.3.2	startTime	158
9.52.3.3	endTime	158
9.52.3.4	harmonic	158
9.52.3.5	numBunches	158
9.52.3.6	bunchMask	158
9.52.3.7	numValues	158
9.53	Tms::CycleParam Class Reference	159
9.53.1	Detailed Description	160
9.53.2	Constructor & Destructor Documentation	160
9.53.2.1	CycleParam	160
9.53.2.2	CycleParam	160
9.53.3	Member Data Documentation	160
9.53.3.1	cycleType	160
9.53.3.2	info	160
9.53.3.3	channel	160
9.53.3.4	pllCycleStartFrequency	160
9.53.3.5	pllInitialFrequency	161
9.53.3.6	pllInitialFrequencyDelay	161
9.53.3.7	pllFrefGain	161
9.53.3.8	pllGain	161
9.53.3.9	pllDdsMinimum	161
9.53.3.10	pllDdsMaximum	161
9.53.3.11	frefPhaseDelay	161
9.53.3.12	stateTable	161
9.53.3.13	settings	161
9.54	Tms::CycleParamDb Class Reference	162
9.54.1	Detailed Description	162
9.54.2	Constructor & Destructor Documentation	162
9.54.2.1	CycleParamDb	162
9.54.3	Member Function Documentation	162
9.54.3.1	getCycleTypes	162
9.54.3.2	getFileNames	163
9.54.3.3	getCycleParams	163
9.54.3.4	setCycleParams	163
9.54.3.5	deleteCycleParams	163

9.54.3.6	readCycleParams	163
9.54.3.7	writeCycleParams	163
9.54.4	Member Data Documentation	163
9.54.4.1	obaseDir	163
9.55	Tms::CycleParamEdit Class Reference	164
9.55.1	Detailed Description	165
9.55.2	Constructor & Destructor Documentation	165
9.55.2.1	CycleParamEdit	165
9.55.2.2	CycleParamEdit	165
9.55.3	Member Function Documentation	165
9.55.3.1	clear	165
9.55.3.2	getString	165
9.55.3.3	setString	165
9.55.3.4	readFromFile	165
9.55.3.5	writeToFile	165
9.55.3.6	setStates	165
9.55.3.7	getStates	165
9.55.3.8	getDefaultState	165
9.55.3.9	getdefaultPickupPositions	166
9.55.3.10	value	166
9.55.3.11	bunch	166
9.55.3.12	generateState	166
9.56	Tms::CycleParamItem Class Reference	167
9.56.1	Constructor & Destructor Documentation	167
9.56.1.1	CycleParamItem	167
9.56.1.2	CycleParamItem	167
9.56.2	Member Data Documentation	167
9.56.2.1	cycleType	167
9.56.2.2	channel	167
9.57	Tms::CycleParamState Class Reference	168
9.57.1	Constructor & Destructor Documentation	169
9.57.1.1	CycleParamState	169
9.57.2	Member Function Documentation	169
9.57.2.1	clear	169
9.57.2.2	getString	169
9.57.2.3	setString	169

9.57.3	Member Data Documentation	169
9.57.3.1	period	169
9.57.3.2	bunchMask	169
9.57.3.3	mean1Mask	169
9.57.3.4	mean2Mask	169
9.57.3.5	loHarmonic	169
9.57.3.6	loPhase	170
9.57.3.7	useLoFref	170
9.57.3.8	acquireData	170
9.57.3.9	gateWidth	170
9.57.3.10	gatePhase	170
9.57.3.11	blrWidth	170
9.57.3.12	blrPhase	170
9.58	Tms::CycleTypeInfo Class Reference	171
9.58.1	Constructor & Destructor Documentation	171
9.58.1.1	CycleTypeInfo	171
9.58.1.2	CycleTypeInfo	171
9.58.2	Member Data Documentation	171
9.58.2.1	cycleType	171
9.58.2.2	info	171
9.58.2.3	periods	171
9.59	Tms::CycleTypeInfoPeriod Class Reference	172
9.59.1	Detailed Description	172
9.59.2	Constructor & Destructor Documentation	172
9.59.2.1	CycleTypeInfoPeriod	172
9.59.2.2	CycleTypeInfoPeriod	172
9.59.3	Member Data Documentation	172
9.59.3.1	cyclePeriod	172
9.59.3.2	harmonic	172
9.59.3.3	numBunches	173
9.59.3.4	bunchMask	173
9.60	Tms::Data Class Reference	174
9.60.1	Detailed Description	174
9.60.2	Constructor & Destructor Documentation	174
9.60.2.1	Data	174
9.60.2.2	Data	174

9.60.3	Member Data Documentation	174
9.60.3.1	numValues	174
9.60.3.2	dataType	175
9.60.3.3	numBunches	175
9.60.3.4	numChannels	175
9.60.3.5	dataValues	175
9.60.3.6	errors	175
9.61	Tms::DataInfo Class Reference	176
9.61.1	Detailed Description	176
9.61.2	Constructor & Destructor Documentation	177
9.61.2.1	DataInfo	177
9.61.2.2	DataInfo	177
9.61.3	Member Data Documentation	177
9.61.3.1	cycleNumber	177
9.61.3.2	channel	177
9.61.3.3	cyclePeriod	177
9.61.3.4	startTime	177
9.61.3.5	orbitNumber	177
9.61.3.6	bunchNumber	177
9.61.3.7	function	177
9.61.3.8	argument	177
9.61.3.9	numValues	177
9.61.3.10	beyondPeriod	178
9.62	Tms::DataValue Class Reference	179
9.62.1	Detailed Description	179
9.62.2	Constructor & Destructor Documentation	179
9.62.2.1	DataValue	179
9.62.2.2	DataValue	179
9.62.3	Member Data Documentation	179
9.62.3.1	sigma	179
9.62.3.2	deltaX	179
9.62.3.3	deltaY	179
9.62.3.4	time	180
9.63	Tms::NameValue Class Reference	181
9.63.1	Constructor & Destructor Documentation	181
9.63.1.1	NameValue	181

9.63.1.2	NameValue	181
9.63.2	Member Data Documentation	181
9.63.2.1	name	181
9.63.2.2	value	181
9.64	Tms::PuChannel Class Reference	182
9.64.1	Detailed Description	182
9.64.2	Constructor & Destructor Documentation	182
9.64.2.1	PuChannel	182
9.64.2.2	PuChannel	182
9.64.3	Member Data Documentation	182
9.64.3.1	moduleNum	182
9.64.3.2	pupeNum	182
9.64.3.3	pupeChan	182
9.65	Tms::PuControl Class Reference	184
9.65.1	Detailed Description	185
9.65.2	Constructor & Destructor Documentation	185
9.65.2.1	PuControl	185
9.65.3	Member Function Documentation	185
9.65.3.1	getVersion	185
9.65.3.2	init	186
9.65.3.3	setProcessPriority	186
9.65.3.4	configure	186
9.65.3.5	setControlInfo	186
9.65.3.6	setNextCycle	186
9.65.3.7	test	186
9.65.3.8	getStatus	186
9.65.3.9	getStatistics	186
9.65.3.10	getMasterPuChannel	186
9.65.3.11	setTestMode	187
9.65.3.12	setTimingSignals	187
9.65.3.13	captureDiagnostics	187
9.65.3.14	setTestData	187
9.65.3.15	setPupeConfig	187
9.65.3.16	getPupeConfig	187
9.66	Tms::PupeConfig Class Reference	188
9.66.1	Constructor & Destructor Documentation	188

9.66.1.1	PupeConfig	188
9.66.1.2	PupeConfig	188
9.66.2	Member Data Documentation	188
9.66.2.1	internalTimingMask	188
9.66.2.2	adcSysclkSync	188
9.66.2.3	disableBlr	188
9.67	Tms::PuProcess Class Reference	189
9.67.1	Detailed Description	189
9.67.2	Constructor & Destructor Documentation	190
9.67.2.1	PuProcess	190
9.67.3	Member Function Documentation	190
9.67.3.1	getVersion	190
9.67.3.2	getCycleInformation	190
9.67.3.3	getStatus	190
9.67.3.4	getData	190
9.67.3.5	addEventServer	190
9.67.3.6	requestData	190
9.68	Tms::PuStateTable Class Reference	191
9.68.1	Detailed Description	191
9.68.2	Constructor & Destructor Documentation	191
9.68.2.1	PuStateTable	191
9.68.2.2	PuStateTable	191
9.68.3	Member Data Documentation	191
9.68.3.1	period	191
9.68.3.2	state	192
9.68.3.3	harmonic	192
9.68.3.4	numBunches	192
9.68.3.5	bunchMask	192
9.68.3.6	phaseTable	192
9.69	Tms::PuStatus Class Reference	193
9.69.1	Detailed Description	193
9.69.2	Constructor & Destructor Documentation	193
9.69.2.1	PuStatus	193
9.69.2.2	PuStatus	193
9.69.3	Member Data Documentation	193
9.69.3.1	running	193

9.69.3.2	error	193
9.70	SigGen Class Reference	194
9.70.1	Constructor & Destructor Documentation	194
9.70.1.1	SigGen	194
9.70.1.2	~SigGen	194
9.70.2	Member Function Documentation	194
9.70.2.1	config	194
9.70.2.2	generate	194
9.70.3	Member Data Documentation	194
9.70.3.1	osampleRate	194
9.70.3.2	ox	194
9.71	SigGenBeam Class Reference	195
9.71.1	Constructor & Destructor Documentation	195
9.71.1.1	SigGenBeam	195
9.71.1.2	~SigGenBeam	195
9.71.2	Member Function Documentation	195
9.71.2.1	config	195
9.71.2.2	generate	195
9.71.2.3	generateIntegrated	196
9.71.3	Member Data Documentation	196
9.71.3.1	oharmonic	196
9.71.3.2	obunchSet	196
9.71.3.3	oreduce	196
9.71.3.4	obl	196
9.71.3.5	oamplitude	196
9.71.3.6	ofref	196
9.72	SigGenNoise Class Reference	197
9.72.1	Constructor & Destructor Documentation	197
9.72.1.1	SigGenNoise	197
9.72.1.2	~SigGenNoise	197
9.72.2	Member Function Documentation	197
9.72.2.1	config	197
9.72.2.2	generate	197
9.72.3	Member Data Documentation	197
9.72.3.1	oamplitude	197
9.73	SigGenPulse Class Reference	198

9.73.1	Constructor & Destructor Documentation	198
9.73.1.1	SigGenPulse	198
9.73.1.2	~SigGenPulse	198
9.73.2	Member Function Documentation	198
9.73.2.1	config	198
9.73.2.2	generate	198
9.73.3	Member Data Documentation	199
9.73.3.1	ofreq	199
9.73.3.2	oamplitude	199
9.73.3.3	oonTime	199
9.73.3.4	ostartTime	199
9.74	SigGenSine Class Reference	200
9.74.1	Constructor & Destructor Documentation	200
9.74.1.1	SigGenSine	200
9.74.1.2	~SigGenSine	200
9.74.2	Member Function Documentation	200
9.74.2.1	config	200
9.74.2.2	generate	200
9.74.3	Member Data Documentation	200
9.74.3.1	ofreq	200
9.74.3.2	oamplitude	200
9.75	SigGenSquare Class Reference	201
9.75.1	Constructor & Destructor Documentation	201
9.75.1.1	SigGenSquare	201
9.75.1.2	~SigGenSquare	201
9.75.2	Member Function Documentation	201
9.75.2.1	config	201
9.75.2.2	generate	201
9.75.3	Member Data Documentation	201
9.75.3.1	ofreq	201
9.75.3.2	oamplitude	201
9.75.3.3	ooffset	201
9.76	Tms::Simulation Class Reference	203
9.76.1	Constructor & Destructor Documentation	203
9.76.1.1	Simulation	203
9.76.1.2	Simulation	203

9.76.2	Member Data Documentation	203
9.76.2.1	timing	203
9.76.2.2	data	203
9.76.2.3	setNextCycle	203
9.76.2.4	cycleType	204
9.77	vector Class Reference	205
9.78	Tms::TestCaptureInfo Class Reference	206
9.78.1	Detailed Description	206
9.78.2	Constructor & Destructor Documentation	207
9.78.2.1	TestCaptureInfo	207
9.78.2.2	TestCaptureInfo	207
9.78.3	Member Data Documentation	207
9.78.3.1	source	207
9.78.3.2	clock	207
9.78.3.3	startTime	207
9.78.3.4	postTriggerDelay	207
9.78.3.5	triggerMask	207
9.78.3.6	triggerAnd	207
9.78.3.7	triggerStore	207
9.78.3.8	triggerSourceData	207
9.79	Tms::TmsControl Class Reference	208
9.79.1	Detailed Description	210
9.79.2	Constructor & Destructor Documentation	210
9.79.2.1	TmsControl	210
9.79.3	Member Function Documentation	210
9.79.3.1	getVersion	210
9.79.3.2	setProcessPriority	210
9.79.3.3	init	210
9.79.3.4	configure	210
9.79.3.5	getConfiguration	211
9.79.3.6	setControlInfo	211
9.79.3.7	getControlInfo	211
9.79.3.8	delControlInfo	211
9.79.3.9	getControlList	212
9.79.3.10	setNextCycle	212
9.79.3.11	test	212

9.79.3.12	getStatus	212
9.79.3.13	getStatistics	213
9.79.3.14	getPuChannel	213
9.79.3.15	setSimulation	213
9.79.3.16	getSimulation	213
9.79.3.17	setTestMode	213
9.79.3.18	setTimingSignals	214
9.79.3.19	captureDiagnostics	214
9.79.3.20	setTestData	214
9.79.3.21	setPupeConfig	214
9.79.3.22	getPupeConfig	215
9.79.3.23	puServerStarted	215
9.80	Tms::TmsEvent Class Reference	216
9.80.1	Detailed Description	216
9.80.2	Constructor & Destructor Documentation	216
9.80.2.1	TmsEvent	216
9.80.3	Member Function Documentation	216
9.80.3.1	errorEvent	216
9.80.3.2	cycleStartEvent	217
9.80.3.3	cycleStopEvent	217
9.80.3.4	dataEvent	217
9.81	Tms::TmsEventServerList Class Reference	218
9.81.1	Constructor & Destructor Documentation	218
9.81.1.1	TmsEventServerList	218
9.81.1.2	~TmsEventServerList	218
9.81.2	Member Function Documentation	218
9.81.2.1	append	218
9.81.2.2	del	218
9.81.2.3	errorEvent	218
9.81.2.4	cycleStartEvent	218
9.81.2.5	cycleStopEvent	219
9.81.2.6	dataEvent	219
9.81.3	Member Data Documentation	219
9.81.3.1	oLock	219
9.81.3.2	oeventServers	219
9.82	Tms::TmsPhase Union Reference	220

9.82.1	Detailed Description	220
9.82.2	Member Data Documentation	220
9.82.2.1	lo1	220
9.82.2.2	blr	220
9.82.2.3	gate	220
9.82.2.4	lo2	220
9.82.2.5	spare	220
9.82.2.6	meanFilter1	220
9.82.2.7	meanFilter2	220
9.82.2.8	"@4	220
9.82.2.9	value	220
9.83	Tms::TmsProcess Class Reference	221
9.83.1	Detailed Description	222
9.83.2	Constructor & Destructor Documentation	222
9.83.2.1	TmsProcess	222
9.83.3	Member Function Documentation	222
9.83.3.1	getVersion	222
9.83.3.2	getCycleInfo	222
9.83.3.3	getCycleInformation	222
9.83.3.4	getCycleTypeInfoInformation	223
9.83.3.5	getData	223
9.83.3.6	addEventServer	223
9.83.3.7	requestData	224
9.84	Tms::TmsState Union Reference	225
9.84.1	Detailed Description	225
9.84.2	Member Data Documentation	226
9.84.2.1	aquireData	226
9.84.2.2	pllReference1	226
9.84.2.3	pllReference2	226
9.84.2.4	pllFeedbackSelect	226
9.84.2.5	pllLO1FromAddress	226
9.84.2.6	pllLO2FromAddress	226
9.84.2.7	spare0	226
9.84.2.8	cycleStop	226
9.84.2.9	calStop	226
9.84.2.10	calStart	226

9.84.2.11 injection	226
9.84.2.12 hchange	226
9.84.2.13 delay	226
9.84.2.14 "@2	226
9.84.2.15 value	226
10 File Documentation	227
10.1 /src/cern/tms/beam/libBeam/BArray.h File Reference	227
10.1.1 Define Documentation	227
10.1.1.1 BArray_H	227
10.2 /src/cern/tms/beam/libBeam/BBuffer.cpp File Reference	228
10.2.1 Define Documentation	228
10.2.1.1 SIZE	228
10.3 /src/cern/tms/beam/libBeam/BBuffer.h File Reference	229
10.3.1 Define Documentation	229
10.3.1.1 BBUFFER_H	229
10.4 /src/cern/tms/beam/libBeam/BCond.cpp File Reference	230
10.5 /src/cern/tms/beam/libBeam/BCond.h File Reference	231
10.5.1 Define Documentation	231
10.5.1.1 BCOND_H	231
10.6 /src/cern/tms/beam/libBeam/BCondInt.cpp File Reference	232
10.7 /src/cern/tms/beam/libBeam/BCondInt.h File Reference	233
10.7.1 Define Documentation	233
10.7.1.1 BCONDINT_H	233
10.8 /src/cern/tms/beam/libBeam/BDir.cpp File Reference	234
10.8.1 Function Documentation	234
10.8.1.1 wild	234
10.8.2 Variable Documentation	234
10.8.2.1 wildString	234
10.9 /src/cern/tms/beam/libBeam/BDir.h File Reference	235
10.9.1 Define Documentation	235
10.9.1.1 BDIR_H	235
10.10/src/cern/tms/beam/libBeam/BEntry.cpp File Reference	236
10.11/src/cern/tms/beam/libBeam/BEntry.h File Reference	237
10.12/src/cern/tms/beam/libBeam/BError.cpp File Reference	238
10.13/src/cern/tms/beam/libBeam/BError.h File Reference	239
10.13.1 Define Documentation	239

10.13.1.1 BERROR_H	239
10.14/src/cern/tms/beam/libBeam/BEvent.cpp File Reference	240
10.15/src/cern/tms/beam/libBeam/BEvent.h File Reference	241
10.15.1 Define Documentation	241
10.15.1.1 BEvent_H	241
10.15.2 Enumeration Type Documentation	241
10.15.2.1 BEventType	241
10.16/src/cern/tms/beam/libBeam/BFile.cpp File Reference	242
10.16.1 Define Documentation	242
10.16.1.1 STRBUF	242
10.17/src/cern/tms/beam/libBeam/BFile.h File Reference	243
10.17.1 Define Documentation	243
10.17.1.1 BFILE_H	243
10.18/src/cern/tms/beam/libBeam/BList.h File Reference	244
10.18.1 Define Documentation	244
10.18.1.1 BLIST_H	244
10.19/src/cern/tms/beam/libBeam/BList_func.h File Reference	245
10.20/src/cern/tms/beam/libBeam/BMutex.cpp File Reference	246
10.20.1 Define Documentation	246
10.20.1.1 MDEBUG	246
10.21/src/cern/tms/beam/libBeam/BMutex.h File Reference	247
10.21.1 Define Documentation	247
10.21.1.1 BMUTEX_H	247
10.22/src/cern/tms/beam/libBeam/BNameValue.h File Reference	248
10.22.1 Define Documentation	248
10.22.1.1 BNAMEVALUE_H	248
10.22.1.2 TEMPLATE_NEW	248
10.23/src/cern/tms/beam/libBeam/Boap.cpp File Reference	249
10.23.1 Define Documentation	250
10.23.1.1 APIVERSION_TEST	250
10.23.1.2 DEBUG	250
10.23.1.3 dprintf	250
10.23.1.4 IS_BIG_ENDIAN	250
10.23.2 Function Documentation	250
10.23.2.1 swap16	250
10.23.2.2 swap32	250

10.23.2.3 swap64	250
10.23.2.4 swap8	250
10.23.3 Variable Documentation	250
10.23.3.1 boapPort	250
10.23.3.2 roundSize	250
10.24/src/cern/tms/beam/libBeam/Boap.h File Reference	251
10.24.1 Typedef Documentation	252
10.24.1.1 BoapFunc	252
10.24.1.2 BoapService	252
10.24.2 Enumeration Type Documentation	252
10.24.2.1 BoapPriority	252
10.24.2.2 BoapType	252
10.24.3 Variable Documentation	252
10.24.3.1 BoapMagic	252
10.25/src/cern/tms/beam/libBeam/BoapnsC.cc File Reference	253
10.26/src/cern/tms/beam/libBeam/BoapnsC.h File Reference	254
10.26.1 Define Documentation	254
10.26.1.1 BOAPNSC_H	254
10.27/src/cern/tms/beam/libBeam/BoapnsD.cc File Reference	255
10.28/src/cern/tms/beam/libBeam/BoapnsD.h File Reference	256
10.28.1 Define Documentation	256
10.28.1.1 BOAPNSD_H	256
10.29/src/cern/tms/beam/libBeam/BoapSimple.cc File Reference	257
10.29.1 Define Documentation	257
10.29.1.1 DEBUG	257
10.29.1.2 dprintf	257
10.29.2 Variable Documentation	257
10.29.2.1 roundSize	257
10.30/src/cern/tms/beam/libBeam/BoapSimple.h File Reference	258
10.30.1 Typedef Documentation	259
10.30.1.1 BoapFunc	259
10.30.1.2 BoapService	259
10.30.1.3 Double	259
10.30.1.4 Int16	259
10.30.1.5 Int32	259
10.30.1.6 Int8	259

10.30.1.7 UInt16	259
10.30.1.8 UInt32	259
10.30.1.9 UInt8	259
10.30.2 Enumeration Type Documentation	259
10.30.2.1 BoapType	259
10.31/src/cern/tms/beam/libBeam/BObject.cc File Reference	260
10.31.1 Define Documentation	260
10.31.1.1 DEBUG	260
10.32/src/cern/tms/beam/libBeam/BObject.h File Reference	261
10.32.1 Define Documentation	261
10.32.1.1 BOBJECT_H	261
10.32.2 Typedef Documentation	261
10.32.2.1 BMember	261
10.32.2.2 BMemberList	261
10.33/src/cern/tms/beam/libBeam/BPoll-1.cpp File Reference	262
10.34/src/cern/tms/beam/libBeam/BPoll.cpp File Reference	263
10.35/src/cern/tms/beam/libBeam/BPoll.h File Reference	264
10.35.1 Define Documentation	264
10.35.1.1 BPOLL_H	264
10.36/src/cern/tms/beam/libBeam/BRefData.cpp File Reference	265
10.36.1 Define Documentation	265
10.36.1.1 CHUNK	265
10.36.1.2 DEBUG	265
10.37/src/cern/tms/beam/libBeam/BRefData.h File Reference	266
10.37.1 Define Documentation	266
10.37.1.1 BREFDATA_H	266
10.38/src/cern/tms/beam/libBeam/BRtc.cpp File Reference	267
10.39/src/cern/tms/beam/libBeam/BRtc.h File Reference	268
10.40/src/cern/tms/beam/libBeam/BRWLock.cpp File Reference	269
10.41/src/cern/tms/beam/libBeam/BRWLock.h File Reference	270
10.41.1 Define Documentation	270
10.41.1.1 BRWLOCK_H	270
10.42/src/cern/tms/beam/libBeam/BSema.cpp File Reference	271
10.43/src/cern/tms/beam/libBeam/BSema.h File Reference	272
10.43.1 Define Documentation	272
10.43.1.1 BSEMA_H	272

10.44/src/cern/tms/beam/libBeam/BSocket.cpp File Reference	273
10.44.1 Define Documentation	273
10.44.1.1 IP_MTU	273
10.45/src/cern/tms/beam/libBeam/BSocket.h File Reference	274
10.45.1 Define Documentation	274
10.45.1.1 BSOCKET_H	274
10.46/src/cern/tms/beam/libBeam/BString.cpp File Reference	275
10.46.1 Define Documentation	275
10.46.1.1 DEBUG	275
10.46.1.2 MINUS	275
10.46.1.3 STRIP	275
10.46.2 Function Documentation	275
10.46.2.1 gmatch	275
10.46.2.2 operator<<	275
10.46.2.3 operator>>	275
10.47/src/cern/tms/beam/libBeam/BString.h File Reference	276
10.47.1 Define Documentation	276
10.47.1.1 BSTRING_H	276
10.47.2 Function Documentation	276
10.47.2.1 operator<<	276
10.47.2.2 operator>>	276
10.48/src/cern/tms/beam/libBeam/BThread.cpp File Reference	277
10.49/src/cern/tms/beam/libBeam/BThread.h File Reference	278
10.49.1 Define Documentation	278
10.49.1.1 BTHREAD_H	278
10.50/src/cern/tms/beam/libBeam/BTimer.cpp File Reference	279
10.51/src/cern/tms/beam/libBeam/BTimer.h File Reference	280
10.52/src/cern/tms/beam/libBeam/BTypes.h File Reference	281
10.52.1 Define Documentation	283
10.52.1.1 BTYPES_H	283
10.52.2 Typedef Documentation	283
10.52.2.1 BArrayDouble	283
10.52.2.2 BArrayFloat	283
10.52.2.3 BDouble	283
10.52.2.4 BFloat	283
10.52.2.5 BInt16	283

10.52.2.6 BInt32	283
10.52.2.7 BInt64	283
10.52.2.8 BInt8	283
10.52.2.9 BSize	283
10.52.2.10 BUInt	283
10.52.2.11 BUInt16	283
10.52.2.12 BUInt32	283
10.52.2.13 BUInt64	283
10.52.2.14 BUInt8	283
10.52.2.15 Double	283
10.52.2.16 Float	283
10.52.2.17 Int16	283
10.52.2.18 Int32	283
10.52.2.19 Int64	283
10.52.2.20 Int8	283
10.52.2.21 IUInt16	283
10.52.2.22 UInt32	283
10.52.2.23 UInt64	283
10.52.2.24 UInt8	283
10.53/src/cern/tms/beam/libBeam/BUrl.cpp File Reference	284
10.54/src/cern/tms/beam/libBeam/BUrl.h File Reference	285
10.54.1 Define Documentation	285
10.54.1.1 BURL_H	285
10.55overview.dox File Reference	286
10.56SigGen.cpp File Reference	287
10.56.1 Define Documentation	287
10.56.1.1 DEBUG	287
10.56.1.2 dprintf	287
10.57SigGen.h File Reference	288
10.57.1 Define Documentation	288
10.57.1.1 SigGen_h	288
10.57.2 Typedef Documentation	288
10.57.2.1 BSignalList	288
10.57.2.2 Sample	288
10.58test1.cpp File Reference	289
10.58.1 Function Documentation	289

10.58.1.1 main	289
10.58.1.2 printCycleParams	289
10.59TmsC.cc File Reference	290
10.60TmsC.h File Reference	291
10.60.1 Detailed Description	291
10.60.2 Define Documentation	292
10.60.2.1 TMS_C_H	292
10.61TmsCycleParam-1.cc File Reference	293
10.62TmsCycleParam.cc File Reference	294
10.63TmsCycleParam.h File Reference	295
10.63.1 Define Documentation	295
10.63.1.1 TmsCycleParam_H	295
10.64TmsD.cc File Reference	296
10.65TmsD.h File Reference	297
10.65.1 Define Documentation	298
10.65.1.1 TMSD_H	298
10.66TmsEventServerList.cc File Reference	299
10.67TmsEventServerList.h File Reference	300
10.67.1 Define Documentation	300
10.67.1.1 TmsEventServerList_H	300
10.68tmsFunctions.dox File Reference	301
10.69TmsLib.cc File Reference	302
10.70TmsLib.h File Reference	303
10.70.1 Define Documentation	304
10.70.1.1 TmsLib_H	304
10.71TmsS.cc File Reference	305
10.72TmsT.cc File Reference	306

Chapter 1

Main Page

Author:

Dr Terry Barnaby

Version:

1.2.3

Date:

2007-12-10

1.1 Introduction

This document covers the BEAM LibTms software API for the CERN trajectory measurement system. This API provides the ability to control and receive data from the TMS System. The API is an object orientated API implemented in 'C++' with a number of object classes. The API operates over a network type interface using an RPC type mechanism.

The LibTms API makes use of the BEAM standard class library. The BEAM standard class library provides a small set of low level 'C++' classes for strings, lists and system interface functions. There is some brief information on the BEAM class library later on in this page.

1.2 Overview

Generally users of the system are only concerned with the top level, System Controller API. This is the API that control and data gathering clients use to control and gather data from the system. The System Controller API (TmsApi) is implemented using a simple, object orientated, RPC mechanism. Two main objects, the [Tms::TmsControl](#) and [Tms::TmsProcess](#) objects, provide the full API.

The TmsApi has been developed using the BOAP (BEAM Object Access Protocol). This provides a simple but powerful Object Orientated RPC mechanism. The TmsApi is written in a high level interface definition language (IDL). The bidl tool generates the client and server side 'C++' interface and implementation files for the API. These are then provided as a set of 'C++' header files and a binary library file for the clients to link to. The BOAP system employs a simple BOAP name server process that provides a translation between object names and IPAddress/Socket numbers. The BOAP name server runs on the System Controller. More information on the BOAP system can be found in the libBeam documentation.

There are two main Objects that are used by clients of the TMS API. They are the [Tms::TmsControl](#) and the [Tms::TmsProcess](#) objects. The [Tms::TmsControl](#) object is used for system configuration, testing and diagnostics. The [Tms::TmsProcess](#) object is used for normal clients for Proton Synchrotron (PS) Cycle information configuration and data access. There is some example client code in the `tmsExamples` of the source code and displayed later on this page. These objects communicate through a network connection with the `TmsServer` process running on the TMS System Controller. The TMS System Controller operates as a multi-threaded process and can communicate with multiple clients simultaneously.

The TMS system takes most of its system timing signals from digital timing lines connected to the TMS rack hardware. The only timing information that external software needs to supply is the next cycle number and cycle type information. The cycle number is a 32bit unsigned number identifying the next Proton Synchrotron (PS) machine cycle. The cycle type is an ASCII string defining the type of BEAM present in the PS machine. The cycle type defines a set of state/phase tables to be loaded in order to measure the BEAM in the machine. The CERN client software needs to provide this information by calling the `setNextCycle()` function before the next PS cycle is initiated.

The TMS system keeps a library of state/phase tables indexed by the cycle type. These are loaded into the individual PUPE engines FPGA's during the `CYCLE_STOP` to `CYCLE_START` period. The API provides the `setControlInfo` and `delControlInfo` calls to maintain this database.

A client would generally use the [Tms::TmsProcess](#) object for its interface to the TMS system. It would use `getData()` to fetch the required data from the system. There is also an event based data interface implemented using the `requestData()` call and `dataEvent()` event call.

Each of the TMS API calls return an error object. If there is an error, an appropriate error number will be given together with an ASCII string describing the error.

1.3 BEAM class library

The BEAM class library implements some basic low level classes and is used by the TMS API implementation itself. The main class functionality includes:

- [BString](#) - A simple string class
- [BList](#) - A templated list class
- [BArray](#) - A templated array class
- [BError](#) - An error return class containing an integer and string
- [BSocket](#) - A Network socket access class
- [BThread](#) - A thread implementation class
- [BPoll](#) - A file descriptor event polling class
- [BMutex](#) - A mutex lock
- [BRWLock](#) - A read/write lock
- [BSema](#) - A semaphore
- [BCondInt](#) - An integer condition class
- [BFile](#) - A simple file access class
- [BDir](#) - A simple directory access class
- [BEntry](#) - A name/value pair list class

- [BNameValue](#) - A name/value pair class
- [BRtc](#) - A realtime clock
- [BTimer](#) - A simple timer class
- [BUrl](#) - URL access class

1.4 Examples

There are some examples of client applications using the TmsApi in the **tmsExamples** directory of the source code. A simple Data Access client example is listed below:

```

/*****
 *      TmsDataClient.cpp      TMS API example code for a Data Client
 *      T.Barnaby,           BEAM Ltd,           2007-02-07
 *****/
 *
 *      This is a very basic example of using the TmsApi from a clients perspective.
 *      It is designed to give an overview of using the API.
 */
#include <iostream>
#include <stdio.h>
#include <TmsD.h>
#include <TmsC.h>

using namespace Tms;
using namespace std;

// Function to reads some data
BError tmsTest(TmsProcess& tmsProcess){
    BError          err;
    DataInfo        dataInfo;
    Data            data;
    UInt32          cn = 0;
    BString          ct;

    // Find out the current cycle number and type
    if(err = tmsProcess.getCycleInfo(cn, ct)){
        return err.set(1, BString("Error: Getting Cycle Number: ") + err.getString());
    }

    printf("Getting data for cycles starting at cycle: %u\n", cn);

    for(; ; cn++){
        // Setup dataInfo
        printf("GetData: Cycle Number: %u\n", cn);
        dataInfo.cycleNumber    = cn;
        dataInfo.channel        = 1;
        dataInfo.cyclePeriod    = CyclePeriodEvent0;
        dataInfo.startTime      = 0;
        dataInfo.orbitNumber     = 0;
        dataInfo.bunchNumber    = 0;
        dataInfo.function       = DataFunctionRaw;
        dataInfo.argument        = 0;
        dataInfo.numValues      = 1024;
        dataInfo.beyondPeriod   = 1;

        if(err = tmsProcess.getData(dataInfo, data)){
            return err.set(1, BString("Error: Getting Data: ") + err.getString());
        }
        printf("Data: NumValues: %d\n", data.numValues);
    }
}

```

```

    }

    return err;
}

int main(int argc, char** argv){
    BError      err;
    BString      host = "localhost";
    TmsProcess   tmsProcess;

    if(argc == 2)
        host = argv[1];

    // Connect to the Process service
    if(err = tmsProcess.connectService(BString("/") + host + "/tmsProcess")){
        cerr << "Error: " << err.getString() << "\n";
        return 1;
    }

    // Run a normal data gathering cycle as a normal client would.
    if(err = tmsTest(tmsProcess)){
        cerr << "Error: " << err.getString() << "\n";
        return 1;
    }

    return 0;
}

```

A simple Control client example is listed below:

```

/*****
 *      TmsControlClient1.cpp      TMS API example code
 *
 *      T.Barnaby,      BEAM Ltd,      2007-02-07
 *****/
 *
 *      This is a very basic example of using the TmsApi from a clients perspective.
 *      It is designed to give an overview of using the API.
 */
#include <iostream>
#include <stdio.h>
#include <TmsD.h>
#include <TmsC.h>

using namespace Tms;
using namespace std;

const UInt32    tmsStateNum = 16;
const UInt32    tmsPickupNum = 40;

// Initialise and test the TMS system
BError tmsInit(TmsControl& tmsControl){
    BError      err;
    ConfigInfo   configInfo;
    BIter        i;
    BList<BError>   errorList;
    BList<NameValue>   nvList;
    BString      version;

    // Get Version
    if(err = tmsControl.getVersion(version)){
        return err.set(1, BString("Error: initialising TMS: ") + err.getString());
    }
    cout << "Version: " << version << "\n";

    // Initialise TMS system
    if(err = tmsControl.init()){
        return err.set(1, BString("Error: initialising TMS: ") + err.getString());
    }
}

```

```

    }

    // Test TMS system
    if(err = tmsControl.test(errorList)){
        return err.set(1, BString("Error: testing TMS: ") + err.getString());
    }

    for(errorList.start(i); !errorList.isEnd(i); errorList.next(i)){
        cout << "Warning: " << errorList[i].getString() << "\n";
    }

    // Get Status of TMS system
    if(err = tmsControl.getStatus(nvList)){
        return err.set(1, BString("Error: getting status: ") + err.getString());
    }

    for(nvList.start(i); !nvList.isEnd(i); nvList.next(i)){
        cout << nvList[i].name << ":\t" << nvList[i].value << "\n";
    }

    return err;
}

int main(int argc, char** argv){
    BError          err;
    BString          host = "localhost";
    TmsControl       tmsControl;
    TmsProcess       tmsProcess;

    if(argc == 2)
        host = argv[1];

    // Connect to the Control service
    if(err = tmsControl.connectService(BString("/") + host + "/tmsControl")){
        cerr << "Error: " << err.getString() << "\n";
        return 1;
    }

    // Connect to the Process service
    if(err = tmsProcess.connectService(BString("/") + host + "/tmsProcess")){
        cerr << "Error: " << err.getString() << "\n";
        return 1;
    }

    // Initialise and test the TMS system. Normally carried out by a configuration
    // and test client program.
    if(err = tmsInit(tmsControl)){
        cerr << "Error: " << err.getString() << "\n";
        return 1;
    }

    return 0;
}

```

A simple Control client to set the next cycle information example is listed below:

```

/*****
*      TmsControlClient2.cpp    TMS API example code
*                               T.Barnaby,      BEAM Ltd,      2007-02-07
*****/

*
*      This is a very basic example of using the TmsApi to set the
*      TMS's cycleNumber and cycleType.
*      It is designed to give an overview of using the API.
*/
#include <iostream>
#include <stdio.h>

```

```
#include <unistd.h>
#include <TmsD.h>
#include <TmsC.h>

using namespace Tms;
using namespace std;

// Loop sending next cycle information
BError tmsControlLoop(TmsControl& tmsControl){
    BError          err;
    UInt32          cn = 0;
    BString          ct = "Beam3";

    while(1){
        // Wait for next cycle information
        usleep(1200000);

        // Set next cycle information
        cn = cn + 1;
        ct = "Beam3";

        printf("SendNextCycle\n");
        // Send the next cycle information to the TMS server
        if(err = tmsControl.setNextCycle(cn, ct)){
            cerr << "Error: " << err.getString() << "\n";
        }
    }

    return err;
}

int main(int argc, char** argv){
    BError          err;
    BString          host = "localhost";
    TmsControl       tmsControl;

    if(argc == 2)
        host = argv[1];

    // Connect to the Control service
    if(err = tmsControl.connectService(BString("/") + host + "/tmsControl")){
        cerr << "Error: " << err.getString() << "\n";
        return 1;
    }

    // Set the network priority high
    if(err = tmsControl.setPriority(BSocket::PriorityHigh)){
        cerr << "Error: " << err.getString() << "\n";
        return 1;
    }

    // Set the TmsServer thread priority high
    if(err = tmsControl.setProcessPriority(PriorityHigh)){
        cerr << "Error: " << err.getString() << "\n";
        return 1;
    }

    if(err = tmsControlLoop(tmsControl)){
        cerr << "Error: " << err.getString() << "\n";
        return 1;
    }

    return 0;
}
```

Chapter 2

Directory Hierarchy

2.1 Directories

This directory hierarchy is sorted roughly, but not completely, alphabetically:

beam	21
libBeam	22

Chapter 3

Namespace Index

3.1 Namespace List

Here is a list of all namespaces with brief descriptions:

Boapns	25
Tms	27

Chapter 4

Class Index

4.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

BArray< T >	33
BBuffer	34
BCond	36
BCondBool	37
BCondInt	39
BCondValue	42
BCondWrap	45
BEntry	51
BError	59
BEventError	64
BEvent	62
BEventError	64
BEventInt	65
BEventPipe	67
BFile	69
BIter	73
BList< T >	74
BDir	48
BList< T >::Node	81
BList< BEntry >	74
BEntryList	56
BEntryFile	54
BList< BNameValue< T > >	74
BNameValueList< T >	85
BList< dirent * >	74
BMutex	82
BNameValue< T >	84
Boapns::BoapEntry	90
BoapFuncEntry	91
BoapPacket	93
BoapPacketHead	98
BoapServiceEntry	106

BoapServiceObject	107
BObject	113
BPoll	115
BRefData	118
BRtc	120
BRWLock	124
BSema	126
BSignal	128
BSocket	130
BoapClientObject	86
Boapns::Boapns	92
Tms::PuControl	184
Tms::PuProcess	189
Tms::TmsControl	208
Tms::TmsEvent	216
Tms::TmsProcess	221
BoapClientObject	86
BoapSignalObject	111
BoapSignalObject	111
BSocketAddress	135
BSocketAddressINET	137
BString	140
BThread	148
BoapServer	99
BoapServerConnection	104
BRtcThreaded	122
BTimer	150
BUrl	153
Tms::ConfigInfo	155
Tms::CycleInformation	156
Tms::CycleInformationPeriod	157
Tms::CycleParam	159
Tms::CycleParamEdit	164
Tms::CycleParamDb	162
Tms::CycleParamItem	167
Tms::CycleParamState	168
Tms::CycleTypeInfoInformation	171
Tms::CycleTypeInfoInformationPeriod	172
Tms::Data	174
Tms::DataInfo	176
Tms::DataValue	179
Tms::NameValue	181
Tms::PuChannel	182
Tms::PupeConfig	188
Tms::PuStateTable	191
Tms::PuStatus	193
SigGen	194
SigGenBeam	195
SigGenNoise	197
SigGenPulse	198
SigGenSine	200
SigGenSquare	201

Tms::Simulation	203
vector	205
Tms::TestCaptureInfo	206
Tms::TmsEventServerList	218
Tms::TmsPhase	220
Tms::TmsState	225

Chapter 5

Class Index

5.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

BArray< T >	33
BBuffer	34
BCond	36
BCondBool (Thread conditional boolean)	37
BCondInt (Thread conditional integer)	39
BCondValue (Thread conditional value)	42
BCondWrap	45
BDir (File system directory class)	48
BEntry (Manipulate a name value pair)	51
BEntryFile (File of Entries)	54
BEntryList (List of Entries. Where an entry is a name value pair)	56
BError (Error return class)	59
BEvent (This class provides a base class for all event objects that can be sent over the events interface)	62
BEventError	64
BEventInt (This class provides an interface for sending simple integer events via a file descriptor. This allows threads to send events that can be picked up by the poll system call)	65
BEventPipe (This class provides a base interface for sending events via a pipe. This allows threads to send events that can be picked up by the poll system call)	67
BFile (File operations class)	69
BIter (Iterator for BList)	73
BList< T > (Template based list class)	74
BList< T >::Node	81
BMutex (Mutex class)	82
BNameValue< T >	84
BNameValueList< T >	85
BoapClientObject	86
Boapns::BoapEntry	90
BoapFuncEntry	91
Boapns::Boapns	92
BoapPacket	93
BoapPacketHead	98
BoapServer	99

BoapServerConnection	104
BoapServiceEntry	106
BoapServiceObject	107
BoapSignalObject	111
BObject	113
BPoll (This class provides an interface for polling a number of file descriptors. It uses round robin polling)	115
BRefData (Referenced data storage)	118
BRtc (Realtime clock)	120
BRtcThreaded (Threaded real time clock)	122
BRWLock (Thread read-write locks)	124
BSema (Semaphore class)	126
BSignal	128
BSocket	130
BSocketAddress (Socket Address)	135
BSocketAddressINET (IP aware socket address)	137
BString	140
BThread	148
BTimer (Stopwatch style timer)	150
BUrl (Basic access to a Url)	153
Tms::ConfigInfo (This class describes the configuration of the TMS)	155
Tms::CycleInformation	156
Tms::CycleInformationPeriod (Cycle information)	157
Tms::CycleParam (This class defines the parameters for a PS processing cycle)	159
Tms::CycleParamDb (Internal CycleParameter management class)	162
Tms::CycleParamEdit (Cycle Parameter management class)	164
Tms::CycleParamItem	167
Tms::CycleParamState	168
Tms::CycleTypeInfoInformation	171
Tms::CycleTypeInfoInformationPeriod (Cycle Type information)	172
Tms::Data (This class stores the raw data)	174
Tms::DataInfo (This class defines the data to be acquired and/or fetched)	176
Tms::DataValue (This is the definition of a single data value)	179
Tms::NameValue	181
Tms::PuChannel (This class stores a Physical Pick-Up channel id)	182
Tms::PuControl (This class defines the parameters for a test data capture)	184
Tms::PupeConfig	188
Tms::PuProcess (This interface provides functions to configure and capture data from individual pick-up)	189
Tms::PuStateTable (This class defines the Pick-Up state table)	191
Tms::PuStatus (This class stores the status of an individual Pick-Up)	193
SigGen	194
SigGenBeam	195
SigGenNoise	197
SigGenPulse	198
SigGenSine	200
SigGenSquare	201
Tms::Simulation	203
vector	205
Tms::TestCaptureInfo (This class defines the parameters for a test data capture)	206
Tms::TmsControl (This interface provides functions to control, test and get statistics from the TMS as a whole)	208
Tms::TmsEvent (This interface provides functions for events to be sent to clients from the TMS as a whole)	216

Tms::TmsEventServerList	218
Tms::TmsPhase (The Tms Phase Table Entry)	220
Tms::TmsProcess (This interface provides functions to capture data from the TMS as a whole) .	221
Tms::TmsState (The Tms State entry)	225

Chapter 6

File Index

6.1 File List

Here is a list of all files with brief descriptions:

/src/cern/tms/beam/libBeam/BArray.h	227
/src/cern/tms/beam/libBeam/BBuffer.cpp	228
/src/cern/tms/beam/libBeam/BBuffer.h	229
/src/cern/tms/beam/libBeam/BCond.cpp	230
/src/cern/tms/beam/libBeam/BCond.h	231
/src/cern/tms/beam/libBeam/BCondInt.cpp	232
/src/cern/tms/beam/libBeam/BCondInt.h	233
/src/cern/tms/beam/libBeam/BDir.cpp	234
/src/cern/tms/beam/libBeam/BDir.h	235
/src/cern/tms/beam/libBeam/BEntry.cpp	236
/src/cern/tms/beam/libBeam/BEntry.h	237
/src/cern/tms/beam/libBeam/BError.cpp	238
/src/cern/tms/beam/libBeam/BError.h	239
/src/cern/tms/beam/libBeam/BEvent.cpp	240
/src/cern/tms/beam/libBeam/BEvent.h	241
/src/cern/tms/beam/libBeam/BFile.cpp	242
/src/cern/tms/beam/libBeam/BFile.h	243
/src/cern/tms/beam/libBeam/BList.h	244
/src/cern/tms/beam/libBeam/BList_func.h	245
/src/cern/tms/beam/libBeam/BMutex.cpp	246
/src/cern/tms/beam/libBeam/BMutex.h	247
/src/cern/tms/beam/libBeam/BNameValue.h	248
/src/cern/tms/beam/libBeam/Boap.cpp	249
/src/cern/tms/beam/libBeam/Boap.h	251
/src/cern/tms/beam/libBeam/BoapnsC.cc	253
/src/cern/tms/beam/libBeam/BoapnsC.h	254
/src/cern/tms/beam/libBeam/BoapnsD.cc	255
/src/cern/tms/beam/libBeam/BoapnsD.h	256
/src/cern/tms/beam/libBeam/BoapSimple.cc	257
/src/cern/tms/beam/libBeam/BoapSimple.h	258
/src/cern/tms/beam/libBeam/BObject.cc	260
/src/cern/tms/beam/libBeam/BObject.h	261
/src/cern/tms/beam/libBeam/BPoll-1.cpp	262

/src/cern/tms/beam/libBeam/BPoll.cpp	263
/src/cern/tms/beam/libBeam/BPoll.h	264
/src/cern/tms/beam/libBeam/BRefData.cpp	265
/src/cern/tms/beam/libBeam/BRefData.h	266
/src/cern/tms/beam/libBeam/BRtc.cpp	267
/src/cern/tms/beam/libBeam/BRtc.h	268
/src/cern/tms/beam/libBeam/BRWLock.cpp	269
/src/cern/tms/beam/libBeam/BRWLock.h	270
/src/cern/tms/beam/libBeam/BSema.cpp	271
/src/cern/tms/beam/libBeam/BSema.h	272
/src/cern/tms/beam/libBeam/BSocket.cpp	273
/src/cern/tms/beam/libBeam/BSocket.h	274
/src/cern/tms/beam/libBeam/BString.cpp	275
/src/cern/tms/beam/libBeam/BString.h	276
/src/cern/tms/beam/libBeam/BThread.cpp	277
/src/cern/tms/beam/libBeam/BThread.h	278
/src/cern/tms/beam/libBeam/BTimer.cpp	279
/src/cern/tms/beam/libBeam/BTimer.h	280
/src/cern/tms/beam/libBeam/BTypes.h	281
/src/cern/tms/beam/libBeam/BUrl.cpp	284
/src/cern/tms/beam/libBeam/BUrl.h	285
SigGen.cpp	287
SigGen.h	288
test1.cpp	289
TmsC.cc	290
TmsC.h (This file contains the TmsAPi class definitions)	291
TmsCycleParam-1.cc	293
TmsCycleParam.cc	294
TmsCycleParam.h	295
TmsD.cc	296
TmsD.h	297
TmsEventServerList.cc	299
TmsEventServerList.h	300
TmsLib.cc	302
TmsLib.h	303
TmsS.cc	305
TmsT.cc	306

Chapter 7

Directory Documentation

7.1 /src/cern/tms/beam/ Directory Reference

Directories

- directory [libBeam](#)

7.2 /src/cern/tms/beam/libBeam/ Directory Reference

Files

- file [BArray.h](#)
- file [BBuffer.cpp](#)
- file [BBuffer.h](#)
- file [BCond.cpp](#)
- file [BCond.h](#)
- file [BCondInt.cpp](#)
- file [BCondInt.h](#)
- file [BDir.cpp](#)
- file [BDir.h](#)
- file [BEntry.cpp](#)
- file [BEntry.h](#)
- file [BError.cpp](#)
- file [BError.h](#)
- file [BEvent.cpp](#)
- file [BEvent.h](#)
- file [BFile.cpp](#)
- file [BFile.h](#)
- file [BList.h](#)
- file [BList_func.h](#)
- file [BMutex.cpp](#)
- file [BMutex.h](#)
- file [BNameValue.h](#)
- file [Boap.cpp](#)
- file [Boap.h](#)
- file [BoapnsC.cc](#)
- file [BoapnsC.h](#)
- file [BoapnsD.cc](#)
- file [BoapnsD.h](#)
- file [BoapSimple.cc](#)
- file [BoapSimple.h](#)
- file [BObject.cc](#)
- file [BObject.h](#)
- file [BPoll-1.cpp](#)
- file [BPoll.cpp](#)
- file [BPoll.h](#)
- file [BRefData.cpp](#)
- file [BRefData.h](#)
- file [BRtc.cpp](#)
- file [BRtc.h](#)
- file [BRWLock.cpp](#)
- file [BRWLock.h](#)
- file [BSema.cpp](#)
- file [BSema.h](#)
- file [BSocket.cpp](#)
- file [BSocket.h](#)
- file [BString.cpp](#)

- file [BString.h](#)
- file [BThread.cpp](#)
- file [BThread.h](#)
- file [BTimer.cpp](#)
- file [BTimer.h](#)
- file [BTypes.h](#)
- file [BUrl.cpp](#)
- file [BUrl.h](#)

Chapter 8

Namespace Documentation

8.1 Boapns Namespace Reference

Classes

- class [Boapns](#)
- class [BoapEntry](#)

Functions

- [Boapns](#) ([BString](#) name)
- [BError](#) [getVersion](#) ([BString](#) &version)
- [BError](#) [getEntryList](#) ([BList](#)< [BoapEntry](#) > &entryList)
- [BError](#) [getEntry](#) ([BString](#) name, [BoapEntry](#) &entry)
- [BError](#) [addEntry](#) ([BoapEntry](#) entry)
- [BError](#) [delEntry](#) ([BString](#) name)
- [BError](#) [getNewName](#) ([BString](#) &name)

Variables

- const [BUInt32](#) [apiVersion](#) = 0

8.1.1 Function Documentation

8.1.1.1 BError Boapns::addEntry (BoapEntry *entry*)

8.1.1.2 Boapns::Boapns (BString *name*)

8.1.1.3 BError Boapns::delEntry (BString *name*)

8.1.1.4 BError Boapns::getEntry (BString *name*, BoapEntry & *entry*)

8.1.1.5 BError Boapns::getEntryList (BList< BoapEntry > & *entryList*)

8.1.1.6 BError Boapns::getNewName (BString & *name*)

8.1.1.7 BError Boapns::getVersion (BString & *version*)

8.1.2 Variable Documentation

8.1.2.1 const BUInt32 Boapns::apiVersion = 0

8.2 Tms Namespace Reference

Classes

- class [PuControl](#)
This class defines the parameters for a test data capture.
- class [PuProcess](#)
This interface provides functions to configure and capture data from individual pick-up.
- class [TmsControl](#)
This interface provides functions to control, test and get statistics from the TMS as a whole.
- class [TmsProcess](#)
This interface provides functions to capture data from the TMS as a whole.
- class [TmsEvent](#)
This interface provides functions for events to be sent to clients from the TMS as a whole.
- class [CycleParamState](#)
- class [CycleParamEdit](#)
Cycle Parameter management class.
- class [NameValue](#)
- class [PuChannel](#)
This class stores a Physical Pick-Up channel id.
- class [PuStatus](#)
This class stores the status of an individual Pick-Up.
- class [ConfigInfo](#)
This class describes the configuration of the TMS.
- class [DataInfo](#)
This class defines the data to be acquired and/or fetched.
- class [DataValue](#)
This is the definition of a single data value.
- class [Data](#)
This class stores the raw data.
- class [PuStateTable](#)
This class defines the Pick-Up state table.
- class [CycleParam](#)
This class defines the parameters for a PS processing cycle.
- class [CycleParamItem](#)
- class [TestCaptureInfo](#)

This class defines the parameters for a test data capture.

- class [PupeConfig](#)
- class [CycleInformationPeriod](#)
Cycle information.
- class [CycleInformation](#)
- class [CycleTypeInformationPeriod](#)
Cycle Type information.
- class [CycleTypeInformation](#)
- class [Simulation](#)
- class [TmsEventServerList](#)
- union [TmsState](#)
The [Tms](#) State entry.
- union [TmsPhase](#)
The [Tms](#) Phase Table Entry.
- class [CycleParamDb](#)
Internal CycleParameter management class.

Enumerations

- enum [Errors](#) {
[ErrorOk](#), [ErrorMisc](#), [ErrorWarning](#), [ErrorInit](#),
[ErrorConfig](#), [ErrorParam](#), [ErrorNotImplemented](#), [ErrorComms](#),
[ErrorCommsTimeout](#), [ErrorMC](#), [ErrorFpga](#), [ErrorStateTable](#),
[ErrorCycleNumber](#), [ErrorDataNotAvailable](#), [ErrorDataGone](#), [ErrorDataFuture](#),
[ErrorTimeout](#) }
- enum [CyclePeriod](#) {
[CyclePeriodAll](#), [CyclePeriodCalibration](#), [CyclePeriodEvent0](#), [CyclePeriodEvent1](#),
[CyclePeriodEvent2](#), [CyclePeriodEvent3](#), [CyclePeriodEvent4](#), [CyclePeriodEvent5](#),
[CyclePeriodEvent6](#), [CyclePeriodEvent7](#), [CyclePeriodEvent8](#), [CyclePeriodEvent9](#) }
- enum [DataType](#) { [DataTypeRaw](#) }
- enum [DataFunction](#) {
[DataFunctionRaw](#), [DataFunctionMean](#), [DataFunctionMeanAll](#), [DataFunctionMean0](#),
[DataFunctionMean1](#) }
- enum [TestOutput](#) { [TestOutputFrefLocal](#), [TestOutputPIIL1](#), [TestOutputPIIL2](#) }
- enum [Priority](#) { [PriorityLow](#), [PriorityNormal](#), [PriorityHigh](#) }
- enum [TimingSig](#) {
[TimingSigClock](#) = 0x01, [TimingSigCycleStart](#) = 0x02, [TimingSigCycleStop](#) = 0x04, [TimingSigCal-](#)
[Start](#) = 0x08,
[TimingSigCalStop](#) = 0x10, [TimingSigInjection](#) = 0x20, [TimingSigHChange](#) = 0x40, [TimingSigFRef](#)
= 0x80 }
The timing signal bits.

- enum `CaptureClock` {
`ClkAdcDiv_1` = 0x00, `ClkAdcDiv_2` = 0x01, `ClkAdcDiv_5` = 0x02, `ClkAdcDiv_10` = 0x03,
`ClkAdcDiv_20` = 0x04, `ClkAdcDiv_50` = 0x05, `ClkAdcDiv_100` = 0x06, `ClkAdcDiv_200` = 0x07,
`ClkAdcDiv_500` = 0x08, `ClkAdcDiv_1000` = 0x09, `ClkAdcDiv_2000` = 0x0A, `ClkAdcDiv_5000` =
0x0B,
`ClkAdcDiv_10000` = 0x0C, `ClkAdcDiv_20000` = 0x0D, `ClkAdcDiv_50000` = 0x0E, `ClkAdcDiv_-`
`100000` = 0x0F,
`ClkMs` = 0x10, `ClkFref` = 0x11 }

The Diagnostics Capture Clock settings.

Variables

- const `BUInt32 apiVersion` = 0
- const unsigned int `tmsNumPickups` = 40
The default number of pick ups.
- const unsigned int `tmsPhaseTableSize` = 512
The size of the Phase Table.

8.2.1 Enumeration Type Documentation

8.2.1.1 enum Tms::CaptureClock

The Diagnostics Capture Clock settings.

Enumerator:

ClkAdcDiv_1 ADC Clock.
ClkAdcDiv_2 ADC Clock divided by 2.
ClkAdcDiv_5 ADC Clock divided by 5.
ClkAdcDiv_10 ADC Clock divided by 10.
ClkAdcDiv_20 ADC Clock divided by 20.
ClkAdcDiv_50 ADC Clock divided by 50.
ClkAdcDiv_100 ADC Clock divided by 100.
ClkAdcDiv_200 ADC Clock divided by 200.
ClkAdcDiv_500 ADC Clock divided by 500.
ClkAdcDiv_1000 ADC Clock divided by 1000.
ClkAdcDiv_2000 ADC Clock divided by 2000.
ClkAdcDiv_5000 ADC Clock divided by 5000.
ClkAdcDiv_10000 ADC Clock divided by 10000.
ClkAdcDiv_20000 ADC Clock divided by 20000.
ClkAdcDiv_50000 ADC Clock divided by 50000.
ClkAdcDiv_100000 ADC Clock divided by 100000.
ClkMs Millisecond Clock.
ClkFref FREF.

8.2.1.2 enum Tms::CyclePeriod**Enumerator:**

CyclePeriodAll
CyclePeriodCalibration
CyclePeriodEvent0
CyclePeriodEvent1
CyclePeriodEvent2
CyclePeriodEvent3
CyclePeriodEvent4
CyclePeriodEvent5
CyclePeriodEvent6
CyclePeriodEvent7
CyclePeriodEvent8
CyclePeriodEvent9

8.2.1.3 enum Tms::DataFunction**Enumerator:**

DataFunctionRaw
DataFunctionMean
DataFunctionMeanAll
DataFunctionMean0
DataFunctionMean1

8.2.1.4 enum Tms::DataType**Enumerator:**

DataTypeRaw

8.2.1.5 enum Tms::Errors**Enumerator:**

ErrorOk
ErrorMisc
ErrorWarning
ErrorInit
ErrorConfig
ErrorParam
ErrorNotImplemented
ErrorComms

ErrorCommsTimeout

ErrorMC

ErrorFpga

ErrorStateTable

ErrorCycleNumber

ErrorDataNotAvailable

ErrorDataGone

ErrorDataFuture

ErrorTimeout

8.2.1.6 enum Tms::Priority

Enumerator:

PriorityLow

PriorityNormal

PriorityHigh

8.2.1.7 enum Tms::TestOutput

Enumerator:

TestOutputFrefLocal

TestOutputPllL1

TestOutputPllL2

8.2.1.8 enum Tms::TimingSig

The timing signal bits.

Enumerator:

TimingSigClock 10MHz System Clock

TimingSigCycleStart CYCLE_START event.

TimingSigCycleStop CYCLE_STOP event.

TimingSigCalStart CAL_START event.

TimingSigCalStop CAL_STOP event.

TimingSigInjection INJECTION event.

TimingSigHChange HCHANGE event.

TimingSigFref FREF signal.

8.2.2 Variable Documentation

8.2.2.1 `const BUInt32 Tms::apiVersion = 0`

8.2.2.2 `const unsigned int Tms::tmsNumPickups = 40`

The default number of pick ups.

8.2.2.3 `const unsigned int Tms::tmsPhaseTableSize = 512`

The size of the Phase Table.

Chapter 9

Class Documentation

9.1 BArray< T > Class Template Reference

```
#include <BArray.h>
```

Public Member Functions

- [BArray \(\)](#)
- [BArray \(BSize size, T value=T\(\)\)](#)
- [BArray \(const BArray &array\)](#)

9.1.1 Detailed Description

template<class T> class BArray< T >

Template based Array class. This is based on the Standard C++ library vector class and has all of the functionality of that class.

9.1.2 Constructor & Destructor Documentation

9.1.2.1 template<class T> BArray< T >::BArray () [inline]

9.1.2.2 template<class T> BArray< T >::BArray (BSize *size*, T *value* = T()) [inline]

9.1.2.3 template<class T> BArray< T >::BArray (const BArray< T > & *array*) [inline]

The documentation for this class was generated from the following file:

- /src/cern/tms/beam/libBeam/[BArray.h](#)

9.2 BBuffer Class Reference

```
#include <BBuffer.h>
```

Public Member Functions

- [BBuffer \(\)](#)
Create and manipulate a data buffer. On creation the buffer size defaults to 1024 bytes.
- [~BBuffer \(\)](#)
- [int setSize \(uint32_t size\)](#)
Sets the bufer size.
- [int setData \(const void *data, uint32_t size\)](#)
Sets buffer data resized to contain the data.
- [int writeData \(uint32_t pos, const void *data, uint32_t size\)](#)
Writes data into buffer from offset pos.
- [void * data \(\)](#)
The data.
- [uint32_t size \(\)](#)
Size of the buffer in bytes.

Private Attributes

- [uint32_t osize](#)
- [uint32_t odatasize](#)
- [void * odata](#)

9.2.1 Constructor & Destructor Documentation

9.2.1.1 BBuffer::BBuffer ()

Create and manipulate a data buffer. On creation the buffer size defaults to 1024 bytes.

9.2.1.2 BBuffer::~~BBuffer ()

9.2.2 Member Function Documentation

9.2.2.1 int BBuffer::setSize (uint32_t size)

Sets the bufer size.

9.2.2.2 int BBuffer::setData (const void * data, uint32_t size)

Sets buffer data resized to contain the data.

9.2.2.3 int BBuffer::writeData (uint32_t pos, const void * data, uint32_t size)

Writes data into buffer from offset pos.

9.2.2.4 void * BBuffer::data ()

The data.

9.2.2.5 uint32_t BBuffer::size ()

Size of the buffer in bytes.

9.2.3 Member Data Documentation**9.2.3.1 uint32_t BBuffer::osize [private]****9.2.3.2 uint32_t BBuffer::odatasize [private]****9.2.3.3 void* BBuffer::odata [private]**

The documentation for this class was generated from the following files:

- [/src/cern/tms/beam/libBeam/BBuffer.h](#)
- [/src/cern/tms/beam/libBeam/BBuffer.cpp](#)

9.3 BCond Class Reference

```
#include <BCond.h>
```

Public Member Functions

- [BCond \(\)](#)
Thread conditional variable.
- [~BCond \(\)](#)
- [int signal \(\)](#)
- [int wait \(\)](#)
- [int timedWait \(int timeOutUs\)](#)

Private Attributes

- `pthread_mutex_t` [omutex](#)
- `pthread_cond_t` [ocond](#)

9.3.1 Constructor & Destructor Documentation

9.3.1.1 BCond::BCond ()

Thread conditional variable.

9.3.1.2 BCond::~~BCond ()

9.3.2 Member Function Documentation

9.3.2.1 int BCond::signal ()

9.3.2.2 int BCond::wait ()

9.3.2.3 int BCond::timedWait (int *timeOutUs*)

9.3.3 Member Data Documentation

9.3.3.1 pthread_mutex_t BCond::omutex [private]

9.3.3.2 pthread_cond_t BCond::ocond [private]

The documentation for this class was generated from the following files:

- [/src/cern/tms/beam/libBeam/BCond.h](#)
- [/src/cern/tms/beam/libBeam/BCond.cpp](#)

9.4 BCondBool Class Reference

Thread conditional boolean.

```
#include <BCondInt.h>
```

Public Member Functions

- [BCondBool \(\)](#)
- [~BCondBool \(\)](#)
- [int set \(\)](#)
Set value. Wakes waiting.
- [int clear \(\)](#)
Clear Value.
- [int value \(\)](#)
Current value.
- [int wait \(\)](#)
Wait until value is true.
- [int timedWait \(int timeOutUs\)](#)
Wait until set, with timeout.

Private Attributes

- `pthread_mutex_t` [omutex](#)
- `pthread_cond_t` [ocond](#)
- `int` [ovalue](#)

9.4.1 Detailed Description

Thread conditional boolean.

9.4.2 Constructor & Destructor Documentation

9.4.2.1 BCondBool::BCondBool ()

9.4.2.2 BCondBool::~~BCondBool ()

9.4.3 Member Function Documentation

9.4.3.1 int BCondBool::set ()

Set value. Wakes waiting.

9.4.3.2 `int BCondBool::clear ()`

Clear Value.

9.4.3.3 `int BCondBool::value ()`

Current value.

9.4.3.4 `int BCondBool::wait ()`

Wait until value is true.

9.4.3.5 `int BCondBool::timedWait (int timeOutUs)`

Wait until set, with timeout.

9.4.4 Member Data Documentation

9.4.4.1 `pthread_mutex_t BCondBool::omutex` [private]

9.4.4.2 `pthread_cond_t BCondBool::ocond` [private]

9.4.4.3 `int BCondBool::ovalue` [private]

The documentation for this class was generated from the following files:

- [/src/cern/tms/beam/libBeam/BCondInt.h](#)
- [/src/cern/tms/beam/libBeam/BCondInt.cpp](#)

9.5 BCondInt Class Reference

Thread conditional integer.

```
#include <BCondInt.h>
```

Public Member Functions

- [BCondInt](#) ()
- [~BCondInt](#) ()
- void [setValue](#) (int value)
Set value.
- int [increment](#) ()
Increment.
- int [decrement](#) ()
Decrement.
- int [value](#) ()
Current value.
- int [wait](#) ()
Wait until value is 0.
- int [waitIncrement](#) (int timeOutUs=0)
Wait until value is 0 then increment.
- int [waitNotZero](#) ()
Wait until value is not 0.
- int [waitNotZeroDecrement](#) ()
Wait until value is not 0 and then decrement.
- int [tryNotZeroDecrement](#) ()
Test if value is not 0, if not zero then decrement.
- int [timedWait](#) (int timeOutUs)
Wait for the condition, with timeout.
- void [operator++](#) (int)
- void [operator--](#) (int)

Private Attributes

- pthread_mutex_t [omutex](#)
- pthread_cond_t [ocond](#)
- int [ovalue](#)

9.5.1 Detailed Description

Thread conditional integer.

9.5.2 Constructor & Destructor Documentation

9.5.2.1 BCondInt::BCondInt ()

9.5.2.2 BCondInt::~~BCondInt ()

9.5.3 Member Function Documentation

9.5.3.1 void BCondInt::setValue (int *value*)

Set value.

9.5.3.2 int BCondInt::increment ()

Increment.

9.5.3.3 int BCondInt::decrement ()

Decrement.

9.5.3.4 int BCondInt::value ()

Current value.

9.5.3.5 int BCondInt::wait ()

Wait until value is 0.

9.5.3.6 int BCondInt::waitIncrement (int *timeOutUs* = 0)

Wait until value is 0 then increment.

9.5.3.7 int BCondInt::waitNotZero ()

Wait until value is not 0.

9.5.3.8 int BCondInt::waitNotZeroDecrement ()

Wait until value is not 0 and then decrement.

9.5.3.9 int BCondInt::tryNotZeroDecrement ()

Test if value is not 0, if not zero then decrement.

9.5.3.10 int BCondInt::timedWait (int *timeOutUs*)

Wait for the condition, with timeout.

9.5.3.11 void BCondInt::operator++ (int) [inline]

9.5.3.12 void BCondInt::operator-- (int) [inline]

9.5.4 Member Data Documentation

9.5.4.1 pthread_mutex_t BCondInt::omutex [private]

9.5.4.2 pthread_cond_t BCondInt::ocond [private]

9.5.4.3 int BCondInt::ovalue [private]

The documentation for this class was generated from the following files:

- [/src/cern/tms/beam/libBeam/BCondInt.h](#)
- [/src/cern/tms/beam/libBeam/BCondInt.cpp](#)

9.6 BCondValue Class Reference

Thread conditional value.

```
#include <BCondInt.h>
```

Public Member Functions

- [BCondValue](#) ()
- [~BCondValue](#) ()
- void [setValue](#) (int value)
Set the value. Wakes waiting.
- int [value](#) ()
Current value.
- int [increment](#) (int v=1)
Increment. Wakes waiting.
- int [decrement](#) (int v=1)
Decrement. Wakes waiting.
- int [waitMoreThanOrEqual](#) (int v, int decrement=0, int timeOutUs=0)
Wait until value is at least the value given.
- int [waitLessThanOrEqual](#) (int v, int increment=0, int timeOutUs=0)
Wait until value is equal to or below the value given.
- int [waitLessThan](#) (int v, int timeOutUs=0)
Wait until value is equal to or below the value given.
- void [operator+=](#) (int v)
Add to value. Wakes waiting.
- void [operator-=](#) (int v)
Subtract from value. Wakes waiting.
- void [operator++](#) (int)
Increment value. Wakes waiting.
- void [operator--](#) (int)
Decrement value. Wakes waiting.

Private Attributes

- pthread_mutex_t [omutex](#)
- pthread_cond_t [ocond](#)
- int [ovalue](#)

9.6.1 Detailed Description

Thread conditional value.

9.6.2 Constructor & Destructor Documentation

9.6.2.1 BCondValue::BCondValue ()

9.6.2.2 BCondValue::~~BCondValue ()

9.6.3 Member Function Documentation

9.6.3.1 void BCondValue::setValue (int *value*)

Set the value. Wakes waiting.

9.6.3.2 int BCondValue::value ()

Current value.

9.6.3.3 int BCondValue::increment (int *v* = 1)

Increment. Wakes waiting.

9.6.3.4 int BCondValue::decrement (int *v* = 1)

Decrement. Wakes waiting.

9.6.3.5 int BCondValue::waitMoreThanOrEqual (int *v*, int *decrement* = 0, int *timeOutUs* = 0)

Wait until value is at least the value given.

9.6.3.6 int BCondValue::waitLessThanOrEqual (int *v*, int *increment* = 0, int *timeOutUs* = 0)

Wait until value is equal to or below the value given.

9.6.3.7 int BCondValue::waitLessThan (int *v*, int *timeOutUs* = 0)

Wait until value is equal to or below the value given.

9.6.3.8 void BCondValue::operator+= (int *v*) [inline]

Add to value. Wakes waiting.

9.6.3.9 void BCondValue::operator-= (int *v*) [inline]

Subtract from value. Wakes waiting.

9.6.3.10 void BCondValue::operator++ (int) [inline]

Increment value. Wakes waiting.

9.6.3.11 void BCondValue::operator-- (int) [inline]

Decrement value. Wakes waiting.

9.6.4 Member Data Documentation**9.6.4.1 pthread_mutex_t BCondValue::omutex [private]****9.6.4.2 pthread_cond_t BCondValue::ocond [private]****9.6.4.3 int BCondValue::ovalue [private]**

The documentation for this class was generated from the following files:

- [/src/cern/tms/beam/libBeam/BCondInt.h](#)
- [/src/cern/tms/beam/libBeam/BCondInt.cpp](#)

9.7 BCondWrap Class Reference

```
#include <BCondInt.h>
```

Public Member Functions

- [BCondWrap](#) ()
- [~BCondWrap](#) ()
- void [setValue](#) (uint32_t value)
Set the value. Wakes waiting.
- uint32_t [value](#) ()
Current value.
- uint32_t [increment](#) (uint32_t v=1)
Increment. Wakes waiting.
- uint32_t [decrement](#) (uint32_t v=1)
Decrement. Wakes waiting.
- int [waitMoreThanOrEqual](#) (uint32_t v, uint32_t decrement=0, uint32_t timeOutUs=0)
Wait until value is at least the value given.
- int [waitLessThanOrEqual](#) (uint32_t v, uint32_t increment=0, uint32_t timeOutUs=0)
Wait until value is equal to or below the value given.
- int [waitLessThan](#) (uint32_t v, uint32_t timeOutUs=0)
Wait until value is equal to or below the value given.
- void [operator+=](#) (int v)
Add to value. Wakes waiting.
- void [operator-=](#) (int v)
Subtract from value. Wakes waiting.
- void [operator++](#) (int)
Increment value. Wakes waiting.
- void [operator--](#) (int)
Decrement value. Wakes waiting.

Private Member Functions

- int [diff](#) (uint32_t v)

Private Attributes

- pthread_mutex_t [omutex](#)
- pthread_cond_t [ocond](#)
- uint32_t [ovalue](#)

9.7.1 Constructor & Destructor Documentation

9.7.1.1 BCondWrap::BCondWrap ()

9.7.1.2 BCondWrap::~~BCondWrap ()

9.7.2 Member Function Documentation

9.7.2.1 void BCondWrap::setValue (uint32_t *value*)

Set the value. Wakes waiting.

9.7.2.2 uint32_t BCondWrap::value ()

Current value.

9.7.2.3 uint32_t BCondWrap::increment (uint32_t *v* = 1)

Increment. Wakes waiting.

9.7.2.4 uint32_t BCondWrap::decrement (uint32_t *v* = 1)

Decrement. Wakes waiting.

9.7.2.5 int BCondWrap::waitMoreThanOrEqual (uint32_t *v*, uint32_t *decrement* = 0, uint32_t *timeOutUs* = 0)

Wait until value is at least the value given.

9.7.2.6 int BCondWrap::waitLessThanOrEqual (uint32_t *v*, uint32_t *increment* = 0, uint32_t *timeOutUs* = 0)

Wait until value is equal to or below the value given.

9.7.2.7 int BCondWrap::waitLessThan (uint32_t *v*, uint32_t *timeOutUs* = 0)

Wait until value is equal to or below the value given.

9.7.2.8 void BCondWrap::operator+=(int *v*) [inline]

Add to value. Wakes waiting.

9.7.2.9 void BCondWrap::operator-= (int v) [inline]

Subtract from value. Wakes waiting.

9.7.2.10 void BCondWrap::operator++ (int) [inline]

Increment value. Wakes waiting.

9.7.2.11 void BCondWrap::operator- (int) [inline]

Decrement value. Wakes waiting.

9.7.2.12 int BCondWrap::diff (uint32_t v) [private]**9.7.3 Member Data Documentation****9.7.3.1 pthread_mutex_t BCondWrap::omutex [private]****9.7.3.2 pthread_cond_t BCondWrap::ocond [private]****9.7.3.3 uint32_t BCondWrap::ovalue [private]**

The documentation for this class was generated from the following files:


- [/src/cern/tms/beam/libBeam/BCondInt.h](#)
- [/src/cern/tms/beam/libBeam/BCondInt.cpp](#)

9.8 BDir Class Reference

File system directory class.

```
#include <BDir.h>
```

Inheritance diagram for BDir::



Public Member Functions

- [BDir](#) ()
- [BDir](#) ([BString](#) name)
- [~BDir](#) ()
- [BError open](#) ([BString](#) name)
Reads named directory.
- [BError error](#) ()
Current value of error.
- [BError read](#) ()
read/re-reads directory
- void [clear](#) ()
Clears list.
- void [setWild](#) ([BString](#) wild)
Set wildcard filter string used on read.
- void [setSort](#) (int on)
Set alpha sort on/off.
- [BString entryName](#) ([BIter](#) i)
Get filename.
- struct stat [entryStat](#) ([BIter](#) i)
Get file stats.
- struct stat64 [entryStat64](#) ([BIter](#) i)
Get file stats 64.

Private Attributes

- [BError oerror](#)
- [BString odirname](#)
- [BString owild](#)
- [int osort](#)

9.8.1 Detailed Description

File system directory class.

9.8.2 Constructor & Destructor Documentation

9.8.2.1 BDir::BDir ()

9.8.2.2 BDir::BDir (BString *name*)

9.8.2.3 BDir::~~BDir ()

9.8.3 Member Function Documentation

9.8.3.1 BError BDir::open (BString *name*)

Reads named directory.

9.8.3.2 BError BDir::error ()

Current value of error.

9.8.3.3 BError BDir::read ()

read/re-reads directory

9.8.3.4 void BDir::clear () [virtual]

Clears list.

Reimplemented from [BList< T >](#).

9.8.3.5 void BDir::setWild (BString *wild*)

Set wildcard filter string used on read.

9.8.3.6 void BDir::setSort (int *on*)

Set alpha sort on/off.

9.8.3.7 BString BDir::entryName (BIter *i*)

Get filename.

9.8.3.8 struct stat BDir::entryStat (BIter *i*) [read]

Get file stats.

9.8.3.9 struct stat64 BDir::entryStat64 (BIter *i*) [read]

Get file stats 64.

9.8.4 Member Data Documentation

9.8.4.1 BError BDir::oerror [private]

9.8.4.2 BString BDir::odirname [private]

9.8.4.3 BString BDir::owild [private]

9.8.4.4 int BDir::osort [private]

The documentation for this class was generated from the following files:

- [/src/cern/tms/beam/libBeam/BDir.h](#)
- [/src/cern/tms/beam/libBeam/BDir.cpp](#)

9.9 BEntry Class Reference

Manipulate a name value pair.

```
#include <BEntry.h>
```

Public Member Functions

- [BEntry](#) ()
- [BEntry](#) ([BString](#) name, [BString](#) value)
Set name and value.
- [BEntry](#) ([BString](#) line)
Set name and value from white space delimited string.
- [BString](#) [getName](#) ()
Get the name.
- [BString](#) [getValue](#) ()
Get the value.
- void [setLine](#) ([BString](#) line)
Set name and value from white space delimited string.
- void [setName](#) ([BString](#) name)
Set the name.
- void [setValue](#) ([BString](#) value)
Set the value.
- [BString](#) [line](#) ()
Return name and value as padded single string.
- void [print](#) ()
Print name and value.

Private Attributes

- [BString](#) [oname](#)
- [BString](#) [ovalue](#)

9.9.1 Detailed Description

Manipulate a name value pair.

9.9.2 Constructor & Destructor Documentation

9.9.2.1 BEntry::BEntry ()

9.9.2.2 BEntry::BEntry (BString *name*, BString *value*)

Set name and value.

9.9.2.3 BEntry::BEntry (BString *line*)

Set name and value from white space delimited string.

9.9.3 Member Function Documentation

9.9.3.1 BString BEntry::getName ()

Get the name.

9.9.3.2 BString BEntry::getValue ()

Get the value.

9.9.3.3 void BEntry::setLine (BString *line*)

Set name and value from white space delimited string.

9.9.3.4 void BEntry::setName (BString *name*)

Set the name.

9.9.3.5 void BEntry::setValue (BString *value*)

Set the value.

9.9.3.6 BString BEntry::line ()

Return name and value as padded single string.

9.9.3.7 void BEntry::print ()

Print name and value.

9.9.4 Member Data Documentation

9.9.4.1 BString BEntry::oname [private]

9.9.4.2 BString BEntry::ovalue [private]

The documentation for this class was generated from the following files:


- [/src/cern/tms/beam/libBeam/BEntry.h](#)
- [/src/cern/tms/beam/libBeam/BEntry.cpp](#)

9.10 BEntryFile Class Reference

File of Entries.

```
#include <BEntry.h>
```

Inheritance diagram for BEntryFile::



Public Member Functions

- [BEntryFile \(\)](#)
- [BEntryFile \(BString filename\)](#)
Opens entryfile.
- [~BEntryFile \(\)](#)
- [int open \(BString filename\)](#)
Opens entryfile.
- [int read \(\)](#)
Reads entry file and builds list.
- [int write \(\)](#)
Writes list to entryfile.
- [int writeList \(BEntryList &l\)](#)
Writes specified list to file.
- [void clear \(\)](#)
Clears current list.

Private Attributes

- [BString ofilename](#)
- [BString ocomments](#)

9.10.1 Detailed Description

File of Entries.

9.10.2 Constructor & Destructor Documentation

9.10.2.1 BEntryFile::BEntryFile ()

9.10.2.2 BEntryFile::BEntryFile (BString *filename*)

Opens entryfile.

9.10.2.3 BEntryFile::~~BEntryFile ()

9.10.3 Member Function Documentation

9.10.3.1 int BEntryFile::open (BString *filename*)

Opens entryfile.

9.10.3.2 int BEntryFile::read ()

Reads entry file and builds list.

9.10.3.3 int BEntryFile::write ()

Writes list to entryfile.

9.10.3.4 int BEntryFile::writeList (BEntryList & *l*)

Writes specified list to file.

9.10.3.5 void BEntryFile::clear () [virtual]

Clears current list.

Reimplemented from [BEntryList](#).

9.10.4 Member Data Documentation

9.10.4.1 BString BEntryFile::ofilename [private]

9.10.4.2 BString BEntryFile::ocomments [private]

The documentation for this class was generated from the following files:


- /src/cern/tms/beam/libBeam/[BEntry.h](#)
- /src/cern/tms/beam/libBeam/[BEntry.cpp](#)

9.11 BEntryList Class Reference

List of Entries. Where an entry is a name value pair.

```
#include <BEntry.h>
```

Inheritance diagram for BEntryList::



Public Member Functions

- [BEntryList](#) ()
- [int isSet](#) ([BString](#) name)
1 if name is in list and value is set
- [BEntry *](#) [find](#) ([BString](#) name)
Returns entry if name is found otherwise NULL.
- [BString](#) [findValue](#) ([BString](#) name)
Returns value of name. Returns "" if name not found.
- [int setValue](#) ([BString](#) name, [BString](#) value)
Set the value of name. Returns 0 if name not found.
- [int setValueRaw](#) ([BString](#) name, [BString](#) value)
Raw setting of value without looking up existing entry.
- [void deleteEntry](#) ([BString](#) name)
Deletes the entry.
- [void print](#) ()
Print list.
- [BString](#) [getString](#) ()
Return list as string. Each Entry padded and on a new line.
- [void insert](#) ([BIter](#) &i, const [BEntry](#) &item)
Insert item before item.
- [void del](#) ([BIter](#) &i)
Delete specified item.
- [void clear](#) ()
Clear the list.

Private Attributes

- [BIter olastPos](#)

9.11.1 Detailed Description

List of Entries. Where an entry is a name value pair.

9.11.2 Constructor & Destructor Documentation

9.11.2.1 BEntryList::BEntryList ()

9.11.3 Member Function Documentation

9.11.3.1 int BEntryList::isSet (BString *name*)

1 if name is in list and value is set

9.11.3.2 BEntry * BEntryList::find (BString *name*)

Returns entry if name is found otherwise NULL.

9.11.3.3 BString BEntryList::findValue (BString *name*)

Returns value of name. Returns "" if name not found.

9.11.3.4 int BEntryList::setValue (BString *name*, BString *value*)

Set the value of name. Returns 0 if name not found.

9.11.3.5 int BEntryList::setValueRaw (BString *name*, BString *value*)

Raw setting of value without looking up existing entry.

9.11.3.6 void BEntryList::deleteEntry (BString *name*)

Deletes the entry.

9.11.3.7 void BEntryList::print ()

Print list.

9.11.3.8 BString BEntryList::getString ()

Return list as string. Each Entry padded and on a new line.

9.11.3.9 void BEntryList::insert (BIter & *i*, const BEntry & *item*) [virtual]

Insert item before item.

Reimplemented from [BList< BEntry >](#).

9.11.3.10 void BEntryList::del (BIter & *i*) [virtual]

Delete specified item.

Reimplemented from [BList< BEntry >](#).

9.11.3.11 void BEntryList::clear () [virtual]

Clear the list.

Reimplemented from [BList< BEntry >](#).

Reimplemented in [BEntryFile](#).

9.11.4 Member Data Documentation**9.11.4.1 BIter BEntryList::olastPos** [private]

The documentation for this class was generated from the following files:


- [/src/cern/tms/beam/libBeam/BEntry.h](#)
- [/src/cern/tms/beam/libBeam/BEntry.cpp](#)

9.12 BError Class Reference

Error return class.

```
#include <BError.h>
```

Inheritance diagram for BError::



Public Types

- enum `Type` { `NONE` = 0, `ERROR` = 1 }

Public Member Functions

- `BError` (int errNo=`NONE`, `BString` errStr="")
Create object.
- `BError` (`BString` errStr)
Create with error set and error string.
- `BError` copy ()
Return an independant copy.
- `BError` & `set` (int errNo, `BString` errStr="")
Set error number and message.
- `BError` & `setError` (`BString` errStr="")
Set error type ERROR with optional message.
- `BString` `getString` () const
Get error message.
- int `getErrorNo` () const
Get The error number.
- `operator int` () const
Return error number.

Private Attributes

- int `oerrNo`
- `BString` `oerrStr`

9.12.1 Detailed Description

Error return class.

9.12.2 Member Enumeration Documentation

9.12.2.1 enum BError::Type

Enumerator:

NONE

ERROR

9.12.3 Constructor & Destructor Documentation

9.12.3.1 BError::BError (int *errNo* = NONE, BString *errStr* = "")

Create object.

9.12.3.2 BError::BError (BString *errStr*)

Create with error set and error string.

9.12.4 Member Function Documentation

9.12.4.1 BError BError::copy ()

Return an independant copy.

9.12.4.2 BError & BError::set (int *errNo*, BString *errStr* = "")

Set error number and message.

9.12.4.3 BError & BError::setError (BString *errStr* = "")

Set error type ERROR with optional message.

9.12.4.4 BString BError::getString () const

Get error message.

9.12.4.5 int BError::getErrorNo () const

Get The error number.

9.12.4.6 BError::operator int () const

Return error number.

9.12.5 Member Data Documentation

9.12.5.1 int BError::oerrNo [private]

9.12.5.2 BString BError::oerrStr [private]

The documentation for this class was generated from the following files:


- [/src/cern/tms/beam/libBeam/BError.h](#)
- [/src/cern/tms/beam/libBeam/BError.cpp](#)

9.13 BEvent Class Reference

This class provides a base class for all event objects that can be sent over the events interface.

```
#include <BEvent.h>
```

Inheritance diagram for BEvent::



Public Member Functions

- [BEvent](#) (uint32_t type)
- virtual [~BEvent](#) ()
- uint32_t [getType](#) ()
- virtual [BError](#) [getBinary](#) (void *data, uint32_t &size)
- virtual [BError](#) [setBinary](#) (void *data, uint32_t &size)

Private Attributes

- uint32_t [otype](#)
The event type.

9.13.1 Detailed Description

This class provides a base class for all event objects that can be sent over the events interface.

9.13.2 Constructor & Destructor Documentation

9.13.2.1 [BEvent::BEvent](#) (uint32_t type)

9.13.2.2 [BEvent::~~BEvent](#) () [virtual]

9.13.3 Member Function Documentation

9.13.3.1 [uint32_t BEvent::getType](#) ()

9.13.3.2 [BError BEvent::getBinary](#) (void * data, uint32_t & size) [virtual]

Reimplemented in [BEventError](#).

9.13.3.3 [BError BEvent::setBinary](#) (void * data, uint32_t & size) [virtual]

Reimplemented in [BEventError](#).

9.13.4 Member Data Documentation

9.13.4.1 uint32_t BEvent::otype [private]

The event type.


The documentation for this class was generated from the following files:

- [/src/cern/tms/beam/libBeam/BEvent.h](#)
- [/src/cern/tms/beam/libBeam/BEvent.cpp](#)

9.14 BEventError Class Reference

```
#include <BEvent.h>
```

Inheritance diagram for BEventError::



Public Member Functions

- [BEventError](#) (int errNo=NONE, [BString](#) errStr="")
- [BError](#) [getBinary](#) (void *data, uint32_t &size)
- [BError](#) [setBinary](#) (void *data, uint32_t &size)

9.14.1 Constructor & Destructor Documentation

9.14.1.1 [BEventError::BEventError](#) (int *errNo* = NONE, [BString](#) *errStr* = "")

9.14.2 Member Function Documentation

9.14.2.1 [BError](#) [BEventError::getBinary](#) (void **data*, uint32_t &*size*) [virtual]

Reimplemented from [BEvent](#).

9.14.2.2 [BError](#) [BEventError::setBinary](#) (void **data*, uint32_t &*size*) [virtual]

Reimplemented from [BEvent](#).

The documentation for this class was generated from the following files:

- /src/cern/tms/beam/libBeam/[BEvent.h](#)
- /src/cern/tms/beam/libBeam/[BEvent.cpp](#)

9.15 BEventInt Class Reference

This class provides an interface for sending simple integer events via a file descriptor. This allows threads to send events that can be picked up by the poll system call.

```
#include <BEvent.h>
```

Public Member Functions

- [BEventInt \(\)](#)
- [~BEventInt \(\)](#)
- [BError sendEvent \(int event\)](#)
Send an event.
- [BError getEvent \(int &event, int timeOutUs=-1\)](#)
Receive the event.
- [int getFd \(\)](#)

Private Attributes

- [int ofds \[2\]](#)
File descriptors for pipe.

9.15.1 Detailed Description

This class provides an interface for sending simple integer events via a file descriptor. This allows threads to send events that can be picked up by the poll system call.

9.15.2 Constructor & Destructor Documentation

9.15.2.1 BEventInt::BEventInt ()

9.15.2.2 BEventInt::~~BEventInt ()

9.15.3 Member Function Documentation

9.15.3.1 BError BEventInt::sendEvent (int event)

Send an event.

9.15.3.2 BError BEventInt::getEvent (int & event, int timeOutUs = -1)

Receive the event.

9.15.3.3 int BEventInt::getFd ()

9.15.4 Member Data Documentation

9.15.4.1 int BEventInt::ofds[2] [private]

File descriptors for pipe.

The documentation for this class was generated from the following files:

- [/src/cern/tms/beam/libBeam/BEvent.h](#)
- [/src/cern/tms/beam/libBeam/BEvent.cpp](#)

9.16 BEventPipe Class Reference

This class provides a base interface for sending events via a pipe. This allows threads to send events that can be picked up by the poll system call.

```
#include <BEvent.h>
```

Public Member Functions

- [BEventPipe \(\)](#)
- [~BEventPipe \(\)](#)
- [BError sendEvent \(BEvent *event\)](#)
Send an event.
- [BError getEvent \(BEvent *event, int timeOutUs=-1\)](#)
Receive the event.
- [int getReceiveFd \(\)](#)
returns the receive file descriptor for the poll system call

Private Attributes

- [int ofds \[2\]](#)
File descriptors for pipe.

9.16.1 Detailed Description

This class provides a base interface for sending events via a pipe. This allows threads to send events that can be picked up by the poll system call.

9.16.2 Constructor & Destructor Documentation

9.16.2.1 BEventPipe::BEventPipe ()

9.16.2.2 BEventPipe::~~BEventPipe ()

9.16.3 Member Function Documentation

9.16.3.1 BError BEventPipe::sendEvent (BEvent * event)

Send an event.

9.16.3.2 BError BEventPipe::getEvent (BEvent * event, int timeOutUs = -1)

Receive the event.

9.16.3.3 int BEventPipe::getReceiveFd ()

returns the receive file descriptor for the poll system call

9.16.4 Member Data Documentation

9.16.4.1 int BEventPipe::ofds[2] [private]

File descriptors for pipe.

The documentation for this class was generated from the following files:

- [/src/cern/tms/beam/libBeam/BEvent.h](#)
- [/src/cern/tms/beam/libBeam/BEvent.cpp](#)

9.17 BFile Class Reference

File operations class.

```
#include <BFile.h>
```

Public Member Functions

- **BFile** ()
Create opened specified file.
- **BFile** (BString name, BString mode)
Create opened specified file.
- **BFile** (const BFile &file)
Create opened specified file.
- **~BFile** ()
- **BError open** (BString name, BString mode)
Open file.
- **BError open** (FILE *file)
Assign object to opened file handle.
- **BError close** ()
Close file.
- **BError error** ()
Returns current error state.
- **FILE * getFd** ()
File descriptor.
- **int length** ()
File size in bytes.
- **int setVBuf** (char *buf, int mode, size_t size)
Set stream buffering options.
- **int read** (void *buf, int nbytes)
Read from file.
- **int readString** (BString &str)
Read string. (ref fgets).
- **int write** (const void *buf, int nbytes)
Write to file.
- **int writeString** (const BString &str)
Write string to file.
- **int seek** (int pos, int whence)

Set seek position.

- int `printf` (const char *fmt,...)
Formatted print into the file.
- `BFile & operator=` (const `BFile` &file)

Private Attributes

- FILE * `ofile`
- BString `ofilename`
- BString `omode`
- BError `oerror`

9.17.1 Detailed Description

File operations class.

9.17.2 Constructor & Destructor Documentation

9.17.2.1 `BFile::BFile ()`

9.17.2.2 `BFile::BFile (BString name, BString mode)`

Create opened specified file.

9.17.2.3 `BFile::BFile (const BFile &file)`

Create opened specified file.

9.17.2.4 `BFile::~~BFile ()`

9.17.3 Member Function Documentation

9.17.3.1 `BError BFile::open (BString name, BString mode)`

Open file.

9.17.3.2 `BError BFile::open (FILE *file)`

Assign object to opened file handle.

9.17.3.3 `BError BFile::close ()`

Close file.

9.17.3.4 BError BFile::error ()

Returns current error state.

9.17.3.5 FILE * BFile::getFd ()

File descriptor.

9.17.3.6 int BFile::length ()

File size in bytes.

9.17.3.7 int BFile::setVBuf (char * *buf*, int *mode*, size_t *size*)

Set stream buffering options.

9.17.3.8 int BFile::read (void * *buf*, int *nbytes*)

Read from file.

9.17.3.9 int BFile::readString (BString & *str*)

Read string. (ref fgets).

9.17.3.10 int BFile::write (const void * *buf*, int *nbytes*)

Write to file.

9.17.3.11 int BFile::writeString (const BString & *str*)

Write string to file.

9.17.3.12 int BFile::seek (int *pos*, int *whence*)

Set seek position.

9.17.3.13 int BFile::printf (const char * *fmt*, ...)

Formatted print into the file.

9.17.3.14 BFile & BFile::operator= (const BFile & *file*)

9.17.4 Member Data Documentation

9.17.4.1 FILE* BFile::ofile [private]

9.17.4.2 BString BFile::ofilename [private]

9.17.4.3 BString BFile::omode [private]

9.17.4.4 BError BFile::oerror [private]

The documentation for this class was generated from the following files:

- [/src/cern/tms/beam/libBeam/BFile.h](#)
- [/src/cern/tms/beam/libBeam/BFile.cpp](#)

9.18 BIter Class Reference

Iterator for [BList](#).

```
#include <BList.h>
```

Public Member Functions

- [BIter](#) (void *i=0)
- [operator void *](#) ()
- [int operator==](#) (const [BIter](#) &i)

Private Attributes

- void * [oi](#)

9.18.1 Detailed Description

Iterator for [BList](#).

9.18.2 Constructor & Destructor Documentation

9.18.2.1 [BIter::BIter](#) (void * *i* = 0) [inline]

9.18.3 Member Function Documentation

9.18.3.1 [BIter::operator void *](#) () [inline]

9.18.3.2 [int BIter::operator==](#) (const [BIter](#) & *i*) [inline]

9.18.4 Member Data Documentation

9.18.4.1 void* [BIter::oi](#) [private]

The documentation for this class was generated from the following file:


- /src/cern/tms/beam/libBeam/[BList.h](#)

9.19 BList< T > Class Template Reference

Template based list class.

```
#include <BList.h>
```

Inheritance diagram for BList< T >::



Public Types

- typedef int(* [SortFunc](#))(T &a, T &b)
Prototype for sorting function.

Public Member Functions

- [BList](#) ()
- [BList](#) (const [BList](#)< T > &l)
- virtual [~BList](#) ()
- void [start](#) ([BIter](#) &i) const
Iterator to start of list.
- [BIter begin](#) () const
Iterator for start of list.
- [BIter end](#) () const
Iterator for end of list.
- [BIter end](#) ([BIter](#) &i) const
Iterator for end of list.
- void [next](#) ([BIter](#) &i) const
Iterator for next item in list.
- void [prev](#) ([BIter](#) &i)
Iterator for previous item in list.
- [BIter goTo](#) (int pos)
Iterator for pos item in list.
- int [position](#) ([BIter](#) i)
Postition in list item with iterator i.
- unsigned int [number](#) ()

Number of items in list.

- `int isEnd (BIter i) const`
True if iterator refers to last item.
- `T & front ()`
Get first item in list.
- `T & rear ()`
Get last item in list.
- `T & get (BIter i)`
Get item specified by iterator in list.
- `const T & get (BIter i) const`
Get item specified by iterator in list.
- `void append (const T &item)`
Append item to list.
- `virtual void insert (BIter &i, const T &item)`
Insert item before item.
- `void insertAfter (BIter &i, const T &item)`
Insert item after item.
- `virtual void clear ()`
Clear the list.
- `virtual void del (BIter &i)`
Delete specified item.
- `void deleteLast ()`
Delete last item.
- `void deleteFirst ()`
Delete first item.
- `void push (const T &i)`
Push item onto list.
- `T pop ()`
Pop item from list deleting item.
- `void queueAdd (const T &i)`
Add item to end of list.
- `T queueGet ()`
Get item from front of list deleting item.

- void `append` (const `BList< T >` &l)
Append list to list.
- void `swap` (`BIter` i1, `BIter` i2)
Swap two items in list.
- void `sort` ()
Sort list based on get(i) values.
- void `sort` (`SortFunc` func)
Sort list based on Sort func.
- `BList< T >` & `operator=` (const `BList< T >` &l)
- `T` & `operator[]` (int i)
- const `T` & `operator[]` (int i) const
- `T` & `operator[]` (`BIter` i)
- const `T` & `operator[]` (`BIter` i) const
- `BList< T >` `operator+` (const `BList< T >` &l) const

Protected Member Functions

- virtual `Node` * `nodeGet` (`BIter` i)
- virtual const `Node` * `nodeGet` (`BIter` i) const
- virtual `Node` * `nodeCreate` (const `T` &item)

Protected Attributes

- `Node` * `onodes`
- unsigned int `olength`

Private Member Functions

- virtual `Node` * `nodeCreate` ()

Classes

- class `Node`

9.19.1 Detailed Description

`template<class T> class BList< T >`

Template based list class.

9.19.2 Member Typedef Documentation

9.19.2.1 `template<class T> typedef int(* BList< T >::SortFunc)(T &a, T &b)`

Prototype for sorting function.

9.19.3 Constructor & Destructor Documentation

9.19.3.1 `template<class T> BList< T >::BList ()` `[inline]`

9.19.3.2 `template<class T> BList< T >::BList (const BList< T > & l)` `[inline]`

9.19.3.3 `template<class T> BList< T >::~~BList ()` `[inline, virtual]`

9.19.4 Member Function Documentation

9.19.4.1 `template<class T> void BList< T >::start (BIter & i) const` `[inline]`

Iterator to start of list.

9.19.4.2 `template<class T> BIter BList< T >::begin () const` `[inline]`

Iterator for start of list.

9.19.4.3 `template<class T> BIter BList< T >::end () const` `[inline]`

Iterator for end of list.

9.19.4.4 `template<class T> BIter BList< T >::end (BIter & i) const` `[inline]`

Iterator for end of list.

9.19.4.5 `template<class T> void BList< T >::next (BIter & i) const` `[inline]`

Iterator for next item in list.

9.19.4.6 `template<class T> void BList< T >::prev (BIter & i)` `[inline]`

Iterator for previous item in list.

9.19.4.7 `template<class T> BIter BList< T >::goTo (int pos)` `[inline]`

Iterator for pos item in list.

9.19.4.8 `template<class T> int BList< T >::position (BIter i)` `[inline]`

Postition in list item with iterator i.

9.19.4.9 `template<class T> unsigned int BList< T >::number ()` `[inline]`

Number of items in list.

9.19.4.10 `template<class T> int BList< T >::isEnd (BIter i) const` [inline]

True if iterator refers to last item.

9.19.4.11 `template<class T> T & BList< T >::front ()` [inline]

Get first item in list.

9.19.4.12 `template<class T> T & BList< T >::rear ()` [inline]

Get last item in list.

9.19.4.13 `template<class T> T & BList< T >::get (BIter i)` [inline]

Get item specified by iterator in list.

9.19.4.14 `template<class T> const T & BList< T >::get (BIter i) const` [inline]

Get item specified by iterator in list.

9.19.4.15 `template<class T> void BList< T >::append (const T & item)` [inline]

Append item to list.

9.19.4.16 `template<class T> void BList< T >::insert (BIter & i, const T & item)` [inline, virtual]

Insert item before item.

Reimplemented in [BEntryList](#).

9.19.4.17 `template<class T> void BList< T >::insertAfter (BIter & i, const T & item)` [inline]

Insert item after item.

9.19.4.18 `template<class T> void BList< T >::clear ()` [inline, virtual]

Clear the list.

Reimplemented in [BDir](#), [BEntryList](#), and [BEntryFile](#).

9.19.4.19 `template<class T> void BList< T >::del (BIter & i)` [inline, virtual]

Delete specified item.

Reimplemented in [BEntryList](#).

9.19.4.20 `template<class T> void BList< T >::deleteLast ()` [inline]

Delete last item.

9.19.4.21 `template<class T> void BList< T >::deleteFirst ()` [inline]

Delete first item.

9.19.4.22 `template<class T> void BList< T >::push (const T & i)` [inline]

Push item onto list.

9.19.4.23 `template<class T> T BList< T >::pop ()` [inline]

Pop item from list deleting item.

9.19.4.24 `template<class T> void BList< T >::queueAdd (const T & i)` [inline]

Add item to end of list.

9.19.4.25 `template<class T> T BList< T >::queueGet ()` [inline]

Get item from front of list deleting item.

9.19.4.26 `template<class T> void BList< T >::append (const BList< T > & l)` [inline]

Append list to list.

9.19.4.27 `template<class T> void BList< T >::swap (BIter i1, BIter i2)` [inline]

Swap two items in list.

9.19.4.28 `template<class T> void BList< T >::sort ()` [inline]

Sort list based on get(i) values.

9.19.4.29 `template<class T> void BList< T >::sort (SortFunc func)` [inline]

Sort list based on Sort func.

9.19.4.30 `template<class T> BList< T > & BList< T >::operator= (const BList< T > & l)`
[inline]

9.19.4.31]

`template<class T> T & BList< T >::operator[] (int i)` [inline]

9.19.4.32]

```
template<class T> const T & BList< T >::operator[] (int i) const [inline]
```

9.19.4.33]

```
template<class T> T & BList< T >::operator[] (BIter i) [inline]
```

9.19.4.34]

```
template<class T> const T & BList< T >::operator[] (BIter i) const [inline]
```

9.19.4.35 `template<class T> BList< T > BList< T >::operator+ (const BList< T > & l) const` [inline]

9.19.4.36 `template<class T> BList< T >::Node * BList< T >::nodeGet (BIter i)` [inline, protected, virtual]

9.19.4.37 `template<class T> const BList< T >::Node * BList< T >::nodeGet (BIter i) const` [inline, protected, virtual]

9.19.4.38 `template<class T> BList< T >::Node * BList< T >::nodeCreate (const T & item)` [inline, protected, virtual]

9.19.4.39 `template<class T> BList< T >::Node * BList< T >::nodeCreate ()` [inline, private, virtual]

9.19.5 Member Data Documentation

9.19.5.1 `template<class T> Node* BList< T >::onodes` [protected]

9.19.5.2 `template<class T> unsigned int BList< T >::olength` [protected]

The documentation for this class was generated from the following files:

- `/src/cern/tms/beam/libBeam/BList.h`
- `/src/cern/tms/beam/libBeam/BList_func.h`

9.20 BList< T >::Node Class Reference

```
#include <BList.h>
```

Public Member Functions

- [Node](#) (const T &i)

Public Attributes

- [Node](#) * [next](#)
- [Node](#) * [prev](#)
- T [item](#)

```
template<class T> class BList< T >::Node
```

9.20.1 Constructor & Destructor Documentation

9.20.1.1 `template<class T> BList< T >::Node::Node (const T & i) [inline]`

9.20.2 Member Data Documentation

9.20.2.1 `template<class T> Node* BList< T >::Node::next`

9.20.2.2 `template<class T> Node* BList< T >::Node::prev`

9.20.2.3 `template<class T> T BList< T >::Node::item`

The documentation for this class was generated from the following file:

- `/src/cern/tms/beam/libBeam/BList.h`

9.21 BMutex Class Reference

Mutex class.

```
#include <BMutex.h>
```

Public Member Functions

- [BMutex \(\)](#)
- [BMutex \(const \[BMutex\]\(#\) &mutex\)](#)
- [~BMutex \(\)](#)
- [int lock \(\)](#)
Set lock, wait in necessary.
- [int unlock \(\)](#)
Unlock the lock.
- [int tryLock \(\)](#)
Test the lock.
- [BMutex & operator= \(const \[BMutex\]\(#\) &mutex\)](#)

Private Attributes

- `pthread_mutex_t` [omutex](#)

9.21.1 Detailed Description

Mutex class.

9.21.2 Constructor & Destructor Documentation

9.21.2.1 [BMutex::BMutex \(\)](#)

9.21.2.2 [BMutex::BMutex \(const \[BMutex\]\(#\) & *mutex*\)](#)

9.21.2.3 [BMutex::~~BMutex \(\)](#)

9.21.3 Member Function Documentation

9.21.3.1 [int \[BMutex::lock \\(\\)\]\(#\)](#)

Set lock, wait in necessary.

9.21.3.2 [int \[BMutex::unlock \\(\\)\]\(#\)](#)

Unlock the lock.

9.21.3.3 int BMutex::tryLock ()

Test the lock.

9.21.3.4 BMutex & BMutex::operator= (const BMutex & *mutex*)

9.21.4 Member Data Documentation

9.21.4.1 pthread_mutex_t BMutex::omutex [private]

The documentation for this class was generated from the following files:

- [/src/cern/tms/beam/libBeam/BMutex.h](#)
- [/src/cern/tms/beam/libBeam/BMutex.cpp](#)

9.22 BNameValue< T > Class Template Reference

```
#include <BNameValue.h>
```

Public Member Functions

- [BNameValue \(\)](#)
- [BNameValue \(BString name, const T &value\)](#)
- [BString getName \(\)](#)
- [T & getValue \(\)](#)

Private Attributes

- [BString oname](#)
- [T ovalue](#)

```
template<class T> class BNameValue< T >
```

9.22.1 Constructor & Destructor Documentation

9.22.1.1 `template<class T> BNameValue< T >::BNameValue () [inline]`

9.22.1.2 `template<class T> BNameValue< T >::BNameValue (BString name, const T & value) [inline]`

9.22.2 Member Function Documentation

9.22.2.1 `template<class T> BString BNameValue< T >::getName () [inline]`

9.22.2.2 `template<class T> T& BNameValue< T >::getValue () [inline]`

9.22.3 Member Data Documentation

9.22.3.1 `template<class T> BString BNameValue< T >::oname [private]`

9.22.3.2 `template<class T> T BNameValue< T >::ovalue [private]`


The documentation for this class was generated from the following file:

- [/src/cern/tms/beam/libBeam/BNameValue.h](#)

9.23 BNameValueList< T > Class Template Reference

```
#include <BNameValue.h>
```

Inheritance diagram for BNameValueList< T >::



Public Member Functions

- T * [find](#) (BString name)

```
template<class T> class BNameValueList< T >
```

9.23.1 Member Function Documentation

9.23.1.1 `template<class T> T* BNameValueList< T >::find (BString name)` [inline]


The documentation for this class was generated from the following file:

- /src/cern/tms/beam/libBeam/[BNameValue.h](#)

9.24 BoapClientObject Class Reference

```
#include <BoapSimple.h>
```

Inheritance diagram for BoapClientObject::



Public Member Functions

- [BoapClientObject \(BString name= ""\)](#)
- [BError connectService \(BString name\)](#)
Connects to the named service.
- [BError disconnectService \(\)](#)
Disconnects from the named service.
- [BString getServiceName \(\)](#)
Get the name of the service.
- [BError ping \(BUInt32 &apiVersion\)](#)
Pings the connection and finds the remotes version number.
- [BError setConnectionPriority \(BoapPriority priority\)](#)
Sets the connection priority.
- [void setMaxLength \(BUInt32 maxLength\)](#)
Sets the maximum packet length.
- [void setTimeout \(int timeout\)](#)
Sets the timeout in micro seconds. -1 is wait indefinitely.
- [BoapClientObject \(BString name\)](#)
- [BError connectService \(BString name\)](#)

Protected Member Functions

- [BError pingLocked \(BUInt32 &apiVersion\)](#)
- [BError checkApiVersion \(\)](#)
- [BError performCall \(BoapPacket &tx, BoapPacket &rx\)](#)
Performs a RPC call to the named service.
- [BError performSend \(BoapPacket &tx\)](#)
Performs a send to the named service.

- [BError performRecv](#) ([BoapPacket](#) &rx)
Performs a receive.
- [BError performSend](#) ([BoapPacket](#) &tx)
- [BError performRecv](#) ([BoapPacket](#) &rx)
- [BError performCall](#) ([BoapPacket](#) &tx, [BoapPacket](#) &rx)

Protected Attributes

- [BString](#) `oname`
- [BUInt32](#) `oapiVersion`
- [BoapPriority](#) `opriority`
- [BoapService](#) `oservice`
- [int](#) `oconnected`
- [BUInt32](#) `omaxLength`
- [BoapPacket](#) `otx`
- [BoapPacket](#) `orx`
- [BMutex](#) `oclock`
- [int](#) `otimeout`
- [int](#) `oreconnect`

9.24.1 Constructor & Destructor Documentation

9.24.1.1 [BoapClientObject::BoapClientObject](#) ([BString](#) *name* = " ")

9.24.1.2 [BoapClientObject::BoapClientObject](#) ([BString](#) *name*)

9.24.2 Member Function Documentation

9.24.2.1 [BError BoapClientObject::connectService](#) ([BString](#) *name*)

Connects to the named service.

9.24.2.2 [BError BoapClientObject::disconnectService](#) ()

Disconnects from the named service.

9.24.2.3 [BString BoapClientObject::getServiceName](#) ()

Get the name of the service.

9.24.2.4 [BError BoapClientObject::ping](#) ([BUInt32](#) & *apiVersion*)

Pings the connection and finds the remotes version number.

9.24.2.5 BError BoapClientObject::setConnectionPriority (BoapPriority *priority*)

Sets the connection priority.

9.24.2.6 void BoapClientObject::setMaxLength (BUInt32 *maxLength*)

Sets the maximum packet length.

9.24.2.7 void BoapClientObject::setTimeout (int *timeout*)

Sets the timeout in micro seconds. -1 is wait indefinitely.

9.24.2.8 BError BoapClientObject::pingLocked (BUInt32 & *apiVersion*) [protected]**9.24.2.9 BError BoapClientObject::checkApiVersion ()** [protected]**9.24.2.10 BError BoapClientObject::performCall (BoapPacket & *tx*, BoapPacket & *rx*)**
[protected]

Performs a RPC call to the named service.

9.24.2.11 BError BoapClientObject::performSend (BoapPacket & *tx*) [protected]

Performs a send to the named service.

9.24.2.12 BError BoapClientObject::performRecv (BoapPacket & *rx*) [protected]

Performs a receive.

9.24.2.13 **BError** BoapClientObject::connectService (BString *name*)

9.24.2.14 **BError** BoapClientObject::performSend (BoapPacket & *tx*) [protected]

9.24.2.15 **BError** BoapClientObject::performRecv (BoapPacket & *rx*) [protected]

9.24.2.16 **BError** BoapClientObject::performCall (BoapPacket & *tx*, BoapPacket & *rx*)
[protected]

9.24.3 Member Data Documentation

9.24.3.1 **BString** BoapClientObject::oname [protected]

9.24.3.2 **BUInt32** BoapClientObject::oapiVersion [protected]

9.24.3.3 **BoapPriority** BoapClientObject::opriority [protected]

9.24.3.4 **BoapService** BoapClientObject::oservice [protected]

9.24.3.5 **int** BoapClientObject::oconnected [protected]

9.24.3.6 **BUInt32** BoapClientObject::omaxLength [protected]

9.24.3.7 **BoapPacket** BoapClientObject::otx [protected]

9.24.3.8 **BoapPacket** BoapClientObject::orx [protected]

9.24.3.9 **BMutex** BoapClientObject::olock [protected]

9.24.3.10 **int** BoapClientObject::otimeout [protected]

9.24.3.11 **int** BoapClientObject::oreconnect [protected]

The documentation for this class was generated from the following files:

- [/src/cern/tms/beam/libBeam/Boap.h](#)
- [/src/cern/tms/beam/libBeam/BoapSimple.h](#)
- [/src/cern/tms/beam/libBeam/Boap.cpp](#)
- [/src/cern/tms/beam/libBeam/BoapSimple.cc](#)

9.25 Boapns::BoapEntry Class Reference

```
#include <BoapnsD.h>
```

Public Member Functions

- [BoapEntry \(\)](#)
- [BoapEntry \(BString pname, BString phostName, BList< BString > paddressList, UInt32 pport, UInt32 pservice\)](#)

Public Attributes

- [BString name](#)
- [BString hostName](#)
- [BList< BString > addressList](#)
- [UInt32 port](#)
- [UInt32 service](#)

9.25.1 Constructor & Destructor Documentation

9.25.1.1 Boapns::BoapEntry::BoapEntry ()

9.25.1.2 Boapns::BoapEntry::BoapEntry (BString *pname*, BString *phostName*, BList< BString > *paddressList*, UInt32 *pport*, UInt32 *pservice*)

9.25.2 Member Data Documentation

9.25.2.1 BString Boapns::BoapEntry::name

9.25.2.2 BString Boapns::BoapEntry::hostName

9.25.2.3 BList<BString> Boapns::BoapEntry::addressList

9.25.2.4 UInt32 Boapns::BoapEntry::port

9.25.2.5 UInt32 Boapns::BoapEntry::service

The documentation for this class was generated from the following files:

- [/src/cern/tms/beam/libBeam/BoapnsD.h](#)
- [/src/cern/tms/beam/libBeam/BoapnsD.cc](#)

9.26 BoapFuncEntry Class Reference

```
#include <BoapSimple.h>
```

Public Member Functions

- [BoapFuncEntry](#) (int cmd, [BoapFunc](#) func)
- [BoapFuncEntry](#) (int cmd, [BoapFunc](#) func)

Public Attributes

- [UInt32](#) ocmd
- [BoapFunc](#) ofunc

9.26.1 Constructor & Destructor Documentation

9.26.1.1 [BoapFuncEntry::BoapFuncEntry](#) (int *cmd*, [BoapFunc](#) *func*)

9.26.1.2 [BoapFuncEntry::BoapFuncEntry](#) (int *cmd*, [BoapFunc](#) *func*)

9.26.2 Member Data Documentation

9.26.2.1 [UInt32](#) [BoapFuncEntry::ocmd](#)

9.26.2.2 [BoapFunc](#) [BoapFuncEntry::ofunc](#)


The documentation for this class was generated from the following files:

- [/src/cern/tms/beam/libBeam/Boap.h](#)
- [/src/cern/tms/beam/libBeam/BoapSimple.h](#)
- [/src/cern/tms/beam/libBeam/Boap.cpp](#)
- [/src/cern/tms/beam/libBeam/BoapSimple.cc](#)

9.27 Boapns::Boapns Class Reference

```
#include <BoapnsC.h>
```

Inheritance diagram for Boapns::Boapns::



Public Member Functions

- [Boapns](#) ([BString](#) name="")
- [BError](#) [getVersion](#) ([BString](#) &version)
- [BError](#) [getEntryList](#) ([BList](#)< [BoapEntry](#) > &entryList)
- [BError](#) [getEntry](#) ([BString](#) name, [BoapEntry](#) &entry)
- [BError](#) [addEntry](#) ([BoapEntry](#) entry)
- [BError](#) [delEntry](#) ([BString](#) name)
- [BError](#) [getNewName](#) ([BString](#) &name)

9.27.1 Constructor & Destructor Documentation

9.27.1.1 [Boapns::Boapns::Boapns](#) ([BString](#) *name* = "")

9.27.2 Member Function Documentation

9.27.2.1 [BError](#) [Boapns::Boapns::getVersion](#) ([BString](#) & *version*)

9.27.2.2 [BError](#) [Boapns::Boapns::getEntryList](#) ([BList](#)< [BoapEntry](#) > & *entryList*)

9.27.2.3 [BError](#) [Boapns::Boapns::getEntry](#) ([BString](#) *name*, [BoapEntry](#) & *entry*)

9.27.2.4 [BError](#) [Boapns::Boapns::addEntry](#) ([BoapEntry](#) *entry*)

9.27.2.5 [BError](#) [Boapns::Boapns::delEntry](#) ([BString](#) *name*)

9.27.2.6 [BError](#) [Boapns::Boapns::getNewName](#) ([BString](#) & *name*)

The documentation for this class was generated from the following file:

- /src/cern/tms/beam/libBeam/[BoapnsC.h](#)

9.28 BoapPacket Class Reference

```
#include <BoapSimple.h>
```

Public Member Functions

- [BoapPacket](#) ()
- [~BoapPacket](#) ()
- [int](#) [resize](#) (int size)
- [BError](#) [setData](#) (void *data, int nbytes)
- [int](#) [nbytes](#) ()
- [char *](#) [data](#) ()
- [int](#) [peekHead](#) ([BoapPacketHead](#) &head)
- [UInt32](#) [getCmd](#) ()
- [int](#) [pushHead](#) ([BoapPacketHead](#) &head)
- [int](#) [push](#) ([Int8](#) v)
- [int](#) [push](#) ([UInt8](#) v)
- [int](#) [push](#) ([Int16](#) v)
- [int](#) [push](#) ([UInt16](#) v)
- [int](#) [push](#) ([Int32](#) v)
- [int](#) [push](#) ([UInt32](#) v)
- [int](#) [push](#) ([Int64](#) v)
- [int](#) [push](#) ([UInt64](#) v)
- [int](#) [push](#) (const [BString](#) &v)
- [int](#) [push](#) ([Double](#) v)
- [int](#) [push](#) (const [BError](#) &v)
- [int](#) [push](#) ([UInt32](#) nBytes, const void *data, char *swapType="1")
- [int](#) [popHead](#) ([BoapPacketHead](#) &head)
- [int](#) [pop](#) ([Int8](#) &v)
- [int](#) [pop](#) ([UInt8](#) &v)
- [int](#) [pop](#) ([Int16](#) &v)
- [int](#) [pop](#) ([UInt16](#) &v)
- [int](#) [pop](#) ([Int32](#) &v)
- [int](#) [pop](#) ([UInt32](#) &v)
- [int](#) [pop](#) ([Int64](#) &v)
- [int](#) [pop](#) ([UInt64](#) &v)
- [int](#) [pop](#) ([BString](#) &v)
- [int](#) [pop](#) ([Double](#) &v)
- [int](#) [pop](#) ([BError](#) &v)
- [int](#) [pop](#) ([UInt32](#) nBytes, void *data, char *swapType="1")
- [BoapPacket](#) ()
- [~BoapPacket](#) ()
- [int](#) [resize](#) (int size)
- [BError](#) [setData](#) (void *data, int nbytes)
- [int](#) [nbytes](#) ()
- [char *](#) [data](#) ()
- [int](#) [pushHead](#) ([BoapPacketHead](#) &head)
- [int](#) [push](#) ([Int8](#) v)
- [int](#) [push](#) ([UInt8](#) v)

- int [push](#) ([Int16](#) v)
- int [push](#) ([UInt16](#) v)
- int [push](#) ([Int32](#) v)
- int [push](#) ([UInt32](#) v)
- int [push](#) ([BString](#) &v)
- int [push](#) ([Double](#) v)
- int [push](#) ([BError](#) &v)
- int [push](#) ([UInt32](#) nBytes, const void *data)
- int [popHead](#) ([BoapPacketHead](#) &head)
- int [pop](#) ([Int8](#) &v)
- int [pop](#) ([UInt8](#) &v)
- int [pop](#) ([Int16](#) &v)
- int [pop](#) ([UInt16](#) &v)
- int [pop](#) ([Int32](#) &v)
- int [pop](#) ([UInt32](#) &v)
- int [pop](#) ([BString](#) &v)
- int [pop](#) ([Double](#) &v)
- int [pop](#) ([BError](#) &v)
- int [pop](#) ([UInt32](#) nBytes, void *data)

Private Member Functions

- void [copyWithSwap](#) (void *dst, const void *src, [UInt32](#) nBytes, char *swapType)
- void [updateLen](#) ()
- void [updateLen](#) ()

Private Attributes

- int [osize](#)
- int [onbytes](#)
- char * [odata](#)
- int [opos](#)

9.28.1 Constructor & Destructor Documentation

9.28.1.1 `BoapPacket::BoapPacket ()`

9.28.1.2 `BoapPacket::~~BoapPacket ()`

9.28.1.3 `BoapPacket::BoapPacket ()`

9.28.1.4 `BoapPacket::~~BoapPacket ()`

9.28.2 Member Function Documentation

9.28.2.1 `int BoapPacket::resize (int size)`

9.28.2.2 `BError BoapPacket::setData (void * data, int nbytes)`

9.28.2.3 `int BoapPacket::nbytes ()`

9.28.2.4 `char * BoapPacket::data ()`

9.28.2.5 `int BoapPacket::peekHead (BoapPacketHead & head)`

9.28.2.6 `UInt32 BoapPacket::getCmd ()`

9.28.2.7 `int BoapPacket::pushHead (BoapPacketHead & head)`

9.28.2.8 `int BoapPacket::push (Int8 v)`

9.28.2.9 `int BoapPacket::push (UInt8 v)`

9.28.2.10 `int BoapPacket::push (Int16 v)`

9.28.2.11 `int BoapPacket::push (UInt16 v)`

9.28.2.12 `int BoapPacket::push (Int32 v)`

9.28.2.13 `int BoapPacket::push (UInt32 v)`

9.28.2.14 `int BoapPacket::push (Int64 v)`

9.28.2.15 `int BoapPacket::push (UInt64 v)`

9.28.2.16 `int BoapPacket::push (const BString & v)`

9.28.2.17 `int BoapPacket::push (Double v)`

9.28.2.18 `int BoapPacket::push (const BError & v)`

9.28.2.19 `int BoapPacket::push (UInt32 nBytes, const void * data, char * swapType = "1")`

9.28.2.20 `int BoapPacket::popHead (BoapPacketHead & head)`

9.28.2.21 `int BoapPacket::pop (Int8 & v)`

9.28.2.22 `int BoapPacket::pop (UInt8 & v)`

Generated on Thu Dec 18 13:21:07 2008 for LibTmsApi by Doxygen

9.28.2.23 `int BoapPacket::pop (Int16 & v)`

9.28.2.24 `int BoapPacket::pop (UInt16 & v)`

9.28.2.25 `int BoapPacket::pop (Int32 & v)`

- [/src/cern/tms/beam/libBeam/Boap.h](#)
- [/src/cern/tms/beam/libBeam/BoapSimple.h](#)
- [/src/cern/tms/beam/libBeam/Boap.cpp](#)
- [/src/cern/tms/beam/libBeam/BoapSimple.cc](#)

9.29 BoapPacketHead Struct Reference

```
#include <BoapSimple.h>
```

Public Attributes

- [UInt32 type](#)
- [UInt32 length](#)
- [UInt32 service](#)
- [UInt32 cmd](#)
- [BoapType type](#)
- [BoapService service](#)
- [UInt32 reserved](#) [12]

9.29.1 Member Data Documentation

9.29.1.1 [UInt32 BoapPacketHead::type](#)

9.29.1.2 [UInt32 BoapPacketHead::length](#)

9.29.1.3 [UInt32 BoapPacketHead::service](#)

9.29.1.4 [UInt32 BoapPacketHead::cmd](#)

9.29.1.5 [BoapType BoapPacketHead::type](#)

9.29.1.6 [BoapService BoapPacketHead::service](#)

9.29.1.7 [UInt32 BoapPacketHead::reserved\[12\]](#)


The documentation for this struct was generated from the following files:

- [/src/cern/tms/beam/libBeam/Boap.h](#)
- [/src/cern/tms/beam/libBeam/BoapSimple.h](#)

9.30 BoapServer Class Reference

```
#include <BoapSimple.h>
```

Inheritance diagram for BoapServer::



Public Types

- enum { **NOTHEADS** = 0, **THREADED** = 1 }

Public Member Functions

- **BoapServer** ()
- **~BoapServer** ()
- **BError** **init** (**BString** boapNsHost="", int threaded=0, int isBoapns=0)
- **BError** **run** (int inThread=0)
- **BError** **processEvent** (**BoapPacket** &rx)
- **BError** **addObject** (**BoapServiceObject** *object)
- **BError** **process** (**BoapServerConnection** *conn, **BoapPacket** &rx, **BoapPacket** &tx)
- **BError** **sendEvent** (**BoapPacket** &tx)
- **BSocket** & **getSocket** ()
- **BSocket** & **getEventSocket** ()
- **BError** **processEvent** (int fd)
- **BString** **getHostName** ()
- void **clientGone** (**BoapServerConnection** *client)
- int **getConnectionsNumber** ()
- **BoapServer** ()
- **BError** **init** (int boapNs=0)
- **BError** **run** ()
- **BError** **processEvent** (**BoapPacket** &rx)
- **BError** **addObject** (**BoapServiceObject** *object)
- **BError** **process** (int fd)
- **BError** **sendEvent** (**BoapPacket** &tx)
- **BSocket** & **getSocket** ()
- **BSocket** & **getEventSocket** ()
- **BError** **processEvent** (int fd)
- **BString** **getHostName** ()

Private Member Functions

- void * **function** ()

Private Attributes

- int `othreaded`
- int `oisBoapns`
- `Boapns::Boapns * oboapns`
- `BList< BoapServerConnection * > oclients`
- `BEventInt oclientGoneEvent`
- `BList< BoapServiceEntry > oservices`
- `BPoll opoll`
- `BSocket onet`
- `BSocket onetEvent`
- `BSocketAddressINET onetEventAddress`
- `BString ohostName`
- int `oboapNs`
- `BoapPacket orx`
- `BoapPacket otx`

9.30.1 Member Enumeration Documentation

9.30.1.1 anonymous enum

Enumerator:

NOTHREADS

THREADED

9.30.2 Constructor & Destructor Documentation

9.30.2.1 **BoapServer::BoapServer ()**

9.30.2.2 **BoapServer::~~BoapServer ()**

9.30.2.3 **BoapServer::BoapServer ()**

9.30.3 Member Function Documentation

9.30.3.1 **BError BoapServer::init (BString *boapNsHost* = "", int *threaded* = 0, int *isBoapns* = 0)**

9.30.3.2 **BError BoapServer::run (int *inThread* = 0)**

9.30.3.3 **BError BoapServer::processEvent (BoapPacket & *rx*)**

9.30.3.4 **BError BoapServer::addObject (BoapServiceObject * *object*)**

9.30.3.5 **BError BoapServer::process (BoapServerConnection * *conn*, BoapPacket & *rx*,
BoapPacket & *tx*)**

9.30.3.6 **BError BoapServer::sendEvent (BoapPacket & *tx*)**

9.30.3.7 **BSocket & BoapServer::getSocket ()**

9.30.3.8 **BSocket & BoapServer::getEventSocket ()**

9.30.3.9 **BError BoapServer::processEvent (int *fd*)**

9.30.3.10 **BString BoapServer::getHostName ()**

9.30.3.11 **void BoapServer::clientGone (BoapServerConnection * *client*)**

9.30.3.12 **int BoapServer::getConnectionsNumber ()**

9.30.3.13 **void * BoapServer::function ()** [private, virtual]

Reimplemented from [BThread](#).

- 9.30.3.14 BError BoapServer::init (int *boapNs* = 0)
- 9.30.3.15 BError BoapServer::run ()
- 9.30.3.16 BError BoapServer::processEvent (BoapPacket & *rx*)
- 9.30.3.17 BError BoapServer::addObject (BoapServiceObject * *object*)
- 9.30.3.18 BError BoapServer::process (int *fd*)
- 9.30.3.19 BError BoapServer::sendEvent (BoapPacket & *tx*)
- 9.30.3.20 BSocket& BoapServer::getSocket ()
- 9.30.3.21 BSocket& BoapServer::getEventSocket ()
- 9.30.3.22 BError BoapServer::processEvent (int *fd*)
- 9.30.3.23 BString BoapServer::getHostName ()

9.30.4 Member Data Documentation

- 9.30.4.1 int BoapServer::othreaded [private]
- 9.30.4.2 int BoapServer::oisBoapns [private]
- 9.30.4.3 Boapns::Boapns* BoapServer::oboapns [private]
- 9.30.4.4 BList<BoapServerConnection*> BoapServer::oclients [private]
- 9.30.4.5 BEventInt BoapServer::oclientGoneEvent [private]
- 9.30.4.6 BList< BoapServiceEntry > BoapServer::oservices [private]
- 9.30.4.7 BPoll BoapServer::opoll [private]
- 9.30.4.8 BSocket BoapServer::onet [private]
- 9.30.4.9 BSocket BoapServer::onetEvent [private]
- 9.30.4.10 BSocketAddressINET BoapServer::onetEventAddress [private]
- 9.30.4.11 BString BoapServer::ohostName [private]
- 9.30.4.12 int BoapServer::oboapNs [private]
- 9.30.4.13 BoapPacket BoapServer::orx [private]
- 9.30.4.14 BoapPacket BoapServer::otx [private]

The documentation for this class was generated from the following files:


- /src/cern/tms/beam/libBeam/[Boap.h](#)

- [/src/cern/tms/beam/libBeam/BoapSimple.h](#)
- [/src/cern/tms/beam/libBeam/Boap.cpp](#)
- [/src/cern/tms/beam/libBeam/BoapSimple.cc](#)

9.31 BoapServerConnection Class Reference

```
#include <Boap.h>
```

Inheritance diagram for BoapServerConnection::



Public Member Functions

- `BoapServerConnection` (`BoapServer` &`boapServer`, `int fd`)
- `BError` `process` ()
- `BSocket` & `getSocket` ()
- `void` `setMaxLength` (`BUInt32 maxLength`)

Private Member Functions

- `void *` `function` ()

Private Attributes

- `BoapServer` & `oboapServer`
- `BSocket` `osocket`
- `BoapPacket` `orx`
- `BoapPacket` `otx`
- `BUInt32` `omaxLength`

9.31.1 Constructor & Destructor Documentation

9.31.1.1 `BoapServerConnection::BoapServerConnection` (`BoapServer` & *boapServer*, `int fd`)

9.31.2 Member Function Documentation

9.31.2.1 `BError` `BoapServerConnection::process` ()

9.31.2.2 `BSocket` & `BoapServerConnection::getSocket` ()

9.31.2.3 `void` `BoapServerConnection::setMaxLength` (`BUInt32` *maxLength*)

9.31.2.4 `void *` `BoapServerConnection::function` () [`private`, `virtual`]

Reimplemented from `BThread`.

9.31.3 Member Data Documentation

9.31.3.1 `BoapServer& BoapServerConnection::oboapServer` [private]

9.31.3.2 `BSocket BoapServerConnection::osocket` [private]

9.31.3.3 `BoapPacket BoapServerConnection::orx` [private]

9.31.3.4 `BoapPacket BoapServerConnection::otx` [private]

9.31.3.5 `BUInt32 BoapServerConnection::omaxLength` [private]

The documentation for this class was generated from the following files:

- [/src/cern/tms/beam/libBeam/Boap.h](#)
- [/src/cern/tms/beam/libBeam/Boap.cpp](#)

9.32 BoapServiceEntry Class Reference

```
#include <BoapSimple.h>
```

Public Member Functions

- [BoapServiceEntry](#) ([BoapService](#) service=0, [BoapServiceObject](#) *object=0)
- [BoapServiceEntry](#) ([BoapService](#) service=0, [BoapServiceObject](#) *object=0)

Public Attributes

- [BoapService](#) oservice
- [BoapServiceObject](#) * oobject

9.32.1 Constructor & Destructor Documentation

9.32.1.1 [BoapServiceEntry::BoapServiceEntry](#) ([BoapService](#) *service* = 0, [BoapServiceObject](#) * *object* = 0) [[inline](#)]

9.32.1.2 [BoapServiceEntry::BoapServiceEntry](#) ([BoapService](#) *service* = 0, [BoapServiceObject](#) * *object* = 0) [[inline](#)]

9.32.2 Member Data Documentation

9.32.2.1 [BoapService](#) [BoapServiceEntry::oservice](#)

9.32.2.2 [BoapServiceObject](#) * [BoapServiceEntry::oobject](#)

The documentation for this class was generated from the following files:

- [/src/cern/tms/beam/libBeam/Boap.h](#)
- [/src/cern/tms/beam/libBeam/BoapSimple.h](#)

9.33 BoapServiceObject Class Reference

```
#include <BoapSimple.h>
```

Public Member Functions

- [BoapServiceObject](#) ([BoapServer](#) &server, [BString](#) name="")
- virtual [~BoapServiceObject](#) ()
- [BError](#) setName ([BString](#) name)
- [BError](#) sendEvent ([BString](#) signalName, [Int32](#) arg)
- virtual [BError](#) processEvent ([BString](#) objectName, [BString](#) name, [Int32](#) arg)
- [BString](#) name ()
- [BError](#) doPing ([BoapServerConnection](#) *conn, [BoapPacket](#) &rx, [BoapPacket](#) &tx)
- [BError](#) doConnectionPriority ([BoapServerConnection](#) *conn, [BoapPacket](#) &rx, [BoapPacket](#) &tx)
- [BError](#) process ([BoapServerConnection](#) *conn, [BoapPacket](#) &rx, [BoapPacket](#) &tx)
- virtual [BError](#) processEvent ([BoapPacket](#) &rx)
- [BoapServiceObject](#) ([BoapServer](#) &server, [BString](#) name)
- virtual [~BoapServiceObject](#) ()
- [BError](#) sendEvent ([BString](#) signalName, [Int32](#) arg)
- virtual [BError](#) processEvent ([BString](#) objectName, [BString](#) name, [Int32](#) arg)
- [BString](#) name ()
- [BError](#) process ([BoapPacket](#) &rx, [BoapPacket](#) &tx)
- virtual [BError](#) processEvent ([BoapPacket](#) &rx)

Protected Member Functions

- [BError](#) sendEvent ([BoapPacket](#) &tx)
- [BError](#) sendEvent ([BoapPacket](#) &tx)

Protected Attributes

- [BoapServer](#) & oserver
- [BString](#) oname
- [BUInt32](#) oapiVersion
- [BList](#)< [BoapFuncEntry](#) > ofuncList

9.33.1 Constructor & Destructor Documentation

9.33.1.1 **BoapServiceObject::BoapServiceObject** (BoapServer & *server*, BString *name* = "")

9.33.1.2 **BoapServiceObject::~~BoapServiceObject** () [virtual]

9.33.1.3 **BoapServiceObject::BoapServiceObject** (BoapServer & *server*, BString *name*)

9.33.1.4 **virtual BoapServiceObject::~~BoapServiceObject** () [virtual]

9.33.2 Member Function Documentation

9.33.2.1 **BError BoapServiceObject::setName** (BString *name*)

9.33.2.2 **BError BoapServiceObject::sendEvent** (BString *signalName*, Int32 *arg*)

9.33.2.3 **BError BoapServiceObject::processEvent** (BString *objectName*, BString *name*, Int32 *arg*) [virtual]

9.33.2.4 **BString BoapServiceObject::name** ()

9.33.2.5 **BError BoapServiceObject::doPing** (BoapServerConnection * *conn*, BoapPacket & *rx*, BoapPacket & *tx*)

9.33.2.6 **BError BoapServiceObject::doConnectionPriority** (BoapServerConnection * *conn*, BoapPacket & *rx*, BoapPacket & *tx*)

9.33.2.7 **BError BoapServiceObject::process** (BoapServerConnection * *conn*, BoapPacket & *rx*, BoapPacket & *tx*)

9.33.2.8 **BError BoapServiceObject::processEvent** (BoapPacket & *rx*) [virtual]

9.33.2.9 **BError BoapServiceObject::sendEvent** (BoapPacket & *tx*) [protected]

9.33.2.10 **BError BoapServiceObject::sendEvent** (BString *signalName*, Int32 *arg*)

9.33.2.11 **virtual BError BoapServiceObject::processEvent** (BString *objectName*, BString *name*, Int32 *arg*) [virtual]

9.33.2.12 **BString BoapServiceObject::name** ()

9.33.2.13 **BError BoapServiceObject::process** (BoapPacket & *rx*, BoapPacket & *tx*)

9.33.2.14 **virtual BError BoapServiceObject::processEvent** (BoapPacket & *rx*) [virtual]

9.33.2.15 **BError BoapServiceObject::sendEvent** (BoapPacket & *tx*) [protected]

9.33.3 Member Data Documentation

9.33.3.1 **BoapServer & BoapServiceObject::oserver** [protected]

9.33.3.2 **BString BoapServiceObject::oname** [protected]

9.33.3.3 **BUInt32 BoapServiceObject::oapiVersion** [protected]

Generated on Thu Dec 18 13:21:07 2008 for LibTmsApi by Doxygen

9.33.3.4 **BList< BoapFuncEntry > BoapServiceObject::ofuncList** [protected]


The documentation for this class was generated from the following files:

- [/src/cern/tms/beam/libBeam/Boap.h](#)
- [/src/cern/tms/beam/libBeam/BoapSimple.h](#)
- [/src/cern/tms/beam/libBeam/Boap.cpp](#)
- [/src/cern/tms/beam/libBeam/BoapSimple.cc](#)

9.34 BoapSignalObject Class Reference

```
#include <BoapSimple.h>
```

Inheritance diagram for BoapSignalObject::



Public Member Functions

- [BoapSignalObject \(\)](#)
- [BoapSignalObject \(\)](#)

Protected Member Functions

- [BError performSend \(BoapPacket &tx\)](#)
- [BError performSend \(BoapPacket &tx\)](#)

Protected Attributes

- [BoapPacket otx](#)
- [BoapPacket orx](#)

9.34.1 Constructor & Destructor Documentation

9.34.1.1 [BoapSignalObject::BoapSignalObject \(\)](#)

9.34.1.2 [BoapSignalObject::BoapSignalObject \(\)](#)

9.34.2 Member Function Documentation

9.34.2.1 [BError BoapSignalObject::performSend \(BoapPacket & tx\)](#) [protected]

9.34.2.2 [BError BoapSignalObject::performSend \(BoapPacket & tx\)](#) [protected]

9.34.3 Member Data Documentation

9.34.3.1 [BoapPacket BoapSignalObject::otx](#) [protected]

9.34.3.2 [BoapPacket BoapSignalObject::orx](#) [protected]

The documentation for this class was generated from the following files:

- [/src/cern/tms/beam/libBeam/Boap.h](#)
- [/src/cern/tms/beam/libBeam/BoapSimple.h](#)

- [/src/cern/tms/beam/libBeam/Boap.cpp](#)
- [/src/cern/tms/beam/libBeam/BoapSimple.cc](#)

9.35 BObject Class Reference

```
#include <BObject.h>
```

Public Member Functions

- [BObject](#) ()
- virtual [~BObject](#) ()
- virtual [BError](#) [getBinary](#) (BDataBuf &buf)
- virtual [BError](#) [setBinary](#) (BDataBuf &buf)
- virtual [BString](#) [getString](#) ()
- virtual [BError](#) [setString](#) ([BString](#) str)
- virtual [BMemberList](#) [getMemberList](#) ()
- virtual [BError](#) [addMember](#) ([BString](#) name, [BObject](#) *object)
- virtual void [printIt](#) ()
- virtual BType & [getType](#) ()

Static Public Member Functions

- static [BObject](#) * [createObj](#) ()

Static Public Attributes

- static BType [otype](#) = btypesList.appendType(BType("BObject", BTypeDomainBase, BTypeObject, createObj))

9.35.1 Constructor & Destructor Documentation

9.35.1.1 **BObject::BObject ()**

9.35.1.2 **BObject::~~BObject ()** [virtual]

9.35.2 Member Function Documentation

9.35.2.1 **BError BObject::getBinary (BDataBuf & *buf*)** [virtual]

9.35.2.2 **BError BObject::setBinary (BDataBuf & *buf*)** [virtual]

9.35.2.3 **BString BObject::getString ()** [virtual]

9.35.2.4 **BError BObject::setString (BString *str*)** [virtual]

9.35.2.5 **BMemberList BObject::getMemberList ()** [virtual]

9.35.2.6 **BError BObject::addMember (BString *name*, BObject * *object*)** [virtual]

9.35.2.7 **void BObject::printIt ()** [virtual]

9.35.2.8 **BType & BObject::getType ()** [virtual]

9.35.2.9 **BObject * BObject::createObj ()** [static]

9.35.3 Member Data Documentation

9.35.3.1 **BType BObject::otype = btypesList.appendType(BType("BObject", BTypeDomainBase, BTypeObject, createObj))** [static]

The documentation for this class was generated from the following files:

- [/src/cern/tms/beam/libBeam/BObject.h](#)
- [/src/cern/tms/beam/libBeam/BObject.cc](#)

9.36 BPoll Class Reference

This class provides an interface for polling a number of file descriptors. It uses round robin polling.

```
#include <BPoll.h>
```

Public Types

- typedef struct pollfd [PollFd](#)

Public Member Functions

- [BPoll](#) ()
- [~BPoll](#) ()
- void [append](#) (int fd, int events=POLLIN|POLLERR|POLLHUP|POLLNVAL)
Append a file descriptor to polling list.
- void [delFd](#) (int fd)
Remove a file descriptor from polling list.
- [BError doPoll](#) (int &fd, int timeoutUs=-1)
Perform polling operation.
- int [getPollFdsNum](#) ()
- [PollFd *](#) [getPollFds](#) ()
- void [clear](#) ()

Private Member Functions

- int [nextFd](#) (int i)

Private Attributes

- int [ofdsNum](#)
The number of FD's in list.
- [PollFd *](#) [ofds](#)
The list of poll fd's.
- int [ofdsNext](#)
The next list entry for round robin polling.

9.36.1 Detailed Description

This class provides an interface for polling a number of file descriptors. It uses round robin polling.

9.36.2 Member Typedef Documentation

9.36.2.1 `typedef struct pollfd BPoll::PollFd` `[read]`

9.36.3 Constructor & Destructor Documentation

9.36.3.1 `BPoll::BPoll ()`

9.36.3.2 `BPoll::~~BPoll ()`

9.36.4 Member Function Documentation

9.36.4.1 `void BPoll::append (int fd, int events = POLLIN|POLLERR|POLLHUP|POLLNVAL)`

Append a file descriptor to polling list.

9.36.4.2 `void BPoll::delFd (int fd)`

Remove a file descriptor from polling list.

9.36.4.3 `BError BPoll::doPoll (int &fd, int timeoutUs = -1)`

Perform polling operation.

9.36.4.4 `int BPoll::getPollFdsNum ()`

9.36.4.5 `BPoll::PollFd * BPoll::getPollFds ()`

9.36.4.6 `void BPoll::clear ()`

9.36.4.7 `int BPoll::nextFd (int i)` `[private]`

9.36.5 Member Data Documentation

9.36.5.1 `int BPoll::ofdsNum` `[private]`

The number of FD's in list.

9.36.5.2 `PollFd* BPoll::ofds` `[private]`

The list of poll fd's.

9.36.5.3 `int BPoll::ofdsNext` `[private]`

The next list entry for round robin polling.

The documentation for this class was generated from the following files:

- `/src/cern/tms/beam/libBeam/BPoll.h`

- [/src/cern/tms/beam/libBeam/BPoll-1.cpp](#)
- [/src/cern/tms/beam/libBeam/BPoll.cpp](#)

9.37 BRefData Class Reference

Referenced data storage.

```
#include <BRefData.h>
```

Public Member Functions

- [BRefData](#) ()
- [BRefData](#) (int len)
- [BRefData](#) (const [BRefData](#) &refData)
- [~BRefData](#) ()
- [BRefData](#) * [copy](#) ()
- [BRefData](#) * [addRef](#) ()
- int [deleteRef](#) ()
- int [refCount](#) ()
- char * [data](#) ()
- int [len](#) ()
- void [setLen](#) (int len)
- [BRefData](#) & [operator=](#) ([BRefData](#) &refData)

Private Attributes

- void * [oData](#)
- int [oLen](#)
- int [oSize](#)
- int [oRefCount](#)

9.37.1 Detailed Description

Referenced data storage.

9.37.2 Constructor & Destructor Documentation

9.37.2.1 **BRefData::BRefData ()**

9.37.2.2 **BRefData::BRefData (int *len*)**

9.37.2.3 **BRefData::BRefData (const BRefData & *refData*)**

9.37.2.4 **BRefData::~~BRefData ()**

9.37.3 Member Function Documentation

9.37.3.1 **BRefData * BRefData::copy ()**

9.37.3.2 **BRefData * BRefData::addRef ()**

9.37.3.3 **int BRefData::deleteRef ()**

9.37.3.4 **int BRefData::refCount ()** [inline]

9.37.3.5 **char* BRefData::data ()** [inline]

9.37.3.6 **int BRefData::len ()** [inline]

9.37.3.7 **void BRefData::setLen (int *len*)**

9.37.3.8 **BRefData & BRefData::operator= (BRefData & *refData*)**

9.37.4 Member Data Documentation

9.37.4.1 **void* BRefData::oData** [private]

9.37.4.2 **int BRefData::oLen** [private]

9.37.4.3 **int BRefData::oSize** [private]

9.37.4.4 **int BRefData::oRefCount** [private]

The documentation for this class was generated from the following files:

- [/src/cern/tms/beam/libBeam/BRefData.h](#)
- [/src/cern/tms/beam/libBeam/BRefData.cpp](#)

9.38 BRtc Class Reference

Realtime clock.

```
#include <BRtc.h>
```

Public Member Functions

- [BRtc \(\)](#)
- [~BRtc \(\)](#)
- [BError init](#) (int rate)
Setup interrupt rate.
- void [wait](#) (int delayUs)
Wait specified uS.

Private Attributes

- int [ofd](#)
- int [orate](#)

9.38.1 Detailed Description

Realtime clock.

9.38.2 Constructor & Destructor Documentation

9.38.2.1 BRtc::BRtc ()

9.38.2.2 BRtc::~~BRtc ()

9.38.3 Member Function Documentation

9.38.3.1 BError BRtc::init (int *rate*)

Setup interrupt rate.

9.38.3.2 void BRtc::wait (int *delayUs*)

Wait specified uS.

9.38.4 Member Data Documentation

9.38.4.1 int BRtc::ofd [private]

9.38.4.2 int BRtc::orate [private]

The documentation for this class was generated from the following files:


- [/src/cern/tms/beam/libBeam/BRtc.h](#)
- [/src/cern/tms/beam/libBeam/BRtc.cpp](#)

9.39 BRtcThreaded Class Reference

Threaded real time clock.

```
#include <BRtc.h>
```

Inheritance diagram for BRtcThreaded::



Public Member Functions

- `BRtcThreaded ()`
- `~BRtcThreaded ()`
- `BError init (int rate)`
Setup interrupt rate.
- `void wait (int delayUs)`
Wait specified uS.

Private Member Functions

- `void * function ()`

Private Attributes

- `BRtc orte`
- `int orate`
- `BCond ocond`

9.39.1 Detailed Description

Threaded real time clock.

9.39.2 Constructor & Destructor Documentation

9.39.2.1 BRtcThreaded::BRtcThreaded ()

9.39.2.2 BRtcThreaded::~~BRtcThreaded ()

9.39.3 Member Function Documentation

9.39.3.1 BError BRtcThreaded::init (int rate)

Setup interrupt rate.

9.39.3.2 void BRtcThreaded::wait (int *delayUs*)

Wait specified uS.

9.39.3.3 void * BRtcThreaded::function () [private, virtual]

Reimplemented from [BThread](#).

9.39.4 Member Data Documentation

9.39.4.1 BRtc BRtcThreaded::ortc [private]

9.39.4.2 int BRtcThreaded::orate [private]

9.39.4.3 BCond BRtcThreaded::ocond [private]

The documentation for this class was generated from the following files:

- [/src/cern/tms/beam/libBeam/BRtc.h](#)
- [/src/cern/tms/beam/libBeam/BRtc.cpp](#)

9.40 BRWLock Class Reference

thread read-write locks

```
#include <BRWLock.h>
```

Public Member Functions

- [BRWLock \(\)](#)
- [BRWLock \(const \[BRWLock\]\(#\) &rwlock\)](#)
- [~BRWLock \(\)](#)
- [int rdLock \(\)](#)
Set lock, wait if necessary.
- [int tryRdLock \(\)](#)
Test the lock.
- [int wrLock \(\)](#)
Set lock, wait if necessary.
- [int tryWrLock \(\)](#)
Test the lock.
- [int unlock \(\)](#)
Unlock the lock.
- [BRWLock & operator= \(const \[BRWLock\]\(#\) &rwlock\)](#)

Private Attributes

- `pthread_rwlock_t` [olock](#)

9.40.1 Detailed Description

thread read-write locks

9.40.2 Constructor & Destructor Documentation

9.40.2.1 [BRWLock::BRWLock \(\)](#)

9.40.2.2 [BRWLock::BRWLock \(const \[BRWLock\]\(#\) & *rwlock*\)](#)

9.40.2.3 [BRWLock::~~BRWLock \(\)](#)

9.40.3 Member Function Documentation

9.40.3.1 [int \[BRWLock::rdLock \\(\\)\]\(#\)](#)

Set lock, wait if necessary.

9.40.3.2 int BRWLock::tryRdLock ()

Test the lock.

9.40.3.3 int BRWLock::wrLock ()

Set lock, wait if necessary.

9.40.3.4 int BRWLock::tryWrLock ()

Test the lock.

9.40.3.5 int BRWLock::unlock ()

Unlock the lock.

9.40.3.6 BRWLock & BRWLock::operator= (const BRWLock & *rwlock*)

9.40.4 Member Data Documentation

9.40.4.1 pthread_rwlock_t BRWLock::olock [private]

The documentation for this class was generated from the following files:

- [/src/cern/tms/beam/libBeam/BRWLock.h](#)
- [/src/cern/tms/beam/libBeam/BRWLock.cpp](#)

9.41 BSema Class Reference

Sempahore class.

```
#include <BSema.h>
```

Public Member Functions

- [BSema](#) (int value=0)
- [BSema](#) (const [BSema](#) &sema)
- [~BSema](#) ()
- int [post](#) ()
Post condition.
- int [wait](#) ()
Wait for contition.
- int [timedWait](#) (int timeUs)
Wait for condition with timeout.
- int [tryWait](#) ()
Test for the condition.
- int [getValue](#) () const
- [BSema](#) & [operator=](#) (const [BSema](#) &sema)

Private Attributes

- sem_t [osema](#)

9.41.1 Detailed Description

Sempahore class.

9.41.2 Constructor & Destructor Documentation

9.41.2.1 [BSema::BSema](#) (int *value* = 0)

9.41.2.2 [BSema::BSema](#) (const [BSema](#) & *sema*)

9.41.2.3 [BSema::~~BSema](#) ()

9.41.3 Member Function Documentation

9.41.3.1 int [BSema::post](#) ()

Post condition.

9.41.3.2 int BSema::wait ()

Wait for contition.

9.41.3.3 int BSema::timedWait (int *timeUs*)

Wait for condition with timeout.

9.41.3.4 int BSema::tryWait ()

Test for the condition.

9.41.3.5 int BSema::getValue () const

9.41.3.6 BSema & BSema::operator= (const BSema & *sema*)

9.41.4 Member Data Documentation

9.41.4.1 sem_t BSema::osema [private]

The documentation for this class was generated from the following files:

- [/src/cern/tms/beam/libBeam/BSema.h](#)
- [/src/cern/tms/beam/libBeam/BSema.cpp](#)

9.42 BSignal Class Reference

```
#include <SigGen.h>
```

Public Types

- enum { [NumChannels](#) = 9 }

Public Member Functions

- [BSignal](#) (int [id](#)=0, int [numSamples](#)=0, int [numRepeat](#)=0, int [nextId](#)=0)
- [BSignal](#) (const [BSignal](#) &sig)
- [~BSignal](#) ()
- [BSignal](#) & [operator=](#) (const [BSignal](#) &sig)

Public Attributes

- int [id](#)
- int [numSamples](#)
- int [numRepeat](#)
- int [nextId](#)
- [Sample](#) * [data](#) [[NumChannels](#)]

9.42.1 Member Enumeration Documentation

9.42.1.1 anonymous enum

Enumerator:

NumChannels

9.42.2 Constructor & Destructor Documentation

9.42.2.1 `BSignal::BSignal (int id = 0, int numSamples = 0, int numRepeat = 0, int nextId = 0)`

9.42.2.2 `BSignal::BSignal (const BSignal & sig)`

9.42.2.3 `BSignal::~BSignal ()`

9.42.3 Member Function Documentation

9.42.3.1 `BSignal & BSignal::operator= (const BSignal & sig)`

9.42.4 Member Data Documentation

9.42.4.1 `int BSignal::id`

9.42.4.2 `int BSignal::numSamples`

9.42.4.3 `int BSignal::numRepeat`

9.42.4.4 `int BSignal::nextId`

9.42.4.5 `Sample* BSignal::data[NumChannels]`


The documentation for this class was generated from the following files:

- [SigGen.h](#)
- [SigGen.cpp](#)

9.43 BSocket Class Reference

```
#include <BSocket.h>
```

Inheritance diagram for BSocket::



Public Types

- enum [NType](#) { [STREAM](#), [DGRAM](#) }
- enum [Priority](#) { [PriorityLow](#), [PriorityNormal](#), [PriorityHigh](#) }

Public Member Functions

- [BSocket](#) ()
- [BSocket](#) (int fd)
- [BSocket](#) (NType type)
- [~BSocket](#) ()
- [BError](#) init (NType type)
- int [getFd](#) ()
- [BError](#) bind (const [BSocketAddress](#) &add)
- [BError](#) connect (const [BSocketAddress](#) &add)
- [BError](#) shutdown (int how)
- [BError](#) close ()
- [BError](#) listen (int backlog=5)
- [BError](#) accept (int &fd)
- [BError](#) accept (int &fd, [BSocketAddress](#) &address)
- [BError](#) send (const void *buf, BSize nbytes, BSize &nbytesSent, int flags=0)
- [BError](#) sendTo (const [BSocketAddress](#) &address, const void *buf, BSize nbytes, BSize &nbytesSent, int flags=0)
- [BError](#) recv (void *buf, BSize maxbytes, BSize &nbytesRecv, int flags=0)
- [BError](#) recvFrom ([BSocketAddress](#) &address, void *buf, BSize maxbytes, BSize &nbytesRecv, int flags=0)

- [BError recvWithTimeout](#) (void *buf, [BSize](#) maxbytes, [BSize](#) &nbytesRecv, int timeout, int flags=0)
- [BError recvFromWithTimeout](#) ([BSocketAddress](#) &address, void *buf, [BSize](#) maxbytes, [BSize](#) &nbytesRecv, int timeout, int flags=0)
- [BError setSockOpt](#) (int level, int optname, void *optval, unsigned int optlen)
- [BError getSockOpt](#) (int level, int optname, void *optval, unsigned int *optlen)
- [BError setReuseAddress](#) (int on)
- [BError setBroadCast](#) (int on)
- [BError setPriority](#) ([Priority](#) priority)
- [BError getMTU](#) (uint32_t &mtu)
- [BError getAddress](#) ([BSocketAddress](#) &address)

Private Attributes

- int [osocket](#)

9.43.1 Member Enumeration Documentation

9.43.1.1 enum BSocket::NType

Enumerator:

STREAM

DGRAM

9.43.1.2 enum BSocket::Priority

Enumerator:

PriorityLow

PriorityNormal

PriorityHigh

9.43.2 Constructor & Destructor Documentation

9.43.2.1 BSocket::BSocket ()

9.43.2.2 BSocket::BSocket (int *fd*)

9.43.2.3 BSocket::BSocket (NType *type*)

9.43.2.4 BSocket::~~BSocket ()

9.43.3 Member Function Documentation

9.43.3.1 BError BSocket::init (NType *type*)

9.43.3.2 int BSocket::getFd ()

9.43.3.3 BError BSocket::bind (const BSocketAddress & *add*)

9.43.3.4 BError BSocket::connect (const BSocketAddress & *add*)

9.43.3.5 BError BSocket::shutdown (int *how*)

9.43.3.6 BError BSocket::close ()

9.43.3.7 BError BSocket::listen (int *backlog* = 5)

9.43.3.8 BError BSocket::accept (int & *fd*)

9.43.3.9 BError BSocket::accept (int & *fd*, BSocketAddress & *address*)

9.43.3.10 BError BSocket::send (const void * *buf*, BSize *nbytes*, BSize & *nbytesSent*, int *flags* = 0)

9.43.3.11 BError BSocket::sendTo (const BSocketAddress & *address*, const void * *buf*, BSize *nbytes*, BSize & *nbytesSent*, int *flags* = 0)

9.43.3.12 BError BSocket::recv (void * *buf*, BSize *maxbytes*, BSize & *nbytesRecv*, int *flags* = 0)

9.43.3.13 BError BSocket::recvFrom (BSocketAddress & *address*, void * *buf*, BSize *maxbytes*, BSize & *nbytesRecv*, int *flags* = 0)

9.43.3.14 BError BSocket::recvWithTimeout (void * *buf*, BSize *maxbytes*, BSize & *nbytesRecv*, int *timeout*, int *flags* = 0)

9.43.3.15 BError BSocket::recvFromWithTimeout (BSocketAddress & *address*, void * *buf*, BSize *maxbytes*, BSize & *nbytesRecv*, int *timeout*, int *flags* = 0)

9.43.3.16 BError BSocket::setSockOpt (int *level*, int *optname*, void * *optval*, unsigned int *optlen*)

9.43.3.17 BError BSocket::getSockOpt (int *level*, int *optname*, void * *optval*, unsigned int * *optlen*)

9.43.3.18 BError BSocket::setReuseAddress (int *on*)

9.43.3.19 BError BSocket::setBroadCast (int *on*)

Generated on Thu Dec 18 13:21:07 2008 for LibTmsApi by Doxygen

9.43.3.20 BError BSocket::setPriority (Priority *priority*)

9.43.3.21 BError BSocket::getMTU (uint32_t & *mtu*)

9.43.3.22 BError BSocket::getAddress (BSocketAddress & *address*)


- [/src/cern/tms/beam/libBeam/BSocket.h](#)
- [/src/cern/tms/beam/libBeam/BSocket.cpp](#)

9.44 BSocketAddress Class Reference

Socket Address.

```
#include <BSocket.h>
```

Inheritance diagram for BSocketAddress::



Public Types

- typedef struct sockaddr [SockAddr](#)

Public Member Functions

- [BSocketAddress](#) ()
- [BSocketAddress](#) (const [BSocketAddress](#) &add)
- [BSocketAddress](#) ([SockAddr](#) *address, int len)
- [~BSocketAddress](#) ()
- [BError](#) set ([SockAddr](#) *address, int len)
- const [SockAddr](#) * [raw](#) () const
- int [len](#) () const
- [BSocketAddress](#) & [operator=](#) (const [BSocketAddress](#) &add)
- [operator](#) const [SockAddr](#) * () const
- int [operator==](#) (const [BSocketAddress](#) &add) const
- int [operator!=](#) (const [BSocketAddress](#) &add) const

Private Attributes

- int [olen](#)
- [SockAddr](#) * [oaddress](#)

9.44.1 Detailed Description

Socket Address.

9.44.2 Member Typedef Documentation

9.44.2.1 `typedef struct sockaddr BSocketAddress::SockAddr` [read]

9.44.3 Constructor & Destructor Documentation

9.44.3.1 `BSocketAddress::BSocketAddress ()`

9.44.3.2 `BSocketAddress::BSocketAddress (const BSocketAddress & add)`

9.44.3.3 `BSocketAddress::BSocketAddress (SockAddr * address, int len)`

9.44.3.4 `BSocketAddress::~~BSocketAddress ()`

9.44.4 Member Function Documentation

9.44.4.1 `BError BSocketAddress::set (SockAddr * address, int len)`

9.44.4.2 `const BSocketAddress::SockAddr * BSocketAddress::raw () const`

9.44.4.3 `int BSocketAddress::len () const`

9.44.4.4 `BSocketAddress & BSocketAddress::operator= (const BSocketAddress & add)`

9.44.4.5 `BSocketAddress::operator const SockAddr * () const` [inline]

9.44.4.6 `int BSocketAddress::operator== (const BSocketAddress & add) const`

9.44.4.7 `int BSocketAddress::operator!= (const BSocketAddress & add) const`

9.44.5 Member Data Documentation

9.44.5.1 `int BSocketAddress::olen` [private]

9.44.5.2 `SockAddr* BSocketAddress::oaddress` [private]

The documentation for this class was generated from the following files:


- [/src/cern/tms/beam/libBeam/BSocket.h](#)
- [/src/cern/tms/beam/libBeam/BSocket.cpp](#)

9.45 BSocketAddressINET Class Reference

IP aware socket address.

```
#include <BSocket.h>
```

Inheritance diagram for BSocketAddressINET::



Public Types

- typedef struct sockaddr_in [SockAddrIP](#)

Public Member Functions

- [BError set](#) ([BString](#) hostName, uint32_t port)
- [BError set](#) (uint32_t address, uint32_t port)
- [BError set](#) ([BString](#) hostName, [BString](#) service, [BString](#) type)
- void [setPort](#) (uint32_t port)
- uint32_t [address](#) ()

Returns socket ip address.

- uint32_t [port](#) ()

Returns socket port.

- [BString getString](#) ()

Return string version of address <ip>:<port>.

Static Public Member Functions

- static [BString getHostName](#) ()

Get this hosts network name.

- static [BList](#)< uint32_t > [getIpAddresses](#) ()

Get a list of all the IP addresses of this host.

- static [BList](#)< [BString](#) > [getIpAddressList](#) ()

Get a list of all the IP addresses of this host under hostname.

- static [BList](#)< [BString](#) > [getIpAddressListAll](#) ()

Get a list of all the IP addresses of this host looking at physical interfaces.

9.45.1 Detailed Description

IP aware socket address.

9.45.2 Member Typedef Documentation

9.45.2.1 `typedef struct sockaddr_in BSocketAddressINET::SockAddrIP` [read]

9.45.3 Member Function Documentation

9.45.3.1 `BError BSocketAddressINET::set (BString hostName, uint32_t port)`

9.45.3.2 `BError BSocketAddressINET::set (uint32_t address, uint32_t port)`

9.45.3.3 `BError BSocketAddressINET::set (BString hostName, BString service, BString type)`

9.45.3.4 `void BSocketAddressINET::setPort (uint32_t port)`

9.45.3.5 `uint32_t BSocketAddressINET::address ()`

Returns socket ip address.

9.45.3.6 `uint32_t BSocketAddressINET::port ()`

Returns socket port.

9.45.3.7 `BString BSocketAddressINET::getString ()`

Return string version of address <ip>:<port>.

9.45.3.8 `BString BSocketAddressINET::getHostName ()` [static]

Get this hosts network name.

9.45.3.9 `BList< uint32_t > BSocketAddressINET::getIpAddresses ()` [static]

Get a list of all the IP addresses of this host.

9.45.3.10 `BList< BString > BSocketAddressINET::getIpAddressList ()` [static]

Get a list of all the IP addresses of this host under hostname.

9.45.3.11 `BList< BString > BSocketAddressINET::getIpAddressListAll ()` [static]

Get a list of all the IP addresses of this host looking at physical interfaces.

The documentation for this class was generated from the following files:

- /src/cern/tms/beam/libBeam/[BSocket.h](#)

- [/src/cern/tms/beam/libBeam/BSocket.cpp](#)

9.46 BString Class Reference

```
#include <BString.h>
```

Public Member Functions

- [BString](#) ()
- [BString](#) (const [BString](#) &string)
- [BString](#) (const char *str)
- [BString](#) (char ch)
- [BString](#) (int v)
- [BString](#) (unsigned int v)
- [BString](#) (long v)
- [BString](#) (unsigned long long)
- [BString](#) (double v)
- virtual [~BString](#) ()
- [BString copy](#) ()
Return an independant copy.
- virtual void [strChanged](#) ()
- int [len](#) () const
Length of string.
- const char * [retStr](#) () const
Ptr to char representation.*
- char * [retStrDup](#) () const
Ptr to newly malloc'd char.*
- int [retInt](#) () const
Return string as a int.
- double [retDouble](#) () const
Return string as a double.
- int [compare](#) (const [BString](#) &string) const
Compare strings.
- int [compareWild](#) (const [BString](#) &string) const
Compare string to string with wildcards.
- int [compareWildExpression](#) (const [BString](#) &string) const
Compare string to space delimited patterns.
- [BString add](#) (const [BString](#) &str) const
Add two strings.
- [BString & truncate](#) (int len)
Truncate to length len.

- [BString & pad](#) (int len)
Pad to length len.
- [BString & toUpper](#) ()
Convert to uppercase.
- [BString & toLower](#) ()
Convert to lowercase.
- void [removeNL](#) ()
Remove if present NL from last char.
- [BString subString](#) (int start, int len) const
Returns substring.
- int [del](#) (int start, int len)
Delete substring.
- int [insert](#) (int start, [BString](#) str)
Insert substring.
- void [printf](#) (const char *fmt,...)
Formatted print into the string.
- int [find](#) (char ch) const
Find ch in string searching forwards.
- int [findReverse](#) (char ch) const
Find ch in string searching backwards.
- [BList< BString > getTokenList](#) ([BString](#) separators)
Break string into tokens.
- [BString removeSeparators](#) ([BString](#) separators)
Remove any char from sepatators from string.
- [BString pullToken](#) ([BString](#) terminators)
Pull token from start of string.
- [BString pullSeparators](#) ([BString](#) separators)
Pull separators from start of string.
- [BString pullWord](#) ()
Pull a word out of the head of the string.
- [BString pullLine](#) ()
Pull a line out of the head of the string.
- [BString field](#) (int field) const

- char ** fields ()
- BString & operator= (const BString &string)
- char & operator[] (int pos)
- int operator== (const BString &s) const
- int operator== (const char *s) const
- int operator> (const BString &s) const
- int operator> (const char *s) const
- int operator< (const BString &s) const
- int operator< (const char *s) const
- int operator>= (const BString &s) const
- int operator<= (const BString &s) const
- int operator!= (const BString &s) const
- int operator!= (const char *s) const
- BString operator+ (const BString &s) const
- BString operator+ (const char *s) const
- BString operator+= (const BString &s)
- BString operator+= (const char *s)
- BString operator+ (char ch) const
- BString operator+ (int i) const
- BString operator+ (unsigned int i) const
- BString operator+ (unsigned long long i) const
- operator const char * () const

Static Public Member Functions

- static BString convert (char ch)
Converts char to string.
- static BString convert (int value)
Converts int to string.
- static BString convert (unsigned int value)
Converts uint to string.
- static BString convert (long value)
Converts long to string.
- static BString convert (double value)
Converts double to string.
- static BString convert (unsigned long long value)
Converts u long long to string.
- static BString convertHex (int value)
Converts int to string as hex value.
- static BString convertHex (unsigned int value)
Converts uint to string as hex value.

Protected Attributes

- [BRefData](#) * *ostr*

Private Member Functions

- void [Init](#) (const char **str*)
- int [inString](#) (int *pos*) const
- int [isSpace](#) (char *ch*) const

9.46.1 Constructor & Destructor Documentation

9.46.1.1 BString::BString ()

9.46.1.2 BString::BString (const BString & *string*)

9.46.1.3 BString::BString (const char * *str*)

9.46.1.4 BString::BString (char *ch*)

9.46.1.5 BString::BString (int *v*)

9.46.1.6 BString::BString (unsigned int *v*)

9.46.1.7 BString::BString (long *v*)

9.46.1.8 BString::BString (unsigned long long *value*)

9.46.1.9 BString::BString (double *v*)

9.46.1.10 BString::~BString () [virtual]

9.46.2 Member Function Documentation

9.46.2.1 BString BString::convert (char *ch*) [static]

Converts char to string.

9.46.2.2 BString BString::convert (int *value*) [static]

Converts int to string.

9.46.2.3 BString BString::convert (unsigned int *value*) [static]

Converts uint to string.

9.46.2.4 BString BString::convert (long *value*) [static]

Converts long to string.

9.46.2.5 BString BString::convert (double *value*) [static]

Converts double to string.

9.46.2.6 BString BString::convert (unsigned long long *value*) [static]

Converts u long long to string.

9.46.2.7 BString BString::convertHex (int *value*) [static]

Converts int to string as hex value.

9.46.2.8 BString BString::convertHex (unsigned int *value*) [static]

Converts uint to string as hex value.

9.46.2.9 BString BString::copy ()

Return an independant copy.

9.46.2.10 void BString::strChanged () [virtual]**9.46.2.11 int BString::len () const**

Length of string.

9.46.2.12 const char * BString::retStr () const

Ptr to char* representation.

9.46.2.13 char * BString::retStrDup () const

Ptr to newly malloc'd char*.

9.46.2.14 int BString::retInt () const

Return string as a int.

9.46.2.15 double BString::retDouble () const

Return string as a double.

9.46.2.16 int BString::compare (const BString & *string*) const

Compare strings.

9.46.2.17 int BString::compareWild (const BString & *string*) const

Compare string to string with wildcards.

9.46.2.18 int BString::compareWildExpression (const BString & *string*) const

Compare string to space delimited patterns.

9.46.2.19 BString BString::add (const BString & *str*) const

Add two strings.

9.46.2.20 BString & BString::truncate (int *len*)

Truncate to length len.

9.46.2.21 BString & BString::pad (int *len*)

Pad to length len.

9.46.2.22 BString & BString::toUpper ()

Convert to uppercase.

9.46.2.23 BString & BString::toLower ()

Convert to lowercase.

9.46.2.24 void BString::removeNL ()

Remove if present NL from last char.

9.46.2.25 BString BString::subString (int *start*, int *len*) const

Returns substring.

9.46.2.26 int BString::del (int *start*, int *len*)

Delete substring.

9.46.2.27 int BString::insert (int *start*, BString *str*)

Insert substring.

9.46.2.28 void BString::printf (const char **fmt*, ...)

Formatted print into the string.

9.46.2.29 int BString::find (char *ch*) const

Find *ch* in string searching forwards.

9.46.2.30 int BString::findReverse (char *ch*) const

Find *ch* in string searching backwards.

9.46.2.31 BList< BString > BString::getTokenList (BString *separators*)

Break string into tokens.

9.46.2.32 BString BString::removeSeparators (BString *separators*)

Remove any char from separators from string.

9.46.2.33 BString BString::pullToken (BString *terminators*)

Pull token from start of string.

9.46.2.34 BString BString::pullSeparators (BString *separators*)

Pull separators from start of string.

9.46.2.35 BString BString::pullWord ()

Pull a word out of the head of the string.

9.46.2.36 BString BString::pullLine ()

Pull a line out of the head of the string.

9.46.2.37 BString BString::field (int *field*) const**9.46.2.38 char ** BString::fields ()****9.46.2.39 BString & BString::operator= (const BString & *string*)****9.46.2.40]**

char & BString::operator[] (int *pos*)

- 9.46.2.41 `int BString::operator==(const BString & s) const` [inline]
- 9.46.2.42 `int BString::operator==(const char * s) const` [inline]
- 9.46.2.43 `int BString::operator>(const BString & s) const` [inline]
- 9.46.2.44 `int BString::operator>(const char * s) const` [inline]
- 9.46.2.45 `int BString::operator<(const BString & s) const` [inline]
- 9.46.2.46 `int BString::operator<(const char * s) const` [inline]
- 9.46.2.47 `int BString::operator>=(const BString & s) const` [inline]
- 9.46.2.48 `int BString::operator<=(const BString & s) const` [inline]
- 9.46.2.49 `int BString::operator!=(const BString & s) const` [inline]
- 9.46.2.50 `int BString::operator!=(const char * s) const` [inline]
- 9.46.2.51 `BString BString::operator+(const BString & s) const` [inline]
- 9.46.2.52 `BString BString::operator+(const char * s) const` [inline]
- 9.46.2.53 `BString BString::operator+=(const BString & s)` [inline]
- 9.46.2.54 `BString BString::operator+=(const char * s)` [inline]
- 9.46.2.55 `BString BString::operator+(char ch) const` [inline]
- 9.46.2.56 `BString BString::operator+(int i) const` [inline]
- 9.46.2.57 `BString BString::operator+(unsigned int i) const` [inline]
- 9.46.2.58 `BString BString::operator+(unsigned long long i) const` [inline]
- 9.46.2.59 `BString::operator const char * () const` [inline]
- 9.46.2.60 `void BString::Init(const char * str)` [private]
- 9.46.2.61 `int BString::inString(int pos) const` [private]
- 9.46.2.62 `int BString::isSpace(char ch) const` [private]

9.46.3 Member Data Documentation

9.46.3.1 `BRefData* BString::ostr` [protected]


The documentation for this class was generated from the following files:

- `/src/cern/tms/beam/libBeam/BString.h`
- `/src/cern/tms/beam/libBeam/BString.cpp`

9.47 BThread Class Reference

```
#include <BThread.h>
```

Inheritance diagram for BThread::



Public Member Functions

- [BThread](#) ()
- virtual [~BThread](#) ()
- int [setInitPriority](#) (int policy, int priority)
- int [setInitStackSize](#) (size_t stackSize)
- int [start](#) ()
- void * [result](#) ()
- int [running](#) ()
- int [setPriority](#) (int policy, int priority)
- int [cancel](#) ()
- void * [waitForCompletion](#) ()
- pthread_t [getThread](#) ()
- virtual void * [function](#) ()

Static Private Member Functions

- static void * [startFunc](#) (void *)

Private Attributes

- pthread_t [othread](#)
- size_t [ostackSize](#)
- int [opolicy](#)
- int [opriority](#)
- int [orunning](#)
- void * [oresult](#)

9.47.1 Constructor & Destructor Documentation

9.47.1.1 **BThread::BThread ()**

9.47.1.2 **BThread::~~BThread ()** [virtual]

9.47.2 Member Function Documentation

9.47.2.1 **int BThread::setInitPriority (int *policy*, int *priority*)**

9.47.2.2 **int BThread::setInitStackSize (size_t *stackSize*)**

9.47.2.3 **int BThread::start ()**

9.47.2.4 **void * BThread::result ()**

9.47.2.5 **int BThread::running ()**

9.47.2.6 **int BThread::setPriority (int *policy*, int *priority*)**

9.47.2.7 **int BThread::cancel ()**

9.47.2.8 **void * BThread::waitForCompletion ()**

9.47.2.9 **pthread_t BThread::getThread ()**

9.47.2.10 **void * BThread::function ()** [virtual]

Reimplemented in [BoapServerConnection](#), [BoapServer](#), and [BRtcThreaded](#).

9.47.2.11 **void * BThread::startFunc (void * *arg*)** [static, private]

9.47.3 Member Data Documentation

9.47.3.1 **pthread_t BThread::othread** [private]

9.47.3.2 **size_t BThread::ostackSize** [private]

9.47.3.3 **int BThread::opolicy** [private]

9.47.3.4 **int BThread::opriority** [private]

9.47.3.5 **int BThread::orunning** [private]

9.47.3.6 **void* BThread::oresult** [private]

The documentation for this class was generated from the following files:

- [/src/cern/tms/beam/libBeam/BThread.h](#)
- [/src/cern/tms/beam/libBeam/BThread.cpp](#)

9.48 BTimer Class Reference

Stopwatch style timer.

```
#include <BTimer.h>
```

Public Member Functions

- [BTimer](#) ()
- [~BTimer](#) ()
- void [start](#) ()
Start timer.
- void [stop](#) ()
Stop timer.
- void [clear](#) ()
Clear timer.
- double [getElapsedTime](#) ()
Returns the elapsed time from the last start.
- void [add](#) ([BTimer](#) &timer)
Add two timers.
- double [average](#) ()
Average time is duration between [start\(\)](#) and [stop\(\)](#) / number of stops.
- double [peak](#) ()
Peak time.

Static Private Member Functions

- static double [getTime](#) ()

Private Attributes

- [BMutex](#) olock
- unsigned int [onum](#)
- double [ostartTime](#)
- double [oendTime](#)
- double [oaverage](#)
- double [opeak](#)

9.48.1 Detailed Description

Stopwatch style timer.

9.48.2 Constructor & Destructor Documentation

9.48.2.1 BTimer::BTimer ()

9.48.2.2 BTimer::~~BTimer ()

9.48.3 Member Function Documentation

9.48.3.1 void BTimer::start ()

Start timer.

9.48.3.2 void BTimer::stop ()

Stop timer.

9.48.3.3 void BTimer::clear ()

Clear timer.

9.48.3.4 double BTimer::getElapsedTime ()

Returns the elapsed time from the last start.

9.48.3.5 void BTimer::add (BTimer & *timer*)

Add two timers.

9.48.3.6 double BTimer::average ()

Average time is duration between [start\(\)](#) and [stop\(\)](#) / number of stops.

9.48.3.7 double BTimer::peak ()

Peak time.

9.48.3.8 `double BTimer::getTime ()` [static, private]

9.48.4 Member Data Documentation

9.48.4.1 `BMutex BTimer::olock` [private]

9.48.4.2 `unsigned int BTimer::onum` [private]

9.48.4.3 `double BTimer::ostartTime` [private]

9.48.4.4 `double BTimer::oendTime` [private]

9.48.4.5 `double BTimer::oaverage` [private]

9.48.4.6 `double BTimer::opeak` [private]

The documentation for this class was generated from the following files:

- [/src/cern/tms/beam/libBeam/BTimer.h](#)
- [/src/cern/tms/beam/libBeam/BTimer.cpp](#)

9.49 BUrl Class Reference

Basic access to a Url.

```
#include <BUrl.h>
```

Public Member Functions

- [BUrl \(\)](#)
- [~BUrl \(\)](#)
- [BError readString \(BString url, BString &str\)](#)

Reads URL.

Static Private Member Functions

- static [size_t writeData](#) (void *data, [size_t](#) size, [size_t](#) elSize, void *stream)

Private Attributes

- [BString ores](#)

Static Private Attributes

- static [int oinit](#)

9.49.1 Detailed Description

Basic access to a Url.

9.49.2 Constructor & Destructor Documentation

9.49.2.1 BUrl::BUrl ()

9.49.2.2 BUrl::~~BUrl ()

9.49.3 Member Function Documentation

9.49.3.1 BError BUrl::readString (BString url, BString & str)

Reads URL.

9.49.3.2 `size_t BUrl::writeData (void * data, size_t size, size_t elSize, void * stream)` [static, private]

9.49.4 Member Data Documentation

9.49.4.1 `int BUrl::oinit` [static, private]

9.49.4.2 `BString BUrl::ores` [private]

The documentation for this class was generated from the following files:

- [/src/cern/tms/beam/libBeam/BUrl.h](#)
- [/src/cern/tms/beam/libBeam/BUrl.cpp](#)

9.50 Tms::ConfigInfo Class Reference

This class describes the configuration of the TMS.

```
#include <TmsD.h>
```

Public Member Functions

- [ConfigInfo \(\)](#)
- [ConfigInfo \(BArray< \[PuChannel\]\(#\) > ppuReferences\)](#)

Public Attributes

- [BArray< \[PuChannel\]\(#\) > puReferences](#)

The logical to physical Pick-Up table. Each PuReference includes a Module Controller identifier, a Physical Pick-Up number and a Physical Channel.

9.50.1 Detailed Description

This class describes the configuration of the TMS.

9.50.2 Constructor & Destructor Documentation

9.50.2.1 Tms::ConfigInfo::ConfigInfo ()

9.50.2.2 Tms::ConfigInfo::ConfigInfo (BArray< [PuChannel](#) > *ppuReferences*)

9.50.3 Member Data Documentation

9.50.3.1 BArray< [PuChannel](#) > Tms::ConfigInfo::puReferences

The logical to physical Pick-Up table. Each PuReference includes a Module Controller identifier, a Physical Pick-Up number and a Physical Channel.

The documentation for this class was generated from the following files:

- [TmsD.h](#)
- [TmsD.cc](#)

9.51 Tms::CycleInformation Class Reference

```
#include <TmsD.h>
```

Public Member Functions

- [CycleInformation](#) ()
- [CycleInformation](#) (UInt32 pcycleNumber, BString pcycleType, BList< [CycleInformationPeriod](#) > pperiods)

Public Attributes

- [UInt32](#) cycleNumber
The PS Cycle number.
- [BString](#) cycleType
The Cycle Type Name.
- [BList< \[CycleInformationPeriod\]\(#\) >](#) periods
The list of cycle periods.

9.51.1 Constructor & Destructor Documentation

9.51.1.1 Tms::CycleInformation::CycleInformation ()

9.51.1.2 Tms::CycleInformation::CycleInformation (UInt32 pcycleNumber, BString pcycleType, BList< [CycleInformationPeriod](#) > pperiods)

9.51.2 Member Data Documentation

9.51.2.1 UInt32 Tms::CycleInformation::cycleNumber

The PS Cycle number.

9.51.2.2 BString Tms::CycleInformation::cycleType

The Cycle Type Name.

9.51.2.3 BList<[CycleInformationPeriod](#)> Tms::CycleInformation::periods

The list of cycle periods.

The documentation for this class was generated from the following files:

- [TmsD.h](#)
- [TmsD.cc](#)

9.52 Tms::CycleInformationPeriod Class Reference

Cycle information.

```
#include <TmsD.h>
```

Public Member Functions

- [CycleInformationPeriod](#) ()
- [CycleInformationPeriod](#) (UInt32 pcyclePeriod, UInt32 pstartTime, UInt32 pendTime, UInt32 pharmonic, UInt32 pnumBunches, UInt32 pbunchMask, UInt32 pnumValues)

Public Attributes

- [UInt32 cyclePeriod](#)
The Cycle Period.
- [UInt32 startTime](#)
The start time in ms.
- [UInt32 endTime](#)
The end time in ms.
- [UInt32 harmonic](#)
The Machines harmonic number.
- [UInt32 numBunches](#)
The number of bunches.
- [UInt32 bunchMask](#)
Bitmask defining which buckets the bunches are captured from. Bit 0 is bucket 1, bit 1 is bucket 2 etc.
- [UInt32 numValues](#)
The total number of raw data values available.

9.52.1 Detailed Description

Cycle information.

9.52.2 Constructor & Destructor Documentation

9.52.2.1 Tms::CycleInformationPeriod::CycleInformationPeriod ()

9.52.2.2 Tms::CycleInformationPeriod::CycleInformationPeriod (UInt32 *pcyclePeriod*, UInt32 *pstartTime*, UInt32 *pendTime*, UInt32 *pharmonic*, UInt32 *pnumBunches*, UInt32 *pbunchMask*, UInt32 *pnumValues*)

9.52.3 Member Data Documentation

9.52.3.1 UInt32 Tms::CycleInformationPeriod::cyclePeriod

The Cycle Period.

9.52.3.2 UInt32 Tms::CycleInformationPeriod::startTime

The start time in ms.

9.52.3.3 UInt32 Tms::CycleInformationPeriod::endTime

The end time in ms.

9.52.3.4 UInt32 Tms::CycleInformationPeriod::harmonic

The Machines harmonic number.

9.52.3.5 UInt32 Tms::CycleInformationPeriod::numBunches

The number of bunches.

9.52.3.6 UInt32 Tms::CycleInformationPeriod::bunchMask

Bitmask defining which buckets the bunches are captured from. Bit 0 is bucket 1, bit 1 is bucket 2 etc.

9.52.3.7 UInt32 Tms::CycleInformationPeriod::numValues

The total number of raw data values available.

The documentation for this class was generated from the following files:


- [TmsD.h](#)
- [TmsD.cc](#)

9.53 Tms::CycleParam Class Reference

This class defines the parameters for a PS processing cycle.

```
#include <TmsD.h>
```

Inheritance diagram for Tms::CycleParam::



Public Member Functions

- [CycleParam \(\)](#)
- [CycleParam \(BString pcycleType, BString pinfo, UInt32 pchannel, UInt32 pllCycleStartFrequency, UInt32 pllInitialFrequency, UInt32 pllInitialFrequencyDelay, UInt32 pllFrefGain, UInt32 pllGain, UInt32 pllDdsMinimum, UInt32 pllDdsMaximum, BArray< Int32 > pfrefPhaseDelay, BArray< PuStateTable > pstateTable, BArray< BString > psettings\)](#)

Public Attributes

- [BString cycleType](#)
The Cycle Type Name of this parameter set, normally the BEAM type the set of parameters is designed to measure.
- [BString info](#)
Information on this parameter set.
- [UInt32 channel](#)
The channel number this configuration is for; 0 defines all channels.
- [UInt32 pllCycleStartFrequency](#)
This defines the initial PLL frequency. This is loaded on START_CYCLE.
- [UInt32 pllInitialFrequency](#)
This defines the initial PLL frequency. This is loaded after the delay given in pllInitialFrequencyDelay.
- [UInt32 pllInitialFrequencyDelay](#)
This defines the delay in milliseconds from START_CYCLE when the pllInitialFrequency is loaded.
- [UInt32 pllFrefGain](#)
The gain the FREF signal. This is a value in the range +-8191. A normal value would be around 4096.
- [UInt32 pllGain](#)
The gain of the PLL feedback system. This is the gain reduction of the PLL in terms of right bit shifts. A bit shift of 7 is about unity gain.

- [UInt32 pllDdsMinimum](#)

PLL DDS minimum frequency. If this and pllDdsMaximum is set to 0, this feature is disabled.

- [UInt32 pllDdsMaximum](#)

PLL DDS maximum frequency. If this and pllDdsMinimum is set to 0, this feature is disabled.

- [BArray< Int32 > frefPhaseDelay](#)

The phase delay parameters for the Fref timing signal for each of the Pick-Up channels. This is set based on the position of the Pick-Up's in the PS ring. Its value is based of Fref / 512.

- [BArray< PuStateTable > stateTable](#)

The array of State Table entries for the processing run.

- [BArray< BString > settings](#)

A string array defining the settings for the states. Used for [CycleParam](#) editors.

9.53.1 Detailed Description

This class defines the parameters for a PS processing cycle.

9.53.2 Constructor & Destructor Documentation

9.53.2.1 Tms::CycleParam::CycleParam ()

9.53.2.2 Tms::CycleParam::CycleParam (BString pcycleType, BString pinfo, UInt32 pchannel, UInt32 ppllCycleStartFrequency, UInt32 ppllInitialFrequency, UInt32 ppllInitialFrequencyDelay, UInt32 ppllFrefGain, UInt32 ppllGain, UInt32 ppllDdsMinimum, UInt32 ppllDdsMaximum, BArray< Int32 > pfrefPhaseDelay, BArray< PuStateTable > pstateTable, BArray< BString > psettings)

9.53.3 Member Data Documentation

9.53.3.1 BString Tms::CycleParam::cycleType

The Cycle Type Name of this parameter set, normally the BEAM type the set of parameters is designed to measure.

9.53.3.2 BString Tms::CycleParam::info

Information on this parameter set.

9.53.3.3 UInt32 Tms::CycleParam::channel

The channel number this configuration is for, 0 defines all channels.

9.53.3.4 UInt32 Tms::CycleParam::pllCycleStartFrequency

This defines the initial PLL frequency. This is loaded on START_CYCLE.

9.53.3.5 UInt32 Tms::CycleParam::pllInitialFrequency

This defines the initial PLL frequency. This is loaded after the delay given in pllInitialFrequencyDelay.

9.53.3.6 UInt32 Tms::CycleParam::pllInitialFrequencyDelay

This defines the delay in milliseconds from START_CYCLE when the pllInitialFrequency is loaded.

9.53.3.7 UInt32 Tms::CycleParam::pllFrefGain

The gain the FREF signal. This is a value in the range +-8191. A normal value would be around 4096.

9.53.3.8 UInt32 Tms::CycleParam::pllGain

The gain of the PLL feedback system. This is the gain reduction of the PLL in terms of right bit shifts. A bit shift of 7 is about unity gain.

9.53.3.9 UInt32 Tms::CycleParam::pllDdsMinimum

PLL DDS minimum frequency. If this and pllDdsMaximum is set to 0, this feature is disabled.

9.53.3.10 UInt32 Tms::CycleParam::pllDdsMaximum

PLL DDS maximum frequency. If this and pllDdsMinimum is set to 0, this feature is disabled.

9.53.3.11 BArray<Int32> Tms::CycleParam::frefPhaseDelay

The phase delay parameters for the Fref timing signal for each of the Pick-Up channels. This is set based on the position of the Pick-Up's in the PS ring. Its value is based of Fref / 512.

9.53.3.12 BArray<PuStateTable> Tms::CycleParam::stateTable

The array of State Table entries for the processing run.

9.53.3.13 BArray<BString> Tms::CycleParam::settings

A string array defining the settings for the states. Used for [CycleParam](#) editors.

The documentation for this class was generated from the following files:

- [TmsD.h](#)
- [TmsD.cc](#)

9.54 Tms::CycleParamDb Class Reference

Internal CycleParameter management class.

```
#include <TmsLib.h>
```

Public Member Functions

- [CycleParamDb](#) ([BString](#) baseDir=".")
- [BError](#) [getCycleTypes](#) ([BList](#)< [BString](#) > &typeList)
Get the list of CycleParameter types in the directory.
- [BError](#) [getFileNames](#) ([BList](#)< [BString](#) > &fileList)
Get a list of all of the CycleParameter file names.
- [BError](#) [getCycleParams](#) ([BString](#) fileName, [Tms::CycleParam](#) ¶m)
Get the CycleParameter from the given file name.
- [BError](#) [setCycleParams](#) ([Tms::CycleParam](#) param)
Set the CycleParameters. Writes to the appropriate file name.
- [BError](#) [deleteCycleParams](#) ([BString](#) cycleType, [UInt32](#) puChannel)
Deletes a CycleParameter definition file.
- [BError](#) [readCycleParams](#) ([BString](#) fileName, [Tms::CycleParam](#) ¶m)
Reads a set of CycleParameters from a file.
- [BError](#) [writeCycleParams](#) ([BString](#) fileName, [Tms::CycleParam](#) param)
Writes a set of CycleParameters to a file.

Private Attributes

- [BString](#) obaseDir

9.54.1 Detailed Description

Internal CycleParameter management class.

9.54.2 Constructor & Destructor Documentation

9.54.2.1 Tms::CycleParamDb::CycleParamDb ([BString](#) baseDir = " . ")

9.54.3 Member Function Documentation

9.54.3.1 BError Tms::CycleParamDb::getCycleTypes ([BList](#)< [BString](#) > & typeList)

Get the list of CycleParameter types in the directory.

9.54.3.2 BError Tms::CycleParamDb::getFileNames (BList< BString > &fileList)

Get a list of all of the CycleParameter file names.

9.54.3.3 BError Tms::CycleParamDb::getCycleParams (BString fileName, Tms::CycleParam ¶m)

Get the CycleParameter from the given file name.

9.54.3.4 BError Tms::CycleParamDb::setCycleParams (Tms::CycleParam param)

Set the CycleParameters. Writes to the appropriate file name.

9.54.3.5 BError Tms::CycleParamDb::deleteCycleParams (BString cycleType, UInt32 puChannel)

Deletes a CycleParameter definition file.

9.54.3.6 BError Tms::CycleParamDb::readCycleParams (BString fileName, Tms::CycleParam ¶m)

Reads a set of CycleParameters from a file.

9.54.3.7 BError Tms::CycleParamDb::writeCycleParams (BString fileName, Tms::CycleParam param)

Writes a set of CycleParameters to a file.

9.54.4 Member Data Documentation**9.54.4.1 BString Tms::CycleParamDb::obaseDir [private]**

The documentation for this class was generated from the following files:


- [TmsLib.h](#)
- [TmsLib.cc](#)

9.55 Tms::CycleParamEdit Class Reference

Cycle Parameter management class.

```
#include <TmsCycleParam.h>
```

Inheritance diagram for Tms::CycleParamEdit::



Public Member Functions

- [CycleParamEdit](#) ()
- [CycleParamEdit](#) (const [CycleParam](#) ¶m)
- void [clear](#) ()
- [BString](#) [getString](#) ()
Gets the Cycle Parameters in a string format for writing to a file or display.
- [BError](#) [setString](#) ([BString](#) str)
Sets the Cycle Parameters from a string. For reading from a file.
- [BError](#) [readFromFile](#) ([BString](#) fileName)
Reads the Cycle Parameters from a file.
- [BError](#) [writeToFile](#) ([BString](#) fileName)
Writes the Cycle Parameters to a file.
- [BError](#) [setStates](#) ([BList](#)< [CycleParamState](#) > cycleStates)
Sets the Cycle Parameter states given the state information list.
- [BError](#) [getStates](#) ([BList](#)< [CycleParamState](#) > &cycleStates)
Returns the state information list describing the Cycle Parameter states. These may not be present.

Static Public Member Functions

- static void [getDefaultState](#) ([CycleParamState](#) &state)
Get the default settings for a state.
- static void [getdefaultPickupPositions](#) ([BArray](#)< [Int32](#) > &pos)
Get the default pickup positions.

Private Member Functions

- double [value](#) (int numSamples, int harmonic, double phase, int sample)
- int [bunch](#) (int numSamples, int harmonic, double phase, int sample)
- [BError generateState](#) (int num, [Tms::TmsState](#) state, [CycleParamState](#) stateParam, int lo1Harmonic, double lo1Phase, int lo2Harmonic, double lo2Phase)

9.55.1 Detailed Description

Cycle Parameter management class.

9.55.2 Constructor & Destructor Documentation

9.55.2.1 [Tms::CycleParamEdit::CycleParamEdit \(\)](#)

9.55.2.2 [Tms::CycleParamEdit::CycleParamEdit \(const CycleParam & param\)](#)

9.55.3 Member Function Documentation

9.55.3.1 [void Tms::CycleParamEdit::clear \(\)](#)

9.55.3.2 [BString Tms::CycleParamEdit::getString \(\)](#)

Gets the Cycle Parameters in a string format for writing to a file or display.

9.55.3.3 [BError Tms::CycleParamEdit::setString \(BString str\)](#)

Sets the Cycle Parameters from a string. For reading from a file.

9.55.3.4 [BError Tms::CycleParamEdit::readFromFile \(BString fileName\)](#)

Reads the Cycle Parameters from a file.

9.55.3.5 [BError Tms::CycleParamEdit::writeToFile \(BString fileName\)](#)

Writes the Cycle Parameters to a file.

9.55.3.6 [BError Tms::CycleParamEdit::setStates \(BList< CycleParamState > cycleStates\)](#)

Sets the Cycle Parameter states given the state information list.

9.55.3.7 [BError Tms::CycleParamEdit::getStates \(BList< CycleParamState > & cycleStates\)](#)

Returns the state information list describing the Cycle Parameter states. These may not be present.

9.55.3.8 [void Tms::CycleParamEdit::getDefaultState \(CycleParamState & state\) \[static\]](#)

Get the default settings for a state.

9.55.3.9 void Tms::CycleParamEdit::getDefaultPickupPositions (BArray< Int32 > & pos)
[static]

Get the default pickup positions.

Calculates the base pickup phase values for the PS ring.

9.55.3.10 double Tms::CycleParamEdit::value (int numSamples, int harmonic, double phase, int sample) [private]

9.55.3.11 int Tms::CycleParamEdit::bunch (int numSamples, int harmonic, double phase, int sample) [private]

9.55.3.12 BError Tms::CycleParamEdit::generateState (int num, Tms::TmsState state, CycleParamState stateParam, int lo1Harmonic, double lo1Phase, int lo2Harmonic, double lo2Phase) [private]

This function will generate the phase tables for a given state. It is passed the parameters for the LO1 reference and the LO2 reference. If lo2Harmonic is 1, then FREF is generated.

The documentation for this class was generated from the following files:

- [TmsCycleParam.h](#)
- [TmsCycleParam-1.cc](#)
- [TmsCycleParam.cc](#)

9.56 Tms::CycleParamItem Class Reference

```
#include <TmsD.h>
```

Public Member Functions

- [CycleParamItem \(\)](#)
- [CycleParamItem \(BString pcycleType, UInt32 pchannel\)](#)

Public Attributes

- [BString cycleType](#)

The Cycle Type Name of this parameter set, normally the BEAM type the set of parameters is designed to measure.

- [UInt32 channel](#)

The channel number this configuration is for, 0 defines all channels.

9.56.1 Constructor & Destructor Documentation

9.56.1.1 Tms::CycleParamItem::CycleParamItem ()

9.56.1.2 Tms::CycleParamItem::CycleParamItem (BString pcycleType, UInt32 pchannel)

9.56.2 Member Data Documentation

9.56.2.1 BString Tms::CycleParamItem::cycleType

The Cycle Type Name of this parameter set, normally the BEAM type the set of parameters is designed to measure.

9.56.2.2 UInt32 Tms::CycleParamItem::channel

The channel number this configuration is for, 0 defines all channels.

The documentation for this class was generated from the following files:

- [TmsD.h](#)
- [TmsD.cc](#)

9.57 Tms::CycleParamState Class Reference

```
#include <TmsCycleParam.h>
```

Public Member Functions

- [CycleParamState](#) ()
- void [clear](#) ()
Clear the entry.
- [BString](#) [getString](#) ()
Returns the [CycleParamState](#) in string form.
- [BError](#) [setString](#) ([BString](#) str)
Sets the [CycleParamState](#) from a string.

Public Attributes

- [UInt32](#) [period](#)
The cycle period.
- [UInt32](#) [bunchMask](#)
The set of bunches to capture bit mask.
- [UInt32](#) [mean1Mask](#)
The set of bunches to pass through meanFilter1.
- [UInt32](#) [mean2Mask](#)
The set of bunches to pass through meanFilter2.
- [UInt32](#) [loHarmonic](#)
The LO harmonic number used in this state.
- double [loPhase](#)
The phase offset of the LO as a fraction of FREF (+-1.0).
- int [useLoFref](#)
Flag setting system to use LO as FREF rather than phase table address MSB.
- int [acquireData](#)
Flag to acquire data during this state.
- double [gateWidth](#)
The gate pulse width as a fraction of LO (0 - 1.0).
- double [gatePhase](#)
The gate phase offset as a fraction of LO (0 - 1.0).

- double [blrWidth](#)
The gate pulse width as a fraction of LO (0 - 1.0).
- double [blrPhase](#)
The gate phase offset as a fraction of LO (0 - 1.0).

9.57.1 Constructor & Destructor Documentation

9.57.1.1 Tms::CycleParamState::CycleParamState ()

9.57.2 Member Function Documentation

9.57.2.1 void Tms::CycleParamState::clear ()

Clear the entry.

9.57.2.2 BString Tms::CycleParamState::getString ()

Returns the [CycleParamState](#) in string form.

9.57.2.3 BError Tms::CycleParamState::setString (BString str)

Sets the [CycleParamState](#) from a string.

9.57.3 Member Data Documentation

9.57.3.1 UInt32 Tms::CycleParamState::period

The cycle period.

9.57.3.2 UInt32 Tms::CycleParamState::bunchMask

The set of bunches to capture bit mask.

9.57.3.3 UInt32 Tms::CycleParamState::mean1Mask

The set of bunches to pass through meanFilter1.

9.57.3.4 UInt32 Tms::CycleParamState::mean2Mask

The set of bunches to pass through meanFilter2.

9.57.3.5 UInt32 Tms::CycleParamState::loHarmonic

The LO harmonic number used in this state.

9.57.3.6 double Tms::CycleParamState::loPhase

The phase offset of the LO as a fraction of FREF (+/-1.0).

9.57.3.7 int Tms::CycleParamState::useLoFref

Flag setting system to use LO as FREF rather than phase table address MSB.

9.57.3.8 int Tms::CycleParamState::acquireData

Flag to acquire data during this state.

9.57.3.9 double Tms::CycleParamState::gateWidth

The gate pulse width as a fraction of LO (0 - 1.0).

9.57.3.10 double Tms::CycleParamState::gatePhase

The gate phase offset as a fraction of LO (0 - 1.0).

9.57.3.11 double Tms::CycleParamState::blrWidth

The gate pulse width as a fraction of LO (0 - 1.0).

9.57.3.12 double Tms::CycleParamState::blrPhase

The gate phase offset as a fraction of LO (0 - 1.0).

The documentation for this class was generated from the following files:

- [TmsCycleParam.h](#)
- [TmsCycleParam-1.cc](#)
- [TmsCycleParam.cc](#)

9.58 Tms::CycleTypeInfo Class Reference

```
#include <TmsD.h>
```

Public Member Functions

- [CycleTypeInfo \(\)](#)
- [CycleTypeInfo \(BString pcycleType, BString pinfo, BList< CycleTypeInfoPeriod > pperiods\)](#)

Public Attributes

- [BString cycleType](#)
The Cycle Type Name.
- [BString info](#)
Information string on this cycle type.
- [BList< CycleTypeInfoPeriod > periods](#)
The list of cycle periods.

9.58.1 Constructor & Destructor Documentation

9.58.1.1 Tms::CycleTypeInfo::CycleTypeInfo ()

9.58.1.2 Tms::CycleTypeInfo::CycleTypeInfo (BString *pcycleType*, BString *pinfo*, BList< CycleTypeInfoPeriod > *ppperiods*)

9.58.2 Member Data Documentation

9.58.2.1 BString Tms::CycleTypeInfo::cycleType

The Cycle Type Name.

9.58.2.2 BString Tms::CycleTypeInfo::info

Information string on this cycle type.

9.58.2.3 BList<CycleTypeInfoPeriod> Tms::CycleTypeInfo::periods

The list of cycle periods.

The documentation for this class was generated from the following files:

- [TmsD.h](#)
- [TmsD.cc](#)

9.59 Tms::CycleTypeInformationPeriod Class Reference

Cycle Type information.

```
#include <TmsD.h>
```

Public Member Functions

- [CycleTypeInformationPeriod \(\)](#)
- [CycleTypeInformationPeriod \(UInt32 pcyclePeriod, UInt32 pharmonic, UInt32 pnumBunches, UInt32 pbunchMask\)](#)

Public Attributes

- [UInt32 cyclePeriod](#)
The Cycle Period.
- [UInt32 harmonic](#)
The Machines harmonic number.
- [UInt32 numBunches](#)
The number of bunches.
- [UInt32 bunchMask](#)
Bitmask defining which buckets the bunches are captured from. Bit 0 is bucket 1, bit 1 is bucket 2 etc.

9.59.1 Detailed Description

Cycle Type information.

9.59.2 Constructor & Destructor Documentation

9.59.2.1 Tms::CycleTypeInformationPeriod::CycleTypeInformationPeriod ()

9.59.2.2 Tms::CycleTypeInformationPeriod::CycleTypeInformationPeriod (UInt32 pcyclePeriod, UInt32 pharmonic, UInt32 pnumBunches, UInt32 pbunchMask)

9.59.3 Member Data Documentation

9.59.3.1 UInt32 Tms::CycleTypeInformationPeriod::cyclePeriod

The Cycle Period.

9.59.3.2 UInt32 Tms::CycleTypeInformationPeriod::harmonic

The Machines harmonic number.

9.59.3.3 UInt32 Tms::CycleTypeInfoPeriod::numBunches

The number of bunches.

9.59.3.4 UInt32 Tms::CycleTypeInfoPeriod::bunchMask

Bitmask defining which buckets the bunches are captured from. Bit 0 is bucket 1, bit 1 is bucket 2 etc.

The documentation for this class was generated from the following files:

- [TmsD.h](#)
- [TmsD.cc](#)

9.60 Tms::Data Class Reference

This class stores the raw data.

```
#include <TmsD.h>
```

Public Member Functions

- [Data](#) ()
- [Data](#) ([UInt32](#) pnumValues, [UInt32](#) pdataType, [UInt32](#) pnumBunches, [UInt32](#) pnumChannels, [BArray](#)< [DataValue](#) > pdataValues, [BArray](#)< [BError](#) > perrors)

Public Attributes

- [UInt32](#) numValues
The total number of data samples.
- [UInt32](#) dataType
The type of data in the data block.
- [UInt32](#) numBunches
The number of bunches.
- [UInt32](#) numChannels
The number of channels.
- [BArray](#)< [DataValue](#) > dataValues
The data.
- [BArray](#)< [BError](#) > errors
Individual errors for each channel within dataValues.

9.60.1 Detailed Description

This class stores the raw data.

9.60.2 Constructor & Destructor Documentation

9.60.2.1 Tms::Data::Data ()

9.60.2.2 Tms::Data::Data ([UInt32](#) pnumValues, [UInt32](#) pdataType, [UInt32](#) pnumBunches, [UInt32](#) pnumChannels, [BArray](#)< [DataValue](#) > pdataValues, [BArray](#)< [BError](#) > perrors)

9.60.3 Member Data Documentation

9.60.3.1 [UInt32](#) Tms::Data::numValues

The total number of data samples.

9.60.3.2 UInt32 Tms::Data::dataType

The type of data in the data block.

9.60.3.3 UInt32 Tms::Data::numBunches

The number of bunches.

9.60.3.4 UInt32 Tms::Data::numChannels

The number of channels.

9.60.3.5 BArray<DataValue> Tms::Data::dataValues

The data.

9.60.3.6 BArray<BError> Tms::Data::errors

Individual errors for each channel within dataValues.

The documentation for this class was generated from the following files:

- [TmsD.h](#)
- [TmsD.cc](#)

9.61 Tms::DataInfo Class Reference

This class defines the data to be acquired and/or fetched.

```
#include <TmsD.h>
```

Public Member Functions

- [DataInfo](#) ()
- [DataInfo](#) ([UInt32](#) pcycleNumber, [UInt32](#) pchannel, [UInt32](#) pcyclePeriod, [UInt32](#) pstartTime, [UInt32](#) porbitNumber, [UInt32](#) pbunchNumber, [UInt32](#) pfunction, [UInt32](#) pargument, [UInt32](#) pnumValues, [Int32](#) pbeyondPeriod)

Public Attributes

- [UInt32](#) cycleNumber
The PS Cycle number.
- [UInt32](#) channel
The pick-up channel number.
- [UInt32](#) cyclePeriod
The cycle period the data is from.
- [UInt32](#) startTime
The start time in milli-seconds in the cycle period (starting from 0).
- [UInt32](#) orbitNumber
The starting orbit number (starting from 0).
- [UInt32](#) bunchNumber
The Bunch number (starting from 1 (0 is all bunches)).
- [UInt32](#) function
The data processing function to perform or performed. (0 normal data).
- [UInt32](#) argument
The Argument to the data processing function.
- [UInt32](#) numValues
The total number of data points to return.
- [Int32](#) beyondPeriod
If set allows reads of data beyond the end of the period.

9.61.1 Detailed Description

This class defines the data to be acquired and/or fetched.

9.61.2 Constructor & Destructor Documentation

9.61.2.1 Tms::DataInfo::DataInfo ()

9.61.2.2 Tms::DataInfo::DataInfo (UInt32 *pcycleNumber*, UInt32 *pchannel*, UInt32 *pcyclePeriod*, UInt32 *pstartTime*, UInt32 *porbitNumber*, UInt32 *pbunchNumber*, UInt32 *pfunction*, UInt32 *pargument*, UInt32 *pnumValues*, Int32 *pbeyondPeriod*)

9.61.3 Member Data Documentation

9.61.3.1 UInt32 Tms::DataInfo::cycleNumber

The PS Cycle number.

9.61.3.2 UInt32 Tms::DataInfo::channel

The pick-up channel number.

9.61.3.3 UInt32 Tms::DataInfo::cyclePeriod

The cycle period the data is from.

9.61.3.4 UInt32 Tms::DataInfo::startTime

The start time in milli-seconds in the cycle period (starting from 0).

9.61.3.5 UInt32 Tms::DataInfo::orbitNumber

The starting orbit number (starting from 0).

9.61.3.6 UInt32 Tms::DataInfo::bunchNumber

The Bunch number (starting from 1 (0 is all bunches)).

9.61.3.7 UInt32 Tms::DataInfo::function

The data processing function to perform or performed. (0 normal data).

9.61.3.8 UInt32 Tms::DataInfo::argument

The Argument to the data processing function.

9.61.3.9 UInt32 Tms::DataInfo::numValues

The total number of data points to return.

9.61.3.10 Int32 Tms::DataInfo::beyondPeriod

If set allows reads of data beyond the end of the period.

The documentation for this class was generated from the following files:

- [TmsD.h](#)
- [TmsD.cc](#)

9.62 Tms::DataValue Class Reference

This is the definition of a single data value.

```
#include <TmsD.h>
```

Public Member Functions

- [DataValue](#) ()
- [DataValue](#) ([Int16](#) psigma, [Int16](#) pdeltaX, [Int16](#) pdeltaY, [Int16](#) ptime)

Public Attributes

- [Int16](#) sigma
The Sigma value.
- [Int16](#) deltaX
The DeltaX value.
- [Int16](#) deltaY
The DeltaY value.
- [Int16](#) time
The Time in ms this sample was processed.

9.62.1 Detailed Description

This is the definition of a single data value.

9.62.2 Constructor & Destructor Documentation

9.62.2.1 Tms::DataValue::DataValue ()

9.62.2.2 Tms::DataValue::DataValue ([Int16](#) psigma, [Int16](#) pdeltaX, [Int16](#) pdeltaY, [Int16](#) ptime)

9.62.3 Member Data Documentation

9.62.3.1 [Int16](#) Tms::DataValue::sigma

The Sigma value.

9.62.3.2 [Int16](#) Tms::DataValue::deltaX

The DeltaX value.

9.62.3.3 [Int16](#) Tms::DataValue::deltaY

The DeltaY value.

9.62.3.4 Int16 Tms::DataValue::time

The Time in ms this sample was processed.

The documentation for this class was generated from the following files:

- [TmsD.h](#)
- [TmsD.cc](#)

9.63 Tms::NameValue Class Reference

```
#include <TmsD.h>
```

Public Member Functions

- [NameValue](#) ()
- [NameValue](#) ([BString](#) pname, [BString](#) pvalue)

Public Attributes

- [BString](#) name
The Name of the value.
- [BString](#) value
The actual value in string form.

9.63.1 Constructor & Destructor Documentation

9.63.1.1 Tms::NameValue::NameValue ()

9.63.1.2 Tms::NameValue::NameValue ([BString](#) pname, [BString](#) pvalue)

9.63.2 Member Data Documentation

9.63.2.1 [BString](#) Tms::NameValue::name

The Name of the value.

9.63.2.2 [BString](#) Tms::NameValue::value

The actual value in string form.

The documentation for this class was generated from the following files:

- [TmsD.h](#)
- [TmsD.cc](#)

9.64 Tms::PuChannel Class Reference

This class stores a Physical Pick-Up channel id.

```
#include <TmsD.h>
```

Public Member Functions

- [PuChannel](#) ()
- [PuChannel](#) (UInt8 pmoduleNum, UInt8 ppupeNum, UInt8 ppupeChan)

Public Attributes

- [UInt8 moduleNum](#)
The Module number.
- [UInt8 pupeNum](#)
The PUPE number.
- [UInt8 pupeChan](#)
The PUPE channel.

9.64.1 Detailed Description

This class stores a Physical Pick-Up channel id.

9.64.2 Constructor & Destructor Documentation

9.64.2.1 Tms::PuChannel::PuChannel ()

9.64.2.2 Tms::PuChannel::PuChannel (UInt8 pmoduleNum, UInt8 ppupeNum, UInt8 ppupeChan)

9.64.3 Member Data Documentation

9.64.3.1 UInt8 Tms::PuChannel::moduleNum

The Module number.

9.64.3.2 UInt8 Tms::PuChannel::pupeNum

The PUPE number.

9.64.3.3 UInt8 Tms::PuChannel::pupeChan

The PUPE channel.

The documentation for this class was generated from the following files:


- [TmsD.h](#)
- [TmsD.cc](#)

9.65 Tms::PuControl Class Reference

This class defines the parameters for a test data capture.

```
#include <TmsC.h>
```

Inheritance diagram for Tms::PuControl::



Public Member Functions

- **PuControl** (BString name="")
- **BError getVersion** (BString &version)
Gets the software version.
- **BError init** ()
Initialises the system including loading all of the PUPE engines firmware. The call will return an error object indicating success or an error condition as appropriate.
- **BError setProcessPriority** (UInt32 priority)
Sets the priority of the process servicing this service.
- **BError configure** (ConfigInfo configInfo)
Configure the system for use. This includes mapping the individual physical Pickup channels to logical pickup channels.
- **BError setControlInfo** (CycleParam params)
Sets the control information for the cycle type given and subsequent cycles. The parameters for the processing cycle are passed, this includes the Phase and State table information. The call will return an error object indicating success or an error.
- **BError setNextCycle** (UInt32 cycleNumber, BString cycleType)
Sets the cycle number and type for the next processing cycle. The call will return an error object indicating success or an error condition as appropriate. This should be called at least 10ms before the next CYCLE_START event.
- **BError test** (BList< BError > &errors)
Performs a basic test of the system returning a list of errors. The call will return an error object indicating success or an error condition as appropriate.
- **BError getStatus** (BList< NameValue > &statusList)
Returns the current status of the system. This information includes the number of Pick-Up's present and their individual status.

- [BError](#) [getStatistics](#) ([BList](#)< [NameValue](#) > &statsList)
Returns a list of the statistic values as name/value pairs. The call will return an error object indicating success or an error condition as appropriate.
- [BError](#) [getMasterPuChannel](#) ([PuChannel](#) &puChannel)
Returns the master PU Channel for timing.
- [BError](#) [setTestMode](#) ([PuChannel](#) puChannel, [UInt32](#) testOutput, [UInt32](#) timingDisableMask)
The signal source for the digital test output connector. 0: None, 1: FrefLocal. The timingDisableMask bit mask defines which of the timing inputs should be disabled. If a timing input is disabled it can be still operated by software command.
- [BError](#) [setTimingSignals](#) ([PuChannel](#) puChannel, [UInt32](#) timingSignals)
This function sets the given timing signals to the values as defined in the timingSignals bit array.
- [BError](#) [captureDiagnostics](#) ([PuChannel](#) puChannel, [TestCaptureInfo](#) captureInfo, [BArray](#)< [UInt64](#) > &data)
This function will capture test data.
- [BError](#) [setTestData](#) ([PuChannel](#) puChannel, [Int32](#) on, [BArray](#)< [UInt32](#) > data)
This function will set a PU channel to sample data from memory rather than the ADC's.
- [BError](#) [setPupeConfig](#) ([PuChannel](#) puPhysChannel, [PupeConfig](#) pupeConfig)
Sets special PUPE configuration for test purposes.
- [BError](#) [getPupeConfig](#) ([PuChannel](#) puPhysChannel, [PupeConfig](#) &pupeConfig)
Gets special PUPE configuration for test purposes.

9.65.1 Detailed Description

This class defines the parameters for a test data capture.

This class stores a Physical Pick-Up channel id This class stores the status of an individual Pick-Up This class describes the configuration of the TMS This class defines the data to be acquired and/or fetched This is the definition of a single data value This class stores the raw data This class defines the Pick-Up state table This class defines the parameters for a PS processing cycle Cycle information Cycle Type information This interface provides functions to control, test and get statistics from an individual pick-up

9.65.2 Constructor & Destructor Documentation

9.65.2.1 Tms::PuControl::PuControl (BString name = " ")

9.65.3 Member Function Documentation

9.65.3.1 BError Tms::PuControl::getVersion (BString & version)

Gets the software version.

Parameters:

version A string variable filled in with the version number string.

9.65.3.2 BError Tms::PuControl::init ()

Initialises the system including loading all of the PUPE engines firmware. The call will return an error object indicating success or an error condition as appropriate.

9.65.3.3 BError Tms::PuControl::setProcessPriority (UInt32 *priority*)

Sets the priority of the process servicing this service.

9.65.3.4 BError Tms::PuControl::configure (ConfigInfo *configInfo*)

Configure the system for use. This includes mapping the individual physical PickUp channels to logical pickup channels.

9.65.3.5 BError Tms::PuControl::setControlInfo (CycleParam *params*)

Sets the control information for the cycle type given and subsequent cycles. The parameters for the processing cycle are passed, this includes the Phase and State table information. The call will return an error object indicating success or an error.

9.65.3.6 BError Tms::PuControl::setNextCycle (UInt32 *cycleNumber*, BString *cycleType*)

Sets the cycle number and type for the next processing cycle. The call will return an error object indicating success or an error condition as appropriate. This should be called at least 10ms before the next CYCLE_START event.

9.65.3.7 BError Tms::PuControl::test (BList< BError > & *errors*)

Performs a basic test of the system returning a list of errors. The call will return an error object indicating success or an error condition as appropriate.

9.65.3.8 BError Tms::PuControl::getStatus (BList< NameValue > & *statusList*)

Returns the current status of the system. This information includes the number of Pick-Up's present and their individual status.

9.65.3.9 BError Tms::PuControl::getStatistics (BList< NameValue > & *statsList*)

Returns a list of the statistic values as name/value pairs. The call will return an error object indicating success or an error condition as appropriate.

9.65.3.10 BError Tms::PuControl::getMasterPuChannel (PuChannel & *puChannel*)

Returns the master PU Channel for timing.

9.65.3.11 BError Tms::PuControl::setTestMode (PuChannel *puChannel*, UInt32 *testOutput*, UInt32 *timingDisableMask*)

The signal source for the digital test output connector. 0: None, 1: FrefLocal. The timingDisableMask bit mask defines which of the timing inputs should be disabled. If a timing input is disabled it can be still operated by software command.

9.65.3.12 BError Tms::PuControl::setTimingSignals (PuChannel *puChannel*, UInt32 *timingSignals*)

This function sets the given timing signals to the values as defined in the timingSignals bit array.

9.65.3.13 BError Tms::PuControl::captureDiagnostics (PuChannel *puChannel*, TestCaptureInfo *captureInfo*, BArray< UInt64 > & *data*)

This function will capture test data.

9.65.3.14 BError Tms::PuControl::setTestData (PuChannel *puChannel*, Int32 *on*, BArray< UInt32 > *data*)

This function will set a PU channel to sample data from memory rather than the ADC's.

9.65.3.15 BError Tms::PuControl::setPupeConfig (PuChannel *puPhysChannel*, PupeConfig *pupeConfig*)

Sets special PUPE configuration for test purposes.

9.65.3.16 BError Tms::PuControl::getPupeConfig (PuChannel *puPhysChannel*, PupeConfig & *pupeConfig*)

Gets special PUPE configuration for test purposes.

The documentation for this class was generated from the following files:

- [TmsC.h](#)
- [TmsC.cc](#)
- [tmsFunctions.dox](#)

9.66 Tms::PupeConfig Class Reference

```
#include <TmsD.h>
```

Public Member Functions

- [PupeConfig](#) ()
- [PupeConfig](#) ([UInt32](#) pinternalTimingMask, [Int32](#) padcSysclkSync, [Int32](#) pdisableBlr)

Public Attributes

- [UInt32](#) internalTimingMask
Use internal, software/hardware generated, timing signals for the given signals.
- [Int32](#) adcSysclkSync
Sets the ADC clock to be synchronised with the SYSCLK timing clock.
- [Int32](#) disableBlr
Disable the BLR algorithm.

9.66.1 Constructor & Destructor Documentation

9.66.1.1 Tms::PupeConfig::PupeConfig ()

9.66.1.2 Tms::PupeConfig::PupeConfig ([UInt32](#) pinternalTimingMask, [Int32](#) padcSysclkSync, [Int32](#) pdisableBlr)

9.66.2 Member Data Documentation

9.66.2.1 [UInt32](#) Tms::PupeConfig::internalTimingMask

Use internal, software/hardware generated, timing signals for the given signals.

9.66.2.2 [Int32](#) Tms::PupeConfig::adcSysclkSync

Sets the ADC clock to be synchronised with the SYSCLK timing clock.

9.66.2.3 [Int32](#) Tms::PupeConfig::disableBlr

Disable the BLR algorithm.

The documentation for this class was generated from the following files:


- [TmsD.h](#)
- [TmsD.cc](#)

9.67 Tms::PuProcess Class Reference

This interface provides functions to configure and capture data from individual pick-up.

```
#include <TmsC.h>
```

Inheritance diagram for Tms::PuProcess::



Public Member Functions

- [PuProcess](#) ([BString](#) name="")
- [BError](#) [getVersion](#) ([BString](#) &version)
Gets the software version.
- [BError](#) [getCycleInformation](#) ([UInt32](#) cycleNumber, [CycleInformation](#) &cycleInformation)
Gets information on given cycle number.
- [BError](#) [getStatus](#) ([PuChannel](#) puChannel, [PuStatus](#) &puStatus)
- [BError](#) [getData](#) ([PuChannel](#) puChannel, [DataInfo](#) dataInfo, [Data](#) &data)

This function returns a set of data from the data present in the data cache or directly from the Pick-Up processing engines. The [DataInfo](#) object describes the data required. The call will return the required data along with an error object indicating success or an error condition as appropriate. The call will block until data is ready.

- [BError](#) [addEventServer](#) ([BString](#) name)
Adds an event server.
- [BError](#) [requestData](#) ([PuChannel](#) puChannel, [DataInfo](#) dataInfo)

This adds a request for some data. The [DataInfo](#) object defines the data required. This request can be made at any time. If the data is present in cache the data will be available immediately, if not the system will await the data from a subsequent processing cycle. When the data is available a "data" event will be sent to the client. Not that it is not necessary to use requestData. The client can call [getData\(\)](#) directly although this call will block until the data is actually ready.

9.67.1 Detailed Description

This interface provides functions to configure and capture data from individual pick-up.

9.67.2 Constructor & Destructor Documentation

9.67.2.1 Tms::PuProcess::PuProcess (BString *name* = " ")

9.67.3 Member Function Documentation

9.67.3.1 BError Tms::PuProcess::getVersion (BString & *version*)

Gets the software version.

9.67.3.2 BError Tms::PuProcess::getCycleInformation (UInt32 *cycleNumber*, CycleInformation & *cycleInformation*)

Gets information on given cycle number.

9.67.3.3 BError Tms::PuProcess::getStatus (PuChannel *puChannel*, PuStatus & *puStatus*)

9.67.3.4 BError Tms::PuProcess::getData (PuChannel *puChannel*, DataInfo *dataInfo*, Data & *data*)

This function returns a set of data from the data present in the data cache or directly from the Pick-Up processing engines. The [DataInfo](#) object describes the data required. The call will return the required data along with an error object indicating success or an error condition as appropriate. The call will block until data is ready.

9.67.3.5 BError Tms::PuProcess::addEventServer (BString *name*)

Adds an event server.

9.67.3.6 BError Tms::PuProcess::requestData (PuChannel *puChannel*, DataInfo *dataInfo*)

This adds a request for some data. The [DataInfo](#) object defines the data required. This request can be made at any time. If the data is present in cache the data will be available immediately, if not the system will await the data from a subsequent processing cycle. When the data is available a "data" event will be sent to the client. Not that it is not necessary to use requestData. The client can call [getData\(\)](#) directly although this call will block until the data is actually ready.

The documentation for this class was generated from the following files:

- [TmsC.h](#)
- [TmsC.cc](#)

9.68 Tms::PuStateTable Class Reference

This class defines the Pick-Up state table.

```
#include <TmsD.h>
```

Public Member Functions

- [PuStateTable \(\)](#)
- [PuStateTable \(UInt32 pperiod, UInt32 pstate, UInt32 pharmonic, UInt32 pnumBunches, UInt32 pbunchMask, BArray< UInt8 > pphaseTable\)](#)

Public Attributes

- [UInt32 period](#)
The Cycle period this state is used for.
- [UInt32 state](#)
The State table entry.
- [UInt32 harmonic](#)
The harmonic number for this state.
- [UInt32 numBunches](#)
The number of bunches to capture.
- [UInt32 bunchMask](#)
Bitmask defining which buckets the bunches are captured from. Bit 0 is bucket 1, bit 1 is bucket 2 etc.
- [BArray< UInt8 > phaseTable](#)
The Phase table for this state.

9.68.1 Detailed Description

This class defines the Pick-Up state table.

9.68.2 Constructor & Destructor Documentation

9.68.2.1 Tms::PuStateTable::PuStateTable ()

9.68.2.2 Tms::PuStateTable::PuStateTable (UInt32 pperiod, UInt32 pstate, UInt32 pharmonic, UInt32 pnumBunches, UInt32 pbunchMask, BArray< UInt8 > pphaseTable)

9.68.3 Member Data Documentation

9.68.3.1 UInt32 Tms::PuStateTable::period

The Cycle period this state is used for.

9.68.3.2 UInt32 Tms::PuStateTable::state

The State table entry.

9.68.3.3 UInt32 Tms::PuStateTable::harmonic

The harmonic number for this state.

9.68.3.4 UInt32 Tms::PuStateTable::numBunches

The number of bunches to capture.

9.68.3.5 UInt32 Tms::PuStateTable::bunchMask

Bitmask defining which buckets the bunches are captured from. Bit 0 is bucket 1, bit 1 is bucket 2 etc.

9.68.3.6 BArray<UInt8> Tms::PuStateTable::phaseTable

The Phase table for this state.

The documentation for this class was generated from the following files:

- [TmsD.h](#)
- [TmsD.cc](#)

9.69 Tms::PuStatus Class Reference

This class stores the status of an individual Pick-Up.

```
#include <TmsD.h>
```

Public Member Functions

- [PuStatus \(\)](#)
- [PuStatus \(Int32 pruning, BError perror\)](#)

Public Attributes

- [Int32 running](#)
The Pick-Up is currently running.
- [BError error](#)
The Pick-Up's current error status.

9.69.1 Detailed Description

This class stores the status of an individual Pick-Up.

9.69.2 Constructor & Destructor Documentation

9.69.2.1 Tms::PuStatus::PuStatus ()

9.69.2.2 Tms::PuStatus::PuStatus (Int32 *pruning*, BError *pererror*)

9.69.3 Member Data Documentation

9.69.3.1 Int32 Tms::PuStatus::running

The Pick-Up is currently running.

9.69.3.2 BError Tms::PuStatus::error

The Pick-Up's current error status.


The documentation for this class was generated from the following files:

- [TmsD.h](#)
- [TmsD.cc](#)

9.70 SigGen Class Reference

```
#include <SigGen.h>
```

Inheritance diagram for SigGen::



Public Member Functions

- [SigGen \(\)](#)
- virtual [~SigGen \(\)](#)
- [BError config](#) (double *sampleRate*)
- virtual [BError generate](#) ([Sample](#) **data*, int *numSamples*)

Protected Attributes

- double [osampleRate](#)
- unsigned long long [ox](#)

9.70.1 Constructor & Destructor Documentation

9.70.1.1 [SigGen::SigGen \(\)](#)

9.70.1.2 [SigGen::~~SigGen \(\)](#) [virtual]

9.70.2 Member Function Documentation

9.70.2.1 [BError SigGen::config](#) (double *sampleRate*)

9.70.2.2 [BError SigGen::generate](#) ([Sample](#) * *data*, int *numSamples*) [virtual]

Reimplemented in [SigGenSine](#), [SigGenSquare](#), [SigGenNoise](#), [SigGenPulse](#), and [SigGenBeam](#).

9.70.3 Member Data Documentation

9.70.3.1 [double SigGen::osampleRate](#) [protected]

9.70.3.2 [unsigned long long SigGen::ox](#) [protected]


The documentation for this class was generated from the following files:

- [SigGen.h](#)
- [SigGen.cpp](#)

9.71 SigGenBeam Class Reference

```
#include <SigGen.h>
```

Inheritance diagram for SigGenBeam::



Public Member Functions

- [SigGenBeam \(\)](#)
- virtual [~SigGenBeam \(\)](#)
- [BError config](#) (double *sampleRate*, double *fref*, int *harmonic*, int *bunchSet*, double *reduce*, int *blr*, double *amplitude*)
- [BError generate](#) ([Sample](#) **data*, int *numSamples*)
- [BError generateIntegrated](#) ([Sample](#) **data*, int *numSamples*)

Public Attributes

- int [oharmonic](#)
- int [obunchSet](#)
- double [oreduce](#)
- int [oblr](#)
- double [oamplitude](#)
- double [ofref](#)

9.71.1 Constructor & Destructor Documentation

9.71.1.1 [SigGenBeam::SigGenBeam \(\)](#)

9.71.1.2 [SigGenBeam::~~SigGenBeam \(\)](#) [virtual]

9.71.2 Member Function Documentation

9.71.2.1 [BError SigGenBeam::config](#) (double *sampleRate*, double *fref*, int *harmonic*, int *bunchSet*, double *reduce*, int *blr*, double *amplitude*)

9.71.2.2 [BError SigGenBeam::generate](#) ([Sample](#) * *data*, int *numSamples*) [virtual]

Reimplemented from [SigGen](#).

9.71.2.3 **BError SigGenBeam::generateIntegrated** (*Sample * data*, *int numSamples*)

9.71.3 Member Data Documentation

9.71.3.1 **int SigGenBeam::oharmonic**

9.71.3.2 **int SigGenBeam::obunchSet**

9.71.3.3 **double SigGenBeam::oreduce**

9.71.3.4 **int SigGenBeam::oblr**

9.71.3.5 **double SigGenBeam::oamplitude**

9.71.3.6 **double SigGenBeam::ofref**


The documentation for this class was generated from the following files:

- [SigGen.h](#)
- [SigGen.cpp](#)

9.72 SigGenNoise Class Reference

```
#include <SigGen.h>
```

Inheritance diagram for SigGenNoise::



Public Member Functions

- [SigGenNoise \(\)](#)
- virtual [~SigGenNoise \(\)](#)
- [BError config](#) (double *sampleRate*, double *amplitude*=1.0)
- [BError generate](#) ([Sample](#) **data*, int *numSamples*)

Public Attributes

- double [oamplitude](#)

9.72.1 Constructor & Destructor Documentation

9.72.1.1 [SigGenNoise::SigGenNoise \(\)](#)

9.72.1.2 [SigGenNoise::~~SigGenNoise \(\)](#) [virtual]

9.72.2 Member Function Documentation

9.72.2.1 [BError SigGenNoise::config](#) (double *sampleRate*, double *amplitude* = 1.0)

9.72.2.2 [BError SigGenNoise::generate](#) ([Sample](#) * *data*, int *numSamples*) [virtual]

Reimplemented from [SigGen](#).

9.72.3 Member Data Documentation

9.72.3.1 [double SigGenNoise::oamplitude](#)


The documentation for this class was generated from the following files:

- [SigGen.h](#)
- [SigGen.cpp](#)

9.73 SigGenPulse Class Reference

```
#include <SigGen.h>
```

Inheritance diagram for SigGenPulse::



Public Member Functions

- [SigGenPulse \(\)](#)
- virtual [~SigGenPulse \(\)](#)
- [BError config](#) (double *sampleRate*, double *freq*, double *amplitude*, double *onTime*, double *start-Time*=0.0)
- [BError generate](#) ([Sample](#) **data*, int *numSamples*)

Public Attributes

- double [ofreq](#)
- double [oamplitude](#)
- double [oonTime](#)
- double [ostartTime](#)

9.73.1 Constructor & Destructor Documentation

9.73.1.1 [SigGenPulse::SigGenPulse \(\)](#)

9.73.1.2 [SigGenPulse::~~SigGenPulse \(\)](#) [virtual]

9.73.2 Member Function Documentation

9.73.2.1 [BError SigGenPulse::config](#) (double *sampleRate*, double *freq*, double *amplitude*, double *onTime*, double *startTime* = 0.0)

9.73.2.2 [BError SigGenPulse::generate](#) ([Sample](#) **data*, int *numSamples*) [virtual]

Reimplemented from [SigGen](#).

9.73.3 Member Data Documentation

9.73.3.1 double SigGenPulse::ofreq

9.73.3.2 double SigGenPulse::oamplitude

9.73.3.3 double SigGenPulse::oonTime

9.73.3.4 double SigGenPulse::ostartTime


The documentation for this class was generated from the following files:

- [SigGen.h](#)
- [SigGen.cpp](#)

9.74 SigGenSine Class Reference

```
#include <SigGen.h>
```

Inheritance diagram for SigGenSine::



Public Member Functions

- [SigGenSine \(\)](#)
- virtual [~SigGenSine \(\)](#)
- [BError config](#) (double *sampleRate*, double *freq*, double *amplitude*=1.0)
- [BError generate](#) ([Sample](#) **data*, int *numSamples*)

Public Attributes

- double [ofreq](#)
- double [oamplitude](#)

9.74.1 Constructor & Destructor Documentation

9.74.1.1 [SigGenSine::SigGenSine \(\)](#)

9.74.1.2 [SigGenSine::~~SigGenSine \(\)](#) [virtual]

9.74.2 Member Function Documentation

9.74.2.1 [BError SigGenSine::config](#) (double *sampleRate*, double *freq*, double *amplitude* = 1.0)

9.74.2.2 [BError SigGenSine::generate](#) ([Sample](#) * *data*, int *numSamples*) [virtual]

Reimplemented from [SigGen](#).

9.74.3 Member Data Documentation

9.74.3.1 [double SigGenSine::ofreq](#)

9.74.3.2 [double SigGenSine::oamplitude](#)


The documentation for this class was generated from the following files:

- [SigGen.h](#)
- [SigGen.cpp](#)

9.75 SigGenSquare Class Reference

```
#include <SigGen.h>
```

Inheritance diagram for SigGenSquare::



Public Member Functions

- [SigGenSquare \(\)](#)
- virtual [~SigGenSquare \(\)](#)
- [BError config](#) (double *sampleRate*, double *freq*, double *amplitude*=1.0, double *offset*=0.0)
- [BError generate](#) ([Sample](#) **data*, int *numSamples*)

Public Attributes

- double [ofreq](#)
- double [oamplitude](#)
- double [ooffset](#)

9.75.1 Constructor & Destructor Documentation

9.75.1.1 [SigGenSquare::SigGenSquare \(\)](#)

9.75.1.2 [SigGenSquare::~~SigGenSquare \(\)](#) [virtual]

9.75.2 Member Function Documentation

9.75.2.1 [BError SigGenSquare::config](#) (double *sampleRate*, double *freq*, double *amplitude* = 1.0, double *offset* = 0.0)

9.75.2.2 [BError SigGenSquare::generate](#) ([Sample](#) * *data*, int *numSamples*) [virtual]

Reimplemented from [SigGen](#).

9.75.3 Member Data Documentation

9.75.3.1 double [SigGenSquare::ofreq](#)

9.75.3.2 double [SigGenSquare::oamplitude](#)

9.75.3.3 double [SigGenSquare::ooffset](#)

The documentation for this class was generated from the following files:

- [SigGen.h](#)
- [SigGen.cpp](#)

9.76 Tms::Simulation Class Reference

```
#include <TmsD.h>
```

Public Member Functions

- [Simulation](#) ()
- [Simulation](#) ([Int32](#) ptiming, [Int32](#) pdata, [Int32](#) psetNextCycle, [BString](#) pcycleType)

Public Attributes

- [Int32](#) timing
Simulate timing signals.
- [Int32](#) data
Simulate FREF and Analogue Sigma, DeltaX and DeltaY data.
- [Int32](#) setNextCycle
Simulate setNextCycle.
- [BString](#) cycleType
The cycle type to set.

9.76.1 Constructor & Destructor Documentation

9.76.1.1 Tms::Simulation::Simulation ()

9.76.1.2 Tms::Simulation::Simulation ([Int32](#) ptiming, [Int32](#) pdata, [Int32](#) psetNextCycle, [BString](#) pcycleType)

9.76.2 Member Data Documentation

9.76.2.1 [Int32](#) Tms::Simulation::timing

Simulate timing signals.

9.76.2.2 [Int32](#) Tms::Simulation::data

Simulate FREF and Analogue Sigma, DeltaX and DeltaY data.

9.76.2.3 [Int32](#) Tms::Simulation::setNextCycle

Simulate setNextCycle.

9.76.2.4 BString Tms::Simulation::cycleType

The cycle type to set.

The documentation for this class was generated from the following files:

- [TmsD.h](#)
- [TmsD.cc](#)

9.77 vector Class Reference

Inherited by [BArray< BError >](#), [BArray< BString >](#), [BArray< int32_t >](#), [BArray< Tms::DataValue >](#), [BArray< Tms::PuChannel >](#), [BArray< Tms::PuStateTable >](#), and [BArray< uint8_t >](#).

The documentation for this class was generated from the following file:

- [/src/cern/tms/beam/libBeam/BArray.h](#)

9.78 Tms::TestCaptureInfo Class Reference

This class defines the parameters for a test data capture.

```
#include <TmsD.h>
```

Public Member Functions

- [TestCaptureInfo \(\)](#)
- [TestCaptureInfo \(UInt32 psource, UInt32 pclock, UInt32 pstartTime, UInt32 ppostTriggerDelay, UInt32 ptriggerMask, Int32 ptriggerAnd, Int32 ptriggerStore, Int32 ptriggerSourceData\)](#)

Public Attributes

- [UInt32 source](#)
The source data (0 - 3).
- [UInt32 clock](#)
The Clock source.
- [UInt32 startTime](#)
The start time in ms from CYCLE_START before trigger is activated.
- [UInt32 postTriggerDelay](#)
The delay, in clock cycles, after the trigger before capture starts.
- [UInt32 triggerMask](#)
The Trigger bit mask. This is the bit mask of the 8 timing signals.
- [Int32 triggerAnd](#)
The Trigger function is an AND rather than an OR.
- [Int32 triggerStore](#)
Store the trigger in the upper 8 data bits.
- [Int32 triggerSourceData](#)
Use lower 32bits of data as trigger source rather than timing signals.

9.78.1 Detailed Description

This class defines the parameters for a test data capture.

9.78.2 Constructor & Destructor Documentation

9.78.2.1 Tms::TestCaptureInfo::TestCaptureInfo ()

9.78.2.2 Tms::TestCaptureInfo::TestCaptureInfo (UInt32 *psource*, UInt32 *pclock*, UInt32 *pstartTime*, UInt32 *ppostTriggerDelay*, UInt32 *ptriggerMask*, Int32 *ptriggerAnd*, Int32 *ptriggerStore*, Int32 *ptriggerSourceData*)

9.78.3 Member Data Documentation

9.78.3.1 UInt32 Tms::TestCaptureInfo::source

The source data (0 - 3).

9.78.3.2 UInt32 Tms::TestCaptureInfo::clock

The Clock source.

9.78.3.3 UInt32 Tms::TestCaptureInfo::startTime

The start time in ms from CYCLE_START before trigger is activated.

9.78.3.4 UInt32 Tms::TestCaptureInfo::postTriggerDelay

The delay, in clock cycles, after the trigger before capture starts.

9.78.3.5 UInt32 Tms::TestCaptureInfo::triggerMask

The Trigger bit mask. This is the bit mask of the 8 timing signals.

9.78.3.6 Int32 Tms::TestCaptureInfo::triggerAnd

The Trigger function is an AND rather than an OR.

9.78.3.7 Int32 Tms::TestCaptureInfo::triggerStore

Store the trigger in the upper 8 data bits.

9.78.3.8 Int32 Tms::TestCaptureInfo::triggerSourceData

Use lower 32bits of data as trigger source rather than timing signals.

The documentation for this class was generated from the following files:


- [TmsD.h](#)
- [TmsD.cc](#)

9.79 Tms::TmsControl Class Reference

This interface provides functions to control, test and get statistics from the TMS as a whole.

```
#include <TmsC.h>
```

Inheritance diagram for Tms::TmsControl::



Public Member Functions

- [TmsControl](#) (BString name="")
- [BError getVersion](#) (BString &version)
Gets the software version.
- [BError setProcessPriority](#) (UInt32 priority)
Sets the priority of the process servicing this service.
- [BError init](#) ()
Initialises the system including resetting all of the PUPE engines firmware. The call will return an error object indicating success or an error condition as appropriate.
- [BError configure](#) (ConfigInfo configInfo)
Configure the system for use. This includes mapping the individual physical Pickup channels to logical pickup channels.
- [BError getConfiguration](#) (ConfigInfo &configInfo)
Get the current configuration.
- [BError setControlInfo](#) (CycleParam params)
Sets the control information for the cycle type given. The parameters for the processing cycle are passed, this includes the Phase and State table information. The call will return an error object indicating success or an error.
- [BError getControlInfo](#) (BString cycleType, UInt32 puChannel, CycleParam ¶ms)
Gets the control information for the cycle type and puChannel number given. The call will return an error object indicating success or an error.
- [BError delControlInfo](#) (BString cycleType, UInt32 puChannel)
Deletes the control information for the cycle type and puChannel number given. The call will return an error object indicating success or an error.
- [BError getControlList](#) (BList< CycleParamItem > &itemList)
Gets the list of Cycle Parameters present in the system.

- **BError setNextCycle** (UInt32 cycleNumber, BString cycleType)
Sets the cycle number and type for the next processing cycle. The call will return an error object indicating success or an error condition as appropriate. This should be called at least 10ms before the next CYCLE_START event.
- **BError test** (BList< BError > &errors)
Performs a basic test of the system returning a list of errors. The call will return an error object indicating success or an error condition as appropriate.
- **BError getStatus** (BList< NameValue > &statusList)
Returns the current status of the system. This information includes the number of Pick-Up's present and their individual status.
- **BError getStatistics** (BList< NameValue > &statsList)
Returns a list of the statistic values as name/value pairs. The call will return an error object indicating success or an error condition as appropriate.
- **BError getPuChannel** (UInt32 puChannel, PuChannel &puPhysChannel)
Returns the physical module/Pupe/Channel number given a logical PickUp id. This can be used so that the individual PickUps test functions can be accessed etc.
- **BError setSimulation** (Simulation simulation)
Sets overall simulation modes.
- **BError getSimulation** (Simulation &simulation)
Gets current simulation modes.
- **BError setTestMode** (PuChannel puPhysChannel, UInt32 testOutput, UInt32 timingDisableMask)
The signal source for the digital test output connector. 0: None, 1: FrefLocal. The timingDisableMask bit mask defines which of the timing inputs should be disabled. If a timing input is disabled it can be still operated by software command.
- **BError setTimingSignals** (PuChannel puPhysChannel, UInt32 timingSignals)
This function sets the given timing signals to the values as defined in the timingSignals bit array.
- **BError captureDiagnostics** (PuChannel puPhysChannel, TestCaptureInfo captureInfo, BArray< UInt64 > &data)
This function will capture the diagnostics.
- **BError setTestData** (PuChannel puPhysChannel, Int32 on, BArray< UInt32 > data)
This function will set a PU channel to sample data from memory rather than the ADC's.
- **BError setPupeConfig** (PuChannel puPhysChannel, PupeConfig pupeConfig)
Sets special PUPE configuration for test purposes.
- **BError getPupeConfig** (PuChannel puPhysChannel, PupeConfig &pupeConfig)
Gets special PUPE configuration for test purposes.
- **BError puServerStarted** (UInt32 number)
A TmsPuServer has started.

9.79.1 Detailed Description

This interface provides functions to control, test and get statistics from the TMS as a whole.

9.79.2 Constructor & Destructor Documentation

9.79.2.1 Tms::TmsControl::TmsControl (BString *name* = " ")

9.79.3 Member Function Documentation

9.79.3.1 BError Tms::TmsControl::getVersion (BString & *version*)

Gets the software version.

Parameters:

version A string variable filled in with the version number string.

9.79.3.2 BError Tms::TmsControl::setProcessPriority (UInt32 *priority*)

Sets the priority of the process servicing this service.

Parameters:

priority This is the priority of the process. It can be set to one of: PriorityLow, PriorityNormal, PriorityHigh.

9.79.3.3 BError Tms::TmsControl::init ()

Initialises the system including resetting all of the PUPE engines firmware. The call will return an error object indicating success or an error condition as appropriate.

This function restarts the TMS system. It re-initialises each of the TmsPuServer processes running on the Module Controllers and reboots each of the PUPE boards from scratch loading the current FPGA firmware. All errors and statistics values are reset.

9.79.3.4 BError Tms::TmsControl::configure (ConfigInfo *configInfo*)

Configure the system for use. This includes mapping the individual physical PickUp channels to logical pickup channels.

Parameters:

configInfo The channel mapping table.

This function configures the logical to physical channel mapping table.

9.79.3.5 BError Tms::TmsControl::getConfiguration (ConfigInfo & *configInfo*)

Get the current configuration.

Parameters:

configInfo The channel mapping table that is filled in with the current current channel mapping.

This function reads the current logical to physical channel mapping table.

9.79.3.6 BError Tms::TmsControl::setControlInfo (CycleParam *params*)

Sets the control information for the cycle type given. The parameters for the processing cycle are passed, this includes the Phase and State table information. The call will return an error object indicating success or an error.

Parameters:

params Cycle information parameters (state/phase table information).

This function over-writes or adds an entry in the Cycle Parameter database. The Cycle Parameters define the setting for each processing cycle including the state and phase tables for the PUPE FPGA engines.

9.79.3.7 BError Tms::TmsControl::getControlInfo (BString *cycleType*, UInt32 *puChannel*, CycleParam & *params*)

Gets the control information for the cycle type and puChannel number given. The call will return an error object indicating success or an error.

Parameters:

cycleType This string defines the cycle type for which to get the information.

puChannel This defines the channel to get the information for. 0 means all channels.

params The resuting cycle parameters are placed in this object.

This function reads back the set of Cycle parameters for the given cycle type and channel number. Normall the same cycle parameters are used for all PUPE engines. In this case setting the puChannel to 0 reads the Cycle Parameters that are being used on all channels. If a specific channel has other parameters the puChannel variable can be set to the appropriate channel number to get its particular settings.

9.79.3.8 BError Tms::TmsControl::delControlInfo (BString *cycleType*, UInt32 *puChannel*)

Deletes the control information for the cycle type and puChannel number given. The call will return an error object indicating success or an error.

Parameters:

cycleType This string defines the cycle type to delete from the database.

puChannel This defines the specific channel to delete the information for. 0 means all channels.

This function will delete a set of Cycle parameters from the TMS's Cycle parameter database.

9.79.3.9 BError Tms::TmsControl::getControlList (BList< CycleParamItem > & *itemList*)

Gets the list of Cycle Parameters present in the system.

Parameters:

itemList The list of CycleType information is returned.

This function will return a list of entries describing the Cycle Paramter sets present in the TMS database.

9.79.3.10 BError Tms::TmsControl::setNextCycle (UInt32 *cycleNumber*, BString *cycleType*)

Sets the cycle number and type for the next processing cycle. The call will return an error object indicating success or an error condition as appropriate. This should be called at least 10ms before the next CYCLE_START event.

Parameters:

cycleNumber This is the next cycle number. This should be an incrementing 32bit unsigned value.

cycleType This is a string defining the cycle type for the next cycle.

This call configures the TMS system for the next processing cycle. It defines the cycle number that will be used to tag data captured during the cycle and it defines the type of machine cycle. The cycleType is used to lookup the appropriate state/phase table information to use in the FPGA's. The call should be made at least 10ms before the CYCLE_START event for the cycle it refers to. This gives time for the FPGA's to be loaded with the appropriate state/phase table information. As the function is time critical, the communications channel should be set to a high priority using the [setPriority\(\)](#) call and the processing threads priority should be set to high using the [setProcessPriority\(\)](#) call. The call will return the error: "ErrorCycleNumber", "The next cycle has already started" if the call has not completed before the CYCLE_START event. All client data reads, for this cycle, will also return this error message.

9.79.3.11 BError Tms::TmsControl::test (BList< BError > & *errors*)

Performs a basic test of the system returning a list of errors. The call will return an error object indicating success or an error condition as appropriate.

Parameters:

errors The list of errors is placed in this list object.

This function will perform a test of the TMS system. It will report each test performed and the status of the test in the [BError](#) object. A status value of 0 indicates all was Ok, any other value is an error where the number indicates the error. A string gives the test name and the Ok or error condition as a string.

9.79.3.12 BError Tms::TmsControl::getStatus (BList< NameValue > & *statusList*)

Returns the current status of the system. This information includes the number of Pick-Up's present and their individual status.

Parameters:

statusList The list of status items is placed in this list object.

This function gets the status of the TMS system. It returns a list of name/value pairs.

9.79.3.13 BError Tms::TmsControl::getStatistics (BList< NameValue > & statsList)

Returns a list of the statistic values as name/value pairs. The call will return an error object indicating success or an error condition as appropriate.

Parameters:

statsList The statistics list is placed in this list object.

This function gets the statistics values from the TMS system. It returns a list of name/value pairs.

9.79.3.14 BError Tms::TmsControl::getPuChannel (UInt32 puChannel, PuChannel & puPhysChannel)

Returns the physical module/Pupe/Channel number given a logical PickUp id. This can be used so that the individual PickUps test functions can be accessed etc.

Parameters:

puChannel The logical channel number.

puPhysChannel The physical channel identifier is returned in this variable.

This function is given a logical pick-up channel number. It will return the physical module, pupe number and pupe channle that has been allocated to this channel.

9.79.3.15 BError Tms::TmsControl::setSimulation (Simulation simulation)

Sets overall simulation modes.

9.79.3.16 BError Tms::TmsControl::getSimulation (Simulation & simulation)

Gets current simulation modes.

9.79.3.17 BError Tms::TmsControl::setTestMode (PuChannel puPhysChannel, UInt32 testOutput, UInt32 timingDisableMask)

The signal source for the digital test output connector. 0: None, 1: FrefLocal. The timingDisableMask bit mask defines which of the timing inputs should be disabled. If a timing input is disabled it can be still operated by software command.

Parameters:

puPhysChannel The physical channel identifier.

testOutput The signal to output on the test output. 0 is FREF any other value is undefined at the moment.

timingDisableMask This 8 bit mask defines which of the timing input signals are disabled.

This function sets up a particular pick-up channel's digital test output source and allows the channels input timing signals to be set to a software driven mode rather than taken from the hardware timing inputs. The timing mask bits are: 7 - FREF, 6 - HCHANGE, 5 - INJECTION, 4 - CAL_STOP, 3 - CAL_START, 2 - CYCLE_STOP, 1 - CYCLE_START, 0 - SYSCLOCK

9.79.3.18 BError Tms::TmsControl::setTimingSignals (PuChannel *puPhysChannel*, UInt32 *timingSignals*)

This function sets the given timing signals to the values as defined in the timingSignals bit array.

Parameters:

puPhysChannel The physical channel identifier.

timingSignals The 8 bit mask defining the state of the software driven timing signals.

If the [setTestMode\(\)](#) function had been used to "enable" particular timing signals to be driven by software, then this function can be used to set/reset particular timing signals for the pick-up channel given. The timing signals bits are: 7 - FREF, 6 - HCHANGE, 5 - INJECTION, 4 - CAL_STOP, 3 - CAL_START, 2 - CYCLE_STOP, 1 - CYCLE_START, 0 - SYSCLOCK

9.79.3.19 BError Tms::TmsControl::captureDiagnostics (PuChannel *puPhysChannel*, TestCaptureInfo *captureInfo*, BArray< UInt64 > & *data*)

This function will capture the diagnostics.

9.79.3.20 BError Tms::TmsControl::setTestData (PuChannel *puPhysChannel*, Int32 *on*, BArray< UInt32 > *data*)

This function will set a PU channel to sample data from memory rather than the ADC's.

Parameters:

puPhysChannel The physical channel identifier.

on Boolean to enable the internal data source. 0 is off, 1 is on.

data The array of 32bit data values to use as the FREF, Sigma, DeltaX and DeltaY test signal.

This call loads the PUPE systems test data SDRAM with the data passed in the data array. It then sets up the individual channel to sources its FREF, Sigma, DeltaX and DelatY signals from the test SDRAM. The data source should have a multiple of 2 samples. The "on" parameter is used to enable or disable the individual channels inputs from this test data SDRAM.

9.79.3.21 BError Tms::TmsControl::setPupeConfig (PuChannel *puPhysChannel*, PupeConfig *pupeConfig*)

Sets special PUPE configuration for test purposes.

Parameters:

puPhysChannel The physical channel identifier.

pupeConfig The configuration parameters to use.

This functions sets up some special configuration parameters for the PUPE channel. It is used mainly for diagnostics and test purposes. The main settings it can affect are: The ADC Clock sources PLL synchronisation, internal timing for the digital timing signals and the enabling/dissabling of the BLR algorithm.

9.79.3.22 BError Tms::TmsControl::getPupeConfig (PuChannel *puPhysChannel*, PupeConfig & *pupeConfig*)

Gets special PUPE configuration for test purposes.

Parameters:

puPhysChannel The physical channel identifier.

pupeConfig The returned configuration parameters.

This function returns the current configuration of the given channel.

9.79.3.23 BError Tms::TmsControl::puServerStarted (UInt32 *number*)

A TmsPuServer has started.

Parameters:

number The number of the PuServer started.

This is an internal function called by the TmsPuServer processes to indicate to the TmsServer that they have just started running and are present in the system. The TmsServer will initialise the appropriate tmsPuServer program and its individual PUPE engines on receipt of this call.

The documentation for this class was generated from the following files:


- [TmsC.h](#)
- [TmsC.cc](#)
- [tmsFunctions.dox](#)

9.80 Tms::TmsEvent Class Reference

This interface provides functions for events to be sent to clients from the TMS as a whole.

```
#include <TmsC.h>
```

Inheritance diagram for Tms::TmsEvent::



Public Member Functions

- [TmsEvent](#) ([BString](#) name="")
- [BError errorEvent](#) ([UInt32](#) cycleNumber, [BError](#) error)

This event function gets called on a system error. The errorEvent object contains and error number and string describing the error. The getStatus() call can be used to fetch further information.

- [BError cycleStartEvent](#) ([UInt32](#) cycleNumber)

This event function gets called on the CYCLE_START event with the cycle number about to be processed.

- [BError cycleStopEvent](#) ([UInt32](#) cycleNumber)

This event function gets called on the CYCLE_END event with the cycle number completed.

- [BError dataEvent](#) ([DataInfo](#) dataInfo)

This event function gets called when some requested data becomes available. The [DataInfo](#) object contains information on the data. The getData() call can be used to fetch the actual data.

9.80.1 Detailed Description

This interface provides functions for events to be sent to clients from the TMS as a whole.

9.80.2 Constructor & Destructor Documentation

9.80.2.1 Tms::TmsEvent::TmsEvent (BString name = " ")

9.80.3 Member Function Documentation

9.80.3.1 BError Tms::TmsEvent::errorEvent (UInt32 cycleNumber, BError error)

This event function gets called on a system error. The errorEvent object contains and error number and string describing the error. The getStatus() call can be used to fetch further information.

9.80.3.2 BError Tms::TmsEvent::cycleStartEvent (UInt32 *cycleNumber*)

This event function gets called on the CYCLE_START event with the cycle number about to be processed.

9.80.3.3 BError Tms::TmsEvent::cycleStopEvent (UInt32 *cycleNumber*)

This event function gets called on the CYCLE_END event with the cycle number completed.

9.80.3.4 BError Tms::TmsEvent::dataEvent (DataInfo *dataInfo*)

This event function gets called when some requested data becomes available. The [DataInfo](#) object contains information on the data. The `getData()` call can be used to fetch the actual data.

The documentation for this class was generated from the following files:

- [TmsC.h](#)
- [TmsC.cc](#)

9.81 Tms::TmsEventServerList Class Reference

```
#include <TmsEventServerList.h>
```

Public Member Functions

- [TmsEventServerList \(\)](#)
- [~TmsEventServerList \(\)](#)
- [BError append \(BString name\)](#)
- [BError del \(BString name\)](#)
- [BError errorEvent \(UInt32 cycleNumber, BError error\)](#)

This event function gets called on a system error. The errorEvent object contains an error number and string describing the error. The getStatus() call can be used to fetch further information.

- [BError cycleStartEvent \(UInt32 cycleNumber\)](#)

This event function gets called on the CYCLE_START event with the cycle number about to be processed.

- [BError cycleStopEvent \(UInt32 cycleNumber\)](#)

This event function gets called on the CYCLE_END event with the cycle number completed.

- [BError dataEvent \(DataInfo dataInfo\)](#)

This event function gets called when some requested data becomes available. The DataInfo object contains information on the data. The getData() call can be used to fetch the actual data.

Private Attributes

- [BMutex olock](#)
- [BList< TmsEvent * > oeventServers](#)

9.81.1 Constructor & Destructor Documentation

9.81.1.1 [Tms::TmsEventServerList::TmsEventServerList \(\)](#)

9.81.1.2 [Tms::TmsEventServerList::~~TmsEventServerList \(\)](#)

9.81.2 Member Function Documentation

9.81.2.1 [BError Tms::TmsEventServerList::append \(BString name\)](#)

9.81.2.2 [BError Tms::TmsEventServerList::del \(BString name\)](#)

9.81.2.3 [BError Tms::TmsEventServerList::errorEvent \(UInt32 cycleNumber, BError error\)](#)

This event function gets called on a system error. The errorEvent object contains an error number and string describing the error. The getStatus() call can be used to fetch further information.

9.81.2.4 [BError Tms::TmsEventServerList::cycleStartEvent \(UInt32 cycleNumber\)](#)

This event function gets called on the CYCLE_START event with the cycle number about to be processed.

9.81.2.5 BError Tms::TmsEventServerList::cycleStopEvent (UInt32 *cycleNumber*)

This event function gets called on the CYCLE_END event with the cycle number completed.

9.81.2.6 BError Tms::TmsEventServerList::dataEvent (DataInfo *dataInfo*)

This event function gets called when some requested data becomes available. The [DataInfo](#) object contains information on the data. The `getData()` call can be used to fetch the actual data.

9.81.3 Member Data Documentation

9.81.3.1 BMutex Tms::TmsEventServerList::olock [private]

9.81.3.2 BList<TmsEvent*> Tms::TmsEventServerList::oeventServers [private]

The documentation for this class was generated from the following files:

- [TmsEventServerList.h](#)
- [TmsEventServerList.cc](#)

9.82 Tms::TmsPhase Union Reference

The [Tms](#) Phase Table Entry.

```
#include <TmsLib.h>
```

Public Attributes

- struct {
 - unsigned int [lo1](#):1
 - unsigned int [blr](#):1
 - unsigned int [gate](#):1
 - unsigned int [lo2](#):1
 - unsigned int [spare](#):2
 - unsigned int [meanFilter1](#):1
 - unsigned int [meanFilter2](#):1
- unsigned char [value](#)

9.82.1 Detailed Description

The [Tms](#) Phase Table Entry.

9.82.2 Member Data Documentation

- 9.82.2.1 unsigned int [Tms::TmsPhase::lo1](#)
- 9.82.2.2 unsigned int [Tms::TmsPhase::blr](#)
- 9.82.2.3 unsigned int [Tms::TmsPhase::gate](#)
- 9.82.2.4 unsigned int [Tms::TmsPhase::lo2](#)
- 9.82.2.5 unsigned int [Tms::TmsPhase::spare](#)
- 9.82.2.6 unsigned int [Tms::TmsPhase::meanFilter1](#)
- 9.82.2.7 unsigned int [Tms::TmsPhase::meanFilter2](#)
- 9.82.2.8 struct { ... }
- 9.82.2.9 unsigned char [Tms::TmsPhase::value](#)

The documentation for this union was generated from the following file:


- [TmsLib.h](#)

9.83 Tms::TmsProcess Class Reference

This interface provides functions to capture data from the TMS as a whole.

```
#include <TmsC.h>
```

Inheritance diagram for Tms::TmsProcess::



Public Member Functions

- [TmsProcess](#) ([BString](#) name="")
- [BError getVersion](#) ([BString](#) &version)
Gets the software version.
- [BError getCycleInfo](#) ([UInt32](#) &cycleNumber, [BString](#) &cycleType)
Gets the current cycle number and type.
- [BError getCycleInformation](#) ([UInt32](#) cycleNumber, [CycleInformation](#) &cycleInformation)
Gets information on given cycle number.
- [BError getCycleTypeInfo](#) ([BString](#) cycleType, [CycleTypeInfo](#) &cycleTypeInfo)
Gets information on given cycle Type.
- [BError getData](#) ([DataInfo](#) dataInfo, [Data](#) &data)
This function returns a set of data from the data present in the data cache or directly from the Pick-Up processing engines. The [DataInfo](#) object describes the data required. The call will return the required data along with an error object indicating success or an error condition as appropriate. The call will block until data is ready.
- [BError addEventServer](#) ([BString](#) name)
This call adds an event server to call on events such as the "dataEvent" generated by the requestData(0 call as well as error events. The Client will use this to notify the TmsServer of its local [TmsEvent](#) object.
- [BError requestData](#) ([DataInfo](#) dataInfo)
This adds a request for some data. The [DataInfo](#) object defines the data required. This request can be made at any time. If the data is present in cache the data will be available immediately, if not the system will await the data from a subsequent processing cycle. When the data is available a "data" event will be sent to the client. Not that it is not necessary to use requestData. The client can call [getData\(\)](#) directly although this call will block until the data is actually ready.

9.83.1 Detailed Description

This interface provides functions to capture data from the TMS as a whole.

9.83.2 Constructor & Destructor Documentation

9.83.2.1 Tms::TmsProcess::TmsProcess (BString *name* = " ")

Parameters:

name The name of the [TmsProcess](#) BOAP object to connect to.

The BOAP object name has the general form: "//HostName/ObjectName"

9.83.3 Member Function Documentation

9.83.3.1 BError Tms::TmsProcess::getVersion (BString & *version*)

Gets the software version.

Parameters:

version A string variable filled in with the version number string.

9.83.3.2 BError Tms::TmsProcess::getCycleInfo (UInt32 & *cycleNumber*, BString & *cycleType*)

Gets the current cycle number and type.

Parameters:

cycleNumber The current cycle number is returned here

cycleType The current cycle type is returned here.

This function returns the current TMS cycle number being processed and the type of the cycle.

9.83.3.3 BError Tms::TmsProcess::getCycleInformation (UInt32 *cycleNumber*, CycleInformation & *cycleInformation*)

Gets information on given cycle number.

Parameters:

cycleNumber The current cycle number to get information on

cycleInformation The returned cycle information

This function provides information on the given cycle. It interrogates the first PUPE channel and returns the Cycle information based on the internal state of that channel. The main information returned includes the cycle type and a list of all of the Cycle Periods captured and the times and ammount of data in each.

9.83.3.4 BError Tms::TmsProcess::getCycleTypeInfo(BString cycleType, CycleTypeInfo & cycleTypeInfo)

Gets information on given cycle Type.

9.83.3.5 BError Tms::TmsProcess::getData(DataInfo dataInfo, Data & data)

This function returns a set of data from the data present in the data cache or directly from the Pick-Up processing engines. The [DataInfo](#) object describes the data required. The call will return the required data along with an error object indicating success or an error condition as appropriate. The call will block until data is ready.

Parameters:

dataInfo Information on the type of data required.

data The raw data is returned in this object.

This is the main user function used by clients of the TMS system. It is used to return portions of the acquired data. The fields of the dataInfo parameter define which data is required and are defined in the [DataInfo](#) class documentation.

The call will check to see if the data for the cycle number requested is still present in the PUPE memory. The PUPE memory has enough storage for about 3 seconds worth of data (3 processing cycles). If the data has gone the call will return the error "ErrorDataGone". If the system has not processed the requested cycle, but will do so within 256 seconds, the call will block awaiting the data.

If the channel number is given as 0 the call will interrogate each of the Pick-Up channels and return the combined data from all of them. Note that this could take significant time and may not be possible if the parameter numValues is large. Within the [Data](#) structure returned there is an array of error values, one per channel. If an error occurs on any set of the channels the call will return the first error that occurred and the complete list of errors in the errors array. The actual data will be returned for all channels that did not have an error. Those channels that had an error will have data values of 0 returned.

If the bunch number is given as 0, then the system will return the data for all of the bunches.

The data will be returned in the following order, where B - Bunch, C - Channel:

[C1.B1, C1.B2, C1.B3, C1.B4], [C1.B1, C1.B2, C1.B3, C1.B4], ... [C2.B1, C2.B2, C2.B3, C2.B4], [C2.B1, C2.B2, C2.B3, C2.B4], ...

That is the data is ordered by bunch, then sample, then channel. See the TMS Software documentation manual for more details of this functions operation.

9.83.3.6 BError Tms::TmsProcess::addEventServer(BString name)

This call adds an event server to call on events such as the "dataEvent" generated by the requestData(0 call as well as error events. The Client will use this to notify the TmsServer of its local [TmsEvent](#) object.

Parameters:

name The BOAP object name to add.

Adds an event server that gets called on certain TmsServer events such as data ready, CYCLE_START, CYCLE_STOP and errors.

9.83.3.7 BError Tms::TmsProcess::requestData (DataInfo *dataInfo*)

This adds a request for some data. The [DataInfo](#) object defines the data required. This request can be made at any time. If the data is present in cache the data will be available immediately, if not the system will await the data from a subsequent processing cycle. When the data is available a "data" event will be sent to the client. Not that it is not necessary to use requestData. The client can call [getData\(\)](#) directly although this call will block until the data is actually ready.

Parameters:

dataInfo Information on the type of data required.

This calls sets up a request for data. The *dataInfo* parameter works in the same manner as the "getData" call, defining the portion of data required. This call will return immediatly. Assuming the client has informed the TMS system of an event server object using the "addEventServer" call, then the client will receive the "dataEvent" event when the data become available. The client can then fetch the data using the conventional "getData" call. In the current version of the software the "requestData" call simply sends a message when the data for the requested cycle is ready. In future implementations the TMS system could actually fetch the data automatically from the PUPE boards and store it in memory ready for later retrieval by the getData call.

The documentation for this class was generated from the following files:

- [TmsC.h](#)
- [TmsC.cc](#)
- [tmsFunctions.dox](#)

9.84 Tms::TmsState Union Reference

The [Tms](#) State entry.

```
#include <TmsLib.h>
```

Public Attributes

- struct {
 - unsigned int [acquireData](#):1
 - unsigned int [pllReference1](#):1
 - unsigned int [pllReference2](#):1
 - unsigned int [pllFeedbackSelect](#):1
 - unsigned int [pllLO1FromAddress](#):1
 - unsigned int [pllLO2FromAddress](#):1
 - unsigned int [spare0](#):2
 - unsigned int [cycleStop](#):4
 - unsigned int [calStop](#):4
 - unsigned int [calStart](#):4
 - unsigned int [injection](#):4
 - unsigned int [hchange](#):4
 - unsigned int [delay](#):4

```
};
```

- unsigned int [value](#)

9.84.1 Detailed Description

The [Tms](#) State entry.

9.84.2 Member Data Documentation

- 9.84.2.1 unsigned int Tms::TmsState::aquireData
- 9.84.2.2 unsigned int Tms::TmsState::pllReference1
- 9.84.2.3 unsigned int Tms::TmsState::pllReference2
- 9.84.2.4 unsigned int Tms::TmsState::pllFeedbackSelect
- 9.84.2.5 unsigned int Tms::TmsState::pllLO1FromAddress
- 9.84.2.6 unsigned int Tms::TmsState::pllLO2FromAddress
- 9.84.2.7 unsigned int Tms::TmsState::spare0
- 9.84.2.8 unsigned int Tms::TmsState::cycleStop
- 9.84.2.9 unsigned int Tms::TmsState::calStop
- 9.84.2.10 unsigned int Tms::TmsState::calStart
- 9.84.2.11 unsigned int Tms::TmsState::injection
- 9.84.2.12 unsigned int Tms::TmsState::hchange
- 9.84.2.13 unsigned int Tms::TmsState::delay
- 9.84.2.14 struct { ... }
- 9.84.2.15 unsigned int Tms::TmsState::value

The documentation for this union was generated from the following file:

- [TmsLib.h](#)

Chapter 10

File Documentation

10.1 /src/cern/tms/beam/libBeam/BArray.h File Reference

```
#include <BTypes.h>
#include <vector>
```

Classes

- class [BArray< T >](#)

Defines

- #define [BArray_H](#) 1

10.1.1 Define Documentation

10.1.1.1 #define BArray_H 1

10.2 /src/cern/tms/beam/libBeam/BBuffer.cpp File Reference

```
#include <stdlib.h>
#include <memory.h>
#include <BBuffer.h>
```

Defines

- #define [SIZE](#) 1024

10.2.1 Define Documentation

10.2.1.1 #define SIZE 1024

10.3 /src/cern/tms/beam/libBeam/BBuffer.h File Reference

```
#include <stdint.h>
```

Classes

- class [BBuffer](#)

Defines

- #define [BBUFFER_H](#) 1

10.3.1 Define Documentation

10.3.1.1 #define BBUFFER_H 1

10.4 /src/cern/tms/beam/libBeam/BCond.cpp File Reference

```
#include <BCond.h>  
#include <sys/time.h>  
#include <stdio.h>
```

10.5 /src/cern/tms/beam/libBeam/BCond.h File Reference

```
#include <pthread.h>
```

Classes

- class [BCond](#)

Defines

- #define [BCOND_H](#) 1

10.5.1 Define Documentation

10.5.1.1 #define BCOND_H 1

10.6 /src/cern/tms/beam/libBeam/BCondInt.cpp File Reference

```
#include <BCondInt.h>
#include <sys/time.h>
#include <stdio.h>
#include <errno.h>
```


10.7 /src/cern/tms/beam/libBeam/BCondInt.h File Reference

```
#include <BTypes.h>
#include <pthread.h>
```

Classes

- class [BCondValue](#)
Thread conditional value.
- class [BCondInt](#)
Thread conditional integer.
- class [BCondBool](#)
Thread conditional boolean.
- class [BCondWrap](#)

Defines

- #define [BCONDINT_H](#) 1

10.7.1 Define Documentation

10.7.1.1 #define BCONDINT_H 1

10.8 /src/cern/tms/beam/libBeam/BDir.cpp File Reference

```
#include <BDir.h>
#include <dirent.h>
#include <stdlib.h>
#include <errno.h>
#include <string.h>
```

Functions

- static int [wild](#) (const dirent *e)

Variables

- static [BString wildString](#)

10.8.1 Function Documentation

10.8.1.1 static int [wild](#) (const dirent * *e*) [static]

10.8.2 Variable Documentation

10.8.2.1 [BString wildString](#) [static]

10.9 /src/cern/tms/beam/libBeam/BDir.h File Reference

```
#include <BList.h>
#include <BString.h>
#include <BError.h>
#include <sys/stat.h>
```

Classes

- class [BDir](#)
File system directory class.

Defines

- #define [BDIR_H](#) 1

10.9.1 Define Documentation

10.9.1.1 #define BDIR_H 1

10.10 /src/cern/tms/beam/libBeam/BEntry.cpp File Reference

```
#include <ctype.h>
#include <stdio.h>
#include <string.h>
#include <unistd.h>
#include <fcntl.h>
#include <errno.h>
#include <BEntry.h>
```

10.11 /src/cern/tms/beam/libBeam/BEntry.h File Reference

```
#include <BList.h>
#include <BString.h>
```

Classes

- class [BEntry](#)
Manipulate a name value pair.
- class [BEntryList](#)
List of Entries. Where an entry is a name value pair.
- class [BEntryFile](#)
File of Entries.

10.12 /src/cern/tms/beam/libBeam/BError.cpp File Reference

```
#include <BError.h>
```

10.13 /src/cern/tms/beam/libBeam/BError.h File Reference

```
#include <BString.h>
```

Classes

- class [BError](#)
Error return class.

Defines

- #define [BERROR_H](#) 1

10.13.1 Define Documentation

10.13.1.1 #define BERROR_H 1

10.14 /src/cern/tms/beam/libBeam/BEvent.cpp File Reference

```
#include <stdlib.h>
#include <unistd.h>
#include <errno.h>
#include <BEvent.h>
#include <BPoll.h>
```


10.15 /src/cern/tms/beam/libBeam/BEvent.h File Reference

```
#include <stdint.h>
#include <BError.h>
```

Classes

- class [BEvent](#)

This class provides a base class for all event objects that can be sent over the events interface.

- class [BEventError](#)
- class [BEventPipe](#)

This class provides a base interface for sending events via a pipe. This allows threads to send events that can be picked up by the poll system call.

- class [BEventInt](#)

This class provides an interface for sending simple integer events via a file descriptor. This allows threads to send events that can be picked up by the poll system call.

Defines

- #define [BEvent_H](#) 1

Enumerations

- enum [BEventType](#) { [BEventTypeNone](#), [BEventTypeInt](#), [BEventTypeError](#) }

10.15.1 Define Documentation

10.15.1.1 #define BEvent_H 1

10.15.2 Enumeration Type Documentation

10.15.2.1 enum BEventType

Enumerator:

BEventTypeNone

BEventTypeInt

BEventTypeError

10.16 /src/cern/tms/beam/libBeam/BFile.cpp File Reference

```
#include <BFile.h>
#include <sys/stat.h>
#include <string.h>
#include <stdarg.h>
#include <errno.h>
```

Defines

- #define [STRBUF](#) 10240

10.16.1 Define Documentation

10.16.1.1 #define STRBUF 10240

10.17 /src/cern/tms/beam/libBeam/BFile.h File Reference

```
#include <stdio.h>
#include <BString.h>
#include <BError.h>
```

Classes

- class [BFile](#)
File operations class.

Defines

- #define [BFILE_H](#) 1

10.17.1 Define Documentation

10.17.1.1 #define BFILE_H 1

10.18 /src/cern/tms/beam/libBeam/BList.h File Reference

```
#include <BList_func.h>
```

Classes

- class [BIter](#)
Iterator for [BList](#).
- class [BList< T >](#)
Template based list class.
- class [BList< T >::Node](#)

Defines

- #define [BLIST_H](#) 1

10.18.1 Define Documentation

10.18.1.1 #define BLIST_H 1

10.19 /src/cern/tms/beam/libBeam/BList_func.h File Reference

```
#include <stdlib.h>
#include <stdio.h>
#include <memory.h>
```

10.20 /src/cern/tms/beam/libBeam/BMutex.cpp File Reference

```
#include <BMutex.h>
```

Defines

- #define [MDEBUG](#) 0

10.20.1 Define Documentation

10.20.1.1 #define MDEBUG 0

10.21 /src/cern/tms/beam/libBeam/BMutex.h File Reference

```
#include <pthread.h>
```

Classes

- class [BMutex](#)
Mutex class.

Defines

- #define [BMUTEX_H](#) 1

10.21.1 Define Documentation

10.21.1.1 #define BMUTEX_H 1

10.22 /src/cern/tms/beam/libBeam/BNameValue.h File Reference

```
#include <BList.h>
#include <BString.h>
```

Classes

- class [BNameValue< T >](#)
- class [BNameValueList< T >](#)

Defines

- #define [BNAMEVALUE_H](#) 1
- #define [TEMPLATE_NEW](#) 1

10.22.1 Define Documentation

10.22.1.1 [#define BNAMEVALUE_H](#) 1

10.22.1.2 [#define TEMPLATE_NEW](#) 1

10.23 /src/cern/tms/beam/libBeam/Boap.cpp File Reference

```
#include <stdlib.h>
#include <stdio.h>
#include <errno.h>
#include <unistd.h>
#include <sys/socket.h>
#include <netinet/in.h>
#include <netinet/tcp.h>
#include <Boap.h>
#include <byteswap.h>
#include <BoapnsD.h>
#include <BoapnsC.h>
```

Defines

- #define [DEBUG](#) 0
- #define [APIVERSION_TEST](#) 1
- #define [dprintf](#)(fmt, a...)
- #define [IS_BIG_ENDIAN](#) 1

Functions

- static void [swap8](#) (char *d, char *s)
- static void [swap16](#) (char *d, char *s)
- static void [swap32](#) (char *d, char *s)
- static void [swap64](#) (char *d, char *s)

Variables

- const int [boapPort](#) = 12000

The default BOAP connection port.

- const int [roundSize](#) = 256

10.23.1 Define Documentation

10.23.1.1 `#define APIVERSION_TEST 1`

10.23.1.2 `#define DEBUG 0`

10.23.1.3 `#define dprintf(fmt, a...)`

10.23.1.4 `#define IS_BIG_ENDIAN 1`

10.23.2 Function Documentation

10.23.2.1 `static void swap16 (char *d, char *s)` [inline, static]

10.23.2.2 `static void swap32 (char *d, char *s)` [inline, static]

10.23.2.3 `static void swap64 (char *d, char *s)` [inline, static]

10.23.2.4 `static void swap8 (char *d, char *s)` [inline, static]

10.23.3 Variable Documentation

10.23.3.1 `const int boapPort = 12000`

The default BOAP connection port.

10.23.3.2 `const int roundSize = 256`

10.24 /src/cern/tms/beam/libBeam/Boap.h File Reference

```
#include <stdint.h>
#include <BPoll.h>
#include <BSocket.h>
#include <BThread.h>
#include <BError.h>
#include <BEvent.h>
#include <BMutex.h>
#include <BTypes.h>
```

Namespaces

- namespace [Boapns](#)

Classes

- struct [BoapPacketHead](#)
- class [BoapPacket](#)
- class [BoapClientObject](#)
- class [BoapSignalObject](#)
- class [BoapServiceEntry](#)
- class [BoapServerConnection](#)
- class [BoapServer](#)
- class [BoapFuncEntry](#)
- class [BoapServiceObject](#)

Typedefs

- typedef [UInt32](#) [BoapService](#)
- typedef [BError](#)([BoapServiceObject](#)::* [BoapFunc](#))([BoapServerConnection](#) *conn, [BoapPacket](#) &rx, [BoapPacket](#) &tx)

Enumerations

- enum [BoapType](#) {
 [BoapTypeRpc](#), [BoapTypeRpcReply](#), [BoapTypeSignal](#), [BoapTypeRpc](#),
 [BoapTypeSignal](#) }
- enum [BoapPriority](#) { [BoapPriorityLow](#), [BoapPriorityNormal](#), [BoapPriorityHigh](#) }

Variables

- const [UInt32](#) [BoapMagic](#) = 0x424F4100

10.24.1 Typedef Documentation

10.24.1.1 `typedef BError(BoapServiceObject::* BoapFunc)(BoapServerConnection *conn, BoapPacket &rx, BoapPacket &tx)`

10.24.1.2 `typedef UInt32 BoapService`

10.24.2 Enumeration Type Documentation

10.24.2.1 `enum BoapPriority`

Enumerator:

BoapPriorityLow

BoapPriorityNormal

BoapPriorityHigh

10.24.2.2 `enum BoapType`

Enumerator:

BoapTypeRpc

BoapTypeRpcReply

BoapTypeSignal

BoapTypeRpc

BoapTypeSignal

10.24.3 Variable Documentation

10.24.3.1 `const UInt32 BoapMagic = 0x424F4100`

10.25 /src/cern/tms/beam/libBeam/BoapnsC.cc File Reference

```
#include <BoapnsC.h>
```

Namespaces

- namespace [Boapns](#)

Functions

- [Boapns::Boapns](#) (BString name)
- [BError Boapns::getVersion](#) (BString &version)
- [BError Boapns::getEntryList](#) (BList< BoapEntry > &entryList)
- [BError Boapns::getEntry](#) (BString name, BoapEntry &entry)
- [BError Boapns::addEntry](#) (BoapEntry entry)
- [BError Boapns::delEntry](#) (BString name)
- [BError Boapns::getNewName](#) (BString &name)

10.26 /src/cern/tms/beam/libBeam/BoapnsC.h File Reference

```
#include <stdlib.h>
#include <stdint.h>
#include <Boap.h>
#include <BString.h>
#include <BList.h>
#include <BArray.h>
#include <BoapnsD.h>
```

Namespaces

- namespace [Boapns](#)

Classes

- class [Boapns::Boapns](#)

Defines

- #define [BOAPNSC_H](#) 1

Variables

- const [BUInt32](#) [Boapns::apiVersion](#) = 0

10.26.1 Define Documentation

10.26.1.1 #define BOAPNSC_H 1

10.27 /src/cern/tms/beam/libBeam/BoapnsD.cc File Reference

```
#include <BoapnsD.h>
```

Namespaces

- namespace [Boapns](#)

10.28 /src/cern/tms/beam/libBeam/BoapnsD.h File Reference

```
#include <Boap.h>
#include <BList.h>
#include <BArray.h>
```

Namespaces

- namespace [Boapns](#)

Classes

- class [Boapns::BoapEntry](#)

Defines

- #define [BOAPNSD_H](#) 1

10.28.1 Define Documentation

10.28.1.1 #define BOAPNSD_H 1

10.29 /src/cern/tms/beam/libBeam/BoapSimple.cc File Reference

```
#include <stdlib.h>
#include <stdio.h>
#include <errno.h>
#include <sys/socket.h>
#include <netinet/in.h>
#include <Boap.h>
#include <BoapnsD.h>
#include <BoapnsC.h>
```

Defines

- #define [DEBUG](#) 0
- #define [dprintf](#)(fmt, a...)

Variables

- const int [roundSize](#) = 256

10.29.1 Define Documentation

10.29.1.1 #define [DEBUG](#) 0

10.29.1.2 #define [dprintf](#)(fmt, a...)

10.29.2 Variable Documentation

10.29.2.1 const int [roundSize](#) = 256

10.30 /src/cern/tms/beam/libBeam/BoapSimple.h File Reference

```
#include <stdint.h>
#include <BPoll.h>
#include <BSocket.h>
#include <BError.h>
```

Classes

- struct [BoapPacketHead](#)
- class [BoapPacket](#)
- class [BoapClientObject](#)
- class [BoapSignalObject](#)
- class [BoapServiceEntry](#)
- class [BoapServer](#)
- class [BoapFuncEntry](#)
- class [BoapServiceObject](#)

Typedefs

- typedef int8_t [Int8](#)
- typedef uint8_t [UInt8](#)
- typedef int16_t [Int16](#)
- typedef uint16_t [UInt16](#)
- typedef int32_t [Int32](#)
- typedef uint32_t [UInt32](#)
- typedef double [Double](#)
- typedef uint32_t [BoapService](#)
- typedef [BError](#)([BoapServiceObject](#)::* [BoapFunc](#))([BoapPacket](#) &rx, [BoapPacket](#) &tx)

Enumerations

- enum [BoapType](#) {
 [BoapTypeRpc](#), [BoapTypeRpcReply](#), [BoapTypeSignal](#), [BoapTypeRpc](#),
 [BoapTypeSignal](#) }

10.30.1 Typedef Documentation

10.30.1.1 typedef BError(BoapServiceObject::* BoapFunc)(BoapPacket &rx, BoapPacket &tx)

10.30.1.2 typedef uint32_t BoapService

10.30.1.3 typedef double Double

10.30.1.4 typedef int16_t Int16

10.30.1.5 typedef int32_t Int32

10.30.1.6 typedef int8_t Int8

10.30.1.7 typedef uint16_t UInt16

10.30.1.8 typedef uint32_t UInt32

10.30.1.9 typedef uint8_t UInt8

10.30.2 Enumeration Type Documentation

10.30.2.1 enum BoapType

Enumerator:

BoapTypeRpc

BoapTypeRpcReply

BoapTypeSignal

BoapTypeRpc

BoapTypeSignal

10.31 /src/cern/tms/beam/libBeam/BObject.cc File Reference

```
#include <stdio.h>
#include <ctype.h>
#include <memory.h>
#include <string.h>
#include <BObject.h>
#include <iostream>
```

Defines

- #define [DEBUG](#) 0

10.31.1 Define Documentation

10.31.1.1 #define [DEBUG](#) 0

10.32 /src/cern/tms/beam/libBeam/BObject.h File Reference

```
#include <BType.h>
#include <BDataBuf.h>
#include <BString.h>
#include <BNameValue.h>
#include <BList.h>
#include <BError.h>
```

Classes

- class [BObject](#)

Defines

- #define [BOBJECT_H](#) 1

Typedefs

- typedef [BNameValue](#)< [BObject](#) * > [BMember](#)
- typedef [BNameValueList](#)< [BObject](#) * > [BMemberList](#)

10.32.1 Define Documentation

10.32.1.1 #define BOBJECT_H 1

10.32.2 Typedef Documentation

10.32.2.1 typedef BNameValue<BObject*> BMember

10.32.2.2 typedef BNameValueList<BObject*> BMemberList

10.33 /src/cern/tms/beam/libBeam/BPoll-1.cpp File Reference

```
#include <stdlib.h>
#include <unistd.h>
#include <errno.h>
#include <BPoll.h>
```

10.34 /src/cern/tms/beam/libBeam/BPoll.cpp File Reference

```
#include <stdlib.h>
#include <unistd.h>
#include <errno.h>
#include <BPoll.h>
```

10.35 /src/cern/tms/beam/libBeam/BPoll.h File Reference

```
#include <BList.h>
#include <BError.h>
#include <sys/poll.h>
```

Classes

- class [BPoll](#)

This class provides an interface for polling a number of file descriptors. It uses round robin polling.

Defines

- #define [BPOLL_H](#) 1

10.35.1 Define Documentation

10.35.1.1 #define BPOLL_H 1

10.36 /src/cern/tms/beam/libBeam/BRefData.cpp File Reference

```
#include <stdlib.h>
#include <string.h>
#include <BRefData.h>
```

Defines

- #define [DEBUG](#) 0
- #define [CHUNK](#) 16

10.36.1 Define Documentation

10.36.1.1 #define [CHUNK](#) 16

10.36.1.2 #define [DEBUG](#) 0

10.37 /src/cern/tms/beam/libBeam/BRefData.h File Reference

Classes

- class [BRefData](#)
Referenced data storage.

Defines

- #define [BREFDATA_H](#) 1

10.37.1 Define Documentation

10.37.1.1 #define BREFDATA_H 1

10.38 /src/cern/tms/beam/libBeam/BRtc.cpp File Reference

```
#include <BRtc.h>
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <errno.h>
#include <unistd.h>
#include <fcntl.h>
#include <sys/ioctl.h>
#include <linux/rtc.h>
```

10.39 /src/cern/tms/beam/libBeam/BRtc.h File Reference

```
#include <BError.h>
#include <BThread.h>
#include <BCond.h>
```

Classes

- class [BRtc](#)
Realtime clock.
- class [BRtcThreaded](#)
Threaded real time clock.

10.40 /src/cern/tms/beam/libBeam/BRWLock.cpp File Reference

```
#include <BRWLock.h>
```

10.41 /src/cern/tms/beam/libBeam/BRWLock.h File Reference

```
#include <pthread.h>
```

Classes

- class [BRWLock](#)
thread read-write locks

Defines

- #define [BRWLOCK_H](#) 1

10.41.1 Define Documentation

10.41.1.1 #define BRWLOCK_H 1

10.42 /src/cern/tms/beam/libBeam/BSema.cpp File Reference

```
#include <BSema.h>
#include <errno.h>
#include <sys/time.h>
```

10.43 /src/cern/tms/beam/libBeam/BSema.h File Reference

```
#include <semaphore.h>
```

Classes

- class [BSema](#)
Sempahore class.

Defines

- #define [BSEMA_H](#) 1

10.43.1 Define Documentation

10.43.1.1 #define BSEMA_H 1

10.44 /src/cern/tms/beam/libBeam/BSocket.cpp File Reference

```
#include <stdlib.h>
#include <unistd.h>
#include <stdio.h>
#include <errno.h>
#include <sys/types.h>
#include <sys/socket.h>
#include <arpa/inet.h>
#include <netdb.h>
#include <net/if.h>
#include "BSocket.h"
```

Defines

- #define [IP_MTU](#) 14

10.44.1 Define Documentation

10.44.1.1 #define IP_MTU 14

10.45 /src/cern/tms/beam/libBeam/BSocket.h File Reference

```
#include <BString.h>
#include <BError.h>
#include <BTypes.h>
#include <stdint.h>
#include <sys/types.h>
#include <sys/prctl.h>
```

Classes

- class [BSocketAddress](#)
Socket Address.
- class [BSocketAddressINET](#)
IP aware socket address.
- class [BSocket](#)

Defines

- #define [BSOCKET_H](#) 1

10.45.1 Define Documentation

10.45.1.1 #define BSOCKET_H 1

10.46 /src/cern/tms/beam/libBeam/BString.cpp File Reference

```
#include <stdio.h>
#include <string.h>
#include <stdlib.h>
#include <stdarg.h>
#include <ctype.h>
#include "BString.h"
```

Defines

- #define [DEBUG](#) 0
- #define [STRIP](#) 0x7f
- #define [MINUS](#) '-'

Functions

- static int [gmatch](#) (const char *s, const char *p)
- std::ostream & [operator<<](#) (std::ostream &o, [BString](#) &s)
- std::istream & [operator>>](#) (std::istream &i, [BString](#) &s)

10.46.1 Define Documentation

10.46.1.1 #define [DEBUG](#) 0

10.46.1.2 #define [MINUS](#) '-'

10.46.1.3 #define [STRIP](#) 0x7f

10.46.2 Function Documentation

10.46.2.1 static int [gmatch](#) (const char *s, const char *p) [static]

10.46.2.2 std::ostream& [operator<<](#) (std::ostream &o, [BString](#) &s)

10.46.2.3 std::istream& [operator>>](#) (std::istream &i, [BString](#) &s)

10.47 /src/cern/tms/beam/libBeam/BString.h File Reference

```
#include <BRefData.h>
#include <BList.h>
#include <iostream>
```

Classes

- class [BString](#)

Defines

- #define [BSTRING_H](#) 1

Functions

- std::ostream & [operator<<](#) (std::ostream &o, [BString](#) &s)
- std::istream & [operator>>](#) (std::istream &i, [BString](#) &s)

10.47.1 Define Documentation

10.47.1.1 #define BSTRING_H 1

10.47.2 Function Documentation

10.47.2.1 std::ostream& operator<< (std::ostream & o, BString & s)

10.47.2.2 std::istream& operator>> (std::istream & i, BString & s)

10.48 /src/cern/tms/beam/libBeam/BThread.cpp File Reference

```
#include <BThread.h>
#include <unistd.h>
#include <errno.h>
#include <sys/types.h>
```

10.49 /src/cern/tms/beam/libBeam/BThread.h File Reference

`#include <pthread.h>`

Classes

- class [BThread](#)

Defines

- `#define` [BTHREAD_H](#) 1

10.49.1 Define Documentation

10.49.1.1 `#define BTHREAD_H 1`

10.50 /src/cern/tms/beam/libBeam/BTimer.cpp File Reference

```
#include <BTimer.h>
#include <sys/time.h>
```

10.51 /src/cern/tms/beam/libBeam/BTimer.h File Reference

```
#include <BMutex.h>
```

Classes

- class [BTimer](#)
Stopwatch style timer.

10.52 /src/cern/tms/beam/libBeam/BTypes.h File Reference

```
#include <stdint.h>
#include <sys/types.h>
#include <vector>
```

Defines

- #define [BTYPES_H](#) 1

Typedefs

- typedef int8_t [BInt8](#)
- typedef uint8_t [BUInt8](#)
- typedef int16_t [BInt16](#)
- typedef uint16_t [BUInt16](#)
- typedef int32_t [BInt32](#)
- typedef uint32_t [BUInt32](#)
- typedef int64_t [BInt64](#)
- typedef uint64_t [BUInt64](#)
- typedef float [BFloat](#)
- typedef double [BDouble](#)
- typedef size_t [BSize](#)
- typedef uint32_t [BUInt](#)
- typedef std::vector< float > [BArrayFloat](#)
- typedef std::vector< double > [BArrayDouble](#)
- typedef int8_t [Int8](#)
- typedef uint8_t [UInt8](#)
- typedef int16_t [Int16](#)
- typedef uint16_t [UInt16](#)
- typedef int32_t [Int32](#)
- typedef uint32_t [UInt32](#)
- typedef int64_t [Int64](#)
- typedef uint64_t [UInt64](#)
- typedef float [Float](#)
- typedef double [Double](#)

10.52.1 Define Documentation

10.52.1.1 `#define BTYPES_H 1`

10.52.2 Typedef Documentation

10.52.2.1 `typedef std::vector<double> BArrayDouble`

10.52.2.2 `typedef std::vector<float> BArrayFloat`

10.52.2.3 `typedef double BDouble`

10.52.2.4 `typedef float BFloat`

10.52.2.5 `typedef int16_t BInt16`

10.52.2.6 `typedef int32_t BInt32`

10.52.2.7 `typedef int64_t BInt64`

10.52.2.8 `typedef int8_t BInt8`

10.52.2.9 `typedef size_t BSize`

10.52.2.10 `typedef uint32_t BUInt`

10.52.2.11 `typedef uint16_t BUInt16`

10.52.2.12 `typedef uint32_t BUInt32`

10.52.2.13 `typedef uint64_t BUInt64`

10.52.2.14 `typedef uint8_t BUInt8`

10.52.2.15 `typedef double Double`

10.52.2.16 `typedef float Float`

10.52.2.17 `typedef int16_t Int16`

10.52.2.18 `typedef int32_t Int32`

10.52.2.19 `typedef int64_t Int64`

10.52.2.20 `typedef int8_t Int8`

10.52.2.21 `typedef uint16_t UInt16`

10.52.2.22 `typedef uint32_t UInt32`

10.52.2.23 `typedef uint64_t UInt64`

10.52.2.24 `typedef uint8_t UInt8`

10.53 /src/cern/tms/beam/libBeam/BUrl.cpp File Reference

```
#include <stdio.h>
#include <stdlib.h>
#include <memory.h>
#include <BUrl.h>
#include <curl/curl.h>
```

10.54 /src/cern/tms/beam/libBeam/BUrl.h File Reference

```
#include <stdio.h>
#include <BString.h>
#include <BError.h>
```

Classes

- class [BUrl](#)
Basic access to a Url.

Defines

- #define [BURL_H](#) 1

10.54.1 Define Documentation

10.54.1.1 #define [BURL_H](#) 1

10.55 overview.dox File Reference

10.56 SigGen.cpp File Reference

```
#include <SigGen.h>
#include <math.h>
#include <time.h>
```

Defines

- #define [DEBUG](#) 0
- #define [dprintf](#)(fmt, a...)

10.56.1 Define Documentation

10.56.1.1 #define [DEBUG](#) 0

10.56.1.2 #define [dprintf](#)(fmt, a...)

10.57 SigGen.h File Reference

```
#include <BList.h>
#include <BError.h>
```

Classes

- class [BSignal](#)
- class [SigGen](#)
- class [SigGenSine](#)
- class [SigGenSquare](#)
- class [SigGenNoise](#)
- class [SigGenPulse](#)
- class [SigGenBeam](#)

Defines

- #define [SigGen_h](#) 1

Typedefs

- typedef float [Sample](#)
- typedef [BList](#)< [BSignal](#) > [BSignalList](#)

10.57.1 Define Documentation

10.57.1.1 #define SigGen_h 1

10.57.2 Typedef Documentation

10.57.2.1 typedef BList<BSignal> BSignalList

10.57.2.2 typedef float Sample

10.58 test1.cpp File Reference

```
#include <stdio.h>
#include <TmsLib.h>
```

Functions

- void [printCycleParams](#) (Tms::CycleParam *p*)
- int [main](#) ()

10.58.1 Function Documentation

10.58.1.1 int main ()

10.58.1.2 void printCycleParams (Tms::CycleParam *p*)

10.59 TmsC.cc File Reference

```
#include <TmsC.h>
```

Namespaces

- namespace [Tms](#)

10.60 TmsC.h File Reference

This file contains the TmsAPi class definitions.

```
#include <stdlib.h>
#include <stdint.h>
#include <Boap.h>
#include <BString.h>
#include <BList.h>
#include <BArray.h>
#include <TmsD.h>
```

Namespaces

- namespace [Tms](#)

Classes

- class [Tms::PuControl](#)
This class defines the parameters for a test data capture.
- class [Tms::PuProcess](#)
This interface provides functions to configure and capture data from individual pick-up.
- class [Tms::TmsControl](#)
This interface provides functions to control, test and get statistics from the TMS as a whole.
- class [Tms::TmsProcess](#)
This interface provides functions to capture data from the TMS as a whole.
- class [Tms::TmsEvent](#)
This interface provides functions for events to be sent to clients from the TMS as a whole.

Defines

- #define [TMSC_H](#) 1

Variables

- const [BUInt32](#) [Tms::apiVersion](#) = 0

10.60.1 Detailed Description

This file contains the TmsAPi class definitions.

10.60.2 Define Documentation

10.60.2.1 `#define TMSH 1`

10.61 TmsCycleParam-1.cc File Reference

```
#include <stdlib.h>
#include <stdint.h>
#include <unistd.h>
#include <errno.h>
#include <math.h>
#include <TmsCycleParam.h>
#include <BFile.h>
#include <BEntry.h>
```

Namespaces

- namespace [Tms](#)

10.62 TmsCycleParam.cc File Reference

```
#include <stdlib.h>
#include <stdint.h>
#include <unistd.h>
#include <errno.h>
#include <math.h>
#include <TmsCycleParam.h>
#include <BFile.h>
#include <BEntry.h>
```

Namespaces

- namespace [Tms](#)

10.63 TmsCycleParam.h File Reference

```
#include <TmsLib.h>
```

Namespaces

- namespace [Tms](#)

Classes

- class [Tms::CycleParamState](#)
- class [Tms::CycleParamEdit](#)
Cycle Parameter management class.

Defines

- #define [TmsCycleParam_H](#) 1

10.63.1 Define Documentation

10.63.1.1 #define TmsCycleParam_H 1

10.64 TmsD.cc File Reference

```
#include <TmsD.h>
```

Namespaces

- namespace [Tms](#)

10.65 TmsD.h File Reference

```
#include <Boap.h>
#include <BList.h>
#include <BArray.h>
```

Namespaces

- namespace [Tms](#)

Classes

- class [Tms::NameValue](#)
- class [Tms::PuChannel](#)
This class stores a Physical Pick-Up channel id.
- class [Tms::PuStatus](#)
This class stores the status of an individual Pick-Up.
- class [Tms::ConfigInfo](#)
This class describes the configuration of the TMS.
- class [Tms::DataInfo](#)
This class defines the data to be acquired and/or fetched.
- class [Tms::DataValue](#)
This is the definition of a single data value.
- class [Tms::Data](#)
This class stores the raw data.
- class [Tms::PuStateTable](#)
This class defines the Pick-Up state table.
- class [Tms::CycleParam](#)
This class defines the parameters for a PS processing cycle.
- class [Tms::CycleParamItem](#)
- class [Tms::TestCaptureInfo](#)
This class defines the parameters for a test data capture.
- class [Tms::PupeConfig](#)
- class [Tms::CycleInformationPeriod](#)
Cycle information.
- class [Tms::CycleInformation](#)
- class [Tms::CycleTypeInfoInformationPeriod](#)
Cycle Type information.

- class [Tms::CycleTypeInformation](#)
- class [Tms::Simulation](#)

Defines

- `#define TMSD_H 1`

Enumerations

- enum [Tms::Errors](#) {
[Tms::ErrorOk](#), [Tms::ErrorMisc](#), [Tms::ErrorWarning](#), [Tms::ErrorInit](#),
[Tms::ErrorConfig](#), [Tms::ErrorParam](#), [Tms::ErrorNotImplemented](#), [Tms::ErrorComms](#),
[Tms::ErrorCommsTimeout](#), [Tms::ErrorMC](#), [Tms::ErrorFpga](#), [Tms::ErrorStateTable](#),
[Tms::ErrorCycleNumber](#), [Tms::ErrorDataNotAvailable](#), [Tms::ErrorDataGone](#),
[Tms::ErrorDataFuture](#),
[Tms::ErrorTimeout](#) }
- enum [Tms::CyclePeriod](#) {
[Tms::CyclePeriodAll](#), [Tms::CyclePeriodCalibration](#), [Tms::CyclePeriodEvent0](#),
[Tms::CyclePeriodEvent1](#),
[Tms::CyclePeriodEvent2](#), [Tms::CyclePeriodEvent3](#), [Tms::CyclePeriodEvent4](#),
[Tms::CyclePeriodEvent5](#),
[Tms::CyclePeriodEvent6](#), [Tms::CyclePeriodEvent7](#), [Tms::CyclePeriodEvent8](#),
[Tms::CyclePeriodEvent9](#) }
- enum [Tms::DataType](#) { [Tms::DataTypeRaw](#) }
- enum [Tms::DataFunction](#) {
[Tms::DataFunctionRaw](#), [Tms::DataFunctionMean](#), [Tms::DataFunctionMeanAll](#),
[Tms::DataFunctionMean0](#),
[Tms::DataFunctionMean1](#) }
- enum [Tms::TestOutput](#) { [Tms::TestOutputFrefLocal](#), [Tms::TestOutputPllL1](#), [Tms::TestOutputPllL2](#) }
- enum [Tms::Priority](#) { [Tms::PriorityLow](#), [Tms::PriorityNormal](#), [Tms::PriorityHigh](#) }

10.65.1 Define Documentation

10.65.1.1 `#define TMSD_H 1`

10.66 TmsEventServerList.cc File Reference

```
#include <stdlib.h>
#include <stdint.h>
#include <TmsEventServerList.h>
```

Namespaces

- namespace [Tms](#)

10.67 TmsEventServerList.h File Reference

```
#include <TmsD.h>
```

```
#include <TmsC.h>
```

Namespaces

- namespace [Tms](#)

Classes

- class [Tms::TmsEventServerList](#)

Defines

- #define [TmsEventServerList_H](#) 1

10.67.1 Define Documentation

10.67.1.1 #define TmsEventServerList_H 1

10.68 tmsFunctions.dox File Reference

Namespaces

- namespace [Tms](#)

10.69 TmsLib.cc File Reference

```
#include <stdlib.h>
#include <stdint.h>
#include <unistd.h>
#include <math.h>
#include <TmsLib.h>
#include <BDir.h>
#include <BEntry.h>
#include <BFile.h>
#include <TmsCycleParam.h>
```

Namespaces

- namespace [Tms](#)

10.70 TmsLib.h File Reference

```
#include <TmsD.h>
```

```
#include <TmsC.h>
```

Namespaces

- namespace [Tms](#)

Classes

- union [Tms::TmsState](#)
The [Tms](#) State entry.
- union [Tms::TmsPhase](#)
The [Tms](#) Phase Table Entry.
- class [Tms::CycleParamDb](#)
Internal CycleParameter management class.

Defines

- `#define TmsLib_H 1`

Enumerations

- enum [Tms::TimingSig](#) {
 [Tms::TimingSigClock](#) = 0x01, [Tms::TimingSigCycleStart](#) = 0x02, [Tms::TimingSigCycleStop](#) = 0x04, [Tms::TimingSigCalStart](#) = 0x08,
 [Tms::TimingSigCalStop](#) = 0x10, [Tms::TimingSigInjection](#) = 0x20, [Tms::TimingSigHChange](#) = 0x40, [Tms::TimingSigFRef](#) = 0x80 }
The timing signal bits.
- enum [Tms::CaptureClock](#) {
 [Tms::ClkAdcDiv_1](#) = 0x00, [Tms::ClkAdcDiv_2](#) = 0x01, [Tms::ClkAdcDiv_5](#) = 0x02, [Tms::ClkAdcDiv_10](#) = 0x03,
 [Tms::ClkAdcDiv_20](#) = 0x04, [Tms::ClkAdcDiv_50](#) = 0x05, [Tms::ClkAdcDiv_100](#) = 0x06, [Tms::ClkAdcDiv_200](#) = 0x07,
 [Tms::ClkAdcDiv_500](#) = 0x08, [Tms::ClkAdcDiv_1000](#) = 0x09, [Tms::ClkAdcDiv_2000](#) = 0x0A, [Tms::ClkAdcDiv_5000](#) = 0x0B,
 [Tms::ClkAdcDiv_10000](#) = 0x0C, [Tms::ClkAdcDiv_20000](#) = 0x0D, [Tms::ClkAdcDiv_50000](#) = 0x0E, [Tms::ClkAdcDiv_100000](#) = 0x0F,
 [Tms::ClkMs](#) = 0x10, [Tms::ClkFref](#) = 0x11 }
The Diagnostics Capture Clock settings.

Variables

- const unsigned int `Tms::tmsNumPickups` = 40
The default number of pick ups.
- const unsigned int `Tms::tmsPhaseTableSize` = 512
The size of the Phase Table.

10.70.1 Define Documentation

10.70.1.1 `#define TmsLib_H 1`

10.71 TmsS.cc File Reference

```
#include <TmsC.h>
```

```
#include <TmsS.h>
```

Namespaces

- namespace [Tms](#)

10.72 TmsT.cc File Reference

```
#include <stdlib.h>
#include <stdint.h>
#include <TmsT.h>
```

Index

- ~BBuffer
 - BBuffer, [34](#)
- ~BCond
 - BCond, [36](#)
- ~BCondBool
 - BCondBool, [37](#)
- ~BCondInt
 - BCondInt, [40](#)
- ~BCondValue
 - BCondValue, [43](#)
- ~BCondWrap
 - BCondWrap, [46](#)
- ~BDir
 - BDir, [49](#)
- ~BEntryFile
 - BEntryFile, [55](#)
- ~BEvent
 - BEvent, [62](#)
- ~BEventInt
 - BEventInt, [65](#)
- ~BEventPipe
 - BEventPipe, [67](#)
- ~BFile
 - BFile, [70](#)
- ~BList
 - BList, [77](#)
- ~BMutex
 - BMutex, [82](#)
- ~BObject
 - BObject, [114](#)
- ~BPoll
 - BPoll, [116](#)
- ~BRWLock
 - BRWLock, [124](#)
- ~BRefData
 - BRefData, [119](#)
- ~BRtc
 - BRtc, [120](#)
- ~BRtcThreaded
 - BRtcThreaded, [122](#)
- ~BSema
 - BSema, [126](#)
- ~BSignal
 - BSignal, [129](#)
- ~BSocket
 - BSocket, [133](#)
- ~BSocketAddress
 - BSocketAddress, [136](#)
- ~BString
 - BString, [143](#)
- ~BThread
 - BThread, [149](#)
- ~BTimer
 - BTimer, [151](#)
- ~BUrl
 - BUrl, [153](#)
- ~BoapPacket
 - BoapPacket, [96](#)
- ~BoapServer
 - BoapServer, [101](#)
- ~BoapServiceObject
 - BoapServiceObject, [109](#)
- ~SigGen
 - SigGen, [194](#)
- ~SigGenBeam
 - SigGenBeam, [195](#)
- ~SigGenNoise
 - SigGenNoise, [197](#)
- ~SigGenPulse
 - SigGenPulse, [198](#)
- ~SigGenSine
 - SigGenSine, [200](#)
- ~SigGenSquare
 - SigGenSquare, [201](#)
- ~TmsEventServerList
 - Tms::TmsEventServerList, [218](#)
- /src/cern/tms/beam/ Directory Reference, [21](#)
- /src/cern/tms/beam/libBeam/ Directory Reference, [22](#)
- /src/cern/tms/beam/libBeam/BArray.h, [227](#)
- /src/cern/tms/beam/libBeam/BBuffer.cpp, [228](#)
- /src/cern/tms/beam/libBeam/BBuffer.h, [229](#)
- /src/cern/tms/beam/libBeam/BCond.cpp, [230](#)
- /src/cern/tms/beam/libBeam/BCond.h, [231](#)
- /src/cern/tms/beam/libBeam/BCondInt.cpp, [232](#)
- /src/cern/tms/beam/libBeam/BCondInt.h, [233](#)
- /src/cern/tms/beam/libBeam/BDir.cpp, [234](#)
- /src/cern/tms/beam/libBeam/BDir.h, [235](#)
- /src/cern/tms/beam/libBeam/BEntry.cpp, [236](#)
- /src/cern/tms/beam/libBeam/BEntry.h, [237](#)

- /src/cern/tms/beam/libBeam/BError.cpp, 238
- /src/cern/tms/beam/libBeam/BError.h, 239
- /src/cern/tms/beam/libBeam/BEvent.cpp, 240
- /src/cern/tms/beam/libBeam/BEvent.h, 241
- /src/cern/tms/beam/libBeam/BFile.cpp, 242
- /src/cern/tms/beam/libBeam/BFile.h, 243
- /src/cern/tms/beam/libBeam/BList.h, 244
- /src/cern/tms/beam/libBeam/BList_func.h, 245
- /src/cern/tms/beam/libBeam/BMutex.cpp, 246
- /src/cern/tms/beam/libBeam/BMutex.h, 247
- /src/cern/tms/beam/libBeam/BNameValue.h, 248
- /src/cern/tms/beam/libBeam/BObject.cc, 260
- /src/cern/tms/beam/libBeam/BObject.h, 261
- /src/cern/tms/beam/libBeam/BPoll-1.cpp, 262
- /src/cern/tms/beam/libBeam/BPoll.cpp, 263
- /src/cern/tms/beam/libBeam/BPoll.h, 264
- /src/cern/tms/beam/libBeam/BRWLock.cpp, 269
- /src/cern/tms/beam/libBeam/BRWLock.h, 270
- /src/cern/tms/beam/libBeam/BRefData.cpp, 265
- /src/cern/tms/beam/libBeam/BRefData.h, 266
- /src/cern/tms/beam/libBeam/BRtc.cpp, 267
- /src/cern/tms/beam/libBeam/BRtc.h, 268
- /src/cern/tms/beam/libBeam/BSema.cpp, 271
- /src/cern/tms/beam/libBeam/BSema.h, 272
- /src/cern/tms/beam/libBeam/BSocket.cpp, 273
- /src/cern/tms/beam/libBeam/BSocket.h, 274
- /src/cern/tms/beam/libBeam/BString.cpp, 275
- /src/cern/tms/beam/libBeam/BString.h, 276
- /src/cern/tms/beam/libBeam/BThread.cpp, 277
- /src/cern/tms/beam/libBeam/BThread.h, 278
- /src/cern/tms/beam/libBeam/BTimer.cpp, 279
- /src/cern/tms/beam/libBeam/BTimer.h, 280
- /src/cern/tms/beam/libBeam/BTypes.h, 281
- /src/cern/tms/beam/libBeam/BUrl.cpp, 284
- /src/cern/tms/beam/libBeam/BUrl.h, 285
- /src/cern/tms/beam/libBeam/Boap.cpp, 249
- /src/cern/tms/beam/libBeam/Boap.h, 251
- /src/cern/tms/beam/libBeam/BoapSimple.cc, 257
- /src/cern/tms/beam/libBeam/BoapSimple.h, 258
- /src/cern/tms/beam/libBeam/BoapnsC.cc, 253
- /src/cern/tms/beam/libBeam/BoapnsC.h, 254
- /src/cern/tms/beam/libBeam/BoapnsD.cc, 255
- /src/cern/tms/beam/libBeam/BoapnsD.h, 256
- accept
 - BSocket, 133
- acquireData
 - Tms::CycleParamState, 170
- adcSysclkSync
 - Tms::PupeConfig, 188
- add
 - BString, 145
 - BTimer, 151
- addEntry
 - Boapns, 26
 - Boapns::Boapns, 92
- addEventServer
 - Tms::PuProcess, 190
 - Tms::TmsProcess, 223
- addMember
 - BObject, 114
- addObject
 - BoapServer, 101, 102
- addRef
 - BRefData, 119
- address
 - BSocketAddressINET, 138
- addressList
 - Boapns::BoapEntry, 90
- apiVersion
 - Boapns, 26
 - Tms, 32
- APIVERSION_TEST
 - Boap.cpp, 250
- append
 - BList, 78, 79
 - BPoll, 116
 - Tms::TmsEventServerList, 218
- acquireData
 - Tms::TmsState, 226
- argument
 - Tms::DataInfo, 177
- average
 - BTimer, 151
- BArray, 33
 - BArray, 33
- BArray.h
 - BArray_H, 227
- BArray_H
 - BArray.h, 227
- BArrayDouble
 - BTypes.h, 283
- BArrayFloat
 - BTypes.h, 283
- BBuffer, 34
 - ~BBuffer, 34
 - BBuffer, 34
 - data, 35
 - odata, 35
 - odatasize, 35
 - osize, 35
 - setData, 34
 - setSize, 34
 - size, 35
 - writeData, 34
- BBuffer.cpp
 - SIZE, 228

- BBuffer.h
 - BBUFFER_H, 229
- BBUFFER_H
 - BBuffer.h, 229
- BCond, 36
 - ~BCond, 36
 - BCond, 36
 - ocond, 36
 - omutex, 36
 - signal, 36
 - timedWait, 36
 - wait, 36
- BCond.h
 - BCOND_H, 231
- BCOND_H
 - BCond.h, 231
- BCondBool, 37
 - ~BCondBool, 37
 - BCondBool, 37
 - clear, 37
 - ocond, 38
 - omutex, 38
 - ovalue, 38
 - set, 37
 - timedWait, 38
 - value, 38
 - wait, 38
- BCondInt, 39
 - ~BCondInt, 40
 - BCondInt, 40
 - decrement, 40
 - increment, 40
 - ocond, 41
 - omutex, 41
 - operator++, 41
 - operator-, 41
 - ovalue, 41
 - setValue, 40
 - timedWait, 40
 - tryNotZeroDecrement, 40
 - value, 40
 - wait, 40
 - waitIncrement, 40
 - waitNotZero, 40
 - waitNotZeroDecrement, 40
- BCondInt.h
 - BCONDINT_H, 233
- BCONDINT_H
 - BCondInt.h, 233
- BCondValue, 42
 - ~BCondValue, 43
 - BCondValue, 43
 - decrement, 43
 - increment, 43
 - ocond, 44
 - omutex, 44
 - operator++, 43
 - operator+=, 43
 - operator-, 44
 - operator=, 43
 - ovalue, 44
 - setValue, 43
 - value, 43
 - waitLessThan, 43
 - waitLessThanOrEqual, 43
 - waitMoreThanOrEqual, 43
- BCondWrap, 45
 - ~BCondWrap, 46
 - BCondWrap, 46
 - decrement, 46
 - diff, 47
 - increment, 46
 - ocond, 47
 - omutex, 47
 - operator++, 47
 - operator+=, 46
 - operator-, 47
 - operator=, 46
 - ovalue, 47
 - setValue, 46
 - value, 46
 - waitLessThan, 46
 - waitLessThanOrEqual, 46
 - waitMoreThanOrEqual, 46
- BDir, 48
 - ~BDir, 49
 - BDir, 49
 - clear, 49
 - entryName, 49
 - entryStat, 50
 - entryStat64, 50
 - error, 49
 - odirname, 50
 - oerror, 50
 - open, 49
 - osort, 50
 - owild, 50
 - read, 49
 - setSort, 49
 - setWild, 49
- BDir.cpp
 - wild, 234
 - wildString, 234
- BDir.h
 - BDIR_H, 235
- BDir_H
 - BDir.h, 235
- BDouble

- BTypes.h, 283
- begin
 - BList, 77
- BEntry, 51
 - BEntry, 52
 - getName, 52
 - getValue, 52
 - line, 52
 - oname, 53
 - ovalue, 53
 - print, 52
 - setLine, 52
 - setName, 52
 - setValue, 52
- BEntryFile, 54
 - ~BEntryFile, 55
 - BEntryFile, 55
 - clear, 55
 - ocomments, 55
 - ofilename, 55
 - open, 55
 - read, 55
 - write, 55
 - writeList, 55
- BEntryList, 56
 - BEntryList, 57
 - clear, 58
 - del, 58
 - deleteEntry, 57
 - find, 57
 - findValue, 57
 - getString, 57
 - insert, 57
 - isSet, 57
 - olastPos, 58
 - print, 57
 - setValue, 57
 - setValueRaw, 57
- BError, 59
 - BError, 60
 - copy, 60
 - ERROR, 60
 - getErrorNo, 60
 - getString, 60
 - NONE, 60
 - oerrNo, 61
 - oerrStr, 61
 - operator int, 60
 - set, 60
 - setError, 60
 - Type, 60
- BError.h
 - BERROR_H, 239
- BERROR_H
- BError.h, 239
- BEvent, 62
 - ~BEvent, 62
 - BEvent, 62
 - getBinary, 62
 - getType, 62
 - otype, 63
 - setBinary, 62
- BEvent.h
 - BEvent_H, 241
 - BEventType, 241
 - BEventTypeError, 241
 - BEventTypeInt, 241
 - BEventTypeNone, 241
- BEvent_H
 - BEvent.h, 241
- BEventError, 64
 - BEventError, 64
 - getBinary, 64
 - setBinary, 64
- BEventInt, 65
 - ~BEventInt, 65
 - BEventInt, 65
 - getEvent, 65
 - getFd, 65
 - ofds, 66
 - sendEvent, 65
- BEventPipe, 67
 - ~BEventPipe, 67
 - BEventPipe, 67
 - getEvent, 67
 - getReceiveFd, 67
 - ofds, 68
 - sendEvent, 67
- BEventType
 - BEvent.h, 241
- BEventTypeError
 - BEvent.h, 241
- BEventTypeInt
 - BEvent.h, 241
- BEventTypeNone
 - BEvent.h, 241
- beyondPeriod
 - Tms::DataInfo, 177
- BFile, 69
 - ~BFile, 70
 - BFile, 70
 - close, 70
 - error, 70
 - getFd, 71
 - length, 71
 - oerror, 72
 - ofile, 72
 - ofilename, 72

- omode, [72](#)
- open, [70](#)
- operator=, [71](#)
- printf, [71](#)
- read, [71](#)
- readString, [71](#)
- seek, [71](#)
- setVBuf, [71](#)
- write, [71](#)
- writeString, [71](#)
- BFile.cpp
 - STRBUF, [242](#)
- BFile.h
 - BFILE_H, [243](#)
- BFILE_H
 - BFile.h, [243](#)
- BFloat
 - BTypes.h, [283](#)
- bind
 - BSocket, [133](#)
- BInt16
 - BTypes.h, [283](#)
- BInt32
 - BTypes.h, [283](#)
- BInt64
 - BTypes.h, [283](#)
- BInt8
 - BTypes.h, [283](#)
- BIter, [73](#)
 - BIter, [73](#)
 - oi, [73](#)
 - operator void *, [73](#)
 - operator==, [73](#)
- BList, [74](#)
 - ~BList, [77](#)
 - append, [78](#), [79](#)
 - begin, [77](#)
 - BList, [77](#)
 - clear, [78](#)
 - del, [78](#)
 - deleteFirst, [79](#)
 - deleteLast, [78](#)
 - end, [77](#)
 - front, [78](#)
 - get, [78](#)
 - goTo, [77](#)
 - insert, [78](#)
 - insertAfter, [78](#)
 - isEnd, [77](#)
 - next, [77](#)
 - nodeCreate, [80](#)
 - nodeGet, [80](#)
 - number, [77](#)
 - olength, [80](#)
 - onodes, [80](#)
 - operator+, [80](#)
 - operator=, [79](#)
 - pop, [79](#)
 - position, [77](#)
 - prev, [77](#)
 - push, [79](#)
 - queueAdd, [79](#)
 - queueGet, [79](#)
 - rear, [78](#)
 - sort, [79](#)
 - SortFunc, [76](#)
 - start, [77](#)
 - swap, [79](#)
- BList.h
 - BLIST_H, [244](#)
- BList::Node, [81](#)
 - item, [81](#)
 - next, [81](#)
 - Node, [81](#)
 - prev, [81](#)
- BLIST_H
 - BList.h, [244](#)
- blr
 - Tms::TmsPhase, [220](#)
- blrPhase
 - Tms::CycleParamState, [170](#)
- blrWidth
 - Tms::CycleParamState, [170](#)
- BMember
 - BObject.h, [261](#)
- BMemberList
 - BObject.h, [261](#)
- BMutex, [82](#)
 - ~BMutex, [82](#)
 - BMutex, [82](#)
 - lock, [82](#)
 - omutex, [83](#)
 - operator=, [83](#)
 - tryLock, [82](#)
 - unlock, [82](#)
- BMutex.cpp
 - MDEBUG, [246](#)
- BMutex.h
 - BMUTEX_H, [247](#)
- BMUTEX_H
 - BMutex.h, [247](#)
- BNameValue, [84](#)
 - BNameValue, [84](#)
 - getName, [84](#)
 - getValue, [84](#)
 - oname, [84](#)
 - ovalue, [84](#)
- BNameValue.h

- BNAMEVALUE_H, 248
- TEMPLATE_NEW, 248
- BNAMEVALUE_H
 - BNameValue.h, 248
- BNameValueList, 85
 - find, 85
- Boap.cpp
 - APIVERSION_TEST, 250
 - boapPort, 250
 - DEBUG, 250
 - dprintf, 250
 - IS_BIG_ENDIAN, 250
 - roundSize, 250
 - swap16, 250
 - swap32, 250
 - swap64, 250
 - swap8, 250
- Boap.h
 - BoapFunc, 252
 - BoapMagic, 252
 - BoapPriority, 252
 - BoapPriorityHigh, 252
 - BoapPriorityLow, 252
 - BoapPriorityNormal, 252
 - BoapService, 252
 - BoapType, 252
 - BoapTypeRpc, 252
 - BoapTypeRpcReply, 252
 - BoapTypeSignal, 252
- BoapClientObject, 86
 - BoapClientObject, 87
 - checkApiVersion, 88
 - connectService, 87, 88
 - disconnectService, 87
 - getServiceName, 87
 - oapiVersion, 89
 - oconnected, 89
 - oclock, 89
 - omaxLength, 89
 - oname, 89
 - opriority, 89
 - oreconnect, 89
 - orx, 89
 - oservice, 89
 - otimeout, 89
 - otx, 89
 - performCall, 88, 89
 - performRecv, 88, 89
 - performSend, 88, 89
 - ping, 87
 - pingLocked, 88
 - setConnectionPriority, 87
 - setMaxLength, 88
 - setTimeout, 88
- BoapEntry
 - Boapns::BoapEntry, 90
- BoapFunc
 - Boap.h, 252
 - BoapSimple.h, 259
- BoapFuncEntry, 91
 - BoapFuncEntry, 91
 - ocmd, 91
 - ofunc, 91
- BoapMagic
 - Boap.h, 252
- Boapns, 25
 - addEntry, 26
 - apiVersion, 26
 - Boapns, 26
 - Boapns::Boapns, 92
 - delEntry, 26
 - getEntry, 26
 - getEntryList, 26
 - getNewName, 26
 - getVersion, 26
- Boapns::BoapEntry, 90
 - addressList, 90
 - BoapEntry, 90
 - hostName, 90
 - name, 90
 - port, 90
 - service, 90
- Boapns::Boapns, 92
 - addEntry, 92
 - Boapns, 92
 - delEntry, 92
 - getEntry, 92
 - getEntryList, 92
 - getNewName, 92
 - getVersion, 92
- BoapnsC.h
 - BOAPNSC_H, 254
- BOAPNSC_H
 - BoapnsC.h, 254
- BoapnsD.h
 - BOAPNSD_H, 256
- BOAPNSD_H
 - BoapnsD.h, 256
- BoapPacket, 93
 - ~BoapPacket, 96
 - BoapPacket, 96
 - copyWithSwap, 96
 - data, 96
 - getCmd, 96
 - nbytes, 96
 - odata, 96
 - onbytes, 96
 - opos, 96

- osize, 96
- peekHead, 96
- pop, 96
- popHead, 96
- push, 96
- pushHead, 96
- resize, 96
- setData, 96
- updateLen, 96
- BoapPacketHead, 98
 - cmd, 98
 - length, 98
 - reserved, 98
 - service, 98
 - type, 98
- boapPort
 - Boap.cpp, 250
- BoapPriority
 - Boap.h, 252
- BoapPriorityHigh
 - Boap.h, 252
- BoapPriorityLow
 - Boap.h, 252
- BoapPriorityNormal
 - Boap.h, 252
- BoapServer, 99
 - ~BoapServer, 101
 - addObject, 101, 102
 - BoapServer, 101
 - clientGone, 101
 - function, 101
 - getConnectionsNumber, 101
 - getEventSocket, 101, 102
 - getHostName, 101, 102
 - getSocket, 101, 102
 - init, 101
 - NOTHEADS, 100
 - oboapNs, 102
 - oboapns, 102
 - oclientGoneEvent, 102
 - oclients, 102
 - ohostName, 102
 - oisBoapns, 102
 - onet, 102
 - onetEvent, 102
 - onetEventAddress, 102
 - opoll, 102
 - orx, 102
 - oservices, 102
 - othreaded, 102
 - otx, 102
 - process, 101, 102
 - processEvent, 101, 102
 - run, 101, 102
 - sendEvent, 101, 102
 - THREADED, 100
- BoapServerConnection, 104
 - BoapServerConnection, 104
 - function, 104
 - getSocket, 104
 - oboapServer, 105
 - omaxLength, 105
 - orx, 105
 - osocket, 105
 - otx, 105
 - process, 104
 - setMaxLength, 104
- BoapService
 - Boap.h, 252
 - BoapSimple.h, 259
- BoapServiceEntry, 106
 - BoapServiceEntry, 106
 - oobject, 106
 - oservice, 106
- BoapServiceObject, 107
 - ~BoapServiceObject, 109
 - BoapServiceObject, 109
 - doConnectionPriority, 109
 - doPing, 109
 - name, 109
 - oapiVersion, 109
 - ofuncList, 109
 - oname, 109
 - oserver, 109
 - process, 109
 - processEvent, 109
 - sendEvent, 109
 - setName, 109
- BoapSignalObject, 111
 - BoapSignalObject, 111
 - orx, 111
 - otx, 111
 - performSend, 111
- BoapSimple.cc
 - DEBUG, 257
 - dprintf, 257
 - roundSize, 257
- BoapSimple.h
 - BoapFunc, 259
 - BoapService, 259
 - BoapType, 259
 - BoapTypeRpc, 259
 - BoapTypeRpcReply, 259
 - BoapTypeSignal, 259
 - Double, 259
 - Int16, 259
 - Int32, 259
 - Int8, 259

- UInt16, 259
- UInt32, 259
- UInt8, 259
- BoapType
 - Boap.h, 252
 - BoapSimple.h, 259
- BoapTypeRpc
 - Boap.h, 252
 - BoapSimple.h, 259
- BoapTypeRpcReply
 - Boap.h, 252
 - BoapSimple.h, 259
- BoapTypeSignal
 - Boap.h, 252
 - BoapSimple.h, 259
- BObject, 113
 - ~BObject, 114
 - addMember, 114
 - BObject, 114
 - createObj, 114
 - getBinary, 114
 - getMemberList, 114
 - getString, 114
 - getType, 114
 - otype, 114
 - printIt, 114
 - setBinary, 114
 - setString, 114
- BObject.cc
 - DEBUG, 260
- BObject.h
 - BMember, 261
 - BMemberList, 261
 - BOBJECT_H, 261
- BOBJECT_H
 - BObject.h, 261
- BPoll, 115
 - ~BPoll, 116
 - append, 116
 - BPoll, 116
 - clear, 116
 - delFd, 116
 - doPoll, 116
 - getPollFds, 116
 - getPollFdsNum, 116
 - nextFd, 116
 - ofds, 116
 - ofdsNext, 116
 - ofdsNum, 116
 - PollFd, 116
- BPoll.h
 - BPOLL_H, 264
- BPOLL_H
 - BPoll.h, 264
- BRefData, 118
 - ~BRefData, 119
 - addRef, 119
 - BRefData, 119
 - copy, 119
 - data, 119
 - deleteRef, 119
 - len, 119
 - oData, 119
 - oLen, 119
 - operator=, 119
 - oRefCount, 119
 - oSize, 119
 - refCount, 119
 - setLen, 119
- BRefData.cpp
 - CHUNK, 265
 - DEBUG, 265
- BRefData.h
 - BREFDATA_H, 266
- BREFDATA_H
 - BRefData.h, 266
- BRtc, 120
 - ~BRtc, 120
 - BRtc, 120
 - init, 120
 - ofd, 120
 - orate, 120
 - wait, 120
- BRtcThreaded, 122
 - ~BRtcThreaded, 122
 - BRtcThreaded, 122
 - function, 123
 - init, 122
 - ocond, 123
 - orate, 123
 - ortc, 123
 - wait, 122
- BRWLock, 124
 - ~BRWLock, 124
 - BRWLock, 124
 - olock, 125
 - operator=, 125
 - rdLock, 124
 - tryRdLock, 124
 - tryWrLock, 125
 - unlock, 125
 - wrLock, 125
- BRWLock.h
 - BRWLOCK_H, 270
- BRWLOCK_H
 - BRWLock.h, 270
- BSema, 126
 - ~BSema, 126

- BSema, 126
 - getValue, 127
 - operator=, 127
 - osema, 127
 - post, 126
 - timedWait, 127
 - tryWait, 127
 - wait, 126
- BSema.h
 - BSEMA_H, 272
- BSEMA_H
 - BSema.h, 272
- BSignal, 128
 - ~BSignal, 129
 - BSignal, 129
 - data, 129
 - id, 129
 - nextId, 129
 - NumChannels, 128
 - numRepeat, 129
 - numSamples, 129
 - operator=, 129
- BSignalList
 - SigGen.h, 288
- BSize
 - BTypes.h, 283
- BSocket, 130
 - ~BSocket, 133
 - accept, 133
 - bind, 133
 - BSocket, 133
 - close, 133
 - connect, 133
 - DGRAM, 131
 - getAddress, 133
 - getFd, 133
 - getMTU, 133
 - getSockOpt, 133
 - init, 133
 - listen, 133
 - NType, 131
 - osocket, 133
 - Priority, 131
 - PriorityHigh, 131
 - PriorityLow, 131
 - PriorityNormal, 131
 - recv, 133
 - recvFrom, 133
 - recvFromWithTimeout, 133
 - recvWithTimeout, 133
 - send, 133
 - sendTo, 133
 - setBroadcast, 133
 - setPriority, 133
 - setReuseAddress, 133
 - setSockOpt, 133
 - shutdown, 133
 - STREAM, 131
- BSocket.cpp
 - IP_MTU, 273
- BSocket.h
 - BSOCKET_H, 274
- BSOCKET_H
 - BSocket.h, 274
- BSocketAddress, 135
 - ~BSocketAddress, 136
 - BSocketAddress, 136
 - len, 136
 - oaddress, 136
 - olen, 136
 - operator const SockAddr *, 136
 - operator!=, 136
 - operator=, 136
 - operator==, 136
 - raw, 136
 - set, 136
 - SockAddr, 136
- BSocketAddressINET, 137
 - address, 138
 - getHostName, 138
 - getIpAddresses, 138
 - getIpAddressList, 138
 - getIpAddressListAll, 138
 - getString, 138
 - port, 138
 - set, 138
 - setPort, 138
 - SockAddrIP, 138
- BString, 140
 - ~BString, 143
 - add, 145
 - BString, 143
 - compare, 144
 - compareWild, 144
 - compareWildExpression, 145
 - convert, 143, 144
 - convertHex, 144
 - copy, 144
 - del, 145
 - field, 146
 - fields, 146
 - find, 146
 - findReverse, 146
 - getTokenList, 146
 - Init, 147
 - insert, 145
 - inString, 147
 - isSpace, 147

- len, 144
- operator const char *, 147
- operator!=, 147
- operator<, 147
- operator<=, 147
- operator>, 147
- operator>=, 147
- operator+, 147
- operator+=, 147
- operator=, 146
- operator==, 146, 147
- ostr, 147
- pad, 145
- printf, 145
- pullLine, 146
- pullSeparators, 146
- pullToken, 146
- pullWord, 146
- removeNL, 145
- removeSeparators, 146
- retDouble, 144
- retInt, 144
- retStr, 144
- retStrDup, 144
- strChanged, 144
- subString, 145
- toLower, 145
- toUpper, 145
- truncate, 145
- BString.cpp
 - DEBUG, 275
 - gmatch, 275
 - MINUS, 275
 - operator<<, 275
 - operator>>, 275
 - STRIP, 275
- BString.h
 - BSTRING_H, 276
 - operator<<, 276
 - operator>>, 276
- BSTRING_H
 - BString.h, 276
- BThread, 148
 - ~BThread, 149
 - BThread, 149
 - cancel, 149
 - function, 149
 - getThread, 149
 - opolicy, 149
 - opriority, 149
 - oreult, 149
 - orunning, 149
 - ostackSize, 149
 - othread, 149
 - result, 149
 - running, 149
 - setInitPriority, 149
 - setInitStackSize, 149
 - setPriority, 149
 - start, 149
 - startFunc, 149
 - waitForCompletion, 149
- BThread.h
 - BTHREAD_H, 278
- BTHREAD_H
 - BThread.h, 278
- BTimer, 150
 - ~BTimer, 151
 - add, 151
 - average, 151
 - BTimer, 151
 - clear, 151
 - getElapsedTime, 151
 - getTime, 151
 - oaverage, 152
 - oendTime, 152
 - oclock, 152
 - onum, 152
 - opeak, 152
 - ostartTime, 152
 - peak, 151
 - start, 151
 - stop, 151
- BTypes.h
 - BArrayDouble, 283
 - BArrayFloat, 283
 - BDouble, 283
 - BFloat, 283
 - BInt16, 283
 - BInt32, 283
 - BInt64, 283
 - BInt8, 283
 - BSize, 283
 - BTYPES_H, 283
 - BUInt, 283
 - BUInt16, 283
 - BUInt32, 283
 - BUInt64, 283
 - BUInt8, 283
 - Double, 283
 - Float, 283
 - Int16, 283
 - Int32, 283
 - Int64, 283
 - Int8, 283
 - UInt16, 283
 - UInt32, 283
 - UInt64, 283

- UInt8, 283
- BYPES_H
 - BTypes.h, 283
- BUInt
 - BTypes.h, 283
- BUInt16
 - BTypes.h, 283
- BUInt32
 - BTypes.h, 283
- BUInt64
 - BTypes.h, 283
- BUInt8
 - BTypes.h, 283
- bunch
 - Tms::CycleParamEdit, 166
- bunchMask
 - Tms::CycleInformationPeriod, 158
 - Tms::CycleParamState, 169
 - Tms::CycleTypeInfoInformationPeriod, 173
 - Tms::PuStateTable, 192
- bunchNumber
 - Tms::DataInfo, 177
- BUrl, 153
 - ~BUrl, 153
 - BUrl, 153
 - oinit, 154
 - ores, 154
 - readString, 153
 - writeData, 153
- BUrl.h
 - BURL_H, 285
- BURL_H
 - BUrl.h, 285
- calStart
 - Tms::TmsState, 226
- calStop
 - Tms::TmsState, 226
- cancel
 - BThread, 149
- CaptureClock
 - Tms, 29
- captureDiagnostics
 - Tms::PuControl, 187
 - Tms::TmsControl, 214
- channel
 - Tms::CycleParam, 160
 - Tms::CycleParamItem, 167
 - Tms::DataInfo, 177
- checkApiVersion
 - BoapClientObject, 88
- CHUNK
 - BRefData.cpp, 265
- clear
 - BCondBool, 37
 - BDir, 49
 - BEntryFile, 55
 - BEntryList, 58
 - BList, 78
 - BPoll, 116
 - BTimer, 151
 - Tms::CycleParamEdit, 165
 - Tms::CycleParamState, 169
- clientGone
 - BoapServer, 101
- ClkAdcDiv_1
 - Tms, 29
- ClkAdcDiv_10
 - Tms, 29
- ClkAdcDiv_100
 - Tms, 29
- ClkAdcDiv_1000
 - Tms, 29
- ClkAdcDiv_10000
 - Tms, 29
- ClkAdcDiv_100000
 - Tms, 29
- ClkAdcDiv_2
 - Tms, 29
- ClkAdcDiv_20
 - Tms, 29
- ClkAdcDiv_200
 - Tms, 29
- ClkAdcDiv_2000
 - Tms, 29
- ClkAdcDiv_20000
 - Tms, 29
- ClkAdcDiv_5
 - Tms, 29
- ClkAdcDiv_50
 - Tms, 29
- ClkAdcDiv_500
 - Tms, 29
- ClkAdcDiv_5000
 - Tms, 29
- ClkAdcDiv_50000
 - Tms, 29
- ClkFref
 - Tms, 29
- ClkMs
 - Tms, 29
- clock
 - Tms::TestCaptureInfo, 207
- close
 - BFile, 70
 - BSocket, 133
- cmd
 - BoapPacketHead, 98

- compare
 - BString, 144
- compareWild
 - BString, 144
- compareWildExpression
 - BString, 145
- config
 - SigGen, 194
 - SigGenBeam, 195
 - SigGenNoise, 197
 - SigGenPulse, 198
 - SigGenSine, 200
 - SigGenSquare, 201
- ConfigInfo
 - Tms::ConfigInfo, 155
- configure
 - Tms::PuControl, 186
 - Tms::TmsControl, 210
- connect
 - BSocket, 133
- connectService
 - BoapClientObject, 87, 88
- convert
 - BString, 143, 144
- convertHex
 - BString, 144
- copy
 - BError, 60
 - BRefData, 119
 - BString, 144
- copyWithSwap
 - BoapPacket, 96
- createObj
 - BObject, 114
- CycleInformation
 - Tms::CycleInformation, 156
- CycleInformationPeriod
 - Tms::CycleInformationPeriod, 158
- cycleNumber
 - Tms::CycleInformation, 156
 - Tms::DataInfo, 177
- CycleParam
 - Tms::CycleParam, 160
- CycleParamDb
 - Tms::CycleParamDb, 162
- CycleParamEdit
 - Tms::CycleParamEdit, 165
- CycleParamItem
 - Tms::CycleParamItem, 167
- CycleParamState
 - Tms::CycleParamState, 169
- CyclePeriod
 - Tms, 29
- cyclePeriod
 - Tms::CycleInformationPeriod, 158
 - Tms::CycleTypeInfoInformationPeriod, 172
 - Tms::DataInfo, 177
- CyclePeriodAll
 - Tms, 30
- CyclePeriodCalibration
 - Tms, 30
- CyclePeriodEvent0
 - Tms, 30
- CyclePeriodEvent1
 - Tms, 30
- CyclePeriodEvent2
 - Tms, 30
- CyclePeriodEvent3
 - Tms, 30
- CyclePeriodEvent4
 - Tms, 30
- CyclePeriodEvent5
 - Tms, 30
- CyclePeriodEvent6
 - Tms, 30
- CyclePeriodEvent7
 - Tms, 30
- CyclePeriodEvent8
 - Tms, 30
- CyclePeriodEvent9
 - Tms, 30
- cycleStartEvent
 - Tms::TmsEvent, 216
 - Tms::TmsEventServerList, 218
- cycleStop
 - Tms::TmsState, 226
- cycleStopEvent
 - Tms::TmsEvent, 217
 - Tms::TmsEventServerList, 218
- cycleType
 - Tms::CycleInformation, 156
 - Tms::CycleParam, 160
 - Tms::CycleParamItem, 167
 - Tms::CycleTypeInfoInformation, 171
 - Tms::Simulation, 203
- CycleTypeInfoInformation
 - Tms::CycleTypeInfoInformation, 171
- CycleTypeInfoInformationPeriod
 - Tms::CycleTypeInfoInformationPeriod, 172
- Data
 - Tms::Data, 174
- data
 - BBuffer, 35
 - BoapPacket, 96
 - BRefData, 119
 - BSignal, 129
 - Tms::Simulation, 203

- dataEvent
 - Tms::TmsEvent, 217
 - Tms::TmsEventServerList, 219
- DataFunction
 - Tms, 30
- DataFunctionMean
 - Tms, 30
- DataFunctionMean0
 - Tms, 30
- DataFunctionMean1
 - Tms, 30
- DataFunctionMeanAll
 - Tms, 30
- DataFunctionRaw
 - Tms, 30
- DataInfo
 - Tms::DataInfo, 177
- DataType
 - Tms, 30
- dataType
 - Tms::Data, 174
- DataTypeRaw
 - Tms, 30
- DataValue
 - Tms::DataValue, 179
- dataValues
 - Tms::Data, 175
- DEBUG
 - Boap.cpp, 250
 - BoapSimple.cc, 257
 - BObject.cc, 260
 - BRefData.cpp, 265
 - BString.cpp, 275
 - SigGen.cpp, 287
- decrement
 - BCondInt, 40
 - BCondValue, 43
 - BCondWrap, 46
- del
 - BEntryList, 58
 - BList, 78
 - BString, 145
 - Tms::TmsEventServerList, 218
- delay
 - Tms::TmsState, 226
- delControlInfo
 - Tms::TmsControl, 211
- delEntry
 - Boapns, 26
 - Boapns::Boapns, 92
- deleteCycleParams
 - Tms::CycleParamDb, 163
- deleteEntry
 - BEntryList, 57
- deleteFirst
 - BList, 79
- deleteLast
 - BList, 78
- deleteRef
 - BRefData, 119
- delFd
 - BPoll, 116
- deltaX
 - Tms::DataValue, 179
- deltaY
 - Tms::DataValue, 179
- DGRAM
 - BSocket, 131
- diff
 - BCondWrap, 47
- disableBlr
 - Tms::PupeConfig, 188
- disconnectService
 - BoapClientObject, 87
- doConnectionPriority
 - BoapServiceObject, 109
- doPing
 - BoapServiceObject, 109
- doPoll
 - BPoll, 116
- Double
 - BoapSimple.h, 259
 - BTypes.h, 283
- dprintf
 - Boap.cpp, 250
 - BoapSimple.cc, 257
 - SigGen.cpp, 287
- end
 - BList, 77
- endTime
 - Tms::CycleInformationPeriod, 158
- entryName
 - BDir, 49
- entryStat
 - BDir, 50
- entryStat64
 - BDir, 50
- ERROR
 - BError, 60
- error
 - BDir, 49
 - BFile, 70
 - Tms::PuStatus, 193
- ErrorComms
 - Tms, 30
- ErrorCommsTimeout
 - Tms, 30

- ErrorConfig
 - Tms, [30](#)
- ErrorCycleNumber
 - Tms, [31](#)
- ErrorDataFuture
 - Tms, [31](#)
- ErrorDataGone
 - Tms, [31](#)
- ErrorDataNotAvailable
 - Tms, [31](#)
- errorEvent
 - Tms::TmsEvent, [216](#)
 - Tms::TmsEventServerList, [218](#)
- ErrorFpga
 - Tms, [31](#)
- ErrorInit
 - Tms, [30](#)
- ErrorMC
 - Tms, [31](#)
- ErrorMisc
 - Tms, [30](#)
- ErrorNotImplemented
 - Tms, [30](#)
- ErrorOk
 - Tms, [30](#)
- ErrorParam
 - Tms, [30](#)
- Errors
 - Tms, [30](#)
- errors
 - Tms::Data, [175](#)
- ErrorStateTable
 - Tms, [31](#)
- ErrorTimeout
 - Tms, [31](#)
- ErrorWarning
 - Tms, [30](#)
- field
 - BString, [146](#)
- fields
 - BString, [146](#)
- find
 - BEntryList, [57](#)
 - BNameValueList, [85](#)
 - BString, [146](#)
- findReverse
 - BString, [146](#)
- findValue
 - BEntryList, [57](#)
- Float
 - BTypes.h, [283](#)
- frefPhaseDelay
 - Tms::CycleParam, [161](#)
- front
 - BList, [78](#)
- function
 - BoapServer, [101](#)
 - BoapServerConnection, [104](#)
 - BRtcThreaded, [123](#)
 - BThread, [149](#)
 - Tms::DataInfo, [177](#)
- gate
 - Tms::TmsPhase, [220](#)
- gatePhase
 - Tms::CycleParamState, [170](#)
- gateWidth
 - Tms::CycleParamState, [170](#)
- generate
 - SigGen, [194](#)
 - SigGenBeam, [195](#)
 - SigGenNoise, [197](#)
 - SigGenPulse, [198](#)
 - SigGenSine, [200](#)
 - SigGenSquare, [201](#)
- generateIntegrated
 - SigGenBeam, [195](#)
- generateState
 - Tms::CycleParamEdit, [166](#)
- get
 - BList, [78](#)
- getAddress
 - BSocket, [133](#)
- getBinary
 - BEvent, [62](#)
 - BEventError, [64](#)
 - BObject, [114](#)
- getCmd
 - BoapPacket, [96](#)
- getConfiguration
 - Tms::TmsControl, [210](#)
- getConnectionsNumber
 - BoapServer, [101](#)
- getControlInfo
 - Tms::TmsControl, [211](#)
- getControlList
 - Tms::TmsControl, [211](#)
- getCycleInfo
 - Tms::TmsProcess, [222](#)
- getCycleInformation
 - Tms::PuProcess, [190](#)
 - Tms::TmsProcess, [222](#)
- getCycleParams
 - Tms::CycleParamDb, [163](#)
- getCycleTypeInfoInformation
 - Tms::TmsProcess, [222](#)
- getCycleTypes

- Tms::CycleParamDb, 162
- getData
 - Tms::PuProcess, 190
 - Tms::TmsProcess, 223
- getDefaultPickupPositions
 - Tms::CycleParamEdit, 165
- getDefaultState
 - Tms::CycleParamEdit, 165
- getElapsedTime
 - BTimer, 151
- getEntry
 - Boapns, 26
 - Boapns::Boapns, 92
- getEntryList
 - Boapns, 26
 - Boapns::Boapns, 92
- getErrorNo
 - BError, 60
- getEvent
 - BEventInt, 65
 - BEventPipe, 67
- getEventSocket
 - BoapServer, 101, 102
- getFd
 - BEventInt, 65
 - BFile, 71
 - BSocket, 133
- getFileNames
 - Tms::CycleParamDb, 162
- getHostName
 - BoapServer, 101, 102
 - BSocketAddressINET, 138
- getIpAddresses
 - BSocketAddressINET, 138
- getIpAddressList
 - BSocketAddressINET, 138
- getIpAddressListAll
 - BSocketAddressINET, 138
- getMasterPuChannel
 - Tms::PuControl, 186
- getMemberList
 - BObject, 114
- getMTU
 - BSocket, 133
- getName
 - BEntry, 52
 - BNameValue, 84
- getNewName
 - Boapns, 26
 - Boapns::Boapns, 92
- getPollFds
 - BPoll, 116
- getPollFdsNum
 - BPoll, 116
- getPuChannel
 - Tms::TmsControl, 213
- getPupeConfig
 - Tms::PuControl, 187
 - Tms::TmsControl, 214
- getReceiveFd
 - BEventPipe, 67
- getServiceName
 - BoapClientObject, 87
- getSimulation
 - Tms::TmsControl, 213
- getSocket
 - BoapServer, 101, 102
 - BoapServerConnection, 104
- getSockOpt
 - BSocket, 133
- getStates
 - Tms::CycleParamEdit, 165
- getStatistics
 - Tms::PuControl, 186
 - Tms::TmsControl, 212
- getStatus
 - Tms::PuControl, 186
 - Tms::PuProcess, 190
 - Tms::TmsControl, 212
- getString
 - BEntryList, 57
 - BError, 60
 - BObject, 114
 - BSocketAddressINET, 138
 - Tms::CycleParamEdit, 165
 - Tms::CycleParamState, 169
- getThread
 - BThread, 149
- getTime
 - BTimer, 151
- getTokenList
 - BString, 146
- getType
 - BEvent, 62
 - BObject, 114
- getValue
 - BEntry, 52
 - BNameValue, 84
 - BSema, 127
- getVersion
 - Boapns, 26
 - Boapns::Boapns, 92
 - Tms::PuControl, 185
 - Tms::PuProcess, 190
 - Tms::TmsControl, 210
 - Tms::TmsProcess, 222
- gmatch
 - BString.cpp, 275

- goTo
 - BList, 77
- harmonic
 - Tms::CycleInformationPeriod, 158
 - Tms::CycleTypeInfoInformationPeriod, 172
 - Tms::PuStateTable, 192
- hchange
 - Tms::TmsState, 226
- hostName
 - Boapns::BoapEntry, 90
- id
 - BSignal, 129
- increment
 - BCondInt, 40
 - BCondValue, 43
 - BCondWrap, 46
- info
 - Tms::CycleParam, 160
 - Tms::CycleTypeInfoInformation, 171
- Init
 - BString, 147
- init
 - BoapServer, 101
 - BRtc, 120
 - BRtcThreaded, 122
 - BSocket, 133
 - Tms::PuControl, 185
 - Tms::TmsControl, 210
- injection
 - Tms::TmsState, 226
- insert
 - BEntryList, 57
 - BList, 78
 - BString, 145
- insertAfter
 - BList, 78
- inString
 - BString, 147
- Int16
 - BoapSimple.h, 259
 - BTypes.h, 283
- Int32
 - BoapSimple.h, 259
 - BTypes.h, 283
- Int64
 - BTypes.h, 283
- Int8
 - BoapSimple.h, 259
 - BTypes.h, 283
- internalTimingMask
 - Tms::PupeConfig, 188
- IP_MTU
 - BSocket.cpp, 273
- IS_BIG_ENDIAN
 - Boap.cpp, 250
- isEnd
 - BList, 77
- isSet
 - BEntryList, 57
- isSpace
 - BString, 147
- item
 - BList::Node, 81
- len
 - BRefData, 119
 - BSocketAddress, 136
 - BString, 144
- length
 - BFile, 71
 - BoapPacketHead, 98
- line
 - BEntry, 52
- listen
 - BSocket, 133
- lo1
 - Tms::TmsPhase, 220
- lo2
 - Tms::TmsPhase, 220
- lock
 - BMutex, 82
- loHarmonic
 - Tms::CycleParamState, 169
- loPhase
 - Tms::CycleParamState, 169
- main
 - test1.cpp, 289
- MDEBUG
 - BMutex.cpp, 246
- mean1Mask
 - Tms::CycleParamState, 169
- mean2Mask
 - Tms::CycleParamState, 169
- meanFilter1
 - Tms::TmsPhase, 220
- meanFilter2
 - Tms::TmsPhase, 220
- MINUS
 - BString.cpp, 275
- moduleNum
 - Tms::PuChannel, 182
- name
 - Boapns::BoapEntry, 90
 - BoapServiceObject, 109

- Tms::NameValue, [181](#)
- NameValue
 - Tms::NameValue, [181](#)
- nbytes
 - BoapPacket, [96](#)
- next
 - BList, [77](#)
 - BList::Node, [81](#)
- nextFd
 - BPoll, [116](#)
- nextId
 - BSignal, [129](#)
- Node
 - BList::Node, [81](#)
- nodeCreate
 - BList, [80](#)
- nodeGet
 - BList, [80](#)
- NONE
 - BError, [60](#)
- NOTHREADS
 - BoapServer, [100](#)
- NType
 - BSocket, [131](#)
- number
 - BList, [77](#)
- numBunches
 - Tms::CycleInformationPeriod, [158](#)
 - Tms::CycleTypeInfoInformationPeriod, [172](#)
 - Tms::Data, [175](#)
 - Tms::PuStateTable, [192](#)
- NumChannels
 - BSignal, [128](#)
- numChannels
 - Tms::Data, [175](#)
- numRepeat
 - BSignal, [129](#)
- numSamples
 - BSignal, [129](#)
- numValues
 - Tms::CycleInformationPeriod, [158](#)
 - Tms::Data, [174](#)
 - Tms::DataInfo, [177](#)
- oaddress
 - BSocketAddress, [136](#)
- oamplitude
 - SigGenBeam, [196](#)
 - SigGenNoise, [197](#)
 - SigGenPulse, [199](#)
 - SigGenSine, [200](#)
 - SigGenSquare, [201](#)
- oapiVersion
 - BoapClientObject, [89](#)
- BoapServiceObject, [109](#)
- oaverage
 - BTimer, [152](#)
- obaseDir
 - Tms::CycleParamDb, [163](#)
- oblr
 - SigGenBeam, [196](#)
- oboapNs
 - BoapServer, [102](#)
- oboapns
 - BoapServer, [102](#)
- oboapServer
 - BoapServerConnection, [105](#)
- obunchSet
 - SigGenBeam, [196](#)
- oclientGoneEvent
 - BoapServer, [102](#)
- oclients
 - BoapServer, [102](#)
- ocmd
 - BoapFuncEntry, [91](#)
- ocomments
 - BEntryFile, [55](#)
- ocond
 - BCond, [36](#)
 - BCondBool, [38](#)
 - BCondInt, [41](#)
 - BCondValue, [44](#)
 - BCondWrap, [47](#)
 - BRtcThreaded, [123](#)
- oconnected
 - BoapClientObject, [89](#)
- oData
 - BRefData, [119](#)
- odata
 - BBuffer, [35](#)
 - BoapPacket, [96](#)
- odatasize
 - BBuffer, [35](#)
- odirname
 - BDir, [50](#)
- oendTime
 - BTimer, [152](#)
- oerrNo
 - BError, [61](#)
- oerror
 - BDir, [50](#)
 - BFile, [72](#)
- oerrStr
 - BError, [61](#)
- oeventServers
 - Tms::TmsEventServerList, [219](#)
- ofd
 - BRtc, [120](#)

- ofds
 - BEventInt, 66
 - BEventPipe, 68
 - BPoll, 116
- ofdsNext
 - BPoll, 116
- ofdsNum
 - BPoll, 116
- ofile
 - BFile, 72
- ofileName
 - BFile, 72
- ofilename
 - BEntryFile, 55
- ofref
 - SigGenBeam, 196
- ofreq
 - SigGenPulse, 199
 - SigGenSine, 200
 - SigGenSquare, 201
- ofunc
 - BoapFuncEntry, 91
- ofuncList
 - BoapServiceObject, 109
- oharmonic
 - SigGenBeam, 196
- ohostName
 - BoapServer, 102
- oi
 - BIter, 73
- oinit
 - BUrl, 154
- oisBoapns
 - BoapServer, 102
- olastPos
 - BEntryList, 58
- oLen
 - BRefData, 119
- olen
 - BSocketAddress, 136
- olength
 - BList, 80
- olock
 - BoapClientObject, 89
 - BRWLock, 125
 - BTimer, 152
 - Tms::TmsEventServerList, 219
- omaxLength
 - BoapClientObject, 89
 - BoapServerConnection, 105
- omode
 - BFile, 72
- omutex
 - BCond, 36
 - BCondBool, 38
 - BCondInt, 41
 - BCondValue, 44
 - BCondWrap, 47
 - BMutex, 83
- oname
 - BEntry, 53
 - BNameValue, 84
 - BoapClientObject, 89
 - BoapServiceObject, 109
- onbytes
 - BoapPacket, 96
- onet
 - BoapServer, 102
- onetEvent
 - BoapServer, 102
- onetEventAddress
 - BoapServer, 102
- onodes
 - BList, 80
- onum
 - BTimer, 152
- object
 - BoapServiceEntry, 106
- ooffset
 - SigGenSquare, 201
- oonTime
 - SigGenPulse, 199
- opeak
 - BTimer, 152
- open
 - BDir, 49
 - BEntryFile, 55
 - BFile, 70
- operator const char *
 - BString, 147
- operator const SockAddr *
 - BSocketAddress, 136
- operator int
 - BError, 60
- operator void *
 - BIter, 73
- operator!=
 - BSocketAddress, 136
 - BString, 147
- operator<
 - BString, 147
- operator<<
 - BString.cpp, 275
 - BString.h, 276
- operator<=
 - BString, 147
- operator>
 - BString, 147

- operator>>
 - BString.cpp, 275
 - BString.h, 276
- operator>=
 - BString, 147
- operator+
 - BList, 80
 - BString, 147
- operator++
 - BCondInt, 41
 - BCondValue, 43
 - BCondWrap, 47
- operator+=
 - BCondValue, 43
 - BCondWrap, 46
 - BString, 147
- operator-
 - BCondInt, 41
 - BCondValue, 44
 - BCondWrap, 47
- operator-=
 - BCondValue, 43
 - BCondWrap, 46
- operator=
 - BFile, 71
 - BList, 79
 - BMutex, 83
 - BRefData, 119
 - BRWLock, 125
 - BSema, 127
 - BSignal, 129
 - BSocketAddress, 136
 - BString, 146
- operator==
 - BIter, 73
 - BSocketAddress, 136
 - BString, 146, 147
- opolicy
 - BThread, 149
- opoll
 - BoapServer, 102
- opos
 - BoapPacket, 96
- opriority
 - BoapClientObject, 89
 - BThread, 149
- orate
 - BRtc, 120
 - BRtcThreaded, 123
- orbitNumber
 - Tms::DataInfo, 177
- oreconnect
 - BoapClientObject, 89
- oreduce
 - SigGenBeam, 196
- oRefCount
 - BRefData, 119
- ores
 - BUrl, 154
- oresult
 - BThread, 149
- ortc
 - BRtcThreaded, 123
- orunning
 - BThread, 149
- orx
 - BoapClientObject, 89
 - BoapServer, 102
 - BoapServerConnection, 105
 - BoapSignalObject, 111
- osampleRate
 - SigGen, 194
- osema
 - BSema, 127
- oserver
 - BoapServiceObject, 109
- oservice
 - BoapClientObject, 89
 - BoapServiceEntry, 106
- oservices
 - BoapServer, 102
- oSize
 - BRefData, 119
- osize
 - BBuffer, 35
 - BoapPacket, 96
- osocket
 - BoapServerConnection, 105
 - BSocket, 133
- osort
 - BDir, 50
- ostackSize
 - BThread, 149
- ostartTime
 - BTimer, 152
 - SigGenPulse, 199
- ostr
 - BString, 147
- othread
 - BThread, 149
- othreaded
 - BoapServer, 102
- otimeout
 - BoapClientObject, 89
- otx
 - BoapClientObject, 89
 - BoapServer, 102
 - BoapServerConnection, 105

- BoapSignalObject, 111
- otype
 - BEvent, 63
 - BObject, 114
- ovalue
 - BCondBool, 38
 - BCondInt, 41
 - BCondValue, 44
 - BCondWrap, 47
 - BEntry, 53
 - BNameValue, 84
- overview.dox, 286
- owild
 - BDir, 50
- ox
 - SigGen, 194
- pad
 - BString, 145
- peak
 - BTimer, 151
- peekHead
 - BoapPacket, 96
- performCall
 - BoapClientObject, 88, 89
- performRecv
 - BoapClientObject, 88, 89
- performSend
 - BoapClientObject, 88, 89
 - BoapSignalObject, 111
- period
 - Tms::CycleParamState, 169
 - Tms::PuStateTable, 191
- periods
 - Tms::CycleInformation, 156
 - Tms::CycleTypeInfoInformation, 171
- phaseTable
 - Tms::PuStateTable, 192
- ping
 - BoapClientObject, 87
- pingLocked
 - BoapClientObject, 88
- pllCycleStartFrequency
 - Tms::CycleParam, 160
- pllDdsMaximum
 - Tms::CycleParam, 161
- pllDdsMinimum
 - Tms::CycleParam, 161
- pllFeedbackSelect
 - Tms::TmsState, 226
- pllFrefGain
 - Tms::CycleParam, 161
- pllGain
 - Tms::CycleParam, 161
- pllInitialFrequency
 - Tms::CycleParam, 160
- pllInitialFrequencyDelay
 - Tms::CycleParam, 161
- pllLO1FromAddress
 - Tms::TmsState, 226
- pllLO2FromAddress
 - Tms::TmsState, 226
- pllReference1
 - Tms::TmsState, 226
- pllReference2
 - Tms::TmsState, 226
- PollFd
 - BPoll, 116
- pop
 - BList, 79
 - BoapPacket, 96
- popHead
 - BoapPacket, 96
- port
 - Boapns::BoapEntry, 90
 - BSocketAddressINET, 138
- position
 - BList, 77
- post
 - BSema, 126
- postTriggerDelay
 - Tms::TestCaptureInfo, 207
- prev
 - BList, 77
 - BList::Node, 81
- print
 - BEntry, 52
 - BEntryList, 57
- printCycleParams
 - test1.cpp, 289
- printf
 - BFile, 71
 - BString, 145
- println
 - BObject, 114
- Priority
 - BSocket, 131
 - Tms, 31
- PriorityHigh
 - BSocket, 131
 - Tms, 31
- PriorityLow
 - BSocket, 131
 - Tms, 31
- PriorityNormal
 - BSocket, 131
 - Tms, 31
- process

- BoapServer, [101, 102](#)
- BoapServerConnection, [104](#)
- BoapServiceObject, [109](#)
- processEvent
 - BoapServer, [101, 102](#)
 - BoapServiceObject, [109](#)
- PuChannel
 - Tms::PuChannel, [182](#)
- PuControl
 - Tms::PuControl, [185](#)
- pullLine
 - BString, [146](#)
- pullSeparators
 - BString, [146](#)
- pullToken
 - BString, [146](#)
- pullWord
 - BString, [146](#)
- pupeChan
 - Tms::PuChannel, [182](#)
- PupeConfig
 - Tms::PupeConfig, [188](#)
- pupeNum
 - Tms::PuChannel, [182](#)
- PuProcess
 - Tms::PuProcess, [190](#)
- puReferences
 - Tms::ConfigInfo, [155](#)
- puServerStarted
 - Tms::TmsControl, [215](#)
- push
 - BList, [79](#)
 - BoapPacket, [96](#)
- pushHead
 - BoapPacket, [96](#)
- PuStateTable
 - Tms::PuStateTable, [191](#)
- PuStatus
 - Tms::PuStatus, [193](#)
- queueAdd
 - BList, [79](#)
- queueGet
 - BList, [79](#)
- raw
 - BSocketAddress, [136](#)
- rdLock
 - BRWLock, [124](#)
- read
 - BDir, [49](#)
 - BEntryFile, [55](#)
 - BFile, [71](#)
- readCycleParams
 - Tms::CycleParamDb, [163](#)
- readFromFile
 - Tms::CycleParamEdit, [165](#)
- readString
 - BFile, [71](#)
 - BUrl, [153](#)
- rear
 - BList, [78](#)
- recv
 - BSocket, [133](#)
- recvFrom
 - BSocket, [133](#)
- recvFromWithTimeout
 - BSocket, [133](#)
- recvWithTimeout
 - BSocket, [133](#)
- refCount
 - BRefData, [119](#)
- removeNL
 - BString, [145](#)
- removeSeparators
 - BString, [146](#)
- requestData
 - Tms::PuProcess, [190](#)
 - Tms::TmsProcess, [223](#)
- reserved
 - BoapPacketHead, [98](#)
- resize
 - BoapPacket, [96](#)
- result
 - BThread, [149](#)
- retDouble
 - BString, [144](#)
- retInt
 - BString, [144](#)
- retStr
 - BString, [144](#)
- retStrDup
 - BString, [144](#)
- roundSize
 - Boap.cpp, [250](#)
 - BoapSimple.cc, [257](#)
- run
 - BoapServer, [101, 102](#)
- running
 - BThread, [149](#)
 - Tms::PuStatus, [193](#)
- Sample
 - SigGen.h, [288](#)
- seek
 - BFile, [71](#)
- send
 - BSocket, [133](#)

- sendEvent
 - BEventInt, 65
 - BEventPipe, 67
 - BoapServer, 101, 102
 - BoapServiceObject, 109
- sendTo
 - BSocket, 133
- service
 - Boapns::BoapEntry, 90
 - BoapPacketHead, 98
- set
 - BCondBool, 37
 - BError, 60
 - BSocketAddress, 136
 - BSocketAddressINET, 138
- setBinary
 - BEvent, 62
 - BEventError, 64
 - BObject, 114
- setBroadCast
 - BSocket, 133
- setConnectionPriority
 - BoapClientObject, 87
- setControlInfo
 - Tms::PuControl, 186
 - Tms::TmsControl, 211
- setCycleParams
 - Tms::CycleParamDb, 163
- setData
 - BBuffer, 34
 - BoapPacket, 96
- setError
 - BError, 60
- setInitPriority
 - BThread, 149
- setInitStackSize
 - BThread, 149
- setLen
 - BRefData, 119
- setLine
 - BEntry, 52
- setMaxLength
 - BoapClientObject, 88
 - BoapServerConnection, 104
- setName
 - BEntry, 52
 - BoapServiceObject, 109
- setNextCycle
 - Tms::PuControl, 186
 - Tms::Simulation, 203
 - Tms::TmsControl, 212
- setPort
 - BSocketAddressINET, 138
- setPriority
 - BSocket, 133
 - BThread, 149
- setProcessPriority
 - Tms::PuControl, 186
 - Tms::TmsControl, 210
- setPupeConfig
 - Tms::PuControl, 187
 - Tms::TmsControl, 214
- setReuseAddress
 - BSocket, 133
- setSimulation
 - Tms::TmsControl, 213
- setSize
 - BBuffer, 34
- setSockOpt
 - BSocket, 133
- setSort
 - BDir, 49
- setStates
 - Tms::CycleParamEdit, 165
- setString
 - BObject, 114
 - Tms::CycleParamEdit, 165
 - Tms::CycleParamState, 169
- setTestData
 - Tms::PuControl, 187
 - Tms::TmsControl, 214
- setTestMode
 - Tms::PuControl, 186
 - Tms::TmsControl, 213
- setTimeout
 - BoapClientObject, 88
- setTimingSignals
 - Tms::PuControl, 187
 - Tms::TmsControl, 213
- settings
 - Tms::CycleParam, 161
- setValue
 - BCondInt, 40
 - BCondValue, 43
 - BCondWrap, 46
 - BEntry, 52
 - BEntryList, 57
- setValueRaw
 - BEntryList, 57
- setVBuf
 - BFile, 71
- setWild
 - BDir, 49
- shutdown
 - BSocket, 133
- SigGen, 194
 - ~SigGen, 194
 - config, 194

- generate, 194
- osampleRate, 194
- ox, 194
- SigGen, 194
- SigGen.cpp, 287
 - DEBUG, 287
 - dprintf, 287
- SigGen.h, 288
 - BSignalList, 288
 - Sample, 288
 - SigGen_h, 288
- SigGen_h
 - SigGen.h, 288
- SigGenBeam, 195
 - ~SigGenBeam, 195
 - config, 195
 - generate, 195
 - generateIntegrated, 195
 - oamplitude, 196
 - obl, 196
 - obunchSet, 196
 - ofref, 196
 - oharmonic, 196
 - oreduce, 196
 - SigGenBeam, 195
- SigGenNoise, 197
 - ~SigGenNoise, 197
 - config, 197
 - generate, 197
 - oamplitude, 197
 - SigGenNoise, 197
- SigGenPulse, 198
 - ~SigGenPulse, 198
 - config, 198
 - generate, 198
 - oamplitude, 199
 - ofreq, 199
 - oonTime, 199
 - ostartTime, 199
 - SigGenPulse, 198
- SigGenSine, 200
 - ~SigGenSine, 200
 - config, 200
 - generate, 200
 - oamplitude, 200
 - ofreq, 200
 - SigGenSine, 200
- SigGenSquare, 201
 - ~SigGenSquare, 201
 - config, 201
 - generate, 201
 - oamplitude, 201
 - ofreq, 201
 - offset, 201
 - SigGenSquare, 201
- sigma
 - Tms::DataValue, 179
- signal
 - BCond, 36
- Simulation
 - Tms::Simulation, 203
- SIZE
 - BBuffer.cpp, 228
- size
 - BBuffer, 35
- SockAddr
 - BSocketAddress, 136
- SockAddrIP
 - BSocketAddressINET, 138
- sort
 - BList, 79
- SortFunc
 - BList, 76
- source
 - Tms::TestCaptureInfo, 207
- spare
 - Tms::TmsPhase, 220
- spare0
 - Tms::TmsState, 226
- start
 - BList, 77
 - BThread, 149
 - BTimer, 151
- startFunc
 - BThread, 149
- startTime
 - Tms::CycleInformationPeriod, 158
 - Tms::DataInfo, 177
 - Tms::TestCaptureInfo, 207
- state
 - Tms::PuStateTable, 191
- stateTable
 - Tms::CycleParam, 161
- std::vector, 205
- stop
 - BTimer, 151
- STRBUF
 - BFile.cpp, 242
- strChanged
 - BString, 144
- STREAM
 - BSocket, 131
- STRIP
 - BString.cpp, 275
- subString
 - BString, 145
- swap
 - BList, 79

- swap16
 - Boap.cpp, 250
- swap32
 - Boap.cpp, 250
- swap64
 - Boap.cpp, 250
- swap8
 - Boap.cpp, 250
- TEMPLATE_NEW
 - BNameValue.h, 248
- test
 - Tms::PuControl, 186
 - Tms::TmsControl, 212
- test1.cpp, 289
 - main, 289
 - printCycleParams, 289
- TestCaptureInfo
 - Tms::TestCaptureInfo, 207
- TestOutput
 - Tms, 31
- TestOutputFrefLocal
 - Tms, 31
- TestOutputPiIL1
 - Tms, 31
- TestOutputPiIL2
 - Tms, 31
- THREADED
 - BoapServer, 100
- time
 - Tms::DataValue, 179
- timedWait
 - BCond, 36
 - BCondBool, 38
 - BCondInt, 40
 - BSema, 127
- timing
 - Tms::Simulation, 203
- TimingSig
 - Tms, 31
- TimingSigCalStart
 - Tms, 31
- TimingSigCalStop
 - Tms, 31
- TimingSigClock
 - Tms, 31
- TimingSigCycleStart
 - Tms, 31
- TimingSigCycleStop
 - Tms, 31
- TimingSigFRef
 - Tms, 31
- TimingSigHChange
 - Tms, 31
- TimingSigInjection
 - Tms, 31
- Tms, 27
 - apiVersion, 32
 - CaptureClock, 29
 - ClkAdcDiv_1, 29
 - ClkAdcDiv_10, 29
 - ClkAdcDiv_100, 29
 - ClkAdcDiv_1000, 29
 - ClkAdcDiv_10000, 29
 - ClkAdcDiv_100000, 29
 - ClkAdcDiv_2, 29
 - ClkAdcDiv_20, 29
 - ClkAdcDiv_200, 29
 - ClkAdcDiv_2000, 29
 - ClkAdcDiv_20000, 29
 - ClkAdcDiv_5, 29
 - ClkAdcDiv_50, 29
 - ClkAdcDiv_500, 29
 - ClkAdcDiv_5000, 29
 - ClkAdcDiv_50000, 29
 - ClkFref, 29
 - ClkMs, 29
 - CyclePeriod, 29
 - CyclePeriodAll, 30
 - CyclePeriodCalibration, 30
 - CyclePeriodEvent0, 30
 - CyclePeriodEvent1, 30
 - CyclePeriodEvent2, 30
 - CyclePeriodEvent3, 30
 - CyclePeriodEvent4, 30
 - CyclePeriodEvent5, 30
 - CyclePeriodEvent6, 30
 - CyclePeriodEvent7, 30
 - CyclePeriodEvent8, 30
 - CyclePeriodEvent9, 30
 - DataFunction, 30
 - DataFunctionMean, 30
 - DataFunctionMean0, 30
 - DataFunctionMean1, 30
 - DataFunctionMeanAll, 30
 - DataFunctionRaw, 30
 - DataType, 30
 - DataTypeRaw, 30
 - ErrorComms, 30
 - ErrorCommsTimeout, 30
 - ErrorConfig, 30
 - ErrorCycleNumber, 31
 - ErrorDataFuture, 31
 - ErrorDataGone, 31
 - ErrorDataNotAvailable, 31
 - ErrorFpga, 31
 - ErrorInit, 30
 - ErrorMC, 31

- ErrorMisc, 30
- ErrorNotImplemented, 30
- ErrorOk, 30
- ErrorParam, 30
- Errors, 30
- ErrorStateTable, 31
- ErrorTimeout, 31
- ErrorWarning, 30
- Priority, 31
- PriorityHigh, 31
- PriorityLow, 31
- PriorityNormal, 31
- TestOutput, 31
- TestOutputFrefLocal, 31
- TestOutputPllL1, 31
- TestOutputPllL2, 31
- TimingSig, 31
- TimingSigCalStart, 31
- TimingSigCalStop, 31
- TimingSigClock, 31
- TimingSigCycleStart, 31
- TimingSigCycleStop, 31
- TimingSigFRef, 31
- TimingSigHChange, 31
- TimingSigInjection, 31
- tmsNumPickups, 32
- tmsPhaseTableSize, 32
- Tms::ConfigInfo, 155
 - ConfigInfo, 155
 - puReferences, 155
- Tms::CycleInformation, 156
 - CycleInformation, 156
 - cycleNumber, 156
 - cycleType, 156
 - periods, 156
- Tms::CycleInformationPeriod, 157
 - bunchMask, 158
 - CycleInformationPeriod, 158
 - cyclePeriod, 158
 - endTime, 158
 - harmonic, 158
 - numBunches, 158
 - numValues, 158
 - startTime, 158
- Tms::CycleParam, 159
 - channel, 160
 - CycleParam, 160
 - cycleType, 160
 - frefPhaseDelay, 161
 - info, 160
 - pllCycleStartFrequency, 160
 - pllDdsMaximum, 161
 - pllDdsMinimum, 161
 - pllFrefGain, 161
 - pllGain, 161
 - pllInitialFrequency, 160
 - pllInitialFrequencyDelay, 161
 - settings, 161
 - stateTable, 161
- Tms::CycleParamDb, 162
 - CycleParamDb, 162
 - deleteCycleParams, 163
 - getCycleParams, 163
 - getCycleTypes, 162
 - getFileNames, 162
 - obaseDir, 163
 - readCycleParams, 163
 - setCycleParams, 163
 - writeCycleParams, 163
- Tms::CycleParamEdit, 164
 - bunch, 166
 - clear, 165
 - CycleParamEdit, 165
 - generateState, 166
 - getDefaultPickupPositions, 165
 - getDefaultState, 165
 - getStates, 165
 - getString, 165
 - readFromFile, 165
 - setStates, 165
 - setString, 165
 - value, 166
 - writeToFile, 165
- Tms::CycleParamItem, 167
 - channel, 167
 - CycleParamItem, 167
 - cycleType, 167
- Tms::CycleParamState, 168
 - acquireData, 170
 - blrPhase, 170
 - blrWidth, 170
 - bunchMask, 169
 - clear, 169
 - CycleParamState, 169
 - gatePhase, 170
 - gateWidth, 170
 - getString, 169
 - loHarmonic, 169
 - loPhase, 169
 - mean1Mask, 169
 - mean2Mask, 169
 - period, 169
 - setString, 169
 - useLoFref, 170
- Tms::CycleTypeInformation, 171
 - cycleType, 171
 - CycleTypeInformation, 171
 - info, 171

- periods, 171
- Tms::CycleTypeInfoPeriod, 172
 - bunchMask, 173
 - cyclePeriod, 172
 - CycleTypeInfoPeriod, 172
 - harmonic, 172
 - numBunches, 172
- Tms::Data, 174
 - Data, 174
 - dataType, 174
 - dataValues, 175
 - errors, 175
 - numBunches, 175
 - numChannels, 175
 - numValues, 174
- Tms::DataInfo, 176
 - argument, 177
 - beyondPeriod, 177
 - bunchNumber, 177
 - channel, 177
 - cycleNumber, 177
 - cyclePeriod, 177
 - DataInfo, 177
 - function, 177
 - numValues, 177
 - orbitNumber, 177
 - startTime, 177
- Tms::DataValue, 179
 - DataValue, 179
 - deltaX, 179
 - deltaY, 179
 - sigma, 179
 - time, 179
- Tms::NameValue, 181
 - name, 181
 - NameValue, 181
 - value, 181
- Tms::PuChannel, 182
 - moduleNum, 182
 - PuChannel, 182
 - pupeChan, 182
 - pupeNum, 182
- Tms::PuControl, 184
 - captureDiagnostics, 187
 - configure, 186
 - getMasterPuChannel, 186
 - getPupeConfig, 187
 - getStatistics, 186
 - getStatus, 186
 - getVersion, 185
 - init, 185
 - PuControl, 185
 - setControlInfo, 186
 - setNextCycle, 186
 - setProcessPriority, 186
 - setPupeConfig, 187
 - setTestData, 187
 - setTestMode, 186
 - setTimingSignals, 187
 - test, 186
- Tms::PupeConfig, 188
 - adcSysclkSync, 188
 - disableBlr, 188
 - internalTimingMask, 188
 - PupeConfig, 188
- Tms::PuProcess, 189
 - addEventServer, 190
 - getCycleInformation, 190
 - getData, 190
 - getStatus, 190
 - getVersion, 190
 - PuProcess, 190
 - requestData, 190
- Tms::PuStateTable, 191
 - bunchMask, 192
 - harmonic, 192
 - numBunches, 192
 - period, 191
 - phaseTable, 192
 - PuStateTable, 191
 - state, 191
- Tms::PuStatus, 193
 - error, 193
 - PuStatus, 193
 - running, 193
- Tms::Simulation, 203
 - cycleType, 203
 - data, 203
 - setNextCycle, 203
 - Simulation, 203
 - timing, 203
- Tms::TestCaptureInfo, 206
 - clock, 207
 - postTriggerDelay, 207
 - source, 207
 - startTime, 207
 - TestCaptureInfo, 207
 - triggerAnd, 207
 - triggerMask, 207
 - triggerSourceData, 207
 - triggerStore, 207
- Tms::TmsControl, 208
 - captureDiagnostics, 214
 - configure, 210
 - delControlInfo, 211
 - getConfiguration, 210
 - getControlInfo, 211
 - getControlList, 211

- getPuChannel, 213
- getPupeConfig, 214
- getSimulation, 213
- getStatistics, 212
- getStatus, 212
- getVersion, 210
- init, 210
- puServerStarted, 215
- setControlInfo, 211
- setNextCycle, 212
- setProcessPriority, 210
- setPupeConfig, 214
- setSimulation, 213
- setTestData, 214
- setTestMode, 213
- setTimingSignals, 213
- test, 212
- TmsControl, 210
- Tms::TmsEvent, 216
 - cycleStartEvent, 216
 - cycleStopEvent, 217
 - dataEvent, 217
 - errorEvent, 216
 - TmsEvent, 216
- Tms::TmsEventServerList, 218
 - ~TmsEventServerList, 218
 - append, 218
 - cycleStartEvent, 218
 - cycleStopEvent, 218
 - dataEvent, 219
 - del, 218
 - errorEvent, 218
 - oeventServers, 219
 - oLock, 219
 - TmsEventServerList, 218
- Tms::TmsPhase, 220
 - blr, 220
 - gate, 220
 - lo1, 220
 - lo2, 220
 - meanFilter1, 220
 - meanFilter2, 220
 - spare, 220
 - value, 220
- Tms::TmsProcess, 221
 - addEventServer, 223
 - getCycleInfo, 222
 - getCycleInformation, 222
 - getCycleTypeInformation, 222
 - getData, 223
 - getVersion, 222
 - requestData, 223
 - TmsProcess, 222
- Tms::TmsState, 225
 - acquireData, 226
 - calStart, 226
 - calStop, 226
 - cycleStop, 226
 - delay, 226
 - hchange, 226
 - injection, 226
 - pllFeedbackSelect, 226
 - pllLO1FromAddress, 226
 - pllLO2FromAddress, 226
 - pllReference1, 226
 - pllReference2, 226
 - spare0, 226
 - value, 226
- TmsC.cc, 290
- TmsC.h, 291
 - TMSC_H, 292
- TMSC_H
 - TmsC.h, 292
- TmsControl
 - Tms::TmsControl, 210
- TmsCycleParam-1.cc, 293
- TmsCycleParam.cc, 294
- TmsCycleParam.h, 295
 - TmsCycleParam_H, 295
- TmsCycleParam_H
 - TmsCycleParam.h, 295
- TmsD.cc, 296
- TmsD.h, 297
 - TMSD_H, 298
- TMSD_H
 - TmsD.h, 298
- TmsEvent
 - Tms::TmsEvent, 216
- TmsEventServerList
 - Tms::TmsEventServerList, 218
- TmsEventServerList.cc, 299
- TmsEventServerList.h, 300
 - TmsEventServerList_H, 300
- TmsEventServerList_H
 - TmsEventServerList.h, 300
- tmsFunctions.dox, 301
- TmsLib.cc, 302
- TmsLib.h, 303
 - TmsLib_H, 304
- TmsLib_H
 - TmsLib.h, 304
- tmsNumPickups
 - Tms, 32
- tmsPhaseTableSize
 - Tms, 32
- TmsProcess
 - Tms::TmsProcess, 222
- TmsS.cc, 305

- TmsT.cc, 306
- toLower
 - BString, 145
- toUpper
 - BString, 145
- triggerAnd
 - Tms::TestCaptureInfo, 207
- triggerMask
 - Tms::TestCaptureInfo, 207
- triggerSourceData
 - Tms::TestCaptureInfo, 207
- triggerStore
 - Tms::TestCaptureInfo, 207
- truncate
 - BString, 145
- tryLock
 - BMutex, 82
- tryNotZeroDecrement
 - BCondInt, 40
- tryRdLock
 - BRWLock, 124
- tryWait
 - BSema, 127
- tryWrLock
 - BRWLock, 125
- Type
 - BError, 60
- type
 - BoapPacketHead, 98
- UInt16
 - BoapSimple.h, 259
 - BTypes.h, 283
- UInt32
 - BoapSimple.h, 259
 - BTypes.h, 283
- UInt64
 - BTypes.h, 283
- UInt8
 - BoapSimple.h, 259
 - BTypes.h, 283
- unlock
 - BMutex, 82
 - BRWLock, 125
- updateLen
 - BoapPacket, 96
- useLoFref
 - Tms::CycleParamState, 170
- value
 - BCondBool, 38
 - BCondInt, 40
 - BCondValue, 43
 - BCondWrap, 46
- Tms::CycleParamEdit, 166
- Tms::NameValue, 181
- Tms::TmsPhase, 220
- Tms::TmsState, 226
- wait
 - BCond, 36
 - BCondBool, 38
 - BCondInt, 40
 - BRtc, 120
 - BRtcThreaded, 122
 - BSema, 126
- waitForCompletion
 - BThread, 149
- waitIncrement
 - BCondInt, 40
- waitLessThan
 - BCondValue, 43
 - BCondWrap, 46
- waitLessThanOrEqual
 - BCondValue, 43
 - BCondWrap, 46
- waitMoreThanOrEqual
 - BCondValue, 43
 - BCondWrap, 46
- waitNotZero
 - BCondInt, 40
- waitNotZeroDecrement
 - BCondInt, 40
- wild
 - BDir.cpp, 234
- wildString
 - BDir.cpp, 234
- write
 - BEntryFile, 55
 - BFile, 71
- writeCycleParams
 - Tms::CycleParamDb, 163
- writeData
 - BBuffer, 34
 - BUrl, 153
- writeList
 - BEntryFile, 55
- writeString
 - BFile, 71
- writeToFile
 - Tms::CycleParamEdit, 165
- wrLock
 - BRWLock, 125